

# Assignment I: Q3

Friday, 27 June 2025 00:27

## 3 Hash Functions

Consider the following Hash Function  $H$  defined by the recurrence:

$$H_i = H_{i-1} \oplus E(M_i, H_{i-1})$$

where  $M_i$  is a message block,  $H_i$  is its corresponding hash block and  $H_0$  is some initial value (which can be selected arbitrarily by the attacker).

The output digest of a message is then defined as:

$$H(M_1 || M_2 || \dots || M_N) = H_N$$

Let  $E$  be DES encryption scheme. DES has Complementation Property, where means that if  $Y = E(K, X)$ , then  $Y' = E(K', X')$ ,  $A'$  is such that the 0s in  $A$  are replaced by 1 and vice versa.

1. Use this property to find a collision for message  $M_1 || M_2 || \dots || M_N$ . (Marks 10)

2. Show that a similar attack succeeds for the recurrence:

$$H_i = M_i \oplus E(H_{i-1}, M_i)$$

(Marks 5)

Total marks :15

Property	EXPRESSION 1	EXPRESSION 2
Absorption	$A + A * B = A$	$A * (A + B) = A$
Adjacency	$A * B + A * B' = A$	$(A + B) * (A + B') = A$
Associative	$A + (B + C) = (A + B) + C$	$A * (B * C) = (A * B) * C$
Commutative	$A + B = B + A$	$A * B = B * A$
Complement	$A + A' = 1$	$A * A' = 0$
Consensus	$(A * X) + (A' * Y) + (X * Y) = (A * X) + (A' * Y) + (X * Y)$	$(A * X) + (A' * Y) = (A * X) + (A' * Y) + (X * Y)$
DeMorgan	$(A + B)' = A' * B'$	$(A * B)' = A' + B'$
Distributive	$A * (B + C) = A * B + A * C$	$A + B * C = (A + B) * (A + C)$
Idempotency	$A + A = A$	$A * A = A$
Identity	$A + 0 = A$	$A * 1 = A$
Involution	$(A')' = A$	
Null	$A + 1 = 1$	$A * 0 = 0$
Simplification	$A + A * B = A + B$	$A * (A + B) = A * B$

Table 2.21: Properties of algebra

## DeMorgan XOR

XOR gets much more interesting. Unlike AND and OR, the truth table for XOR is symmetric.

A	B	A ⊕ B
0	0	0
0	1	1
1	0	1
1	1	0

This means  
 $A \oplus B = A' \oplus B'$

The usual symbol. The output is 1 when A OR B is 1, but not both.  
Alternate symbol. The output is 1 when A OR B is 0, but not both.



confirm

$$\begin{aligned}
 a) \quad H_i' &= H_{i-1}' \oplus E(M_i, H_{i-1}') \\
 H_i' &= (H_{i-1} \oplus E(M_i, H_{i-1}))' \\
 &= H_{i-1}' \oplus E(M_i, H_{i-1}') \quad (\text{De Morgan law XOR}) \\
 &= H_{i-1}' \oplus E(M_i, H_{i-1}') \quad (A \oplus B = A' \oplus B') \\
 &= H_i'
 \end{aligned}$$

$$\therefore H_i' = H_i$$

$$\therefore H(M_1 || M_2 || \dots || M_i) = H(M_1 || M_2 || \dots || M_i)$$

$$\therefore H(M_1' || M_2' || \dots || M_i') = H(M_1 || M_2 || \dots || M_i)$$

$\therefore$  for  $i = N$

$$H_N' = H_N$$

$M_i$  is a message block and  $H_i$  is its hash. Let  $E$  be DES encryption scheme. DES has Complementation Property, where means that if  $Y = E(K, X)$ , then  $Y' = E(K', X')$ ,  $A'$  is such that the 0s in  $A$  are replaced by 1 and vice versa.

1. Use this property to find a collision for blocks  $M_1, M_2, \dots, M_N$ . (Marks 10)
2. Show that a similar attack succeeds for

$$H_i = M_i \oplus E(H_{i-1}, M_i)$$

(Marks 5)

Total marks :15

$$\begin{aligned}
 b) \quad H_i' &= [M_i \oplus E(H_{i-1}, M_i)]' \\
 &= M_i' \oplus E(H_{i-1}', M_i') \quad (\text{XOR De Morgan law}) \\
 &= M_i' \oplus E(H_{i-1}', M_i') \quad (\text{DES complementary property}) \\
 &= M_i' \oplus E(H_{i-1}, M_i) \quad (\text{XOR } A \oplus B = A' \oplus B') \\
 \therefore H_i' &= H_i
 \end{aligned}$$

Thus taking XOR of  $M$  still permits collision  
 $H_i' = H_i$