

CS21 Decidability and Tractability

Lecture 12
February 3, 2014

February 3, 2014

CS21 Lecture 12

1

Outline

- undecidable problems
 - computation histories
 - surprising contrasts between decidable/undecidable
- Rice's Theorem
- Post Correspondence problem


February 3, 2014

CS21 Lecture 12

2

Definition of reduction

- More refined notion of reduction:
 - “many-one” reduction (commonly)
 - “mapping” reduction (book)




February 3, 2014

CS21 Lecture 12

3

Definition of reduction



- function f should be **computable**

Definition: $f : \Sigma^* \rightarrow \Sigma^*$ is **computable** if there exists a TM M_f such that on every $w \in \Sigma^*$ M_f halts on w with $f(w)$ written on its tape.

February 3, 2014

CS21 Lecture 12

4

Definition of reduction

- Notation: “A many-one reduces to B” is written

$$A \leq_m B$$
 - “yes maps to yes and no maps to no” means:
 $w \in A$ maps to $f(w) \in B$ & $w \notin A$ maps to $f(w) \notin B$
- B is at least as “hard” as A
 - more accurate: B at least as “expressive” as A

February 3, 2014

CS21 Lecture 12

5

Using reductions

Definition: $A \leq_m B$ if there is a computable function f such that for all w

$$w \in A \Leftrightarrow f(w) \in B$$

Theorem: if $A \leq_m B$ and B is decidable then A is decidable

Proof:

- decider for A: on input w , compute $f(w)$, run decider for B, do whatever it does.

February 3, 2014

CS21 Lecture 12

6

Using reductions

- Main use: given language NEW, prove it is **undecidable** by showing $OLD \leq_m NEW$, where OLD known to be **undecidable**
 - proof by contradiction
 - if NEW decidable, then OLD decidable
 - OLD undecidable. Contradiction.
- common to reduce in wrong direction.
- review this argument to check yourself.

February 3, 2014

CS21 Lecture 12

7

Using reductions

Theorem: if $A \leq_m B$ and B is RE then A is RE

Proof:

- TM for recognizing A: on input w, compute $f(w)$, run TM that recognizes B, do whatever it does.
- Main use: given language NEW, prove it is **not RE** by showing $OLD \leq_m NEW$, where OLD known to be **not RE**.

February 3, 2014


CS21 Lecture 12

8

Many-one reduction example

- Showed E_{TM} undecidable. Consider:

$$co-E_{TM} = \{ \langle M \rangle : L(M) \neq \emptyset \}$$



- $f(\langle M, w \rangle) = \langle M' \rangle$ where M' is TM that
 - on input x, if $x \neq w$, then reject
 - else simulate M on x, and accept if M does


- f clearly computable

February 3, 2014

CS21 Lecture 12

9

Many-one reduction example



- $f(\langle M, w \rangle) = \langle M' \rangle$ where M' is TM that
 - on input x, if $x \neq w$, then reject
 - else simulate M on x, and accept if M does

- f clearly computable

- yes maps to yes?
 - if $\langle M, w \rangle \in A_{TM}$ then $f(\langle M, w \rangle) \in co-E_{TM}$
- no maps to no?
 - if $\langle M, w \rangle \notin A_{TM}$ then $f(\langle M, w \rangle) \notin co-E_{TM}$

February 3, 2014

CS21 Lecture 12

10

Undecidable problems

Theorem: The language
 $REGULAR = \{ \langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular} \}$

is undecidable.

Proof:

- reduce from A_{TM} (i.e. show $A_{TM} \leq_m REGULAR$)
- what should $f(\langle M, w \rangle)$ produce?

February 3, 2014

CS21 Lecture 12

11

Undecidable problems

Proof:

- $f(\langle M, w \rangle) = \langle M' \rangle$ described below

on input x:
 • if x has form $0^n 1^n$, accept
 • else simulate M on w and accept x if M accepts

- is f computable?
- YES maps to YES?
 - $\langle M, w \rangle \in A_{TM} \Rightarrow f(\langle M, w \rangle) \in REGULAR$
- NO maps to NO?
 - $\langle M, w \rangle \notin A_{TM} \Rightarrow f(\langle M, w \rangle) \notin REGULAR$

February 3, 2014

CS21 Lecture 12

12

Dec. and undec. problems

- the boundary between decidability and undecidability is often quite delicate
 - seemingly related problems
 - one decidable
 - other undecidable
- We will see two examples of this phenomenon next.

February 3, 2014

CS21 Lecture 12

13

Computation histories

- Recall configuration of a TM: string uqv with $u, v \in \Gamma^*$, $q \in Q$
- The sequence of configurations M goes through on input w is a **computation history of M on input w**
 - may be *accepting*, or *rejecting*
 - reserve the term for halting computations
 - nondeterministic machines may have several computation histories for a given input.

February 3, 2014

CS21 Lecture 12

14

Linear Bounded Automata

- LBA definition: TM that is prohibited from moving head off right side of input.
- machine prevents such a move, just like a TM prevents a move off left of tape
 - How many possible configurations for a LBA M on input w with $|w| = n$, m states, and $p = |\Gamma|$?
 - counting gives: mnp^n

February 3, 2014

CS21 Lecture 12

15

Dec. and undec. problems

- two problems we have seen with respect to TMs, now regarding LBAs:
 - LBA acceptance:

$$A_{LBA} = \{ \langle M, w \rangle : \text{LBA } M \text{ accepts input } w \}$$
 - LBA emptiness:

$$E_{LBA} = \{ \langle M \rangle : \text{LBA } M \text{ has } L(M) = \emptyset \}$$
- Both decidable? both undecidable? one decidable?

February 3, 2014

CS21 Lecture 12

16

Dec. and undec. problems

Theorem: A_{LBA} is decidable.

Proof:

- input $\langle M, w \rangle$ where M is a LBA
- key: only mnp^n configurations
- if M hasn't halted after this many steps, it must be looping forever.
- simulate M for mnp^n steps
- if it halts, accept or reject accordingly,
- else reject since it must be looping

February 3, 2014

CS21 Lecture 12

17

Dec. and undec. problems

Theorem: E_{LBA} is undecidable.

Proof:

- reduce from $\text{co-}A_{TM}$ (i.e. show $\text{co-}A_{TM} \leq_m E_{LBA}$)
- what should $f(\langle M, w \rangle)$ produce?
- Idea:
 - produce LBA B that accepts exactly the **accepting computation histories** of M on input w

February 3, 2014

CS21 Lecture 12

18

Dec. and undec. problems

Proof:

– $f(\langle M, w \rangle) = \langle B \rangle$ described below

on input x , check if x has form

$\#C_1\#C_2\#C_3\#\dots\#C_k\#$

- check that C_1 is the start configuration for M on input w

- check that $C_i \Rightarrow^1 C_{i+1}$

- check that C_k is an accepting configuration for M

- is B an LBA?

- is f computable?

- YES maps to YES?

$\langle M, w \rangle \in \text{CO-A}_{\text{TM}} \Rightarrow$

$f(M, w) \in E_{\text{LBA}}$

- NO maps to NO?

$\langle M, w \rangle \notin \text{CO-A}_{\text{TM}} \Rightarrow$

$f(M, w) \notin E_{\text{LBA}}$