

CS21 Decidability and Tractability

Lecture 17
February 14, 2014

February 14, 2014

CS21 Lecture 17

1

Outline

- The complexity class P
 - examples of problems in P

February 14, 2014

CS21 Lecture 17

2

Time complexity

Definition: the running time (“time complexity”) of a TM M is a function

$$f: \mathbb{N} \rightarrow \mathbb{N}$$

where $f(n)$ is the maximum number of steps M uses on any input of length n .

- “ M runs in time $f(n)$,” “ M is a $f(n)$ time TM”

February 14, 2014

CS21 Lecture 17

3

Time complexity

- We do not care about fine distinctions
 - e.g. how many additional steps M takes to check that it is at the left of tape
- We care about the behavior on **large inputs**
 - general-purpose algorithm should be “scalable”
 - overhead for e.g. initialization shouldn’t matter in big picture

February 14, 2014

CS21 Lecture 17

4

Time complexity

- Measure time complexity using **asymptotic notation** (“big-oh notation”)
 - disregard lower-order terms in running time
 - disregard coefficient on highest order term
- example:

$$f(n) = 6n^3 + 2n^2 + 100n + 102781$$
 - “ $f(n)$ is order n^3 ”
 - write $f(n) = O(n^3)$

February 14, 2014

CS21 Lecture 17

5

Time complexity

On input x :

- scan tape left-to-right, reject if 0 to right of 1 $O(n)$ steps
- repeat while 0’s, 1’s on tape: $\leq n$ repeats
 - scan, crossing off one 0, one 1 $O(n)$ steps
- if only 0’s or only 1’s remain, reject; if neither 0’s nor 1’s remain, accept $O(n)$ steps
- total = $O(n) + n \cdot O(n) + O(n) = O(n^2)$

February 14, 2014

CS21 Lecture 17

6

Asymptotic notation facts

- “logarithmic”: $O(\log n)$
 - $\log_b n = (\log_2 n)/(\log_2 b)$
 - so $\log_b n = O(\log_2 n)$ for any constant b ;
therefore suppress base when write it
- “polynomial”: $O(n^c) = n^{O(1)}$
 - also: $c^{O(\log n)} = O(n^c) = n^{O(1)}$
- “exponential”: $O(2^{n^\delta})$ for $\delta > 0$

each bound
asymptotically
less than next

February 14, 2014

CS21 Lecture 17

7

Time complexity

- Recall:
 - language is a set of strings
 - a **complexity class** is a set of languages
 - complexity classes we’ve seen:
 - Regular Languages, Context-Free Languages, Decidable Languages, RE Languages, co-RE languages

Definition: $\text{TIME}(t(n)) = \{L : \text{there exists a TM } M \text{ that decides } L \text{ in time } O(t(n))\}$

February 14, 2014

CS21 Lecture 17

8

Time complexity

- We saw that $L = \{0^k 1^k : k \geq 0\}$ is in $\text{TIME}(n^2)$.
- Book: it is also in $\text{TIME}(n \log n)$ by giving a more clever algorithm
- Can prove: $O(n \log n)$ time required on a single tape TM.
- How about on a multitape TM?

February 14, 2014

CS21 Lecture 17

9

Time Complexity

- 2-tape TM M deciding $L = \{0^k 1^k : k \geq 0\}$.

On input x :

- scan tape left-to-right, reject if 0 to right of 1 $O(n)$
- scan 0’s on tape 1, copying them to tape 2 $O(n)$
- scan 1’s on tape 1, crossing off 0’s on tape 2 $O(n)$
- if all 0’s crossed off before done with 1’s reject
- if 0’s remain after done with ones, reject; otherwise accept.

total:
 $3 \cdot O(n)$
 $= O(n)$

February 14, 2014

CS21 Lecture 17

10

Multitape TMs

- Convenient to “program” multitape TMs rather than single ones
 - equivalent when talking about decidability
 - not equivalent when talking about time complexity

Theorem: Let $t(n)$ satisfy $t(n) \geq n$. Every multi-tape TM running in time $t(n)$ has an equivalent TM running in time $O(t(n)^2)$.


February 14, 2014

CS21 Lecture 17

11

Multitape TMs

simulation of k -tape TM by single-tape TM:




February 14, 2014

CS21 Lecture 17

12

Multitape TMs



February 14, 2014

CS21 Lecture 17

13

Multitape TMs

- Moral: feel free to use k-tape TMs, but be aware of slowdown in conversion to TM
 - note: if $t(n) = O(n^c)$ then $t(n)^2 = O(n^{2c}) = O(n^c)$
 - note: if $t(n) = O(2^{n^\delta})$ for $\delta > 0$ then $t(n)^2 = O(2^{2n^\delta}) = O(2^{n^\delta})$ for $\delta' > 0$
- high-level operations you are used to using can be simulated by TM with only polynomial slowdown
 - e.g., copying, moving, incrementing/decrementing, arithmetic operations $+$, $-$, $*$, $/$

February 14, 2014

CS21 Lecture 17

14

Extended Church-Turing Thesis

- the belief that TMs formalize our intuitive notion of an efficient algorithm is:

The "extended" Church-Turing Thesis
everything we can compute in time $t(n)$ on a physical computer can be computed on a Turing Machine in time $t(n)^{O(1)}$ (polynomial slowdown)

- quantum computers challenge this belief

February 14, 2014

CS21 Lecture 17

15

Time Complexity

- interested in a coarse classification of problems. For this purpose,
 - treat any polynomial running time as "efficient" or "tractable"
 - treat any exponential running time as inefficient or "intractable"

Key definition: "P" or "polynomial-time" is

$$P = \bigcup_{k \geq 1} \text{TIME}(n^k)$$

February 14, 2014

CS21 Lecture 17

16

Time Complexity

- Why polynomial-time?
 - insensitive to particular deterministic model of computation chosen
 - closed under modular composition
 - empirically: qualitative breakthrough to achieve polynomial running time is followed by quantitative improvements from impractical (e.g. n^{100}) to practical (e.g. n^3 or n^2)

February 14, 2014

CS21 Lecture 17

17

Examples of languages in P

- Recall: positive integers x, y are relatively prime if their Greatest Common Divisor (GCD) is 1.
- will show the following language is in P:

$$\text{RELPRIME} = \{ \langle x, y \rangle : x \text{ and } y \text{ are relatively prime} \}$$
- what is the running time of the algorithm that tries all divisors up to $\max\{x, y\}$?

February 14, 2014

CS21 Lecture 17

18

Euclid's Algorithm

- possibly earliest recorded algorithm

on input $\langle x, y \rangle$:

- repeat until $y = 0$
 - set $x = x \bmod y$
 - swap x, y
- x is the $\text{GCD}(x, y)$. If $x = 1$, accept; otherwise reject

Example run on input $\langle 10, 22 \rangle$:

$x, y = 10, 22$
 $x, y = 22, 10$
 $x, y = 10, 2$
 $x, y = 2, 0$
 reject

February 14, 2014

CS21 Lecture 17

19

Euclid's Algorithm

- possibly earliest recorded algorithm

on input $\langle x, y \rangle$:

- repeat until $y = 0$
 - set $x = x \bmod y$
 - swap x, y
- x is the $\text{GCD}(x, y)$. If $x = 1$, accept; otherwise reject

Example run on input $\langle 24, 5 \rangle$:

$x, y = 24, 5$
 $x, y = 5, 4$
 $x, y = 4, 1$
 $x, y = 1, 0$
 accept

February 14, 2014

CS21 Lecture 17

20

Euclid's Algorithm

on input $\langle x, y \rangle$:

- (1) repeat until $y = 0$
 - (2) set $x = x \bmod y$
 - (3) swap x, y
- x is the $\text{GCD}(x, y)$. If $x = 1$, accept; otherwise reject

Claim: value of x reduced by $\frac{1}{2}$ at every execution of (2) except possibly first one.

Proof:

- every 2 times through loop, (x, y) each reduced by $\frac{1}{2}$
- loops $\leq 2 \cdot \max\{\log_2 x, \log_2 y\}$ = $O(n = |\langle x, y \rangle|)$; poly time for each loop

- after (2) $x < y$
- after (3) $x > y$
- if $x/2 \geq y$, then $x \bmod y < y \leq x/2$
- if $x/2 < y$, then $x \bmod y = x - y < x/2$

February 14, 2014

CS21 Lecture 17

21

A puzzle

- Find an efficient algorithm to solve the following problem:
- Input: sequence of pairs of symbols
e.g. $(A, b), (E, D), (d, C), (B, a)$
- Goal: determine if it is possible to circle at least one symbol in each pair without circling upper and lower case of same symbol.

February 14, 2014

CS21 Lecture 17

22

A puzzle

- Find an efficient algorithm to solve the following problem.
- Input: sequence of pairs of symbols
e.g. $(A, b), (E, D), (d, C), (b, a)$
- Goal: determine if it is possible to circle at least one symbol in each pair without circling upper and lower case of same symbol.

February 14, 2014

CS21 Lecture 17

23

2SAT

- This is a disguised version of the language $2SAT = \{\text{formulas in Conjunctive Normal Form with 2 literals per clause for which there exists a satisfying truth assignment}\}$
 – CNF = “AND of ORs”
 $(A, b), (E, D), (d, C), (b, a)$
 $(x_1 \vee \neg x_2) \wedge (x_5 \vee x_4) \wedge (\neg x_4 \vee x_3) \wedge (\neg x_2 \vee \neg x_1)$
 – satisfying truth assignment = assignment of TRUE/FALSE to each variable so that whole formula is TRUE

February 14, 2014

CS21 Lecture 17

24

2SAT

Theorem: There is a polynomial-time algorithm deciding 2SAT ("2SAT $\in P$ ").

Proof: algorithm described on next slides.


February 14, 2014

CS21 Lecture 17

25

Algorithm for 2SAT

- Build a graph with separate nodes for each literal.
- add directed edge (x, y) iff formula includes clause $(\neg x \vee y)$ or $(y \vee \neg x)$ (equiv. to $x \Rightarrow y$)



e.g. $(x_1 \vee \neg x_2) \wedge (x_5 \vee x_4) \wedge (\neg x_4 \vee x_3) \wedge (\neg x_2 \vee \neg x_1)$

February 14, 2014

CS21 Lecture 17

26

Algorithm for 2SAT

Claim: formula is unsatisfiable iff there is some variable x with a path from x to $\neg x$ and a path from $\neg x$ to x in derived graph.

- Proof (\Leftarrow)
 - edges represent implication \Rightarrow . By transitivity of \Rightarrow , a path from x to $\neg x$ means $x \Rightarrow \neg x$, and a path from $\neg x$ to x means $\neg x \Rightarrow x$.

February 14, 2014

CS21 Lecture 17

27

Algorithm for 2SAT

- Proof (\Rightarrow)
 - to construct a satisfying assign. (if no x with a path from x to $\neg x$ and a path from $\neg x$ to x):
 - pick unassigned literal s with no path from s to $\neg s$
 - assign it TRUE, as well as all nodes reachable from it; assign negations of these literals FALSE
 - note: path from s to t and s to $\neg t$ implies path from $\neg t$ to $\neg s$ and t to $\neg s$, implies path from s to $\neg s$
 - note: path s to t (assigned FALSE) implies path from $\neg t$ (assigned TRUE) to $\neg s$, so s already assigned at that point.

February 14, 2014

CS21 Lecture 17

28

Algorithm for 2SAT

- Algorithm:
 - build derived graph
 - for every pair $x, \neg x$ check if there is a path from x to $\neg x$ and from $\neg x$ to x in the graph
- Running time of algorithm (input length n):
 - $O(n)$ to build graph
 - $O(n)$ to perform each check
 - $O(n)$ checks
 - running time $O(n^2)$. 2SAT $\in P$.

February 14, 2014

CS21 Lecture 17

29

Another puzzle

- Find an efficient algorithm to solve the following problem.
- Input: sequence of *triples* of symbols
e.g. (A, b, C), (E, D, b), (d, A, C), (c, b, a)
- Goal: determine if it is possible to circle at least one symbol in each *triple* without circling upper and lower case of same symbol.

February 14, 2014

CS21 Lecture 17

30