

CS21 Decidability and Tractability

Lecture 4
January 13, 2014

January 13, 2014

CS21 Lecture 3

1

Outline

- Pumping Lemma
- Pushdown Automata
- Context-Free Grammars and Languages

January 13, 2014

CS21 Lecture 3

2

Non-regular languages

Pumping Lemma: Let L be a regular language. **There exists** an integer p ("pumping length") for which **every** $w \in L$ with $|w| \geq p$ can be written as

$w = xyz$ such that

1. for every $i \geq 0$, $xy^iz \in L$, and
2. $|y| > 0$, and
3. $|xy| \leq p$.

January 13, 2014

CS21 Lecture 3

3

Non-regular languages

- Using the Pumping Lemma to prove L is not regular:
 - assume L is regular
 - then there exists a pumping length p
 - select a string $w \in L$ of length at least p
 - argue that **for every** way of writing $w = xyz$ that satisfies (2) and (3) of the Lemma, pumping on y yields a string not in L .
 - contradiction.

January 13, 2014

CS21 Lecture 3

4

Pumping Lemma Examples

- Theorem: $L = \{0^i1^j : i > j\}$ is not regular.
- Proof:

– let p be the pumping length for L

– choose $w = 0^{p+1}1^p$

$w = \underbrace{000000000}_{p+1} \dots \underbrace{01111111}_{p} \dots 1$

– $w = xyz$, with $|y| > 0$ and $|xy| \leq p$.

January 13, 2014

CS21 Lecture 3

5

Pumping Lemma Examples

- 1 possibility:

$w = \underbrace{00000000}_{x} \underbrace{000}_{y} \underbrace{0\dots011111111}_{z} \dots 1$

- pumping on y gives strings in the language (?)
- this seems like a problem...
- Lemma states that **for every** $i \geq 0$, $xy^iz \in L$
- xy^0z not in L . So L not regular.


January 13, 2014

CS21 Lecture 3

6

Proof of the Pumping Lemma

- Let M be a FA that recognizes L .
- Set p = number of states of M .
- Consider $w \in L$ with $|w| \geq p$. On input w , M must go through *at least* $p+1$ states. **There must be a repeated state** (among first $p+1$).



January 13, 2014

CS21 Lecture 3

7

FA Summary

- A “problem” is a **language**
- A “computation” receives an input and either accepts, rejects, or loops forever.
- A “computation” **recognizes** a language (it may also **decide** the language).
- **Finite Automata** perform simple computations that read the input from left to right and employ a finite memory.

January 13, 2014

CS21 Lecture 3

8

FA Summary

- The languages recognized by FA are the **regular languages**.
- The regular languages are **closed** under union, concatenation, and star.
- **Nondeterministic Finite Automata** may have several choices at each step.
- NFAs recognize **exactly the same** languages that FAs do.

January 13, 2014

CS21 Lecture 3

9

FA Summary


- **Regular expressions** are languages built up from the operations union, concatenation, and star.
- Regular expressions describe **exactly the same** languages that FAs (and NFAs) recognize.
- Some languages are **not regular**. This can be proved using the **Pumping Lemma**.

January 13, 2014

CS21 Lecture 3

10

Machine view of FA




January 13, 2014

CS21 Lecture 3

11

Machine view of FA




January 13, 2014

CS21 Lecture 3

12

Machine view of FA




January 13, 2014

CS21 Lecture 3

13

Machine view of FA



January 13, 2014

CS21 Lecture 3

14

A more powerful machine


- limitation of FA related to fact that they can only “remember” a bounded amount of information
- What is the **simplest** alteration that adds unbounded “memory” to our machine?
- Should be able to recognize, e.g., $\{0^n 1^n : n \geq 0\}$

January 13, 2014

CS21 Lecture 3

15

Pushdown Automata




January 13, 2014

CS21 Lecture 3

16

Pushdown Automata




January 13, 2014

CS21 Lecture 3

17

Pushdown Automata




January 13, 2014

CS21 Lecture 3

18

Pushdown Automata




January 13, 2014

CS21 Lecture 3

19

Pushdown Automata




January 13, 2014

CS21 Lecture 3

20

Pushdown Automata



January 13, 2014

CS21 Lecture 3

21

Pushdown Automata (PDA)


- We will define **nondeterministic** pushdown automata immediately
 - potentially several choices of “next step”
- Deterministic PDA defined later
 - weaker than NPDA
- Two ways to describe NPDA
 - diagram
 - formal definition

January 13, 2014

CS21 Lecture 3

22

NPDA diagram



January 13, 2014

CS21 Lecture 3

23

NPDA operation

- Taking a transition labeled:
 - $a, b \rightarrow c$
 - $a \in (\Sigma \cup \{\epsilon\})$
 - $b, c \in (\Gamma \cup \{\epsilon\})$
 - read a from tape, or don't read from tape if $a = \epsilon$
 - pop b from stack, or don't pop from stack if $b = \epsilon$
 - push c onto stack, or don't push onto stack if $c = \epsilon$


January 13, 2014

CS21 Lecture 3

24

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• tape: 0 0 1 1 Stack contents: \$


January 13, 2014

CS21 Lecture 3

25

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• tape: 0 0 1 1 Stack contents: 0 \$


January 13, 2014

CS21 Lecture 3

26

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• tape: 0 0 1 1 Stack contents: 0 0 \$


January 13, 2014

CS21 Lecture 3

27

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• tape: 0 0 1 1 Stack contents: 0 0 \$


January 13, 2014

CS21 Lecture 3

28

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• tape: 0 0 1 1 Stack contents: 0 \$


January 13, 2014

CS21 Lecture 3

29

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• tape: 0 0 1 1 Stack contents: \$
 accepted


January 13, 2014

CS21 Lecture 3

30

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• tape: 0 0 1 Stack contents: \$


January 13, 2014

CS21 Lecture 3

31

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• tape: 0 0 1 Stack contents: 0 \$


January 13, 2014

CS21 Lecture 3

32

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• tape: 0 0 1 Stack contents: 0 0 \$


January 13, 2014

CS21 Lecture 3

33

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• tape: 0 0 1 Stack contents: 0 0 \$


January 13, 2014

CS21 Lecture 3

34

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• tape: 0 0 1 Stack contents: 0 \$
 not accepted


January 13, 2014

CS21 Lecture 3

35

Example NPDA

$\Sigma = \{0, 1\}$
 $\Gamma = \{0, 1, \$\}$



• What language does this NPDA accept?

January 13, 2014

CS21 Lecture 3

36

Formal definition of NPDA

- A NPDA is a 6-tuple $(Q, \Sigma, \Gamma, \delta, q_0, F)$ where:
 - Q is a finite set called the **states**
 - Σ is a finite set called the **tape alphabet**
 - Γ is a finite set called the **stack alphabet**
 - $\delta: Q \times (\Sigma \cup \{\epsilon\}) \times (\Gamma \cup \{\epsilon\}) \rightarrow \wp(Q \times (\Gamma \cup \{\epsilon\}))$ is a function called the **transition function**
 - q_0 is an element of Q called the **start state**
 - F is a subset of Q called the **accept states**

January 13, 2014

CS21 Lecture 3

37

Formal definition of NPDA


- NPDA $M = (Q, \Sigma, \Gamma, \delta, q_0, F)$ accepts string $w \in \Sigma^*$ if w can be written as $w_1 w_2 w_3 \dots w_m \in (\Sigma \cup \{\epsilon\})^*$, and
- there exist states $r_0, r_1, r_2, \dots, r_m$, and
- there exist strings s_0, s_1, \dots, s_m in $(\Gamma \cup \{\epsilon\})^*$
 - $r_0 = q_0$ and $s_0 = \epsilon$
 - $(r_{i+1}, b) \in \delta(r_i, w_{i+1}, a)$, where $s_i = at$, $s_{i+1} = bt$ for some $t \in \Gamma^*$
 - $r_m \in F$

January 13, 2014

CS21 Lecture 3

38

Example of formal definition



- $Q = \{q_0, q_1, q_2, q_3\}$
 - $\Sigma = \{0, 1\}$
 - $\Gamma = \{0, 1, \$\}$
 - $F = \{q_0, q_3\}$
 - $\delta(q_0, \epsilon, \epsilon) = \{(q_1, \$)\}$
 - $\delta(q_1, 0, \epsilon) = \{(q_1, 0)\}$
 - $\delta(q_1, 1, 0) = \{(q_2, \epsilon)\}$
 - $\delta(q_2, 1, 0) = \{(q_2, \epsilon)\}$
 - $\delta(q_2, \epsilon, \$) = \{(q_3, \epsilon)\}$
- other values of $\delta(*, *, *)$ equal $\{\}$

January 13, 2014

CS21 Lecture 3

39

Exercise

Design a NPDA for the language

$\{a^i b^j c^k : i, j, k \geq 0 \text{ and } i = j \text{ or } i = k\}$

January 13, 2014

CS21 Lecture 3

40