```
1: #!/usr/bin/python3
 2:
 3: import numpy as np
 4: import matplotlib.pyplot as plt
 6: def f(x, t):
 7:
        return 2*t*x
 8:
 9: def act(t):
10:
        return 2*np.exp(np.power(t,2.0))
11:
12: def RungeKutta(func, init, a, b, h=0.025):
        X = []
13:
14:
        T = np.arange(a, b + h, h)
        x = init
15:
16:
        for t in T:
17:
            X.append(x)
            k1 = h * func(x, t)
18:
19:
            k2 = h * func(x + k1 / 2, t + h / 2)
20:
            k3 = h * func(x + k2 / 2, t + h / 2)
21:
            k4 = h * func(x + k3, t + h)
            x += (1/6) * (k1 + 2 * k2 + 2 * k3 + k4)
22:
23:
        return X, T
24:
25: # PROBLEM 1
26: v0x = 600*np.cos(3.1415/3)
27: v0y = 600*np.sin(3.1415/3)
28: def x(t,c):
29:
        return v0x/c*(1-np.exp(-c*t))
30: def y(t,c):
        return -(9.81/c)*t+(v0y*c+9.81)/np.power(c,2.0)*(1-np.exp(-c*t))
31:
32: X1 = []
33: Y1 = []
34: t1 = 0
35: X1.append(v0x*t1)
36: Y1.append(v0y*t1-0.5*9.81*np.power(t1,2.0))
37: while Y1[-1] >= 0:
38:
        X1.append(v0x*t1)
39:
        Y1.append(v0y*t1-0.5*9.81*np.power(t1,2.0))
40:
        t1 += 1.0
41: X2 = []
42: Y2 = []
43: t2 = 0
44: X2.append(x(t2, 0.005))
45: Y2.append(y(t2,0.005))
46: while Y2[-1] >= 0:
47:
        X2.append(x(t2, 0.005))
48:
        Y2.append(y(t2,0.005))
       t2 += 1.0
49:
50: X3 = []
51: Y3 = []
52: t3 = 0
53: X3.append(x(t3, 0.01))
54: Y3.append(y(t3, 0.01))
55: while Y3[-1] >= 0:
56:
        X3.append(x(t3, 0.01))
57:
        Y3.append(y(t3, 0.01))
58:
        t3 += 1.0
59:
60: fig, (ax1, ax2) = plt.subplots(2)
61: ax1.plot(X1, Y1, 'k-', label="C=0.0")
62: ax1.plot(X2, Y2, 'k--', label="C=0.005")
63: ax1.plot(X3, Y3, 'k:', label="C=0.01")
```

```
hw2.py
             Thu Feb 07 10:24:41 2019
   64: ax1.set_title("#1")
   65: ax1.legend()
   66: # plt.plot(X1, Y1)
   67: # plt.plot(X2, Y2)
   68: # plt.plot(X3, Y3)
   69: # plt.show()
   70:
   71:
   72: # PROBLEM 2
   73: X, T = RungeKutta(f, 2.0, 0, 1, 0.025)
   74: ax2.plot(T, [act(t) for t in T], 'k--', label="Analytical")
   75: ax2.plot(T, X, 'k-', label="Runge-Kutta")
   76: ax2.set_title("#2")
   77: ax2.set_xlabel("X(1)=5.465")
   78: ax2.legend()
   79: fig.set_size_inches(6,9)
   80: # plt.show()
   81: plt.savefig("hw2.ps", papertype="a4")
```