



APPLICATION

Pevalit

Stir Flexkleber

Adhesive for insulating
facades with
reinforcing fibers



- Used in thermo insulation facade systems.
- Adhesion of insulation panels in facades.
- Leveling of insulation panels and covering those with a reinforcing mesh, thickness of 4 to 8 mm.
- Insulation panels should be of expanded polystyrene (Styrofoam), or from mineral fibers.
- Covering and leveling layers of smooth concrete.
- Usage in layers of indoor or outdoor environments.

TECHNICAL PARAMETERS

- Sanding:** From 0-1.5 mm.
- Dry mass density:** 1600-1900 kg/m³
- Certified:** EN ETAG 004 ETA -11/0340
- Work temperatures:** +5°C - +30°C.
- Mixing with water:** approximately 4 min., with around 26-28% water/25kg.
- Working time in container:** Up to 4 hours after mixing.
- Spending:** for panel adhesion 4-5 kg/m²; for covering panels with reinforcing mesh 4-5 kg/m²
- Adhesion (separation) from the layers of concrete:** After 28 days 0.3 N/mm²
- Adhesion (separation) from the layers of polystyrene:** After 28 days 0.08 N/mm²
- Material color:** White.
- Packaging:** 25 kg.
- Best before:** In the original packaging 12 months, in a warehouse without moisture.