



Pevalit Stir Light

Adhesive for
insulating facades
with EPS grains



APPLICATION

- Used in thermo insulation facade systems.
- Adhesion of insulation panels in facades.
- Leveling of insulation panels and covering those with a reinforcing mesh, thickness of 4 to 8 mm.
- Insulation panels should be of expanded polystyrene (Styrofoam), or from mineral fibers.
- Covering and leveling layers of smooth concrete.
- Usage in layers of indoor or outdoor environments.
- Distinguished for its specific light weight.

TECHNICAL PARAMETERS

- Sanding:** From 0-1.2 mm.
- Dry mass density:** 1050-1200 kg/m³
- Norm:** MKC EN 998-1/Kop: 2006.
- Pressure durability (after 28 days):** CS IV .
- Water absorption:** W1.
- Work temperatures:** +5°C - +30°C.
- Mixing with water:** approximately 4 min., with around 26-28% water/25kg.
- Working time in container:** Up to 4 hours after mixing.
- Spending:** for panel adhesion 4-5 kg/m²; for covering panels with reinforcing mesh 4-5 kg/m²
- Adhesion (separation) from the layers of concrete:** After 28 days 0.3 N/mm²
- Adhesion (separation) from the layers of polystyrene:** After 28 days 0.08 N/mm²
- Material color:** White.
- Packaging:** 25 kg.
- Best before:** In the original packaging 12 months, in a warehouse without moisture.