Palm OS Programming Recipes

Exchange Manager: Sending a whole database

This recipe describes how to send a database using the Palm OS exchange library. The example application sends itself, a Palm resource database. You can substitute any other database or use a different mechanism to get the database ID. In the sample code, the `DmGetNextDatabaseByTypeCreator` function obtains the database ID.

The key to sending a database is an exchange library function called `ExgDBWrite` that converts a Palm database into the `.pdb` format used by the Palm Desktop.

Follow these steps to send a database:

In Constructor:

- Add a menu item for beaming or any other UI components that are applicable to your application.

Open the source file containing the event handling function that handles the beam menu item.

- Make sure that `ExgMgr.h` is included as a header file.
- Create and initialize an `ExgSocketType` data structure with information about which library to use and the data to be sent. Make sure initialize the description, type, target and/or name.
- Set `name` to the database name.
- Call `ExgPut` to establish the connection with the exchange library.
- Call `ExgDBWrite` to send the database.
- Call `ExgDisconnect` to end the connection.

The following code segment is an example of the above procedure:

```
static void BeamThisApp()
{
    ExgSocketType exgSocket;
    UInt16 cardNo;
    LocalID dbID;
    DmSearchStateType searchState;
    Err err;
    Char *appName = "ExgMgrBeamDB";

    err = DmGetNextDatabaseByTypeCreator(true, &searchState,
        sysFileTApplication, appFileCreator, true,
        &cardNo, &dbID);
    if (!err)
    {
        // important to init structure to zeros...
        MemSet(&exgSocket,sizeof(exgSocket),0);
        exgSocket.description = appName;
        exgSocket.name = "ExgMgrBeamDB.prc";

        err = ExgPut(&exgSocket);
```

```
        if (err == 0)
        {
            ExgDBWrite(WriteProc, &exgSocket, appName, dbID, cardNo);
            ExgDisconnect(&exgSocket,err);
        }
    }
}
```

The following archives contain a Code Warrior project with this sample code. The application beams itself when you use a shortcut or the command bar. See `MainForm.c` for details.

- Windows
- Mac