PalmSource™ 99

Debugging Serial Drivers

Bruce Thompson
Senior Developer Support Engineer

3Com
More connected.

Why Not Use a Source Level Debugger?

PalmSource 99

- Real-time nature of most protocols prevents stopping execution for long periods of time
- Source level debugger might work for direct serial connection with simple protocols
- Interference of the debugger at interrupt time where most drivers are operating

General Tips

- Test your driver using simple serial communication device first
- For example, if writing IR app, test using wired serial first then introduce IR
- Have a test harness that will exercise the driver using known code

Alternate Debugging Methods

PalmSource 99

- Printf
- Audio cues
- Asserts
- Hardware
- Logging

Printfs

- DbgMessage sends text messages to the debug console
  - Won’t work over serial debug link
  - Slow when used with Poser
- Use HostFPrintF when debugging using Poser

Audio Cues (aka ‘beep’)

PalmSource 99

- SndPlaySystemSound(sndError)
- Usually not a great way to debug
- Might be useful for SrmSetWakeupHandler callback

"asserts"

PalmSource 99

- ErrNonFatalDisplay
- Good way to catch unexpected situations

Hardware

- Second serial port for debugging
  - PalmPilot upgrade card has 2nd serial port, so serial port can be used for debugging if application uses IR
  - Think of Poser as a second serial port
- Serial analyzer
  - Nice if you have one
  - Nearly crucial if low level timing is an issue

Logging

- Use conditional macros so logging info can be selectively chosen based on problem
- Log to circular RAM buffer
  - Otherwise writing to database interferes with serial communication timing
- Write log to memo pad entry(s) at close of serial device
- Alternatively, write log to HotSync® log

Logging

PalmSource 99

- Some examples…

PalmDebugger with Real Device

PalmSource 99

- Connect to debugger before testing
  - Use shortcut . 1
  - Prevents hangs in ErrorDisplay dialog
- Connect to debugger after Debugger is called (or crash occurs)
  - May have to change connection speeds to match serial device speed to successfully attach to debugger

Poser—Serial Port / IR Emulation

PalmSource 99

- Poser emulates serial port
- IrLib I/O redirected thru serial port when running on Poser
  - Has trouble if receiving connection (timing issues)
  - Works okay if initiating connection
- Have to configure receiving device to use IrDA protocol through serial port

PalmDebugger w/Poser

- Doesn’t use serial to communicate with Poser, so doesn’t get in way of serial driver
- Can test (and debug fatal situations) without the need for a real device

Poser—HostControl

- Better way to do "Printf"
- Another way to do logging
- May not be appropriate for all situations
  - Some things require real device(Ir, Palm VII™)

Header Files for Info Mentioned

PalmSource 99

- (All in Incs/Core/System)
- DLServer.h
- ErrorMgr.h
- HostControl.h


PalmSource™ 99
3Com
More connected.