

- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default


⚠ **MAXIMUM** current per I/O pin is 20mA

⚠ **MAXIMUM** current per +3.3V pin is 50mA

NOTE: CIPO/COPI have previously been referred to as MISO/MOSI

VIN 6-20 V input to the board.





- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default
- Analog
- Communication
- Timer
- Interrupt
- Sercom


MAXIMUM current per I/O pin is 20mA

MAXIMUM current per +3.3V pin is 50mA

NOTE: CIPO/COPI have previously been referred to as MISO/MOSI

VIN 6-20 V input to the board.





Ground

Power

LED

Internal Pin

SWD Pin

Digital Pin

Analog Pin

Other Pin

Microcontroller's Port

Default

Analog

Communication

Timer

Interrupt

Sercom

⚠ MAXIMUM current per I/O pin is 20mA

⚠ MAXIMUM current per +3.3V pin is 50mA

NOTE: CIP0/COPI have previously been referred to as MISO/MOSI

VIN 6-20 V input to the board.



This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/4.0/> or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.