

my boss app — Run Demo Server (Docker)

Audience: DevOps, developers, QA

1. Full demo deploy (recommended)

From repo root:

```
cp .env.example .env
./infrastructure/scripts/deploy-demo-server.sh 127.0.0.1
ALLOW_DEPLOY=1 ./infrastructure/scripts/deploy-mobile-web.sh
./infrastructure/scripts/start-demo-tunnel.sh           # optional: public URL
./infrastructure/scripts/verify-mobile-api.sh 127.0.0.1 --gateway
./infrastructure/scripts/verify-localhost.sh
```

2. Docker compose reference

```
COMPOSE="docker compose -f infrastructure/docker/docker-compose.demo.yml"

$COMPOSE up -d --build
$COMPOSE --profile with-admin up -d --build admin-portal
$COMPOSE ps
$COMPOSE logs -f auth-service
$COMPOSE down
```

3. Published ports

Container	Host port	URL
API gateway	8090	http://HOST:8090/app/ (mobile web)
myboss-auth	3001	http://HOST:8090/auth/api/v1/docs
myboss-user	3002	http://HOST:8090/user/api/v1/docs
myboss-config	3003	http://HOST:8090/config/api/v1/docs (Chat)
myboss-squad	3004	http://HOST:8090/squad/api/v1/docs
myboss-survey	3005	http://HOST:8090/survey/api/v1/docs
myboss-admin	8081	http://HOST:8081 or via gateway <code>/login</code>

4. Swagger documentation

All services expose OpenAPI at `/api/v1/docs` when `APP_ENV=demo` or `SWAGGER_ENABLED=true`.

Chat endpoints are documented under the **Chat** tag in config-service Swagger.

See [`docs/api/CHAT_API.md`](`../api/CHAT_API.md`).

5. Demo login

Role	Email	Notes
Employee	demo@orange.com	OTP in sign-in response (<code>demoOtpCode</code>)
No-squad test	omar.t@orange.com	Chat/gallery locked
Admin	admin@orange.com	admin123

Auth verify endpoint: `POST /auth/verify-2fa` (not verify-otp).

6. Helper scripts

Script	Purpose
<code>deploy-demo-server.sh</code>	Build + start all backend containers
<code>deploy-mobile-web.sh</code>	Build Flutter web → gateway <code>/app/</code>
<code>verify-mobile-api.sh</code>	Governance + JWT + Swagger + chat smoke
<code>verify-localhost.sh</code>	Full local feature verification
<code>verify-backend.sh</code>	Health checks only
<code>start-demo-tunnel.sh</code>	Cloudflare public URL
<code>build-local-android.sh</code>	Demo APK for physical Android devices

7. Android demo APK

```
cd apps/mobile
./build-local-android.sh
```

Output: `build/android-dist/myboss-demo-<lan-ip>.apk`

Install on phone (same Wi-Fi as Mac, or use Cloudflare tunnel URL baked into the APK).

8. Troubleshooting

Issue	Fix
Build fails	<code>docker compose ... build --no-cache</code>
Port in use	<code>docker compose ... down ; lsof -i :8090</code>
401 on squad/chat	Pass <code>Authorization: Bearer {token}</code>
Mobile web stale	<code>ALLOW_DEPLOY=1 ./infrastructure/scripts/deploy-mobile-web.sh</code>

Orange — my boss app — Docker

Orange — my boss app — Generated from 02_RUN_DEMO_SERVER.md