

my boss app — Testing Guide

Audience: QA, developers, DevOps

Covers: Backend smoke tests, Swagger, auth, chat, mobile checklist

1. Automated verification (recommended)

```
# Gateway + JWT + Swagger + chat
./infrastructure/scripts/verify-mobile-api.sh 127.0.0.1 --gateway

# Full localhost (squad, chat send/reply, surveys)
./infrastructure/scripts/verify-localhost.sh

# Backend health only
./infrastructure/scripts/verify-backend.sh
```

2. Swagger UI (interactive API docs)

Service	Local gateway	Direct port
Auth	http://127.0.0.1:8090/auth/api/v1/docs	:3001
User	http://127.0.0.1:8090/user/api/v1/docs	:3002
Config (+ Chat)	http://127.0.0.1:8090/config/api/v1/docs	:3003
Squad	http://127.0.0.1:8090/squad/api/v1/docs	:3004
Survey	http://127.0.0.1:8090/survey/api/v1/docs	:3005

Public tunnel: append `/auth/api/v1/docs` etc. to your Cloudflare base URL.

To test JWT endpoints in Swagger: Authorize → `Bearer {accessToken}` .

3. Backend health

```
curl http://127.0.0.1:8090/health
curl http://127.0.0.1:8090/auth/api/v1/health
```

4. Auth flow (employee)

```
# Step 1 - Sign in
curl -X POST http://127.0.0.1:8090/auth/api/v1/auth/sign-in \
-H "Content-Type: application/json" \
-d '{"email":"demo@orange.com"}'

# Response includes sessionId and demoOtpCode (demo mode)

# Step 2 - Verify OTP (endpoint is verify-2fa)
curl -X POST http://127.0.0.1:8090/auth/api/v1/auth/verify-2fa \
-H "Content-Type: application/json" \
-d '{"sessionId":"<SESSION_ID>","code":"<OTP>"}'
```

Expected: `accessToken` , `refreshToken` , `user` .

Orange error format on failure:

```
{ "code": 41, "reason": "Invalid credentials", "message": "..." }
```

5. Chat API test (native squad messaging)

Full reference: [`docs/api/CHAT_API.md`](`../../api/CHAT_API.md`)

```
# Public
curl http://127.0.0.1:8090/config/api/v1/chat/config
curl http://127.0.0.1:8090/config/api/v1/chat/health

# JWT required
curl http://127.0.0.1:8090/config/api/v1/chat/visitor \
  -H "Authorization: Bearer <ACCESS_TOKEN>"

# Send message
curl -X POST http://127.0.0.1:8090/config/api/v1/chat/messages \
  -H "Authorization: Bearer <ACCESS_TOKEN>" \
  -H "Content-Type: application/json" \
  -d '{"recipientId": "1", "text": "QA test message"}'

# Poll messages
curl "http://127.0.0.1:8090/config/api/v1/chat/messages?peerId=1" \
  -H "Authorization: Bearer <ACCESS_TOKEN>"
```

Mobile chat rules:

- User must be in a **squad** (`demo@orange.com` ✓, `omar.t@orange.com` ✕)
- Contacts = squad members only

6. Admin flow

1. Open: `http://127.0.0.1:8090/login` (or :8081)

1. Login: `admin@orange.com` / `admin123`

7. Through Apigee (after connection)

Replace base with `https://api-demo.orange.com` :

```
curl https://api-demo.orange.com/auth/api/v1/health
curl https://api-demo.orange.com/config/api/v1/chat/config
```

See `03_APIGEE_CONNECTION.md`.

8. Mobile app manual test

Step	Action	Expected
1	Open /app/ , sign in demo@orange.com	OTP screen → home
2	Toggle EN / AR	Labels change
3	Tap Live Chat FAB (home tab)	Squad contact picker
4	Select squad member, send message	Message appears; peer can reply
5	Sign in omar.t@orange.com	Chat FAB hidden / locked
6	Gallery tab	Upload locked without squad
7	Profile → Log out	Returns to sign-in
8	Session wait / invalid token	Redirect to sign-in

9. Backend unit tests

```
cd apps/backend
npm run test:auth
npm run test:user
npm run test:config
npm run test:squad
npm run test:survey
```

10. Test checklist

- ☐ All 5 health endpoints OK
- ☐ All 5 Swagger UIs load
- ☐ Employee sign-in + verify-2fa works
- ☐ JWT required on squad/user/chat (401 without token)
- ☐ Orange error envelope on 401
- ☐ Squad create/join works

- ☐ Chat send + poll between squad members
 - ☐ Chat locked for no-squad user
 - ☐ Survey submit + catalog works
 - ☐ Gallery upload (in-squad user)
 - ☐ Mobile EN/AR + logout + session redirect
 - ☐ Apigee paths (post-integration)
-

Orange — my boss app — QA

Orange — my boss app — Generated from 04_TESTING_GUIDE.md