

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Finding Frequent Itemsets and
Association Rules

Marzena Kryszkiewicz

HUMAN CAPITAL
HUMAN - BEST INVESTMENT

EUROPEAN UNION
EUROPEAN
SOCIAL FUND

Project is co-financed by European Union within European Social Fund

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Basic Notions and Properties

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Association Rules - Informally

- Let item *{fish}* occur in 5% of sales transactions and set *{fish, white wine}* occur in 4% of them. This information allows us to derive an *association rule* stating that:
4 out of 5 customers; that is, 80% of customers who buy fish also buy white wine.
- In order to derive such rules we need to know how many transactions support respective sets of items (or itemsets).

3

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Support of Itemsets

- Let dataset *D* be a set of *transactions*, where each transaction is a subset of items in *I*.
- Support of an itemset X*, denoted by $sup(X)$, is the number of transactions in *D* that contain all items in *X*; that is,
$$sup(X) = |\{T \in D \mid X \subseteq T\}|.$$

4

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Example: Supports of Itemsets

Example dataset *D*

<i>Id</i>	<i>Transaction</i>
<i>T</i> ₁	ABCDEG
<i>T</i> ₂	ABCDEF
<i>T</i> ₃	ABCDEH
<i>T</i> ₄	ABDE
<i>T</i> ₅	ACDEH
<i>T</i> ₆	BCE

- $sup(ABC) = 3$.
- $sup(EH) = 2$.
- Supports of all supersets of *EH* are not greater than 2 either.
- Supports of all subsets of *EH* can be greater than 2.

5

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Relative Support of Itemsets

- Relative support of an itemset X*, denoted by $rSup(X)$, is the ratio of the number of the transactions in *D* that contain all items in *X* to the number of all transactions in *D*:
$$rSup(X) = sup(X) / |D|.$$
- Remark:** $rSup(X)$ can be regarded as an estimation of the probability of the occurrence of itemset *X* in *D*.

6



Example: Relative Supports

Example dataset D

Id	Transaction
T ₁	ABCDEG
T ₂	ABCDEF
T ₃	ABCDEH
T ₄	ABDE
T ₅	ACDEH
T ₆	BCE

- $rSup(ABC) = 3/6 = 50\%$,
- $rSup(EH) = 2/6 \approx 33\%$.

7



Frequent Itemsets

- X is defined a *frequent itemset* if $sup(X) > minSup$,

where $minSup$ is the user-defined threshold value.

- **Basic property of itemsets:** Supports of supersets of an itemset X are not greater than $sup(X)$.

8



Example: In(frequent) Itemsets

Example dataset D

Id	Transaction
T ₁	ABCDEG
T ₂	ABCDEF
T ₃	ABCDEH
T ₄	ABDE
T ₅	ACDEH
T ₆	BCE

- $sup(ABC) = 3$, $sup(EH) = 2$.
- Let $minSup = 2$. Then: ABC is frequent, EH is not frequent.
- Supports of all supersets of EH are not greater than 2 either, hence *supersets of EH are not frequent*.
- However, supports of subsets of EH can be greater than 2. Thus, *it may happen that subsets of EH are frequent*.

9



Association Rules (ARs)

- An *association rule* is an expression associating two itemsets:

$$X \rightarrow Y,$$

where $\emptyset \neq Y \subseteq I$ and $X \subseteq I \setminus Y$.

- X is called an *antecedent* of $X \rightarrow Y$.
- Y is called a *consequent* of $X \rightarrow Y$.
- $X \rightarrow Y$ is said to be *based on* $X \cup Y$, and $X \cup Y$ is called the *base* of $X \rightarrow Y$.

10



Support of Association Rule

- *Support* of $X \rightarrow Y$ is defined as the number of transactions that contains the base of $X \rightarrow Y$; that is,

$$sup(X \rightarrow Y) = sup(X \cup Y).$$

- *Relative support* of $X \rightarrow Y$ is defined as the relative support of its base:

$$rSup(X \rightarrow Y) = rSup(X \cup Y).$$

11



Confidence of Association Rule

- *Confidence* of $X \rightarrow Y$ is defined as the ratio of the number of transactions that contain the base $X \cup Y$ to the number of transactions containing the antecedent X :

$$conf(X \rightarrow Y) = sup(X \rightarrow Y) / sup(X).$$

- **Remark:** $conf(X \rightarrow Y)$ can be regarded as an estimation of the conditional probability that Y occurs in a transaction T provided X occurs in T .

12



Example: Association Rules

Example dataset D

Id	Transaction
T ₁	ABCDEG
T ₂	ABCDEF
T ₃	ABCDEH
T ₄	ABDE
T ₅	ACDEH
T ₆	BCE

$$\text{sup}(ABC) = 3, \text{sup}(A) = 5.$$

Hence:

- $\text{sup}(\{A\} \rightarrow \{BC\}) = \text{sup}(\{ABC\}) = 3,$
- $\text{conf}(\{A\} \rightarrow \{BC\}) = \text{sup}(\{ABC\}) / \text{sup}(\{A\}) = 3/5.$

13



Strong Association Rules

- **Strong association rules (AR)** are defined as those rules in AR whose support is above *minSup* and confidence is above *minConf*, that is,

$$AR = \{X \rightarrow Y \in AR \mid \text{sup}(X \rightarrow Y) > \text{minSup} \wedge \text{conf}(X \rightarrow Y) > \text{minConf}\},$$

where $\text{minSup} \in [0, |D|)$ and $\text{minConf} \in [0, 1)$.

14



Strong ARs and Frequent Itemsets

$$AR = \{X \rightarrow Y \in AR \mid \text{sup}(X \rightarrow Y) > \text{minSup} \wedge \text{conf}(X \rightarrow Y) > \text{minConf}\}$$

$$= \{X \rightarrow Y \in AR \mid \text{sup}(X \cup Y) > \text{minSup} \wedge \text{conf}(X \rightarrow Y) > \text{minConf}\}$$

$$= \{X \rightarrow Y \in AR \mid (X \cup Y) \text{ is frequent} \wedge \text{conf}(X \rightarrow Y) > \text{minConf}\}$$

15



Discovery of Strong Association Rules

AR is discovered in two steps:

- Find frequent itemsets **F** and their supports in dataset D.
- Generate **AR** only from **F**: Let $Z \in \mathbf{F}$, $Z \neq \emptyset$ and $Y \subseteq Z$. Then, any candidate rule $Z \setminus Y \rightarrow Y$ is a strong association one if: $\text{sup}(Z) / \text{sup}(Z \setminus Y) > \text{minConf}$.

16



Finding Frequent Itemsets and Association Rules with Apriori



Finding Frequent Itemsets

- Within each iteration i :
 - Determine supports of candidate itemsets of length i .
 - From those candidates of length i that turned out frequent, create candidates of length $i + 1$.

18



Example: Frequent 1-Itemsets

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acfh
6	bef
7	h
8	af

- Let minSup = 1
- Iteration 1:
 $C_0 \rightarrow F_0: \emptyset_8$
 $C_1 \rightarrow F_1: a_6 b_5 c_4 e_4 f_4 h_3$

19



Example: Frequent 2-Itemsets

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acfh
6	bef
7	h
8	af

- Let minSup = 1
- After iteration 1:
 $F_1: a_6 b_5 c_4 e_4 f_4 h_3$
- Iteration 2:
 $C_2 \rightarrow F_2: ab_4 ac_4 ae_3 af_3 ah_2 bc_3 be_4 bf_2 bh_1$
 $ce_2 cf_2 ch_2 ef_2 eh_0 fh_1$

Itemsets found as infrequent after support calculation.

20



Example: Frequent 3-Itemsets

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acfh
6	bef
7	h
8	af

- Let minSup = 1
- After iteration 2:
 $F_2: ab_4 ac_4 ae_3 af_3 ah_2 bc_3 be_4 bf_2$
 $ce_2 cf_2 ch_2 ef_2$
- Iteration 3:
 $C_3 \rightarrow F_3: abc_3 abe_3 abf_1 abh ace_2 acf_2 ach_2$
 $aef_1 aeh afh bce_2 bcf_1 bef_2 cef_1 ceh$
 cfh

Itemsets found as infrequent as supersets of infrequent itemsets.

21



Example: Frequent 4-Itemsets

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acfh
6	bef
7	h
8	af

- Let minSup = 1
- After iteration 3:
 $F_3: abc_3 abe_3 ace_2 acf_2 ach_2 bce_2 bef_2$
- Iteration 4:
 $C_4 \rightarrow F_4: abce_2 acef aceh acfh$

22



Example: Frequent 5-Itemsets

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acfh
6	bef
7	h
8	af

- Let minSup = 1
- After iteration 4:
 $F_4: abce_2$
- Iteration 5:
 $C_5: -$

23



Example: Found Frequent Itemsets

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acfh
6	bef
7	h
8	af

- \emptyset_8
 $a_6 b_5 c_4 e_4 f_4 h_3$
 $ab_4 ac_4 ae_3 af_3 ah_2 bc_3 be_4 bf_2 ce_2 cf_2 ch_2 ef_2$
 $abc_3 abe_3 ace_2 acf_2 ach_2 bce_2 bef_2$
 $abce_2$
- Note:** Let n be the length of a longest frequent itemset.
Apriori finds in either n or $n+1$ iterations all frequent itemsets.

24



Properties of the Apriori method of creating candidates...

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acfh
6	bef
7	h
8	af

- Let $\text{minSup} = 1$
- After iteration 3:
 $F_3: abc_3 abe_3 ace_2 acf_2 ach_2 bce_2 bef_2$
- Iteration 4:
 $C_4 \rightarrow F_4: abce_2 acef aceh acfh$
- Note: abc and abe are parents of $abce$.
- General observation.** Parents of each candidate of length i are its first two frequent subsets of length $i - 1$.

25



Properties of the Apriori method of creating candidates...

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acfh
6	bef
7	h
8	af

- Let $\text{minSup} = 1$
- After iteration 3:
 $F_3: abc_3 abe_3 ace_2 acf_2 ach_2 bce_2 bef_2$
- Iteration 4:
 $C_4 \rightarrow F_4: abce_2 acef aceh acfh$
- Note: ace and acf are parents of $acef$.

26



Properties of the Apriori method of creating candidates

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acfh
6	bef
7	h
8	af

- Let $\text{minSup} = 1$
- After iteration 3:
 $F_3: abc_3 abe_3 ace_2 acf_2 ach_2 bce_2 bef_2$
- Iteration 4:
 $C_4 \rightarrow F_4: abce_2 acef aceh acfh$
- Why was itemset $bcef$ not created?
Because its second parent $bcf \notin F_3$.

27



Discovery of Association Rules with AprioriRuleGen...

- Candidate rules are built from each non-empty frequent itemset.
- Let Z be a given non-empty frequent itemset. In iteration i , candidate rules of the form:

$$Z \setminus Y \rightarrow Y,$$

where $Y \subset Z$ and $|Y| = i$.

28



Discovery of Association Rules with AprioriRuleGen...

- In iteration $i+1$, consequents of candidate rules of base Z are created by merging i -item consequents of strong association rules of base Z that were found in the previous iteration.
- Property.** Let $r_1: Z \setminus Y \rightarrow Y$ and $r_2: Z \setminus Y' \rightarrow Y'$, where $Y \subset Y'$, be association rules.
 - $\text{conf}(r_1) \geq \text{conf}(r_2)$,
 - If $\text{conf}(r_1) \leq \text{minConf}$, then $\text{conf}(r_2) \leq \text{minConf}$.²⁹



Example of Useless Creation of Candidate Rules

- Example.** Let $\text{minSup} = 1$, $\text{minConf} = 60\%$, base = $\{abce\}_2$, $r_1: ce \rightarrow ab$ [2, 2/2] and $r_2: be \rightarrow ac$ [2, 2/4] be candidate rules considered in iteration 2. So, r_1 is strong, while r_2 is not strong. Let us consider rule r_3 of base $\{abce\}$ whose consequent is the union of the consequents of rules r_1 and r_2 ; that is, rule $r_3: e \rightarrow abc$. Hence:
 - $\text{sup}(r_3) = \text{sup}(\{abce\}) = 2$,
 - $\text{conf}(r_3) = \frac{\text{sup}(\{abce\})}{\text{sup}(\{e\})} \leq \frac{\text{sup}(\{abce\})}{\text{sup}(\{be\})} = \text{conf}(r_2) = \frac{2}{4} < \text{minConf}$.
 Thus, r_3 is not strong.

30



Example: Discovery of ARs...

Frequent itemsets ($\text{minSup} = 1$): \emptyset_8

$a_5 b_5 c_4 e_4 f_4 h_3$
 $ab_4 ac_4 ae_3 af_3 ah_2 bc_3 be_4 bf_2 ce_2 cf_2 ch_2 ef_2$
 $abc_3 abe_3 ace_2 acf_2 ach_2 bce_2 bef_2$
 $abce_2$

Let $\text{minConf} = 60\%$, $Z = abce$.

Iteration 1:

- Consequents of candidate rules: $Y_1 = \{a, b, c, e\}$.
- Candidate rules:
 - $bce \rightarrow a$ [2, 2/2];
 - $ace \rightarrow b$ [2, 2/2];
 - $abe \rightarrow c$ [2, 2/3];
 - $abc \rightarrow e$ [2, 2/3].
- Strong association rules:
 - $bce \rightarrow a$ [2, 2/2];
 - $ace \rightarrow b$ [2, 2/2];
 - $abe \rightarrow c$ [2, 2/3];
 - $abc \rightarrow e$ [2, 2/3].

31



Example: Discovery of ARs...

Frequent itemsets:

\emptyset_8
 $a_5 b_5 c_4 e_4 f_4 h_3$
 $ab_4 ac_4 ae_3 af_3 ah_2 bc_3 be_4 bf_2 ce_2 cf_2 ch_2 ef_2$
 $abc_3 abe_3 ace_2 acf_2 ach_2 bce_2 bef_2$
 $abce_2$

Iteration 2 ($\text{minConf} = 60\%$, $Z = abce$):

- Consequents of ARs found in iteration 1: $Y_1 = \{a, b, c, e\}$.
- Consequents of candidate rules: $Y_2 = \{ab, ac, ae, bc, be, ce\}$.
- Candidate rules:
 - $ce \rightarrow ab$ [2, 2/2]; $ae \rightarrow bc$ [2, 2/3];
 - $be \rightarrow ac$ [2, 2/4]; $ac \rightarrow be$ [2, 2/4];
 - $bc \rightarrow ae$ [2, 2/3]; $ab \rightarrow ce$ [2, 2/4];
- Strong association rules:
 - $ce \rightarrow ab$ [2, 2/2];
 - $bc \rightarrow ae$ [2, 2/3];
 - $ae \rightarrow bc$ [2, 2/3].

32



Example: Discovery of ARs...

Frequent itemsets ($\text{minSup} = 1$): \emptyset_8

$a_5 b_5 c_4 e_4 f_4 h_3$
 $ab_4 ac_4 ae_3 af_3 ah_2 bc_3 be_4 bf_2 ce_2 cf_2 ch_2 ef_2$
 $abc_3 abe_3 ace_2 acf_2 ach_2 bce_2 bef_2$
 $abce_2$

Iteration 3 ($\text{minConf} = 60\%$, $Z = abce$):

- Consequents of ARs found in iteration 2: $Y_2 = \{ab, ae, bc\}$.
- Consequents of candidate rules: $Y_3 = \{abe\}$.
- Candidate rules:
 - $c \rightarrow abe$ [2, 2/4];
- Strong association rules:
 - None

33



Example: Found ARs

Frequent itemsets ($\text{minSup} = 1$): \emptyset_8

$a_5 b_5 c_4 e_4 f_4 h_3$
 $ab_4 ac_4 ae_3 af_3 ah_2 bc_3 be_4 bf_2 ce_2 cf_2 ch_2 ef_2$
 $abc_3 abe_3 ace_2 acf_2 ach_2 bce_2 bef_2$
 $abce_2$

Strong association rules ($\text{minConf} = 60\%$, $Z = abce$):

- $bce \rightarrow a$ [2, 2/2];
- $ace \rightarrow b$ [2, 2/2];
- $abe \rightarrow c$ [2, 2/3];
- $abc \rightarrow e$ [2, 2/3];
- $ce \rightarrow ab$ [2, 2/2];
- $bc \rightarrow ae$ [2, 2/3];
- $ae \rightarrow bc$ [2, 2/3].

34



Important Operations in Apriori and AprioriRuleGen

- An important time-consuming operation in *Apriori* is searching i item candidates supported by a given transaction.
- An important time-consuming operation in *AprioriRuleGen* is searching frequent i itemsets (candidate rule consequents) of a given frequent itemset in order to learn their supports.
- Thus, in both cases i item subsets of a given itemset are searched.

35



Usage of a Hash Tree

- A hash tree is used in order to make the identification of i item subsets of a given itemset efficient.
- In particular, all i item candidate sets are stored in a hash tree.

36

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Creation of a Hash Tree with 3-Itemsets
Candidates...

candidate	coded candidate
abc	123
abe	125
abf	126
ace	135
acf	136
ach	138
aef	156
bce	235
bcf	236
bef	256
beh	258
cef	356

012

123

125

Assumptions:

- $h(x) = x \bmod 3$
- leaf capacity – 2 itemsets

37

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Creation of a Hash Tree with 3-Itemsets
Candidates...

candidate	coded candidate
abc	123
abe	125
abf	126
ace	135
acf	136
ach	138
aef	156
bce	235
bcf	236
bef	256
beh	258
cef	356

012

012

123

125

Assumptions:

- $h(x) = x \bmod 3$
- leaf capacity – 2 itemsets

38

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Creation of a Hash Tree with 3-Itemsets
Candidates...

candidate	coded candidate
abc	123
abe	125
abf	126
ace	135
acf	136
ach	138
aef	156
bce	235
bcf	236
bef	256
beh	258
cef	356

012

012

012

123

125

126

Assumptions:

- $h(x) = x \bmod 3$
- leaf capacity – 2 itemsets

39

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Creation of a Hash Tree with 3-Itemsets
Candidates...

candidate	coded candidate
abc	123
abe	125
abf	126
ace	135
acf	136
ach	138
aef	156
bce	235
bcf	236
bef	256
beh	258
cef	356

012

012

012

135

136

123

125

126

Assumptions:

- $h(x) = x \bmod 3$
- leaf capacity – 2 itemsets

40

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Creation of a Hash Tree with 3-Itemsets
Candidates...

candidate	coded candidate
abc	123
abe	125
abf	126
ace	135
acf	136
ach	138
aef	156
bce	235
bcf	236
bef	256
beh	258
cef	356

012

012

012

012

136

135

138

123

125

126

Assumptions:

- $h(x) = x \bmod 3$
- leaf capacity – 2 itemsets

41

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Creation of a Hash Tree with 3-Itemsets
Candidates...

candidate	coded candidate
abc	123
abe	125
abf	126
ace	135
acf	136
ach	138
aef	156
bce	235
bcf	236
bef	256
beh	258
cef	356

012

012

012

012

136

135

138

123

125

126

156

Assumptions:

- $h(x) = x \bmod 3$
- leaf capacity – 2 itemsets

42

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Creation of a Hash Tree with 3-Itemsets
Candidates...

candidate	coded candidate
abc	123
abe	125
abf	126
ace	135
acf	136
ach	138
aef	156
bce	235
bcf	236
bef	256
beh	258
cef	356

Assumptions:

- $h(x) = x \bmod 3$
- leaf capacity – 2 itemsets

43

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Creation of a Hash Tree with 3-Itemsets
Candidates...

candidate	coded candidate
abc	123
abe	125
abf	126
ace	135
acf	136
ach	138
aef	156
bce	235
bcf	236
bef	256
beh	258
cef	356

Assumptions:

- $h(x) = x \bmod 3$
- leaf capacity – 2 itemsets

44

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Creation of a Hash Tree with 3-Itemsets
Candidates

candidate	coded candidate
abc	123
abe	125
abf	126
ace	135
acf	136
ach	138
aef	156
bce	235
bcf	236
bef	256
beh	258
cef	356

Assumptions:

- $h(x) = x \bmod 3$
- leaf capacity – 2 itemsets

45

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Candidate 3-Itemsets in a Hash Tree

candidate	coded candidate
abc	123
abe	125
abf	126
ace	135
acf	136
ach	138
aef	156
bce	235
bcf	236
bef	256
beh	258
cef	356

Assumptions:

- $h(x) = x \bmod 3$
- leaf capacity – 2 itemsets

46

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Searching for Subsets in a Hash Tree...

candidate	coded candidate
abc	123
abe	125
abf	126
...	...

Assumption:

- $h(x) = x \bmod 3$

transaction	coded transaction
...	...
bcef	2356
...	...

- 4 subsets of transaction *bcef* (after coding: 2356) were found.

47

WARSAW UNIVERSITY OF TECHNOLOGY

DEVELOPMENT PROGRAMME

Example: Searching for Subsets in a Hash Tree

candidate	coded candidate
abc	123
abe	125
abf	126
...	...

Assumption:

- $h(x) = x \bmod 3$

transaction	coded transaction
...	...
acde	1345
...	...

- 1 subset of transaction *acde* (after coding: 1345) was found.

48

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Finding Frequent Itemsets with Eclat, dEclat & Partition

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Calculating F 's with Eclat...

Id Transaction

1	{abc}
2	{abc}
3	{abc}
4	{ab}
5	{bcd}

- Tidlists (lists of transaction identifiers) of length 1:
 - $t(\{a\}) = \{1,2,3,4\}$, so $sup(\{a\}) = 4$
 - $t(\{b\}) = \{1,2,3,4,5\}$, so $sup(\{b\}) = 5$
 - $t(\{c\}) = \{1,2,3,5\}$, so $sup(\{c\}) = 4$
 - ...
- Tidlists of length 2:
 - $t(\{ab\}) = t(\{a\}) \cap t(\{b\}) = \{1,2,3,4\} \cap \{1,2,3,4,5\} = \{1,2,3,4\}$, so $sup(\{ab\}) = 4$
 - $t(\{ac\}) = t(\{a\}) \cap t(\{c\}) = \{1,2,3,4\} \cap \{1,2,3,5\} = \{1,2,3\}$, so $sup(\{ac\}) = 3$
 - ...

50

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Calculating F 's with Eclat

Id Transaction

1	{abc}
2	{abc}
3	{abc}
4	{ab}
5	{bc}

- Tidlists of length 2:
 - $t(\{ab\}) = \{1,2,3,4\}$, $sup(\{ab\}) = 4$
 - $t(\{ac\}) = \{1,2,3\}$, $sup(\{ac\}) = 3$
 - ...
- Tidlists of length 3:
 - $t(\{abc\}) = t(\{ab\}) \cap t(\{c\}) = \{1,2,3,4\} \cap \{1,2,3\} = \{1,2,3\}$, so $sup(\{abc\}) = 3$
 - ...

51

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Eclat: Calculating F 's with Eclat

Assumption: $minSup = 2$

Id Transaction

1	{abc}
2	{abc}
3	{abc}
4	{ab}
5	{bcd}

52

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Calculating F 's with dEclat...

Id Transaction

1	{abc}
2	{abc}
3	{abc}
4	{ab}
5	{bcd}

- Difflists (differential lists of transaction identifiers) of length 1:
 - $d(\{a\}) = \{5\}$, so $sup(\{a\}) = sup(\emptyset) - |\{5\}| = 4$
 - $d(\{b\}) = \{\}$, so $sup(\{b\}) = sup(\emptyset) - |\{\}| = 5$
 - $d(\{c\}) = \{4\}$, so $sup(\{c\}) = sup(\emptyset) - |\{4\}| = 4$
 - $d(\{d\}) = \{1,2,3,4\}$, so $sup(\{d\}) = sup(\emptyset) - |\{1,2,3,4\}| = 1$
- Difflists of length 2:
 - $d(\{ab\}) = d(\{b\}) \setminus d(\{a\}) = \{\} \setminus \{5\} = \{\}$, so $sup(\{ab\}) = sup(\{a\}) - |\{\}| = 4 - 0 = 4$
 - $d(\{ac\}) = d(\{c\}) \setminus d(\{a\}) = \{4\} \setminus \{5\} = \{4\}$, so $sup(\{ac\}) = sup(\{a\}) - |\{4\}| = 4 - 1 = 3$
 - $d(\{cd\}) = d(\{d\}) \setminus d(\{c\}) = \{1,2,3,4\} \setminus \{4\} = \{1,2,3\}$, so $sup(\{cd\}) = sup(\{c\}) - |\{1,2,3\}| = 4 - 3 = 1$
 - ...

53

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Calculating F 's with dEclat

Id Transaction

1	{abce}
2	{abc}
3	{abc}
4	{ab}
5	{bcd}

- Difflists of length 2:
 - $d(\{ab\}) = \{\}$, $sup(\{ab\}) = 4$
 - $d(\{ac\}) = \{4\}$, $sup(\{ac\}) = 3$
 - ...
- Difflists of length 3:
 - $d(\{abc\}) = d(\{ac\}) \setminus d(\{ab\}) = \{4\} \setminus \{\} = \{4\}$, so $sup(\{abc\}) = sup(\{ab\}) - |\{4\}| = 4 - 1 = 3$
 - ...

54

Example: Calculating F 's with dEclat

Assumption:
• $minSup = 2$

Id	Transaction
1	{abc}
2	{abc}
3	{abc}
4	{ab}
5	{bcd}

$d(X \cup Y) = [d(X) \cup d(Y)] \setminus d(X) = d(Y) \setminus d(X)$
 $sup(X \cup Y) = sup(X) - |d(X \cup Y)|$

55

Calculating F 's with Partition

Assumptions:
 - $minSup = 3$
 - Partition of a transaction dataset into $k = 2$ blocks

Id	Transaction Block
1	{a}
2	{ab}
3	{bc}
4	{acd}
5	{ac}

Local support threshold
 $minSup' = \left\lceil \frac{minSup}{k} \right\rceil = \left\lceil \frac{3}{2} \right\rceil = 2$

Local frequent itemsets (w.r.t. $minSup'$):
 - $F = \{a_2, b_2\}$
 - $F^I = \{a_2, c_2, ac_2\}$

(Global) frequent itemsets (w.r.t. $minSup$):
 - $C = F \cup F^I = \{a, b, c, ac\}$
 - $F = \{a_4\}$

56

Dealing with Non-Transactional Data

57

Transactional Data Set + Taxonomies

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acth
6	bef
7	h
8	af

58

Transactional Data Set with Taxonomies Included in Transactions

Tid	Items
1	abceFSVE
2	abcefFSVME
3	abchFSME
4	abeFVE
5	acthFSME
6	befFVME
7	hM
8	afFME

59

Transactional Data Set + Taxonomies + User Constraints

Tid	Items
1	abceFV
2	abcefFMV
3	abchFM
4	abeV
5	acthFM
6	befFMV
7	hM
8	afFM

60

Transactional Data Set + Negated Items

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acfh
6	bef
7	h
8	af

6 positive items {abcefh}

6 negated items {abcefh}

Tid	Items
1	abcefh
2	abcefh
3	abchef
4	abecfh
5	acfhbe
6	befach
7	habcef
8	afbceh

61

Transactional Data Set + Negated Items

Tid	Items
1	abce
2	abcef
3	abch
4	abe
5	acfh
6	bef
7	h
8	af

6 positive items {abcefh}

6 negated items {abcefh}

$sup(\{befh\}) = 2$
 $conf(\{b\} \rightarrow \{eh\}) = 2/3$
 $conf(\{bh\} \rightarrow \{ef\}) = 2/4$

Tid	Items
1	abcefh
2	abcefh
3	abchef
4	abecfh
5	acfhbe
6	befach
7	habcef
8	afbceh

62

Transactional Data Set + Negated Items

Tid	Items
1	abcefh
2	abcefh
3	abchef
4	abecfh
5	acfhbe
6	befach
7	habcef
8	afbceh

Tid	Items
1	1 2 3 4 11 12
2	1 2 3 4 5 12
3	1 2 3 6 11 12
4	1 2 4 10 11 12
5	1 3 5 6 8 10
6	2 4 5 7 9 12
7	6 7 8 9 10 11
8	1 5 8 9 10 12

Item	a	b	c	e	f	h	a	b	c	e	f	h
item id	1	2	3	4	5	6	7	8	9	10	11	12

Transactional Data Set + Negated Items...

Let n be the number of all distinct items.

Max. number of potentially frequent itemsets without negation = 2^n .

Max. number of potentially frequent itemsets admitting negation = 3^n .

n	max. # itemsets without negation	max. # itemsets admitting negation	difference in orders of magnitude
6	64	729	1
10	1024	59049	2
50	1.13E+15	7.17898E+23	8
100	1.27E+30	5.15378E+47	17
500	3.3E+150	3.636E+238	88

Relational Data → Transactional Data

Height	Colour	Grade
tall	green	5
short	black	4
short	green	4

Tid	Items
1	{1, 3, 6}
2	{2, 4, 5}
3	{2, 3, 5}

Item	(H=tall)	(H=short)	(C=green)	(C=black)	(G=4)	(G=5)
item id	1	2	3	4	5	6
attribute	1	1	2	2	3	3

65

Relational Data → Transactional Data

Height	Colour	Grade
tall	green	5
short	black	4
short	green	4

Tid	Items
1	{1, 3, 6}
2	{2, 4, 5}
3	{2, 3, 5}

Item	(H=tall)	(H=short)	(C=green)	(C=black)	(G=4)	(G=5)
item id	1	2	3	4	5	6
attribute	1	1	2	2	3	3

$\{2\} \rightarrow \{5\}$ [2, 2/2]. So, $(H=short) \rightarrow (G=4)$ [2, 100%].
 $\{3\} \rightarrow \{5\}$ [1, 1/2]. So, $(C=green) \rightarrow (G=4)$ [1, 50%].
 $\{2,3\} \rightarrow \{5\}$ [1, 1/1]. So, $(H=short) \wedge (C=green) \rightarrow (G=4)$ [1, 100%].

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

References...

- Agrawal R., Imielinski T., Swami A.: Mining Associations Rules between Sets of Items in Large Databases. In: Proc. of the ACM SIGMOD Conference on Management of Data, Washington, USA (1993) 207–216
- Rakesh Agrawal, Ramakrishnan Srikant: Fast Algorithms for Mining Association Rules in Large Databases. [VLDB 1994](#): 487-499
- Agrawal R., Mannila H., Srikant R., Toivonen H., Verkamo A.I.: Fast Discovery of Association Rules. In: Fayyad U.M., Piatetsky-Shapiro G., Smyth P., Uthurusamy R. (eds.): Advances in Knowledge Discovery and Data Mining. AAAI, CA (1996) 307–328

67

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

References

- Jiawei Han, Micheline Kamber, Jian Pei: Data Mining: Concept and Techniques, The Morgan Kaufmann Series in Data Management Systems, 2011
- Kryszkiewicz, M.: Concise Representations of Frequent Patterns and Association Rules. Prace Naukowe Politechniki Warszawskiej. Elektronika 142. Publishing House of the Warsaw University of Technology (2002)
- Ashok Savasere, Edward Omiecinski, Shamkant B. Navathe: An Efficient Algorithm for Mining Association Rules in Large Databases. [VLDB 1995](#): 432-444
- Mohammed Javeed Zaki, Karam Gouda: Fast vertical mining using diffsets. [KDD 2003](#): 326-335

68

WARSAW UNIVERSITY OF TECHNOLOGY
DEVELOPMENT PROGRAMME

Additional References – Other Algorithms for Discovery of Frequent Itemsets

- Ferenc Bodon: A fast APRIORI implementation. FIMI 2003
- Chen Wang, Mingsheng Hong, Jian Pei, Haofeng Zhou, Wei Wang, Baile Shi: Efficient Pattern-Growth Methods for Frequent Tree Pattern Mining. PAKDD 2004: 441-451
- Frequent Itemset Mining Implementations Repository: <http://fimi.ua.ac.be/src/>

69