



Cameleonica: Conceptual Design

Functional and quality requirements for acceptable usability

Arkadiusz Bulski

Abstract

This paper describes a conceptual design of the project, that is the functionality, the semantics, the characteristics, and the quality that will be offered to end users. Rationale for some fundamental decisions is explained. Operational scenarios are presented, followed with acceptance tests to establish an acceptable level of usability.

Introduction

Cameleonica project is an innovative filesystem design. Both new commands and well established commands with new semantics are given into hands of end users. Both are highly specialized and broad in application. Consider following operations.

Committing and reverting history of changes is typical of version control systems, with Git for example. Encrypting entire disks is quite common, with TrueCrypt. Hiding files and even entire systems on disk is possible, again with TrueCrypt. Compressing and hashing files is a standard operation, with built-in utilities. They are all available separately, and furthermore, they are all implemented outside of any filesystem. This approach is good for simplicity, as underlying filesystems need to implement only very basic operations. However, an opportunity is missed this way. Filesystem is put into a position where it can provide guarantees that are not achievable to unprivileged programs having no access to underlying storage device, or precompute/cache data for more than one application in a trusted manner. This project aims to offer exactly that.

Whole project can be defined in few (somehow separate) parts: backend system calls and language bindings through which user processes can access content, semantics and features, frontend command-line and graphical tools with which users can manage entire filesystem, on-disk format to which other implementations can refer to, standards compliance, etc.

System call interface

Processes gain access to files through a long existed mechanism called syscalls. For any filesystem to be accessible, certain syscalls need to be implemented. POSIX and Linux standards specify the details. We shall skip the specifics of what exactly needs to be implemented and how, and generally say that following syscalls will need to be provided:

open, creat, read, write, pread, pwrite, readv, writev, lseek, dup, close, chown, chmod, fallocate, ftruncate, utime, link, symlink, unlink, mkdir, rmdir, rename, fsync, fdatasync, fsyncdir, sync, access, stat, statfs, fcntl, ioctl, flock, getdents, listxattr, getxattr, setxattr, removexattr, quotactl, getrlimit, setrlimit

List above may not be accurate. Some syscalls may be removed or added later on. The list only provides a basis for further, more elaborate evaluation of what needs to be provided to meet expectations of super users. Other, modern, popular filesystems may be used to define how these syscalls should work, in addition to on-paper specifications.

Above that, syscalls may be subject to semantics related to specialized features that are Cameleonica-specific and have no counterpart in other filesystems. How operations are affected by these semantics will be defined in further sections, with regard to filesystem as a whole rather than single operations.

Command-line interface

Syscalls can be used to access files within a mounted filesystem but the filesystem must first be created with command-line utilities. Further management of the filesystem would also be done using utilities. Following operations should be available:

- ✓ initializing a filesystem within a container file (regular file or block device)
- ✓ changing volume settings offline (masterkeys)
- ✓ mounting a possibly interrupted filesystem
- ✓ querying file details (fragment mappings)
- ✓ changing file settings online (auto-compression)
- ✓ checking integrity, defragmenting, compressing files
- ✓ management of snapshots and revisions
- ✓ serialization into a compact incremental backup
- ✓ resizing and moving underlying partition on-line
- ✓ emergency recovery of a broken filesystem
- ✓ destruction of a decommissioned filesystem

All operations must be accessible through command-line, either through basic system utilities (cat, fallocate) or with specialized commands listed above.

Graphical user interface

Most management operations are traditionally done with command-line tools. There are however few applications where information may be presented more intuitively with graphics. Following operations could be also available through graphical tools:

- ✓ configuring per-volume and per-file settings
- ✓ checking integrity, defragmenting, compressing files
- ✓ management of snapshots and revisions

Specific details of what information should be presented to user and what changes are allowed will be defined in further sections, when discussing specific features. We shall consider graphical tools as convenient extension of command-line tools. Operations must primarily be accessible through command-line.

Programming language interface

While management can be done with command-line tools, sometimes operations need to be performed in a more automatic way. Program sources usually do not refer directly to syscalls or commands, but rather to language-specific modules that act as wrappers. Cameleonica-specific features should be accessible in at least following languages:

- ✓ C, C#, Java, Python, Ruby

Operations on files should be available via bindings and include at least the following, but may include more:

- ✓ querying file details (fragment mappings)
- ✓ changing file settings online (safety semantics)
- ✓ checking integrity, defragmenting, compressing files
- ✓ management of snapshots and revisions

Additionally, operations on entire filesystem should also be available via another set of classes and methods.

???