



# Creating Private Image Registries

NetApp Solutions

NetApp  
October 20, 2023

This PDF was generated from [https://docs.netapp.com/us-en/netapp-solutions/containers/rh-os-n\\_private\\_registry.html](https://docs.netapp.com/us-en/netapp-solutions/containers/rh-os-n_private_registry.html) on October 20, 2023. Always check docs.netapp.com for the latest.

# Table of Contents

Creating Private Image Registries .....	1
Creating A private image registry .....	1

# Creating Private Image Registries

For most deployments of Red Hat OpenShift, using a public registry like [Quay.io](https://quay.io) or [DockerHub](https://hub.docker.com/) meets most customer's needs. However there are times when a customer may want to host their own private or customized images.

This procedure documents creating a private image registry which is backed by a persistent volume provided by Astra Trident and NetApp ONTAP.



Astra Control Center requires a registry to host the images the Astra containers require. The following section describes the steps to setup a private registry on Red Hat OpenShift cluster and pushing the images required to support the installation of Astra Control Center.

## Creating A private image registry

1. Remove the default annotation from the current default storage class and annotate the Trident-backed storage class as default for the OpenShift cluster.

```
[netapp-user@rhel7 ~]$ oc patch storageclass thin -p '{"metadata": {"annotations": {"storageclass.kubernetes.io/is-default-class": "false"}}}'
storageclass.storage.k8s.io/thin patched

[netapp-user@rhel7 ~]$ oc patch storageclass ocp-trident -p '{"metadata": {"annotations": {"storageclass.kubernetes.io/is-default-class": "true"}}}'
storageclass.storage.k8s.io/ocp-trident patched
```

2. Edit the imageregistry operator by entering the following storage parameters in the `spec` section.

```
[netapp-user@rhel7 ~]$ oc edit
configs.imageregistry.operator.openshift.io

storage:
  pvc:
    claim:
```

3. Enter the following parameters in the `spec` section for creating a OpenShift route with a custom hostname. Save and exit.

```
routes:
  - hostname: astra-registry.apps.ocp-vmw.cie.netapp.com
    name: netapp-astra-route
```



The above route config is used when you want a custom hostname for your route. If you want OpenShift to create a route with a default hostname, you can add the following parameters to the `spec` section: `defaultRoute: true`.

## Custom TLS certificates

When you are using a custom hostname for the route, by default, it uses the default TLS configuration of the OpenShift Ingress operator. However, you can add a custom TLS configuration to the route. To do so, complete the following steps.

- a. Create a secret with the route's TLS certificates and key.

```
[netapp-user@rhel7 ~]$ oc create secret tls astra-route-tls -n openshift-image-registry --cert=/home/admin/netapp-astra/tls.crt --key=/home/admin/netapp-astra/tls.key
```

- b. Edit the imageregistry operator and add the following parameters to the `spec` section.

```
[netapp-user@rhel7 ~]$ oc edit configs.imageregistry.operator.openshift.io

routes:
  - hostname: astra-registry.apps.ocp-vmw.cie.netapp.com
    name: netapp-astra-route
    secretName: astra-route-tls
```

4. Edit the imageregistry operator again and change the management state of the operator to the `Managed` state. Save and exit.

```
oc edit configs.imageregistry/cluster

managementState: Managed
```

5. If all the prerequisites are satisfied, PVCs, pods, and services are created for the private image registry. In a few minutes, the registry should be up.

```
[netapp-user@rhel7 ~]$ oc get all -n openshift-image-registry
```

NAME	READY	STATUS
RESTARTS    AGE		
pod/cluster-image-registry-operator-74f6d954b6-rb7zr	1/1	Running
3            90d		

```

pod/image-pruner-1627257600-f5cpj      0/1      Completed
0          2d9h
pod/image-pruner-1627344000-swqx9      0/1      Completed
0          33h
pod/image-pruner-1627430400-rv5nt      0/1      Completed
0          9h
pod/image-registry-6758b547f-6pnj8      1/1      Running
0          76m
pod/node-ca-bwb5r                      1/1      Running
0          90d
pod/node-ca-f8w54                      1/1      Running
0          90d
pod/node-ca-gjx7h                      1/1      Running
0          90d
pod/node-ca-lcx4k                      1/1      Running
0          33d
pod/node-ca-v7zmx                      1/1      Running
0          7d21h
pod/node-ca-xpppp                      1/1      Running
0          89d

```

NAME	TYPE	CLUSTER-IP	EXTERNAL-
IP PORT(S) AGE			
service/image-registry 5000/TCP 15h	ClusterIP	172.30.196.167	<none>
service/image-registry-operator 60000/TCP 90d	ClusterIP	None	<none>

NAME	DESIRED	CURRENT	READY	UP-TO-DATE
AVAILABLE NODE SELECTOR AGE				
daemonset.apps/node-ca kubernetes.io/os=linux 90d	6	6	6	6

NAME	READY	UP-TO-DATE
AVAILABLE AGE		
deployment.apps/cluster-image-registry-operator 90d	1/1	1
deployment.apps/image-registry 15h	1/1	1

NAME	DESIRED
CURRENT READY AGE	
replicaset.apps/cluster-image-registry-operator-74f6d954b6 1 90d	1
replicaset.apps/image-registry-6758b547f 1 76m	1

```

replicaset.apps/image-registry-78bfbd7f59      0      0
0      15h
replicaset.apps/image-registry-7fcc8d6cc8      0      0
0      80m
replicaset.apps/image-registry-864f88f5b      0      0
0      15h
replicaset.apps/image-registry-cb47fffb      0      0
0      10h

NAME                                         COMPLETIONS   DURATION   AGE
job.batch/image-pruner-1627257600          1/1           10s        2d9h
job.batch/image-pruner-1627344000          1/1           6s         33h
job.batch/image-pruner-1627430400          1/1           5s         9h

NAME                                         SCHEDULE      SUSPEND     ACTIVE     LAST
SCHEDULE   AGE
cronjob.batch/image-pruner                  0 0 * * *      False       0          9h
90d

NAME                                         HOST/PORT
PATH     SERVICES          PORT     TERMINATION  WILDCARD
route.route.openshift.io/public-routes     astra-registry.apps.ocp-
vmw.cie.netapp.com                          image-registry <all>    reencrypt    None

```

6. If you are using the default TLS certificates for the ingress operator OpenShift registry route, you can fetch the TLS certificates using the following command.

```

[netapp-user@rhel7 ~]$ oc extract secret/router-ca --keys=tls.crt -n
openshift-ingress-operator

```

7. To allow OpenShift nodes to access and pull the images from the registry, add the certificates to the docker client on the OpenShift nodes. Create a configmap in the openshift-config namespace using the TLS certificates and patch it to the cluster image config to make the certificate trusted.

```

[netapp-user@rhel7 ~]$ oc create configmap astra-ca -n openshift-config
--from-file=astraregistry.apps.ocp-vmw.cie.netapp.com=tlscert

[netapp-user@rhel7 ~]$ oc patch image.config.openshift.io/cluster
--patch '{"spec":{"additionalTrustedCA":{"name":"astra-ca"}}}'
--type=merge

```

8. The OpenShift internal registry is controlled by authentication. All the OpenShift users can access the OpenShift registry, but the operations that the logged in user can perform depends on the user permissions.

- a. To allow a user or a group of users to pull images from the registry, the user(s) must have the registry-viewer role assigned.

```
[netapp-user@rhel7 ~]$ oc policy add-role-to-user registry-viewer ocp-user

[netapp-user@rhel7 ~]$ oc policy add-role-to-group registry-viewer ocp-user-group
```

- b. To allow a user or group of users to write or push images, the user(s) must have the registry-editor role assigned.

```
[netapp-user@rhel7 ~]$ oc policy add-role-to-user registry-editor ocp-user

[netapp-user@rhel7 ~]$ oc policy add-role-to-group registry-editor ocp-user-group
```

9. For OpenShift nodes to access the registry and push or pull the images, you need to configure a pull secret.

```
[netapp-user@rhel7 ~]$ oc create secret docker-registry astra-registry-credentials --docker-server=astra-registry.apps.ocp-vmw.cie.netapp.com --docker-username=ocp-user --docker-password=password
```

10. This pull secret can then be patched to serviceaccounts or be referenced in the corresponding pod definition.

- a. To patch it to service accounts, run the following command.

```
[netapp-user@rhel7 ~]$ oc secrets link <service_account_name> astra-registry-credentials --for=pull
```

- b. To reference the pull secret in the pod definition, add the following parameter to the `spec` section.

```
imagePullSecrets:
  - name: astra-registry-credentials
```

11. To push or pull an image from workstations apart from OpenShift node, complete the following steps.
  - a. Add the TLS certificates to the docker client.

```
[netapp-user@rhel7 ~]$ sudo mkdir /etc/docker/certs.d/astra-registry.apps.ocp-vmw.cie.netapp.com

[netapp-user@rhel7 ~]$ sudo cp /path/to/tls.crt
/etc/docker/certs.d/astra-registry.apps.ocp-vmw.cie.netapp.com
```

b. Log into OpenShift using the `oc login` command.

```
[netapp-user@rhel7 ~]$ oc login --token=sha256~D49SpB_lesSrJYwrM0LIO-VRcjWHu0a27vKa0 --server=https://api.ocp-vmw.cie.netapp.com:6443
```

c. Log into the registry using OpenShift user credentials with the `podman/docker` command.

#### **podman**

```
[netapp-user@rhel7 ~]$ podman login astra-registry.apps.ocp-vmw.cie.netapp.com -u kubeadmin -p $(oc whoami -t) --tls
-verify=false
```

+

NOTE: If you are using `kubeadmin` user to log into the private registry, then use token instead of password.

#### **docker**

```
[netapp-user@rhel7 ~]$ docker login astra-registry.apps.ocp-vmw.cie.netapp.com -u kubeadmin -p $(oc whoami -t)
```

+

NOTE: If you are using `kubeadmin` user to log into the private registry, then use token instead of password.

d. Push or pull the images.



### podman

```
[netapp-user@rhel7 ~]$ podman push astra-registry.apps.ocp-vmw.cie.netapp.com/netapp-astra/vault-controller:latest  
[netapp-user@rhel7 ~]$ podman pull astra-registry.apps.ocp-vmw.cie.netapp.com/netapp-astra/vault-controller:latest
```

### docker

```
[netapp-user@rhel7 ~]$ docker push astra-registry.apps.ocp-vmw.cie.netapp.com/netapp-astra/vault-controller:latest  
[netapp-user@rhel7 ~]$ docker pull astra-registry.apps.ocp-vmw.cie.netapp.com/netapp-astra/vault-controller:latest
```

Next: [Solution Validation/Use Cases: Red Hat OpenShift with NetApp.](#)

## Copyright information

Copyright © 2023 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.