

# **AWS FSx ONTAP and EC2 Provision**

**NetApp Solutions** 

NetApp October 20, 2023

# **Table of Contents**

AW	S FSx ONTAP Cluster and EC2 Instance Provision	1
F	Purpose	1
A	Audience	1
L	icense	1
S	Solution deployment	1
٧	Where to find additional information	6

# AWS FSx ONTAP Cluster and EC2 Instance Provision

NetApp Solutions Engineering Team

#### **Purpose**

This toolkit automates the tasks of provisioning of an AWS FSx ONTAP storage cluster and an EC2 compute instance, which can be subsequently used for database deployment.

This solution addresses the following use cases:

- Provision an EC2 compute instance in AWS cloud in a predefined VPC subnet and set ssh key for EC2 instance access as ec2-user.
- Provision an AWS FSx ONTAP storage cluster in desired availability zones and configure a storage SVM and set cluster admin user fsxadmin password.

#### **Audience**

This solution is intended for the following people:

- A DBA who manages databases in AWS EC2 environment.
- A database solution architect who is interested in database deployment in AWS EC2 ecosystem.
- A storage administrator who manages AWS FSx ONTAP storage that supports databases.
- An application owner who likes to standup database in AWS EC2 ecosystem.

#### License

By accessing, downloading, installing or using the content in this GitHub repository, you agree the terms of the License laid out in License file.



There are certain restrictions around producing and/or sharing any derivative works with the content in this GitHub repository. Please make sure you read the terms of the License before using the content. If you do not agree to all of the terms, do not access, download or use the content in this repository.

### Solution deployment

Prerequisites for deployment

Deployment requires the following prerequisites.

An Organization and AWS account has been setup in AWS public cloud
An user to run the deployment has been created
IAM roles has been configured
IAM roles granted to user to permit provisioning the resources

VPC and security configuration

- A VPC has been created to host the resources to be provisioned
- A security group has been configured for the VPC
- A ssh key pair has been created for EC2 instance access

Network configuration

Subnets has been created for VPC with network segments assigned Route tables and network ACL configured
NAT gateways or internet gateways configured for internet access

#### Download the toolkit

git clone https://github.com/NetApp/na\_aws\_fsx\_ec2\_deploy.git

#### Connectivity and authentication

The toolkit is supposed to be executed from an AWS cloud shell. AWS cloud shell is a browser-based shell that makes it easy to securely manage, explore, and interact with your AWS resources. CloudShell is pre-authenticated with your console credentials. Common development and operations tools are pre-installed, so no local installation or configuration is required.

#### Terraform provider.tf and main.tf files configuration

The provider.tf defines the provider that Terraform is provisioning resources from via API calls. The main.tf defines the resources and attributes of resources that are to be provisioned. Following are some details:

```
provider.tf:
  terraform {
    required_providers {
        aws = {
            source = "hashicorp/aws"
            version = "~> 4.54.0"
        }
    }
}
```

```
main.tf:
  resource "aws_instance" "ora_01" {
                                  = var.ami
                                  = var.instance_type
    instance_type
    subnet id
                                  = var.subnet id
    key name
                                  = var.ssh key name
   root_block_device {
                                  = "qp3"
     volume type
      volume size
                                  = var.root volume size
    tags = {
      Name
                                  = var.ec2_tag
  }
  . . . .
```

#### Terraform variables.tf and terraform.tfvars configuration

The variables.tf declares the variables to be used in main.tf. The terraform.tfvars contains the actual values for the variables. Following are some examples:

```
variables.tf:
  ### EC2 instance variables ###
variable "ami" {
 type = string
 description = "EC2 AMI image to be deployed"
}
variable "instance type" {
 type = string
 description = "EC2 instance type"
}
. . . .
terraform.tfvars:
 # EC2 instance variables
ami
                      = "ami-06640050dc3f556bb" //RedHat 8.6 AMI
instance_type
                     = "t2.micro"
ec2_tag
                    = "ora 01"
                    = "subnet-04f5fe7073ff514fb"
subnet id
ssh_key_name
                    = "sufi new"
                    = 30
root_volume_size
. . . .
```

#### Step by step procedures - executed in sequence

1. Install Terraform in AWS cloud shell.

git clone https://github.com/tfutils/tfenv.git ~/.tfenv

mkdir ~/bin

ln -s ~/.tfenv/bin/\* ~/bin/

tfenv install

tfenv use 1.3.9

2. Download the toolkit from NetApp GitHub public site

git clone https://github.com/NetApp-Automation/na\_aws\_fsx\_ec2\_deploy.git

3. Run init to initialize terraform

terraform init

4. Output the execution plan

terraform plan -out=main.plan

5. Apply the execution plan

terraform apply "main.plan"

6. Run destroy to remove the resources when done

terraform destroy

## Where to find additional information

where to find additional information		
To learn more about the NetApp solution automation, review the following website NetApp Solution Automation		

#### Copyright information

Copyright © 2023 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

#### **Trademark information**

NETAPP, the NETAPP logo, and the marks listed at <a href="http://www.netapp.com/TM">http://www.netapp.com/TM</a> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.