

BestServe API — Client Documentation

Version: v1

This document describes the BestServe API endpoints, request/response schemas, and example payloads intended for client developers. Authentication uses a Bearer JWT returned by **/api/Auth/token**. Include the token in the HTTP Authorization header: Authorization: Bearer <token>

Auth - Get Token

Method: POST **Path:** /api/Auth/token

Returns authentication token for partners (client credentials). Use this token as Bearer when calling protected endpoints.

Request Schema:

```
{ "type": "object", "properties": { "clientId": { "type": "string", "nullable": true }, "clientSecret": { "type": "string", "nullable": true } } }
```

Response Schema / Type:

```
{ "200": "string (JWT token)" }
```

Examples:

Request:

```
{ "clientId": "partner-123", "clientSecret": "s3cr3t" }
```

Response Example:

```
{ "token": "eyJhbGciOi..." }
```

Auth - Login Admin

Method: POST **Path:** /api/Auth/LoginAdmin

Admin login endpoint; returns authentication token or admin session information.

Request Schema:

```
{ "type": "object", "required": [ "email", "password" ], "properties": { "email": { "minLength": 1, "type": "string", "format": "email" }, "password": { "minLength": 1, "type": "string" } }, "additionalProperties": false }
```

Response Schema / Type:

```
{ "200": "string or object (token/session)" }
```

Examples:

Request:

```
{ "email": "admin@example.com", "password": "P@ssword123" }
```

Response Example:

```
{ "token": "eyJhbGciOi..." }
```

PestServices - Get Categories

Method: GET **Path:** /api/PestServices/categories

Returns a list of service categories available.

Response Schema / Type:

```
{ "type": "array", "items": "ServiceCategory" }
```

Examples:

Response Example (array):

```
[ { "id": 1, "name": "Residential Pest Control", "imageUrl": "https://example.com/images/residential.png" } ]
```

PestServices - Get Subcategories

Method: GET **Path:** /api/PestServices/subcategories

Returns a list of service subcategories available.

Response Schema / Type:

```
{ "type": "array", "items": "ServiceSubcategory" }
```

Examples:

Response Example (array):

```
[ { "id": 10, "name": "Termite Control", "imageUrl": "https://example.com/images/termite.png" } ]
```

PestServices - Get Packages

Method: GET **Path:** /api/PestServices/packages

Returns a list of available packages for pest services.

Response Schema / Type:

```
{ "type": "array", "items": "Package" }
```

Examples:

Response Example (array):

```
[ { "id": 101, "name": "Basic Home Pack", "price": 999.0, "imageUrl":  
"https://example.com/images/package_basic.png" } ]
```

PestServices - Book Service

Method: POST **Path:** /api/PestServices/BookService

Create a booking for a pest service. Returns booking reference or confirmation string.

Request Schema:

```
{ "type": "object", "properties": { "userId": { "type": "string", "nullable": true },  
"phone": { "type": "string", "nullable": true }, "name": { "type": "string",  
"nullable": true }, "address": { "type": "string", "nullable": true }, "packageId": {  
"type": "integer", "format": "int32" }, "bookingAmount": { "type": "number", "format":  
"double" }, "sourcePartnerId": { "type": "string", "nullable": true } },  
"additionalProperties": false }
```

Response Schema / Type:

```
{ "200": "string (booking reference)" }
```

Examples:

Request:

```
{ "userId": "user-789", "phone": "+911234567890", "name": "John Doe", "address": "12 MG Road,  
Mumbai, India", "packageId": 5, "bookingAmount": 1499.0, "sourcePartnerId": "partner-123" }
```

Response Example:

```
{ "bookingRef": "BK-2025-0001" }
```

Schema Reference

LoginModelView

```
{ "type": "object", "required": [ "email", "password" ], "properties": { "email": { "minLength": 1, "type": "string", "format": "email" }, "password": { "minLength": 1, "type": "string" } }, "additionalProperties": false }
```

PartnerLoginDto

```
{ "type": "object", "properties": { "clientId": { "type": "string", "nullable": true }, "clientSecret": { "type": "string", "nullable": true } } }
```

ServiceCategory

```
{ "type": "object", "properties": { "id": { "type": "integer", "format": "int32" }, "name": { "type": "string", "nullable": true }, "imageUrl": { "type": "string", "nullable": true } }, "additionalProperties": false }
```

ServiceSubcategory

```
{ "type": "object", "properties": { "id": { "type": "integer", "format": "int32" }, "name": { "type": "string", "nullable": true }, "imageUrl": { "type": "string", "nullable": true } }, "additionalProperties": false }
```

Package

```
{ "type": "object", "properties": { "id": { "type": "integer", "format": "int32" }, "name": { "type": "string", "nullable": true }, "price": { "type": "number", "format": "double" }, "imageUrl": { "type": "string", "nullable": true } }, "additionalProperties": false }
```

CreateBookingDto

```
{ "type": "object", "properties": { "userId": { "type": "string", "nullable": true }, "phone": { "type": "string", "nullable": true }, "name": { "type": "string", "nullable": true }, "address": { "type": "string", "nullable": true }, "packageId": { "type": "integer", "format": "int32" }, "bookingAmount": { "type": "number", "format": "double" }, "sourcePartnerId": { "type": "string", "nullable": true } }, "additionalProperties": false }
```

Notes: - All request/response bodies use application/json content type unless otherwise specified. - Authentication: obtain a JWT from **/api/Auth/token** and include it in the **Authorization** header as Bearer <token>. - Error responses follow standard HTTP status codes; include 4xx for client errors, 5xx for server errors. - If you need code samples (cURL, C#, JavaScript) or more detailed field descriptions, reply and I will add them.