

SENG 275

SOFTWARE TESTING

DR. NAVNEET KAUR POPLI

DEPT. OF ELECTRICAL AND COMPUTER
ENGINEERING



JUNIT TESTING



University
of Victoria



Unit testing frameworks in different languages

- Java: junit

<https://junit.org/junit5/docs/current/user-guide/#writing-tests>

- Python: unittest

<https://docs.pytest.org/en/7.2.x/reference/reference.html#api-reference>

- Javascript: jestjs

- Go: testify



University
of Victoria


Junit

- JUnit is an open-source Unit Testing Framework for JAVA.
- It is useful for Java Developers to write and run repeatable tests.
- **Erich Gamma and Kent Beck** initially developed it.
- <https://www.youtube.com/watch?v=1zaCvLVU70o>
- It is an instance of xUnit architecture.
- It is used for Unit Testing of a small chunk of code.



How JUnit works?

















- JUnit is a Java testing framework used to test a piece of java code.
- It has a **Runner** which determines the tests, executes those tests, validates these tests using **assertions** and **reports the results to the developers**.



Where should the test be located?

- Typically, unit tests are created in a **separate source folder** to keep the test code separate from the real code.
- The standard convention from the Maven and Gradle build tools is to use:
- **src/main/java** - for Java classes
- **src/test/java** - for test classes



- ▼  SpecificationBasedTesting
 - ▼  src/main/java
 - ▼  (default package)
 - >  Age.java
 - >  Burger.java
 - >  Calculator.java
 - >  EvenOddParameterized.java
 - >  LeapYear.java
 -  src/main/resources
 - ▼  src/test/java
 - ▼  (default package)
 - >  AgeTest.java
 - >  BurgerTest.java
 - >  CalculatorTest.java
 - >  EvenOddParameterizedTest.java
 - >  LeapYearTests.java



JUNIT ASSERTIONS AND ANNOTATIONS



Assertions and Annotations

- The simplest form of **self-testing** is the *assertion*.
- An assertion is a **Boolean expression** at a specific point in a program which will be **true unless there is a bug** in the program.
- In other words, an **assertion states that a certain condition must be true at the time the assertion is executed**.
- JUnit **Annotations** is a special form of syntactic meta-data that can be added to Java source code for better code readability and structure.



Annotations for Junit testing

@Test annotation is applied over methods to mark them as test methods.

Visibility of @Test annotated methods can be made public, default and protected in Junit 5 but in Junit 4 they can only be public.

@Test(timeout=1000) annotation specifies that method will be failed if it takes longer than 1000 milliseconds (1 second).

@BeforeClass/@BeforeAll annotation specifies that method will be invoked only once, before starting all the tests. JUnit 5 supports @BeforeAll instead of @BeforeClass. Sometimes several tests need to share computationally expensive setup (like logging into a database). While this can compromise the independence of tests, sometimes it is a necessary optimization.

@Before/@BeforeEach annotation specifies that method will be invoked before each test case. This annotation is commonly used to develop necessary preconditions for each @Test method. JUnit 5 supports @BeforeEach instead of @Before. E.g., clearing the changes made by a test to a **list** before the next test.



```
public class MyTestClass {
```

```
    @BeforeClass
```

```
    public void initGlobalResources() {
```

```
        /* This method will be called only once per test class. */
```

```
    }
```

```
    @Before
```

```
    public void initializeResources() {
```

```
        /* This method will be called before calling every test. */
```

```
    }
```

```
    @Test
```

```
    public void myTestMethod1() {
```

```
        /* initializeResources() method will be called before calling this method */
```

```
    }
```



Annotations for Junit 4 testing

@AfterClass/@AfterAll annotation specifies that method will be invoked only once, after finishing all the tests. If you allocate expensive external resources in a **@BeforeClass** method, you need to release them after all the tests in the class have run. Annotating a public static void method with **@AfterClass** causes that method to be run after all the tests in the class have been run.

@After/@AfterEach annotation specifies that method will be invoked after each test case. The annotations **@AfterClass** and **@After** are same in functionality. The only difference is the method annotated with **@AfterClass** will be called once per test class based, and the method annotated with **@After** will be called once per test based.



```
public class MyTestClass {
```

```
    @Test
```

```
    public void myTestMethod1() {  
        // write your test code here...  
    }
```

```
    @After
```

```
    public void initResources() {  
        /**  
         * This method will be called after every test method.  
         */  
    }
```


```
    @AfterClass
```

```
    public void closeGlobalResources() {  
        /**  
         * This method will be called only once per test class. It will be called  
         * after executing all tests.  
         */  
    }
```



University
of Victoria

Order of execution



THE AAA STRATEGY




University
of Victoria



AAA Strategy

Arrange-Act-Assert (AAA)



methodpoet.com



University
of Victoria

Program to find square of an integer

```
public class Class1{  
    public int sqr(int n)  
    {  
        return n*n;  
    }  
}
```

@Test

```
public void testsqr()  
{
```

```
    Class1 obj=new Class1(); → Arrange
```

```
    int result=obj.sqr(4); → Act
```

```
    assertEquals(16,result); → Assert
```

```
}
```

LET'S TRY SOME ASSERTIONS AND ANNOTATIONS



Assert (the e-a order)

- **assertEquals**(expected, actual)
- **assertTrue**(condition)
- **assertFalse**(condition)
- **assertArrayEquals**(expectedArray, actualArray);
- **assertThat**(some_object_or_value).has_some_relation_to(some_other_object_or_value)



assertThat

- The `assertThat` assertion is the only one in JUnit 4 that has a **reverse order (a-e)** of the parameters compared to the other assertions.

`assertThat([value], [matcher statement]);`

- `assertThat(some_number).isNotEqualTo(some_other_number);`
- `assertThat(some_object_reference).isNotNull();`
- `assertThat(some_object).isSameAs(some_other_object_reference);`
- `assertThat(some_condition).isTrue();`
- `assertThat(some_condition).isFalse();`



The Benefit of Using AssertThat Over Other Assert Methods

Readability:

“Assert that the actual value is equal to the expected value 100.”

- `assertThat(actual, equalTo(100));`

//OR

- `assertThat(actual, is(equalTo(100)));`

//OR

`assertThat(actual, is(100));`



University
of Victoria

Create a Calculator class and test it

- Create a 'Calculator' class
- In it create functions
 - `int doSum(int a, int b)` which calculates sum of two integers
 - `int doProduct(int a, int b)` which calculates product of two integers
 - Boolean `compareTwoNums(int a, int b)` which compares two integers for equality.
- Now create tests for testing these functions
 - `void testSum()`
 - `void testProduct()`
 - `void testCompare()`
- Now create annotations
 - to be performed before every test `@Before`
 - before the entire class `@BeforeClass`
 - which must be performed after each test `@After`
 - to be performed after the entire class `@AfterClass`




Calculator class

```
public class Calculator {  
    //sum  
    public int doSum(int a, int b) {  
        return a + b;  
    }  
  
    //product  
    public int doProduct(int a, int b) {  
        return a * b;  
    }  
  
    //compare  
    public Boolean compareTwoNums(int a, int b) {  
        return a == b;  
    }  
}
```

Test doSum() function using CalculatorTest junit class

```
public class CalculatorTest{
    Calculator c=new Calculator();
    @Test
    public void testSum()
    {
        int expected=17;
        int actual=c.doSum(12, 3);
        assertEquals(expected, actual);
        /*note: sometimes Assert.assertEquals() might work if
        assertEquals() is deprecated*/
    }
}
```


Test passes



The screenshot shows the JUnit runner interface in an IDE. At the top, there are tabs for 'Package Explorer' and 'JUnit'. Below the tabs is a toolbar with various icons for navigation and actions. The main area displays the test results: 'Finished after 0.026 seconds'. Below this, the summary statistics are shown: 'Runs: 1/1', 'Errors: 0', and 'Failures: 0'. A green progress bar is visible below the summary. At the bottom, a list of test cases is shown, with 'CalculatorTest [Runner: JUnit 4] (0.000 s)' selected and highlighted in blue.

Package Explorer JUnit

Finished after 0.026 seconds

Runs: 1/1 Errors: 0 Failures: 0

CalculatorTest [Runner: JUnit 4] (0.000 s)

Write the entire test class

```
public class CalculatorTest {
    Calculator c=new Calculator();
    @Test
    public void testSum()
    {
        int expected=70;
        int actual=C.doSum(30,40);
        assertEquals(expected,actual);
        System.out.println("The Sum is:
        "+actual);
    }
    @Test
    public void testProduct()
    {
        int expected=35;
        int actual=C.doProduct(5,7);
        assertEquals(expected, actual);
        System.out.println("The Product is:
        "+actual);
    }
}
```

```
}
@Test
public void testCompareTrue()
{
    boolean
    actual=C.compareTwoNums(12,12);
    assertTrue(actual);
    System.out.println("The Comparison
    is: "+actual);
}
@Test
public void testCompareFalse()
{
    boolean
    actual=C.compareTwoNums(12,1);
    assertTrue(actual);
    System.out.println("The Comparison
    is: "+actual);
}
```



Running all 3 tests

Finished after 0.025 seconds

Runs: 3/3

✖ Errors: 0

✖ Failures: 0

✓ testSum - CalculatorTest (0.000 s)

✓ testProduct - CalculatorTest (0.000 s)

✓ testCompare - CalculatorTest (0.000 s)

≡ Failure Trace



University
of Victoria

Complete CalculatorTest Class

- test functions
 - void testSum()
 - void testProduct()
 - void testCompare()
- Before and after annotations
 - to be performed before every test @Before
 - before the entire class @BeforeClass
 - which must be performed after each test @After
 - to be performed after the entire class @AfterClass



```

public class CalculatorTest {
@BeforeClass
/*This will be executed before the entire
class*/
public static void beforeClassMethod()
{System.out.println("Establishing
Connection to the database");}
Calculator C;
@Before
/*This will be executed before each test
method*/
public void init()
{System.out.println("Initializing the
calculator instance");
C=new Calculator();}
@Test
public void testSum()
{int expected=70;
int actual=C.doSum(30,40);
assertEquals(expected,actual);
System.out.println("The Sum is:
"+actual);}
@Test
public void testProduct()
{int expected=35;
int actual=C.doProduct(5,7);
assertEquals(expected, actual);
System.out.println("The Product is:
"+actual);}

```

```

@Test
public void testCompareTrue()
{boolean actual=C.compareTwoNums(12,12);
assertTrue(actual);
System.out.println("The Comparison is:
"+actual);}
@Test
public void testCompareFalse()
{boolean actual=C.compareTwoNums(12,1);
assertTrue(actual);
System.out.println("The Comparison is:
"+actual);}
@After
public void tearDown()
{System.out.println("Test method executed
successfully");}
@AfterClass
/*This will be executed after the entire
class. There are no rules for ordering the
functions*/
public static void afterClassMethod()
{System.out.println("Tearing down
Connection to the database");}
}

```



Output

- Establishing Connection to the database
 - Initializing the calculator instance
 - The Sum is: 70
 - Test method executed successfully
 - Initializing the calculator instance
 - The Comparison is: true
 - Test method executed successfully
 - Initializing the calculator instance
 - The Product is: 35
 - Test method executed successfully
- Tearing down Connection to the database



For IntelliJ

- Create a Gradle project.
- In src.main.java folder, create a Calculator class and in the src.test.java folder create a CalculatorTest class.
- Rest remains the same.



TRY YOURSELF



University
of Victoria



For testing doSum() function having 3 integers, write 4 tests:

1. Test case which adds **three positive** integers (testSum1)
:[30,40,50]=120
2. Test case which adds **three negative** (testSum2)
:[-30,-40,-50]= -120
3. Test case which adds **three same** integers (testSum3)
:[30,30,30]= 90
4. Test case which adds two **positive integers with 0**
(testSum4) :[30,30,0]=60



```
public class CalculatorTest {
    Calculator c;

    @Before
    public void init()
    {
        c=new Calculator();
    }

    @Test
    public void testSum1()
    {
        int expected=120;
        int actual=c.doSum(30,40,50);
        assertEquals(expected, actual);
    }

    @Test
    public void testSum2()
    {
        int expected=-120;
        int actual=c.doSum(-30,-40,-50);
        assertEquals(expected, actual);
    }
}
```

```
@Test
public void testSum3()
{
    int expected=90;
    int actual=c.doSum(30,30,30);
    assertEquals(expected, actual);
}

@Test
public void testSum4()
{
    int expected=60;
    int actual=c.doSum(30,30,0);
    assertEquals(expected, actual);
}
```



Create a program to Calculate SI,CI and test it

$$SI = p \cdot r \cdot t$$

Where:

SI is the Simple **interest** paid

P is the **principal**—the original amount of money borrowed

R is the **interest rate**, a per-year rate, written as a decimal

T is the **time** of the loan, expressed in years or portions of a year

Write a program to calculate SI and CI and test the program using the values given in the solved exercises in the following slides.



University
of Victoria

Solved Example of SI and CI

Treasury Notes (T-notes) are bonds issued by the federal government to cover its expenses. Suppose you obtain a \$1,000 T-note with a 4% annual rate, with a maturity in 2 years. How much interest will you earn?

Solution:

Identify the information given in the problem.

Simple Interest (SI): unknown

Principal (p): \$1000

Rate (r): 4%=0.04

Time (t): 2 years

Put the information in the simple interest equation.

$$SI = 1000 \cdot 0.04 \cdot 2$$

Multiply.

$$SI = 80$$

Answer

You would earn \$80 in interest.



University
of Victoria

Compound Interest

$$CI = P(1 + r/n)^{nt} - P$$

Where:

- P is the principal amount
- r is the rate of interest(decimal)
- n is frequency or no. of times the interest is compounded annually. We will consider frequency to be =1. then

$$CI = P(1 + r)^t - P$$

- t is the overall tenure.



Solved question

- If we invest \$50,000 in an investment account paying 10% interest compounded annually, how much will the CI be in 5 years?
- Because we are starting with \$50,000, $P=50,000$. Our interest rate is 10%, so $r=0.1$. We want to know the CI in 5 years, so

$$CI = P(1+r)^t - P$$

Use the compound interest formula.


$$CI = 50000 * (1+0.1)^5 - 50000 = 30525.500000000003$$

Note: use `Math.pow()` function. E.g., `Math.pow(2,4)` is 2 raised to power 4 which is 16.



Jpacman again – Direction test !!!

1. Complete the unit tests in the board.DirectionTest class in JPacman.
- Open the board.DirectionTest.
 - Create additional test methods in DirectionTest for e.g., the south, east, and west directions. Test for 'north' is done for you.
 - Run the tests, and ensure they pass.



Fail a test

- In your IDE, modify one or more of your test cases so that they fail.
- Repair the tests so that they pass again.

