Updating and Validating A Deep Larning Approach to Nuclear Fuel Transmutation in Cyclus

Samar E. Abdelkawy, Kathryn D. Huff

Advanced Reactors and Fuel Cycles Group, University of Illinois, Urbana, IL, selsafy2@illinois.edu

INTRODUCTION

The nuclear fuel cycle is fundamental to nuclear energy production and reactor operations. Understanding the fuel cycle is essential for assessing how different enrichments and burnups affect the isotopic composition of spent nuclear fuel (SNF), including its concentration of various isotopes and decay heat. These factors play a crucial role in determining appropriate strategies for SNF management strategies, including storage, reprocessing, or disposal. Optimizing these processes requires accurate depletion modeling to inform decision-making on waste handling and potential resource utilization[1].

This work reproduces and further validates the study conducted by Bae et al. (2020)[2], where the authors trained a neural network model on the Unified Database (UDB) for Pressurized Water Reactor (PWR) Uranium Oxide (UOX) fuel with varying enrichments and burnups. Their results demonstrated that the model provided a balance between fidelity and computational efficiency compared to other nuclear fuel cycle simulators. However, with the release of Cyclus version 1.6.0, there is a need update the archetype developed by Bae et al. to ensure compatibility and enable further research applications.

Additionally, since the UDB has been updated, this presents an opportunity to validate the neural network model using new data. Bae et al. noted that, ideally, their model should be tested against a dataset independent from the data it was trained on, but this was not feasible at the time, leading them to validate the model using a subset of their training data. Therefore, a second goal in this study is to integrate their trained neural network model within the Cyclus framework and evaluate its performance using the updated UDB. This allows us to assess whether the model continues to outperform traditional recipe-based methods in fuel cycle simulations.

CYCLUS

Cyclus [3] is an open-source, agent-based nuclear fuel cycle (NFC) simulation framework designed for flexibility and extensibility. Unlike traditional simulators that rely on fixed system models, Cyclus treats each facility—such as reactors, enrichment plants, and storage sites—as independent agents that interact dynamically. These agents operate under predefined rules, exchanging materials through a market-based mechanism called the Dynamic Resource Exchange [4].

A key strength of CYCLUS is its modular architecture, which allows users to define and deploy custom facility models, known as archetypes, implemented in C++ or Python. Standard NFC processes, such as enrichment, reprocessing, and storage, are available in the CYCAMORE [5] repository, while additional community-developed archetypes extend its capabilities for specialized applications, including spent fuel transmutation and diversion modeling. This modularity en-

ables Cyclus to simulate a wide range of NFC scenarios, making it a powerful tool for analyzing the impact of policy decisions, technology changes, and resource availability on nuclear energy systems.

UNIFIED DATABASE

The Unified Database (UDB) is part of the Used Nuclear Fuel Storage, Transportation Disposal Analysis Resource and Data System (UNF-ST&DARDS), developed by Oak Ridge National Laboratory (ORNL) [6]. It serves as a comprehensive, controlled source of spent nuclear fuel (SNF) data, including dry cask attributes, assembly details, economic factors, transportation logistics, and federal waste management considerations. Assembly-specific parameters include initial enrichment, burnup, metric tons of heavy metal (MTHM), assembly type, and discharge date [7]. The database was generated using irradiation and decay calculations performed with SCALE [8], providing mass, heat, and activity estimates for each assembly.

ACKNOWLEDGMENTS

This work was supported by the Department of Nuclear, Plasma, and Radiological Engineering at UIUC through a teaching assistantship. We also acknowledge Oak Ridge National Laboratory for providing the necessary data and the Advanced Reactors and Fuel Cycles Research Group at UIUC, particularly Nythan Ryan, for their guidance and support.

REFERENCES

- A. M. YACOUT, J. J. JACOBSON, G. E. MATTHERN, S. J. PIET, and A. MOISSEYTSEV, "Modeling the Nuclear Fuel Cycle," in "The 23rd International Conference of the System Dynamics Society," Boston," Citeseer (2005).
- 2. J. W. BAE, A. RYKHLEVSKII, G. CHEE, and K. D. HUFF, "Deep learning approach to nuclear fuel transmutation in a fuel cycle simulator," (May 2020).
- 3. K. D. HUFF, M. J. GIDDEN, R. W. CARLSEN, R. R. FLANAGAN, M. B. MCGARRY, A. C. OPOTOWSKY, E. A. SCHNEIDER, A. M. SCOPATZ, and P. P. H. WILSON, "Fundamental concepts in the Cyclus nuclear fuel cycle simulation framework," *Advances in Engineering Software*, **94**, 46–59 (Apr. 2016).
- 4. M. J. GIDDEN and P. P. H. WILSON, "A methodology for determining the dynamic exchange of resources in nuclear fuel cycle simulation," *Nuclear Engineering and Design*, **310**, 378–394 (Dec. 2016).
- R. W. CARLSEN, M. GIDDEN, K. HUFF, A. C. OPO-TOWSKY, O. RAKHIMOV, A. M. SCOPATZ, and P. WIL-SON, "Cycamore v1.0.0," *Figshare* (Jun. 2014).
- 6. J. PETERSON, R. LEFEBVRE, H. SMITH, D. ILAS,

- K. ROBB, T. MICHENER, H. ADKINS, and J. SCAGLIONE, "Used Nuclear Fuel Storage Transportation & Disposal Analysis Resource and Data System (UNF-ST&DARDS)," Tech. rep., FCRD-NFST-2013-000117 Rev. 0, US Department of Energy Nuclear Fuels Storage and Transportation Planning Project (2013).
- 7. J. PETERSON and J. SCAGLIONE, "Fuel Cycle Applications with the Data Stored Within the Unified Database," p. 5 (2015).
- 8. S. M. BOWMAN, "SCALE 6: Comprehensive Nuclear Safety Analysis Code System," *Nuclear Technology*, **174**, 2, 126–148 (May 2011).