

# LEU+ to HALEU Transitions in Advanced Reactor Fuel Cycles

Nathan S. Ryan,<sup>\*</sup> Kathryn D. Huff,<sup>\*</sup> and Madicken Munk,<sup>\*,†</sup>

<sup>\*</sup>Advanced Reactors and Fuel Cycles Group, University of Illinois, Urbana, IL, nsryan2@illinois.edu

<sup>†</sup>Scientific Computing, Reactor Analysis and Modeling Group, Oregon State University, Corvallis, OR

## INTRODUCTION

In 2020, a high assay low enriched uranium (HALEU) workshop report led by Monica Regalbuto [1] highlighted the unique regulatory challenges of establishing a HALEU fuel cycle in the United States of America (USA). They note that part of enriching HALEU is first to produce low enriched uranium plus (LEU+), defined as between 5% and 10%  $^{235}\text{U}$  enrichment. The report notes that LEU+ facilities would fall under a similar category of regulations as our existing low enriched uranium (LEU) fuel cycle, a significant advantage for the U.S. Nuclear Regulatory Commission (NRC) and the USA government. Since then, the idea has cropped up in several forums that, if a reactor could be redesigned to accommodate LEU+, it could serve as a useful intermediary step to HALEU.

In this work, we use CYCLUS to model the nuclear fuel cycle (NFC) of a fuel cycle that deploys AP1000s, Xe100s, and MMRs. After 10 years of operation with LEU+ fuel, the advanced reactor fleet transitions to deploying HALEU versions of the X-Energy Xe-100 (Xe-100) and Micro Modular Reactor (MMR). We will evaluate the impact of this transition on the delayed separative work units (SWU) and mass of HALEU required to meet various demand growth scenarios.

## CYCLUS

CYCLUS [2] is an agent-based NFC simulator that is versatile, open-source, and modular. The software achieves this versatility through a series of generic archetypes that are primarily transaction-based. Over the years, the user community and developers have created a litany of nuclear-specific archetypes for everything from proliferation assessment to fuel burnup. Many standard fuel cycle facilities have been implemented in the CYCAMORE repository [3], which holds technology-agnostic archetypes for material sources, material sinks, enrichment services, separations capabilities, storage services, and a generic reactor.

## SCENARIOS

We will deploy reactors to meet energy demands drawn from U.S. Energy Information Administration (EIA) and U.S. Department of Energy (DOE) projections cited in Table I. The Low growth scenarios correspond to 5, 10, and 15% increases in energy demand by 2050, and the High growth scenarios correspond to a doubling and a tripling of nuclear energy by 2050.

In Table II, we describe the three schemes we used to deploy reactors to meet the energy demand. Through the greedy scheme, we are not attempting to capture the complexity of the deployment problem but rather to explore the implications of deploying a certain number of reactors. This random

TABLE I. Demand Growth Scenarios

Demand Growth	Year-to-Year Increase	Source
No growth	0%	na
Low growth	0.17%, 0.5%, 1%,	[4]
High growth	3.5%, 5.6%	[5]

deployment is a proxy for the complexity of the real-world deployment problem; however, it does not include the nuance of how individual deployments meet an end user's needs, which will drive the strategic decisions that utilities and ratepayers behind the meter make in their reactor choices. Combining the random and greedy schemes allows us to inject some uncertainty around which reactor will be deployed at any given time while ensuring meeting the demand efficiently.

TABLE II. Deployment Schemes

Scheme	Description
Greedy Deployment	Deploy the largest reactor first at each time step, fill in the remaining capacity with the next smallest, and so on.
Random Deployment	Uses a date and hour as seed to sample the reactors list randomly.
Initially Random, Greedy Deployment	Randomly deploys reactors until a reactor bigger than the remaining capacity is proposed for each time step, then fills the remaining capacity with the greedy algorithm.

## ACKNOWLEDGMENTS

This research was performed, in part, using funding received from the DOE Office of Nuclear Energy's Nuclear Energy University Program (Project 23-29656 DE-NE0009390) 'Illuminating Emerging Supply Chain and Waste Management Challenges'.

## REFERENCES

1. M. C. REGALBUTO, "High-Assay Low Enriched Uranium Demand and Deployment Options 2020 HALEU Workshop Report," Tech. Rep. INL/EXT-21-61768, Idaho National Laboratory (Jun. 2020).
2. K. D. HUFF, M. J. GIDDEN, R. W. CARLSEN, R. R. FLANAGAN, M. B. MCGARRY, A. C. OPOTOWSKY, E. A. SCHNEIDER, A. M. SCOPATZ, and P. P. H. WILSON, "Fundamental concepts in the Cyclus nuclear fuel cycle simulation framework," *Advances in Engineering Software*, **94**, 46–59 (Apr. 2016).
3. R. W. CARLSEN, M. GIDDEN, K. HUFF, A. C. OPOTOWSKY, O. RAKHIMOV, A. M. SCOPATZ, and P. WIL-

SON, “Cycamore v1.0.0,” *Figshare* (6 2014).

4. U.S. ENERGY INFORMATION ADMINISTRATION, “Annual Energy Outlook 2023,” Government, U.S. Energy Information Administration (Mar. 2023).
5. JULIE KOZERACKI, CHRIS VLAHOPLUS, KEN ERWIN, ALAN PROPP, SONALI RAZDAN, RASHEED AUGUSTE, TIM STUHLBREHER, CHRISTINA WALROND, MELISSA BATES, ERICA BICKFORD, ANDREW FOSS, DEREK GASTON, CHERYL HERMAN, RORY STANLEY, BILLY VALDERRAMA, KATHERYN SCOTT, TOMOTAROH GRANZIER-NAKAJIMA, PAUL DONOHOO-VALLETT, TOM FANNING, BRENT DIXON, ABDALLA ABOU JAOUDE, and CHRIS LOHSE, “Pathways to Commercial Liftoff: Advanced Nuclear,” *DOE Liftoff Report* (Sep. 2024).