Dynamic Transition Analysis with TIMES: I²CNER Initiative on Challenges in Energy Assessment and Energy Transitions

Anshuman Chaube, James Stubbins, **Kathryn Huff**

University of Illinios at Urbana-Champaign, Department of Nuclear, Plasma, and Radiological Engineering, Urbana, IL 61801

Objectives

Evaluate potential impact of novel energy technologies within Japan's energy system. Specifically:

- Guide practical near term (2010-2050) transition strategies.
- Minimize carbon emissions within realistic constraints.
- Identify high impact technologies.
- Assess role of technology readiness.
- Predict impediments to strategically optimal technology deployment.
- Identify ideal timelines for energy system deployment, infrastructure development, high impact R&D investment.

Introduction

Previous work has compared the impact of innovative energy technologies in various world regions using **static** scenario analyses [1, 2, 4, 5, 7, 8]. We will simulate **dynamic** transition scenarios [3, 9] aimed at minimizing carbon emissions in Japan by 2050. These scenarios will include realistic constraints regarding technology readiness (in terms of generation, transmission & storage) and will combine multiple technologies in a single heterogeneous system model.

Methodology

The Integrated MARKAL-EFOM System (TIMES) model generator [6] [10] optimizes energy systems using linear and mixed-linear algorithms. A user-defined objective function (such as minimizing carbon emissions or costs) is solve within user defined constraints such as energy generation demand.



Figure: Basic methodology for dynamic simulation of Japan's energy system.

Anticipated Results

- Analysis results can be filtered by sector (commercial, industrial, residential, building etc) or by region.
- Many metrics are automatically postprocessed- such as energy intensity, thermal energy efficiency, transmission capacity.
- Technology deployment transitions driven by constrained optimization will have valuable strategic value.

Impact

Results will:

- Optimize realistic decarbonization roadmaps.
- Identify potential transition bottlenecks.
- Help Japan's policymakers create timelines for R&D investment and infrastructure development.
- Quantify system sensitivity to technology readiness.

Timeline

Jan. 2018	Project start:	Literature Review.
Feb. 2018	Data collection:	Japan's current grid.
Mar. 2018	Data collection:	Static projections.
May. 2018	Data collection:	Conventional technologies.
Jun. 2018	Data collection:	i²cner generation technology.
Jul. 2018	Data collection:	i²cner efficiency technology.
Aug. 2018	Data collection:	i²cner storage technology.
Sep. 2018	Scenario simulation:	2010-2050 conventional.
Oct. 2018	Scenario simulation:	2010-2050 i²cner driven.
Dec. 2018	Scenario simulation:	2010-2070.
2019	Sensitivity analysis:	Vary key parameters.

Summary

- Dynamic simulation of Japan's energy system in TIMES model generator using a heterogeneous model and realistic constraints will help develop near-term decarbonization strategies.
- Policymakers will benefit from identification of high impact technologies, and creation of R&D investment and infrastructure development timelines.
- Simulations will quantify system sensitivity to technology readiness, and also account for secondary scenarios where decarbonization is not the main priority.

References

[1] K. Chyong Chi, W. J. Nuttall, and D. M. Reiner.
Dynamics of the UK natural gas industry: System dynamics modelling and long-term energy policy analysis.
Technological Forecasting and Social Change, 76(3):339–357, Mar. 2009.

[2] Y. Y. Feng, S. Q. Chen, and L. X. Zhang.
System dynamics modeling for urban energy consumption and CO2 emissions: A case study of Beijing, China.
Ecological Modelling, 252(Supplement C):44–52, Mar. 2013.

[3] S. Jebaraj and S. Iniyan.
A review of energy models.
Renewable and Sustainable Energy Reviews, 10(4):281–311, Aug. 2006.

[4] Y. Kikuchi.
Simulation-Based Approaches for Design of Smart Energy System: A Review Applying Bibliometric Analysis.
Journal of Chemical Engineering of Japan, 50(6):385–396, 2017.

[5] L. Li, C. Chen, S. Xie, C. Huang, Z. Cheng, H. Wang, Y. Wang, H. Huang, J. Lu, and S. Dhakal.
Energy demand and carbon emissions under different development scenarios for Shanghai, China.
Energy Policy, 38(9):4797–4807, Sept. 2010.

[6] R. Loulou, U. Remme, A. Kanudia, A. Lehtila, and G. Goldstein.
Documentation for the TIMES Model Part II.
Energy technology systems analysis programme (ETSAP), 2005.

[7] N. A. Pambudi, K. Itaoka, A. Kurosawa, and N. Yamakawa.
Impact of Hydrogen fuel for CO2 Emission Reduction in Power Generation Sector in Japan.
Energy Procedia, 105(Supplement C):3075–3082, May 2017.

[8] N. A. Pambudi, K. Itaoka, N. Yamakawa, and A. Kurosawa.
Future Japan power generation sector by introducing hydrogen plant with 80% CO 2 emission reduction target: A preliminary analysis.
In *Sustainable Energy Engineering and Application (ICSEEA), 2016 International Conference on*, pages 66–69. IEEE, 2016.

[9] S. Pfenninger, A. Hawkes, and J. Keirstead.
Energy systems modeling for twenty-first century energy challenges.
Renewable and Sustainable Energy Reviews, 33(Supplement C):74–86, May 2014.

[10] A. J. Seebregts, G. A. Goldstein, and K. Smekens.
Energy/Environmental Modeling with the MARKAL Family of Models.
In *Operations Research Proceedings 2001*, Operations Research Proceedings 2001, pages 75–82. Springer, Berlin, Heidelberg, 2002.
DOI: 10.1007/978-3-642-50282-8_10.

Contact Information

- Web: arfc.github.io
- Email: kdhuff@illinois.edu

Acknowledgements

This research is being performed using funding received from the International Institute for Carbon Neutral Energy Research (I²CNER) Initiative on Challenges in Energy Assessment and Energy Transitions at the University of Illinois under Director Petros Sofronis.

Advanced Reactors & Fuel Cycles

wpi World Premier International Research Center Initiative

I²CNER