

Product & Service

Product

A. LPG Filling Plant

1.1 Storage Tank

1.1.1 Above Ground and Underground/ Mounded LPG Storage Tank:

1.1.1.1 Bullet Tank

Capacity Range: 5MT to 100MT

Design Temperature: -20°C / +50°C

Type: Horizontal/ vertical

Design Code: EN13445

Max WP: 17.2 Bar

Test Pressure: 24.6 Bar

Materials: P355NH

Safety Relief Valve: Rego/SRG, Pop Up Pressure: 17.2 Bar

Magnetic Rochester Level Gauge with magnetic level transmitter

Temperature & Pressure Gauge

1.1.1.2 Spherical Tank

Capacity: 500 MT - 3000 MT

Design Standards: ASME Boiler and Pressure Vessel Code (Section VIII Div 1 or Div 2)

Max WP: 17.2 Bar

Test Pressure: 18 bar to 20 Bar

Shell Thickness: Ranges from 35 mm to 50 mm

Safety Relief Valve: Rego/SRG, Pop Up Pressure: 17.2 Bar

1.1.2 Tank Accessories

1.1.2.1 Internal Excess Flow valve

Excess Flow Valves can be used for filling, vapor equalizing and withdrawal in containers or line applications. Valves are connected to the bottom of the tank for liquid operations. It can also be connected to the top of the tank in vapor operation. When the flow rate increases, the valve closes itself and remains closed. When the pressure is balanced at the inlet and outlet of the valve, the spring of the valve moves the valve to the open position.

1.1.3 Safety Relief Valve

1.1.3.1 Manifold:

Size: 4"-300#

Set Pressure: 250 psi to 350 psi

1.1.3.2 Metric thread with NPT thread valve base

Size: ¼", ½", ¾", 1", 1.25", 2" NPT
Set Pressure: 250 psi to 350 psi

1.1.4 Level Gauge

1.1.4.1 Rotogauge

Type: Manual

Medium: LPG

Use: LPG Storage Tank

1.1.4.2 Magnetic

Mechanical float level gauge to precisely measure the content inside the tank.

Key advantages:

- Mechanic float system
- Dial can be replaced under pressure, many different dials available
- Dials with Electronic sensor are available
- Flange or thread connection
- Horizontal, vertical or various angles mounting possible

1.1.4.3 Remote Tank Monitoring

- Remote Cellular Tank Monitoring Solution
Remote access to tank data from virtually anywhere
- Ideal for remote, unattended, seasonal, or fleet tanks
- 10 Year GaugeLink – BLE battery life, and 5 year Cellular Gateway battery life (replaceable)
- No wires; simple snap-on installation

1.2 Filling Machine

1.2.1 Inline Filling Machine

Accurate filling, with a high accuracy lever III.

Anti-cheating function. Scale will automatic cut-off when it reaches to the setting amount.

ATEX Approved

1.2.2 Carousel

Accurate filling, with a high accuracy lever III.

12 to 48 post carousel.

1.3 LPG Transfer Machinery

1.3.1 LPG Pumps

1.3.1.1 Centrifugal Pump

For Bottling Operation

Multistage Side Channel Pump with Motor

Explosion Proof IP56, IECEx Certified Motor

Flexible coupling, Base & Including Bypass Valve

Flow Rate: 5-15 m³/Hr.

Pressure: 15 Bar

Motor Speed: 1450 RPM

Power: 4-15 KW

1.3.1.2 LPG Sliding Vane Pump

For Road Tanker loading/unloading operation

Vane Pump with Motor

Inlet: 2 in. Female NPT

Outlet: 2 in. Female NPT

Flow-Rate: 41 - 76 GPM (155 - 287 LPM) at 100 psid (6.9 bar)

Power: 4-7.5 kW

1.3.2 Bypass Valve

Bypasses are designed to protect pumps and other system components from damage resulting from excessive pressure

Size: ¾" to 2"

Pressure Range: 1.7 to 10.3 bar

Flowrate: 6.8 to 57 m³/hr

1.3.3 LPG Compressors

OIL FREE PISTON COMPRESSOR

Vapor Volumetric Displacement: 40 to 110 m³/hr

Explosion Proof IP56, IECEx Certified Motor

Differential Pressure: 21 Bar

Motor Speed: 400-800 RPM

Power: 15-25 KW

1.3.4 Air driven Pump

Drive Air Pressure : 3 - 8 bar ~ (45 - 115 psi)

Pressure Ratio : Typically 2:1 to 6:1 (for transfer), and up to 15:1 or 30:1

Max Outlet Pressure : Dependent on ratio; usually 10 - 60 bar ~ (145 - 870 psi)

Drive Air Flow Rate : 0.5 - 2.0 m³ / min

Max Liquid Flow Rate : Up to 10 - 15 L/min

Operating Temperature : -20°C to +80°C

Body / Wetted Materials: Carbon steel cabinet with Stainless Steel (304/316) gas barrels

1.4 Auxiliary Machineries

1.4.1 Leak Detector

1.4.2 Steam Generator

1.5 LPG Hosepipe & Accessories

1.6 Instrumentation

1.6.1 Pressure Gauge

1.6.2 Temperature Gauge

1.6.3 Solenoid Coil & Valve

1.6.4 Pneumatic Cylinder

1.7 Consumables

1.7.1 Rubber Bush

1.7.2 Sealing Sleeve

1.7.3 Plastic Cap

B. LPG Transport & Distribution

1.1 Semi-Trailer LPG Road Tanker/Bobtail

- Storage Capacity Range: 10MT to 30MT
- Operating Temperature: -20°C to +50°C
- Design Pressure: 17.5 Bar
- Test Pressure: 26.5 Bar
- Certification: TÜV/ SGS/ Bureau Veritas
- Tank Body: Cylindrical design in accordance with EN 12493, shell thickness 12-14mm, filling/discharge Line, ball valves, pipe fittings, Magnetic level gauge, Rotogauge, safety relief valve, pressure gauge.
- LPG Unloading system: Vane/Turbine LPG transfer pump with explosion proof motor, LPG hose reel
- Chassis: Half chassis design, "I" cross-section, Dual-speed mechanical trailer support legs, 25-ton dynamic, 50-ton static capacity, Air suspension axles with disc/drum brakes, each with 9-ton capacity

1.2 LPG Transfer Machinery

1.2.1 LPG Pumps

1.2.2 Bypass Valve

1.3 LPG Hosepipe & Accessories

1.3.1 Hose reel

1.3.2 ACME Coupling

- 1.3.3 *Dry Coupling*
 - 1.4 *Measuring Unit*
 - 1.4.1 *Mass Flowmeter*
 - 1.4.2 *Volumetric Flowmeter*
 - 1.5 *Tank Accessories*
 - 1.5.1 *Internal Safety Relief Valve*
 - 1.5.2 *Level Gauge*
 - 1.5.2.1 *Rotogauge*
 - 1.5.2.2 *Magnetic*
 - 1.5.3 *Internal Excess Flow valve*
 - 1.5.4 *Instrumentations*
 - 1.5.4.1 *Pressure Gauge*
 - 1.5.4.2 *Temperature Gauge*
- C. *Autogas Refueling Station*
 - 1.1 *LPG Tank*
 - 1.1 *Bullet Tank*

Capacity Range: 5MT to 20MT

Design Temperature: -20°C / +50°C

Type: Horizontal/ vertical

Design Code: EN13445

Max WP: 17.2 Bar

Test Pressure: 24.6 Bar

Materials: P355NH

Safety Relief Valve: Rego/SRG, Pop Up Pressure: 17.2 Bar

Magnetic Rochester Level Gauge with magnetic level transmitter

Temperature & Pressure Gauge

- 1.2 *Tank Accessories*
 - 1.2.1 *Internal Safety Relief*
 - 1.2.2 *Level Gauge*
 - 1.2.3 *Internal Excess Flow*

- 1.3 *Dispenser*
 - 1.3.1 *Dispenser*

LPG dispensers feature modular, compact body designs with 1 to 4 nozzles, high-precision measurement via an ATC (automatic temperature compensation) probe, electronic calibration, and single or dual LCD screens with touch keypads.

Flow Rate: Up to 45–50 liters per minute.

Measurement Precision: ±0.5%.

Operating Voltage: 70–264 V AC (or AC220V ±20% at 50Hz).

Ambient Temperature Range: -40°C to +55°C

1.3.2 Accessories

1.4 LPG Pump

1.4.1 Multistage Centrifugal Pump

Multistage Side Channel Pump with Motor
Explosion Proof IP56, IECEx Certified Motor
Flexible coupling, Base & Including Bypass Valve
Flow Rate: 5-15 m³/Hr.
Pressure: 15 Bar
Motor Speed: 1450 RPM
Power: 4-15 KW

1.4.2 Turbine Pump

Maximum Flow Rate : Up to 200 L/min
Max Differential Pressure: 14 bar
Max Working Pressure: Up to 34 bar
Motor Power: 4-5.5 kW
Explosion Proof IP56, IECEx Certified Motor

1.5 Hosepipe & Fittings

1.5.1 Hosepipe

We also have a large stock of hoses and fittings, allowing us to produce all types of EN1762 hoses of different diameters and lengths in a very short time.
Diameter: 1/2" to 8"
Version: EN 1762 DΩ Conductivity by internal elastomer (R<10 Ohms)
Operating pressure: 25 bar
Test pressure: 37.5 bar Operating temperature: -30 +70°C

1.5.2 Coupling

ACME & Dry Type Both Fittings available for various hose sizes
available in different ACME thread sizes: 1"1/4, 2"1/4, 3"1/4.
Dry Coupling: Flow rate:Up to 23,000 lpm (6075.9 gpm)
Sizes and range:1" to 8"

1.5.3 Breakaway couplings

Connections: Flange, Thread
Pressure range: Max. 25 bar (362.5 psi)
Sizes and range: 1" to 12"
Flow rate:Up to 44,500 lpm (11,755.6 gpm)

1.5.4 Pull away couplings

Connections:Thread
Types:FNPT
Pressure range:Max. 25 bar (362.5 psi)
Sizes and range:3/4" to 2"

1.6 Control Panel

It can control 2nos Dispenser and pump with surge protection, phase failure protection, motor protection, high voltage protection and emergency safety feature.

1.7 Pipe & Fittings

1.7.1 Ball Valves

1.7.2 Flanges

1.7.3 Pipe

1.7.4 Fittings

D. LPG Industrial Solution

1.1 LPG Storage Tank

1.2 LPG Vaporizer

1.2.1 Dry Type

1.2.2

1.3 High Pressure Regulator

1.4 Low Pressure Regulator

1.5 Oil Separator

1.6 Hosepipe with adaptor

1.7 Piping & Fittings

1.8 Instrumentations

Service

E. Engineering, Procurement & Construction (EPC)

1.1 LPG Filling Plant

We provide complete EPC solutions for LPG Filling Plants, including plant design, LPG storage systems, filling equipment, piping, electrical and instrumentation systems, installation, testing, and commissioning. Our solutions are customized to meet operational requirements and applicable safety standards.

1.2 Autogas Station

We design, supply, install, and commission complete LPG Autogas Stations for safe and efficient vehicle refueling. Our services include LPG dispensing systems, storage tanks, pumps, piping, electrical systems, safety equipment, and associated civil and mechanical works.

1.3 Reticulation System

1.3.1 Household

Our household LPG reticulation solutions provide safe and reliable centralized LPG distribution for residential buildings, apartments, villas, and housing projects. We design and install complete cylinder bank, manifold, regulator, piping, and safety systems according to site requirements.

1.3.2 Industrial

We provide industrial LPG reticulation systems for factories, commercial facilities, boilers, kitchens, process equipment, and other high-demand applications. Our systems are engineered for reliable gas supply, proper pressure control, operational safety, and efficient LPG utilization.

1.4 Machinery Servicing

We provide professional inspection, maintenance, troubleshooting, repair, and servicing of LPG machinery and equipment. Our service covers LPG filling machines, dispensers, pumps, compressors, flow meters, vaporizers, and related equipment to maintain safe, reliable, and efficient operation.

LPG Trading

1.1 local

1.2 Foreign

