

# QA Test Guide — Step by Step

Printable walkthrough generated from [docs/QA\\_TEST\\_PLAN.md](#). Each case shows its Gherkin scenario and the plain-English steps. Record results on the companion [QA Run Log](#) sheet. Generated 2026-09-04.

End-to-end manual test plan covering the **entire** functionality of the app across all three clients: **Web** (Blazor WASM), **Desktop** (MAUI / Windows), and **Android** (MAUI). Each case is written twice — a **Gherkin** scenario (Given/When/Then, matching this project's convention so it can later seed the automated E2E . Tests Playwright suite) and a **\*\*plain-English walkthrough\*\*** a manual tester can follow step by step.

Brand in examples is "Perezosoft"; substitute your app's brand if rebranded.

## How to use this document

- **Run the Smoke suite (§4) first.** It's the ~15-minute critical path. If any smoke case fails, stop and report — deeper suites will likely cascade.
- **Each case has an ID** (e.g. QA-AUTH-03). Record the result against the ID using the **sign-off sheet (§16)**: Pass / Fail / Blocked / N-A, plus tester, build/commit, date, notes.
- **Priority:** • **Smoke** Smoke (critical path) • • **Core** Core (run every regression) • • **Edge** Edge (run on full regression or when the area changed).
- **Automated in CI** on a case title means a Playwright journey in `tests/E2E.Tests` now exercises the same path on every push (the `e2e` job in `.github/workflows/ci.yml`). Human QA can **spot-check** these rather than run them in full each cycle; they still need a manual pass on Desktop/Android (the E2E job runs Web only) and whenever the area changes. The marker on each case title is authoritative (~35 cases); §15 maps the major journeys. See §17 for the run procedure.
- **Both formats describe the same test.** Read whichever suits you; the Gherkin is the source of truth for automation.
- **"App" = whichever client the suite header names.** Most behavior is identical across clients (same API, same shared RCL UI); the per-client suites (§12–§13) cover the auth transport and session persistence **plus the full per-feature native parity added by NATIVE-6** (share-sheet downloads, hardware back, refresh-on-return, theme/locale persistence — QA-DSK-08..15, QA-AND-07..15).

## 1. Environment & prerequisites

### 1.1 Backing services + API (host machine)

```
docker compose up -d # Postgres + Mailpit
dotnet run --project src/Api --launch-profile https # binds https:7160 (web/desktop) AND http:5238 (android)
```

- **API health/liveness check:** `curl -k https://localhost:7160/health -> 200` (Healthy); `curl -k https://localhost:7160/health/ready -> 200` when the database is reachable (503 if not). \*(The older `curl -k -X POST https://localhost:7160/api/auth/refresh -> 401` reachability check still works.)\*
- **Mailpit UI:** <http://localhost:8025> — this is the dev mail trap. Every magic link, OTP code, and invitation email lands here. Keep it open in a tab throughout testing.

(!) **Email only reaches Mailpit if SMTP points at it.** If your repo-root `.env` has the `Email__Smtp__*` lines set to a real provider (e.g. Brevo), the API sends auth emails there and **Mailpit stays empty** — every email-based case below will appear to "fail." For QA, route mail to Mailpit by **either**:

- commenting out the `Email__Smtp__*` lines in `.env` (unset -> defaults to Mailpit `localhost:1025`), **or**
- leaving `.env` untouched and overriding on the command line (command-line config beats `.env`):

```
```bash
dotnet run --project src/Api --launch-profile https -- \
--Email:Smtp:Host=localhost --Email:Smtp:Port=1025 --Email:Smtp:Username= --Email:Smtp:Password=
```
```

Verify by triggering one OTP (QA-SMK-01) and confirming it appears in Mailpit before running the suite.

(!) **Email delivery is now asynchronous.** Requesting a code/link/invite **enqueues** the email and a background dispatcher (the outbox) sends it — so it appears in Mailpit **\*\*a few seconds later**, not instantly. **Wait briefly before assuming failure.** The **send request now** always returns success\*\* (reliability moved to the background): if an email never arrives while SMTP points at Mailpit, the message is retrying or dead-lettered in the `OutboxMessages` table — it is **no longer** surfaced as a request error.

- Web app: `dotnet run --project src/Web --launch-profile https -> https://localhost:7008.`

(!) Always use the **https** profile for both web and API. Chrome treats `http://localhost` and `https://localhost` as different sites, so the refresh cookie is dropped over http and sign-in silently fails to persist. (See docs/DECISIONS.md / the schemeful-same-site note.)

(!) **The passwordless endpoints are rate-limited** per client IP: the **send** endpoints (`/otp/send`, `/magic-link/send`) default to **5/minute**; the **verify** endpoints (`/otp/verify`, `/mfa/verify`) have their **own, larger budget** (the OTP attempt cap + headroom, default **10/minute**) so the cumulative lockout's distinct message (QA-AUTH-04) surfaces before the throttle can mask it. Exceeding a budget returns **HTTP 429**, shown on `/login` as "Too many requests. Please wait a minute, then try again." — that's the abuse guard working (QA-AUTH-11), **not** a bug. Pace requests, or wait ~1 minute for the window to reset.

## 1.2 Test accounts & data

| Need                           | What to prepare                                                                                                                                                                                            |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Two real Google accounts       | e.g. <code>qa.owner@gmail.com</code> , <code>qa.member@gmail.com</code> — for OAuth + linking + multi-user household flows.                                                                                |
| One Microsoft personal account | for the Microsoft OAuth path (provider pinned to the <code>*consumers*</code> tenant).                                                                                                                     |
| Throwaway email addresses      | any address works for magic-link / OTP — mail is trapped by Mailpit, so the address need not be real. Use distinct ones per test to keep inboxes clean.                                                    |
| Two browser contexts           | a normal window <b>and</b> an incognito/second-profile window. The household invite flow needs two <code>*different*</code> signed-in users at once; incognito gives you an isolated session + cookie jar. |

**Database reset between full runs (optional but recommended):** to retest "new user" onboarding cleanly, you need users that don't yet exist. Either use fresh email addresses each run, or reset the dev DB: `docker compose down -v && docker compose up -d`, then re-apply migrations by starting the API. A volume wipe destroys all test data — only do it on the dev environment.

## 1.3 Desktop (MAUI Windows) — additional setup

- Run the app from Visual Studio (Windows Machine target) or `dotnet build src/Maui -t:Run -f net10.0-windows...`
- API must be running on `https://localhost:7160` (the desktop client's base URL).
- OAuth uses a **loopback browser flow** — your default system browser will open a tab during OAuth.

## 1.4 Android (MAUI) — additional setup

Follow docs/MOBILE\_TESTING.md. The essential bits:

- Emulator (AVD) or USB device running.

- **\*\*adb reverse tcp:5238 tcp:5238 — re-run every time the device/emulator restarts\*\*** (it does not persist). Verify with `adb reverse --list`.
- API started with the **https** profile (binds the cleartext :5238 leg the device uses).
- Provider redirect URIs registered: `http://localhost:5238/signin-google` and `http://localhost:5238/signin-microsoft`.

## 1.5 Environment B — deployed staging (DEPLOY, ADR-017)

Everything above is **Environment A** (local). The same suite also runs against the **deployed staging** environment — one Render container serving the API + WASM **single-origin** over real HTTPS, backed by Neon Postgres and Brevo email. Point the browser at the staging URL (e.g. `https://<app>-staging.onrender.com`) and execute the cases exactly as written. What differs from local:

- **One origin, real TLS.** Web + API share the host, so there's no separate API port and no CORS step.
- **Email is real (Brevo), not Mailpit.** Use **real or plus-addressed inboxes** you can open (e.g. `you+qa1@gmail.com`); there's no mail-trap UI. If a code/link doesn't arrive, check **Brevo -> Transactional -> Logs** (and that a verified sender + `Email__SmtP__FromAddress` are set). Email cases are therefore slower than local — pace them (the passwordless rate limit still applies).
- **Cold start.** Free instances sleep after ~15 min idle; the **first** request of a session can take ~30–60 s. That's expected, not a failure — retry once it wakes.
- **OAuth** buttons appear **only** for providers configured on staging (Google/Microsoft need their redirect URIs registered against the staging host). If unconfigured, the buttons are simply absent (by design) — record those provider cases **N-A** for this environment.
- **Billing** uses Stripe **test mode** — exercise webhooks with `stripe trigger ...` against the staging `/api/billing/webhook`.

**Auto-deploy + smoke gate.** A merge to `develop` that passes CI auto-deploys staging, waits for the new build to be live (`/api/version` reports the pushed commit), and runs an automated post-deploy smoke (liveness/readiness, SPA shell + deep-link, `/api` returns an API-shaped 404, `/api/auth/providers`). A red smoke blocks — so a broken deploy is caught before manual QA starts. Manual QA on staging complements it (the human-only paths: real email, OAuth, billing, visual checks).

## 2. Scope

**In scope:** authentication (all methods, all clients), new-user onboarding, household/tenant management, invitations & joining, account settings (linked providers), localization (EN/ES), transactional emails, cross-cutting security (tenant isolation, auth guards, token lifecycle), and **native (MAUI) feature parity** — the shared-RCL feature surface exercised per platform on Windows + Android (§12–13) with a first-run iOS/macCatalyst smoke (§13b) and a per-release native checklist (§13c).

**\*\*Out of scope** (per `docs/PROJECT_BRIEF.md` OUT list & current state):\*\* SMS OTP, OAuth providers beyond Google/Microsoft, FR/DE/PT languages (scaffolded but not translated — see `docs/LOCALIZATION.md`), and any app-specific domain features not yet built on this platform.

**Platform services with no client UI (API-/operational-level, not manually testable through the app yet):** the append-only audit log, OpenTelemetry telemetry, the health endpoints, the background outbox/inbox/scheduled-jobs, and **file storage** — the `IFileStorage` seam + the signed download endpoint `GET /api/files/{token}` (anonymous, the token *\*is\** the authorization; local-disk only — cloud backends hand out native presigned URLs). These are **covered by automated tests** (`tests/Api.Tests`); browser E2E for them is deliberately out of scope (headless machinery). The **billing page** is NO longer in this list — BILLING-8 shipped `/billing` (§10c, QA-BILL-01/02) with the fake-provider E2E journey (`BillingJourneyTests`). Health has a smoke check (QA-SMK-07); manual cases for the rest will be added when client UI exists. **GDPR data export** (`POST /api/household/export`) and **account erasure** (`DELETE /api/auth/me`) now **have a web UI** (UI-1: owner Household -> Data, Settings -> Danger zone) — covered by the manual cases QA-HH-13 + QA-SET-07. **RBAC role management now has a web UI** (RBAC-3) — covered by the household cases QA-HH-09..12. **MFA now has a web UI** (UI-2) — enrollment/ disable in Settings and the sign-in step-up on Login — covered by QA-MFA-01..03. The **in-app notification center now has a web UI** (UI-3) — the header bell (list, unread count, mark-read, delete/clear) and Settings delivery-preference switches — covered by QA-NOTIF-01..04. The **platform-staff admin surface now has a web UI** (UI-4) — a staff-only `/admin` console (tenant list/detail + impersonation + targeted/broadcast announcements + plan comp/revert + MFA reset) — covered by

QA-ADMIN-01..07. The **public API (PUBAPI)** and **outbound webhooks (HOOKS)** are intentionally UI-less (they're for machines) and **config-gated off** — they have **manual curl/Postman cases in §14b** (QA-API-01..06), in addition to automated tests.

**Automated in CI (Web):** a Playwright/NUnit E2E suite (`tests/E2E.Tests`, currently 34 journeys) runs against the real booted stack on every push — the e2e job in `.github/workflows/ci.yml`. Every case it covers is marked **Automated in CI** on its title (≈35 cases across auth, MFA, i18n, household/roster, invitations, notifications, admin, billing, theme, and GDPR — the case titles are authoritative; §15 maps the major journeys). Human QA can spot-check those on Web and focus effort on the un-automated cases and the native clients — where CI runs two smoke canaries (Android boots the real app and drives the OTP journey on an emulator; Windows is a boot-to-login probe only).

### 3. Test data conventions

- **Owner user** = the account you sign in with first; it auto-creates and owns a household.
- **Member user** = a second account invited into the owner's household.
- Household auto-named on creation; rename it to something recognizable (e.g. "QA House") early so you can spot it in the header tenant badge.

### 4. Smoke suite • Smoke (run first — ~15 min)

The critical path: can a user get in by each method, reach the app, and get out.

#### QA-SMK-01 — Web: OTP sign-in happy path • Smoke (Web) Automated in CI

##### Gherkin

```
Given I am an anonymous user on the /login page of the web app
When I enter my email and request a 6-digit code
And I retrieve the code from Mailpit and submit it
Then I am signed in and land on the home page
And the header shows my household name and my display name
```

##### Walkthrough

- 1 Open <https://localhost:7008> -> you're redirected to /login.
- 2 In the email field enter `qa-smoke@example.com`; click **Email me a 6-digit code**.
- 3 **Expected:** the form switches to a code-entry view ("Enter the 6-digit code sent to ...").
- 4 Open Mailpit (<http://localhost:8025>); open the newest mail; copy the 6-digit code.
- 5 Enter the code; click **Verify code**.
- 6 **Expected:** you land on the home page; the top header shows a tenant badge (household name) and your display name, plus **Household**, **Settings**, **Sign out** buttons.

#### QA-SMK-02 — Web: Google OAuth sign-in • Smoke (Web)

##### Gherkin

```
Given I am on the /login page
When I click "Continue with Google" and complete Google consent
Then I am returned to the app, signed in, on the home page
```

##### Walkthrough

- 1 From /login, click **Continue with Google**.
- 2 **Expected:** full-page redirect to Google's consent screen.
- 3 Choose `qa.owner@gmail.com`, approve.
- 4 **Expected:** redirected back into the app, signed in, on the home page with the header chrome.

#### QA-SMK-03 — Web: Sign out • Smoke (Web) Automated in CI

##### Gherkin

```
Given I am signed in to the web app
When I click "Sign out"
Then I am returned to the /login page
And navigating to /settings redirects me back to /login
```

#### Walkthrough

- 1 While signed in, click **Sign out** in the header.
- 2 **Expected:** you land on /login.
- 3 In the address bar go to /settings.
- 4 **Expected:** you're bounced back to /login (no access without a session).

### QA-SMK-04 — Web: Session persists across reload ("remember me") • Smoke (Web)

#### Gherkin

```
Given I am signed in to the web app
When I reload the page (or reopen the tab)
Then I am still signed in without re-authenticating
```

#### Walkthrough

- 1 Signed in, press F5 / reload.
- 2 **Expected:** brief load, then the app shell — still signed in, no trip to /login. (A silent refresh exchanges the refresh cookie for a new access token on load.)

### QA-SMK-05 — Desktop: OTP sign-in • Smoke (Desktop) — see QA-DSK-01

### QA-SMK-06 — Android: OTP sign-in • Smoke (Android) — see QA-AND-01

### QA-SMK-07 — API health & readiness • Smoke (Platform)

#### Gherkin

```
Given the API is running
When I GET /health and /health/ready
Then /health returns 200 "Healthy"
And /health/ready returns 200 when the database is reachable, 503 when it is not
```

#### Walkthrough

- 1 `curl -k https://localhost:7160/health -> 200`, body Healthy (liveness — process up).
- 2 `curl -k https://localhost:7160/health/ready -> 200` (readiness — Postgres reachable).
- 3 *\*(Optional)\** stop the DB (`docker compose stop db`) and re-run step 2 -> **503**; then `docker compose start db` and confirm it returns to **200**.
- 4 **Expected:** liveness is 200 whenever the process runs; readiness tracks DB reachability. Responses are **status-only** (no connection details leaked).

## 5. Web — Authentication • Core

### QA-AUTH-01 — Magic-link sign-in happy path • Core (Web) Automated in CI

#### Gherkin

```
Given I am an anonymous user on /login
When I enter my email and request a magic link
And I open the emailed link from Mailpit
Then I am signed in and landed in the app
```

#### Walkthrough

- 1 On /login enter `qa-magic@example.com`; click **Email me a magic link**.
- 2 **Expected:** a success panel — "Check your inbox." + "A sign-in link was sent to `qa-magic@example.com`. It expires in 15 minutes." — with a **Use a different email** link.

- 3 In Mailpit open the newest mail; click the sign-in link (or copy it into the same browser).
- 4 **Expected:** the link resolves and you end up signed in, in the app.

## QA-AUTH-02 — Microsoft OAuth sign-in • Core (Web)

### Gherkin

```
Given I am on /login
When I click "Continue with Microsoft" and complete consent
Then I am returned signed in
```

**Account resolution (read before testing):** signing in with a provider whose email matches an existing account links the provider to that account rather than creating a duplicate — but only when the email is **verified**. Google asserts this; Microsoft on the **\*\*consumers\*\*** (personal MSA) tenant is trusted to have a verified email even though it omits the claim (IProviderEmailTrust). For **work/school** tenants (organizations/common/a tenant GUID) and any other provider, a same-email auto-link is **refused** (fail-closed takeover guard, audit MITI-3) — the user signs in with their original method and links the provider from **Settings** instead (QA-SET-02). To test the plain first-time path below, use a Microsoft account whose email has **no** prior account.

### Walkthrough

- 1 Click **Continue with Microsoft**; sign in with a **personal** Microsoft account.
- 2 **Expected:** returned to the app signed in. A brand-new email creates a new account; a personal Microsoft account whose email already exists auto-links to that account (consumers tenant). (If you see a tenant/reply-URL error, the provider registration is the cause — out of app scope, note it.)

## QA-AUTH-03 — OTP wrong code is rejected • Core (Web)

### Gherkin

```
Given I requested an OTP code for my email
When I submit an incorrect 6-digit code
Then I see an "incorrect code" error and remain on the code-entry screen
```

### Walkthrough

- 1 Request an OTP (as QA-SMK-01) but **do not** use the real code.
- 2 Enter 000000; click **Verify code**.
- 3 **Expected:** inline error ("code is incorrect / verification failed"); you stay on the code-entry view and can retry. You are **not** signed in.

## QA-AUTH-04 — OTP cumulative lockout & code expiry • Edge (Web)

### Gherkin

```
Given I requested an OTP code
When I submit wrong codes up to the cumulative limit (default 5 failures per email within a 15-min window)
Then the email is locked – further attempts, INCLUDING a freshly requested code, are rejected until the window elapses
And separately, an unused code is rejected once it passes its lifespan (default 10 minutes)
```

### Walkthrough

- 1 Request an OTP for an email; enter a **wrong** 6-digit code until you hit the cumulative limit (default 5, Auth:Otp:MaxAttempts, counted **\*\*per email across the Auth:Otp:LockoutWindowMinutes = 15-min window\*\***, not per code).
- 2 **Expected:** after the limit, a "too many attempts" lockout error.
- 3 Now request a **fresh** code and submit it — even the **correct** one.
- 4 **Expected:** still rejected — requesting a new code does **NOT** reset the budget (this is the brute-force defense; a resend can't hand the attacker another N guesses). The lock clears after the 15-min window.
- 5 **Expiry sub-case:** separately, request a code and wait past Auth:Otp:CodeLifespanMinutes (default 10) — the stale code is rejected.

**Note (enumeration):** OTP verify returns the **same** generic "invalid code" error whether the code was wrong or there is no active code — it never reveals whether an address has an outstanding OTP. \*(Long-wait cases — lower the config to test fast. The verify throttle's budget deliberately sits **above** the attempt cap — QA-AUTH-11 — so you reach this lockout and see its distinct message before any 429; only hammering faster than ~10 verifies/minute trips the throttle.)\*

## QA-AUTH-11 — Passwordless endpoints are rate-limited • Core (Web)

### Gherkin

```
Given I rapidly request codes/links for the same client
When I exceed the per-IP send limit (default 5 per minute)
Then further requests are rejected with HTTP 429 until the window resets
```

### Walkthrough

- 1 From /login, request an OTP (or magic link) repeatedly in quick succession — more than 5 within a minute.
- 2 **Expected:** after the limit the request is throttled (**HTTP 429**), surfaced on /login as **"Too many requests. Please wait a minute, then try again."** OTP verify has its own, larger per-IP budget — max(send limit, OTP attempt cap + 5) = 10/min by default (so the lockout cap in QA-AUTH-04 is reachable) — with the same 429 + message when exceeded.
- 3 Wait ~1 minute; requests succeed again.

Protects against email-bombing and OTP brute-forcing. Expected behavior, not a defect — see the §1.1 pacing note.

## QA-AUTH-05 — Magic link is single-use • Edge (Web) Automated in CI

### Gherkin

```
Given I signed in by clicking a magic link
When I click the same link a second time
Then it is no longer valid
```

### Walkthrough

- 1 Complete QA-AUTH-01. Then revisit the *\*same\** link from Mailpit.
- 2 **Expected:** it does not grant a second session — you're sent to /login with an invalid-link indication (or simply not signed in). The token is consumed on first use.

## QA-AUTH-06 — Magic link expiry • Edge (Web)

**Walkthrough:** request a link, wait past Auth:MagicLink:TokenLifespanMinutes (default 15), then open it.

**Expected:** rejected as expired; user lands on /login. \*(Lower the config to test fast.)\*

## QA-AUTH-07 — User-enumeration protection • Core (Web)

### Gherkin

```
Given an email address that has no account
When I request a magic link or OTP for it
Then the UI shows the same success/"check your inbox" response as for a real account
```

### Walkthrough

- 1 Request a magic link **and** an OTP for a never-before-used address.
- 2 **Expected:** identical success messaging to a known address — the app never reveals whether an account exists. (Mailpit will still show whatever the system chose to send.)

## QA-AUTH-08 — Login error banners • Edge (Web)

### Gherkin

```
Given the login page is loaded with an error query parameter
Then a human-readable error banner is shown
```

**Walkthrough** — visit each URL and confirm a red banner with sensible copy:

- `/login?error=external_failed` -> external sign-in failed message.
- `/login?error=email_unverified` -> email-unverified message.
- `/login?error=invalid_link` -> invalid/expired link message.
- `/login?error=somethingelse` -> generic "something went wrong" fallback.

## QA-AUTH-09 — Email-format validation • Edge (Web) Automated in CI

**Walkthrough:** on `/login`, click a send button with an empty or malformed email (e.g. `abc`). **Expected:** inline "enter a valid email" validation; no request sent.

## QA-AUTH-10 — Magic link & OTP available on web; OAuth always • Edge (Web)

**Walkthrough:** confirm the web login page shows **both** "Email me a magic link" and "Email me a 6-digit code", plus Google/Microsoft buttons. (Native clients hide magic link — covered in §11–12.)

# 6. Web — Onboarding & new tenant • Core

## QA-ONB-01 — First-ever sign-in auto-creates a household, user is owner • Smoke (Web)

Gherkin

```
Given an email/account that has never signed in before
When I authenticate for the first time (any method)
Then a new household is created and I am its owner
And the header shows that household and my name
```

### Walkthrough

- 1 Sign in with a brand-new account/email (fresh address or post-DB-reset).
- 2 **Expected:** you reach the app immediately (no "create household" prompt — provisioning is automatic). Open **Household:** you are listed with the **Owner** badge and are the only member.

## QA-ONB-02 — Returning user keeps their household • Core (Web)

**Walkthrough:** sign out and back in with the same account. **Expected:** same household, same role, data intact.

# 7. Web — Household management • Core

Roles: **owner** > **admin** > **member** (ADR-009). **Owner + admin** can rename and invite/remove members; **owner-only:** change member roles (promote/demote), transfer ownership, dissolve. Members see a read-only name and a **Leave** button. The owner's row never shows action buttons.

## QA-HH-01 — Owner renames the household • Core (Web)

Gherkin

```
Given I am the household owner on /household
When I change the name and click Rename
Then the new name is saved and reflected in the header tenant badge
```

### Walkthrough

- 1 **Household** -> edit the name field (e.g. "QA House") -> **Rename**.
- 2 **Expected:** success banner; the header tenant badge updates to the new name (a silent refresh updates the claim).

## QA-HH-02 — Member sees read-only household, no owner controls • Core (Web) Automated in CI

**Precondition:** signed in as a \*member\* (use QA-INV flow to create one). **Walkthrough:** open **Household**. **Expected:** household name shown as read-only heading; no rename/invite/transfer controls; a **Leave** button is present.

## QA-HH-03 — Owner removes a member • Core (Web) Automated in CI

## Gherkin

```
Given I am the owner and another member exists
When I click Remove next to that member and confirm
Then they are removed from the household member list
```

### Walkthrough

- 1 As owner with a member present, click **Remove** by the member's row.
- 2 **Expected:** a confirm dialog ("Remove <name>?"); on confirm, success banner and the member disappears from the list. (The removed user is re-homed to a fresh solo household — verify by signing in as them: they now own an empty household — see QA-HH-08.)

## QA-HH-04 — Owner cannot remove themselves • Edge (Web)

**Walkthrough:** as owner, confirm there is **no Remove button on your own row**. (Owner departs via transfer or dissolve, not removal.)

## QA-HH-05 — Transfer ownership • Core (Web) Automated in CI

### Gherkin

```
Given I am the owner and at least one other member exists
When I select that member and click Transfer
Then they become owner and I become a regular member
```

### Walkthrough

- 1 As owner with  $\geq 1$  other member, in **Transfer ownership** pick the member -> **Transfer**.
- 2 **Expected:** success banner. The chosen member now shows the **Owner** badge; your row shows **Member**. The owner-only controls (invite/transfer/dissolve) are no longer available to you, and a **Leave** button now is.

## QA-HH-06 — Owner with other members cannot directly leave/dissolve • Edge (Web)

**Walkthrough:** as owner **with** other members present, confirm the bottom card shows the **Transfer ownership** control (with "you must transfer before leaving" note) — **not** a leave/dissolve button. The single-owner invariant is enforced in the UI.

## QA-HH-07 — Sole owner dissolves the household • Core (Web) Automated in CI

### Gherkin

```
Given I am the only member and owner of my household
When I click "Leave and delete" and confirm
Then the household is dissolved and I am re-homed to a fresh solo household
```

### Walkthrough

- 1 As sole owner (no other members), bottom card ("Leave & dissolve") -> **Leave and delete**.
- 2 **Expected:** a confirm dialog warning the household will be deleted; on confirm, the app reloads and you land signed in with a **new empty household you own** (you're never left tenant-less).

## QA-HH-08 — Member leaves the household • Core (Web) Automated in CI

### Gherkin

```
Given I am a non-owner member
When I click Leave and confirm
Then I leave the household and am re-homed to a fresh solo household I own
```

### Walkthrough

- 1 As a member, **Household** -> **Leave** -> confirm.
- 2 **Expected:** app reloads; you now own a brand-new empty household. The household you left still exists for its remaining members (verify as the owner: the leaver is gone from the member list).

## QA-HH-09 — Owner promotes a member to admin • Core (Web) Automated in CI

**Precondition:** signed in as the owner with at least one **member** present (use the QA-INV flow). **Gherkin**

```
Given I am the owner and another member exists
When I click "Make admin" next to that member
Then their badge changes to Admin
```

#### Walkthrough

- 1 On **Household**, find a member's row -> click **Make admin**.
- 2 **Expected:** success banner ("Role updated."); the member's badge flips from **Member** to **Admin**, and the button becomes **Make member**. (Verify as that user — see QA-HH-11.)

### QA-HH-10 — Owner demotes an admin to member • Core (Web) Automated in CI

#### Gherkin

```
Given I am the owner and an admin exists
When I click "Make member" next to that admin
Then their badge changes back to Member
```

#### Walkthrough

- 1 On **Household**, on an **Admin** row -> click **Make member**.
- 2 **Expected:** success banner; the badge returns to **Member** and the button becomes **Make admin**.

### QA-HH-11 — Admin sees management controls but not role/ownership controls • Core (Web) Automated in CI

**Precondition:** signed in as the admin promoted in QA-HH-09. **Gherkin**

```
Given I am an admin (not the owner)
When I open Household
Then I can rename the household and invite/remove members
But I see no promote/demote (role) controls and no transfer/dissolve — only Leave
```

#### Walkthrough

- 1 As the admin, open **Household**.
- 2 **Expected:** the **rename** field and the **Invitations** card are available; member rows show a **Remove** button **but no Make admin/Make member** buttons (role changes are owner-only). The bottom card shows **Leave** (no Transfer ownership / Leave & delete). The owner's row shows **no** action buttons.

### QA-HH-12 — Member sees no management controls • Edge (Web) Automated in CI

**Walkthrough:** signed in as a plain **member**, open **Household**. **Expected:** read-only name, no Invitations card, no per-row action buttons (no Remove/role controls), only a **Leave** button — unchanged from QA-HH-02 (a member is never shown management controls regardless of the admin tier).

### QA-HH-13 — Owner exports household data • Core (Web)

#### Gherkin

```
Given I am the household owner on /household
When I click "Download household data"
Then I get a link to a JSON export of the household's data
```

#### Walkthrough

- 1 As owner, open **Household** -> the **Data** card -> **Download household data**.
- 2 **Expected:** a success row with a **Download** link; following it downloads a JSON bundle containing the tenant, members and invitations (and each feature's data). Members/admins don't see the Data card (owner-only). No secrets (invitation token hashes) appear in the file.

### QA-HH-14 — Seat quota blocks inviting past the plan limit • Core (Web) Automated in CI

**Precondition:** the platform ships example seat caps (Free = 3 seats, counting members + pending invites; PlanCatalog). A Free household at its cap (e.g. 3 members, or 2 members + 1 pending invite). **Gherkin**

```
Given my Free plan's seats are all used (members + pending invites)
When I invite another member
Then I'm told my seat limit is reached and to upgrade (nothing is invited)
And raising the limit (Pro plan / editing PlanCatalog) lets the invite through
```

#### Walkthrough

- 1 As owner of a Free household at the seat cap, **Household** -> invite a new email.
- 2 **Expected:** an error — "Your plan's seat limit is reached. Upgrade your plan to invite more members." (HTTP 402); no invitation is created and no email is sent.
- 3 Free up a seat (revoke a pending invite / remove a member) **or** move to a higher-seat plan — the next invite succeeds. (Seats count members **plus** pending invites, so invites can't over-provision.)
- 4 **Note:** limits are PlanCatalog data; null/absent = unlimited. Metered-usage caps (IQuotaService.TryConsumeAsync, monthly) are wired the same way where an app calls them.

## 8. Web — Invitations & joining • Core

### QA-INV-01 — Owner invites by email; token revealed + email sent • Smoke (Web) Automated in CI

#### Gherkin

```
Given I am the household owner
When I invite an email address
Then an invitation appears in the pending list with an expiry date
And a one-time join token is revealed in the UI
And an invitation email with a /join link is delivered to Mailpit
```

#### Walkthrough

- 1 **Household** -> Invitations -> enter qa.member@gmail.com -> **Invite**.
- 2 **Expected:** a green panel reveals the raw token + a **Copy** button and notes a join link was emailed; the address shows under **Pending** with an expiry date.
- 3 Check Mailpit: an invitation email addressed to that user, containing a /join?token=... link.

### QA-INV-02 — Invitee accepts and joins (two-user flow) • Smoke (Web) Automated in CI

#### Gherkin

```
Given an invitation exists for a second user
When that user opens the /join link, signs in, and accepts
Then they become a member of the inviter's household
```

#### Walkthrough

- 1 Copy the /join?token=... link from QA-INV-01.
- 2 In an **incognito window**, open the link.
- 3 **Expected:** "You've been invited... sign in to accept." Click **Sign in to accept**; complete any sign-in method as qa.member@gmail.com.
- 4 **Expected:** after sign-in you're returned to the join flow automatically, it processes, and you see "**You're in**" with a **Go to household** button.
- 5 Click it -> **Household** shows you as a **Member** of "QA House".
- 6 Back in the owner window, reload **Household**: the new member appears and the pending invite is gone.

### QA-INV-03 — Already-authenticated user accepts directly • Core (Web)

**Walkthrough:** while already signed in as a \*different\* fresh user, open a valid /join?token=.... **Expected:** it accepts immediately (no sign-in step) and shows success. \*(Note: a user already in a household who accepts another invite moves to the new household — verify their old membership is replaced, honoring the one-tenant invariant.)\*

### QA-INV-04 — Join page with no token offers manual code entry • Edge (Web)

**Walkthrough:** open /join with no ?token=. **Expected:** the **manual invite-code entry** state ("Join with an invite code" + input + submit — the NATIVE-4b path for emailed codes), no crash. Pasting a garbage code shows the inline error and lets you retry ( automated: MembershipLifecycleTests.Pasting\_An\_Invalid\_Code\_Shows\_An\_Inline\_Error).

## QA-INV-05 — Join with invalid/expired/used token • Core (Web)

### Gherkin

```
Given an invitation token that is invalid, already used, or expired
When an authenticated user opens its /join link
Then they see an error state, not a successful join
```

**Walkthrough:** while signed in, open /join?token=garbage123 (or reuse a token already accepted in QA-INV-02). **Expected:** the error state with a **Back to household** link; no membership change.

## QA-INV-06 — Invite an existing member is rejected • Core (Web)

### Gherkin

```
Given a user is already a member of my household
When I invite their email again
Then I get an "already a member" error and no duplicate invite is created
```

**Walkthrough:** as owner, invite the email of someone already in the household. **Expected:** a red "already a member" status (HTTP 409); nothing added to pending.

## QA-INV-07 — Regenerate a pending invitation • Core (Web)

### Gherkin

```
Given a pending invitation exists
When I click Regenerate
Then a new token is issued (revealed) and the old token no longer works
```

### Walkthrough

- 1 On a pending invite, click **Regenerate**.
- 2 **Expected:** a new token is revealed. The **previous** token's /join link now fails (QA-INV-05), the new one works.

## QA-INV-08 — Revoke a pending invitation • Core (Web) Automated in CI

### Gherkin

```
Given a pending invitation exists
When I click Revoke
Then it is removed from pending and its token no longer works
```

**Walkthrough:** click **Revoke** on a pending invite. **Expected:** "invitation revoked" status; it leaves the pending list; opening its old link gives the error state.

## QA-INV-09 — Copy token button • Edge (Web)

**Walkthrough:** click **Copy** on a revealed token; paste elsewhere. **Expected:** the token is on the clipboard. (If the browser blocks clipboard access, the token is still visible to copy manually — no error shown.)

## QA-INV-10 — Accepting an invite after a downgrade is refused (seat re-check) • Core (Web) Automated in CI

**Precondition:** a way to change the tenant's plan — staff comp/revert (QA-ADMIN-06) or the fake provider webhook (E2E does the latter). **Gherkin**

```
Given a household on Pro invited more members than the Free plan allows
And the subscription has since lapsed or been reverted to Free
When an invitee opens a still-valid invitation link
Then joining is refused with a "This household is full" message
And the invitation stays pending (it works again if the owner re-upgrades)
```

### Walkthrough

- 1 Comp the household to Pro (QA-ADMIN-06); as the owner, invite members until members + pending exceeds the Free limit (currently 3).
- 2 Revert the household to Free.
- 3 Sign in as an invitee (fresh browser) and open the invite link / paste the code on /join.
- 4 **Expected:** the join page shows "This household is full" (402 seat\_limit\_reached) — the invitee does not join and no membership changes. Existing members are untouched; new invites are also blocked (QA-HH-14).
- 5 Comp back to Pro and retry the same link. **Expected:** it joins — the refused token self-heals (BILLING-9, ADR-006 addendum).

## 9. Web — Settings / linked accounts • Core

### QA-SET-01 — View linked providers • Core (Web)

#### Gherkin

```
Given I signed up with Google
When I open /settings
Then Google shows as "Connected" and Microsoft shows a "Link" button
```

**Walkthrough:** sign in with Google, open **Settings**. **Expected:** a row per provider; the one you used shows a **Connected** badge + **Unlink**; the other shows **Link**.

### QA-SET-02 — Link a second provider • Core (Web)

#### Gherkin

```
Given I am signed in and Microsoft is not linked
When I click Link on Microsoft and complete consent
Then Microsoft becomes Connected on my account (no new account is created)
```

#### Walkthrough

- 1 **Settings** -> **Link** on Microsoft -> complete consent with a Microsoft account **whose email isn't already used by another app user**.
- 2 **Expected:** returned to Settings with a success banner ("Microsoft linked"); Microsoft now shows **Connected**. You can subsequently sign in with either provider into the *\*same\** account.

### QA-SET-03 — Linking a provider already used by another account is rejected • Core (Web)

#### Gherkin

```
Given a provider identity is already linked to a different user
When I try to link it to my account
Then I get an "already in use" error and it is not linked
```

**Walkthrough:** try to **Link** a Google/Microsoft identity that another app user already owns. **Expected:** Settings shows an "already in use" banner (?link\_error=in\_use); no link made. \*(Expired link-token path shows ?link\_error=expired — exercise if you can stall the flow past the token lifetime.)\*

### QA-SET-04 — Unlink a provider • Core (Web)

#### Gherkin

```
Given two providers are linked to my account
When I click Unlink on one and confirm the dialog
Then it returns to a "Link" state
```

**Walkthrough:** with two providers connected, click **Unlink** on one. **Expected:** a confirm dialog ("Unlink this sign-in method?"); on **confirm** the row reverts to **Link**. **Cancelling** the dialog leaves it **Connected** — no change. \*(The confirm fails closed: if the browser dialog can't run, the unlink is cancelled, never silently performed. The same guarded confirm protects remove-member / leave / dissolve in §7.)\*

### QA-SET-05 — Unlinking your only provider never locks you out • Edge (Web)

#### Gherkin

```
Given Google is my only linked provider
When I unlink it
Then I can still sign in by email (magic link / OTP)
```

**Walkthrough:** unlink your sole provider, sign out, and sign back in with **OTP/magic link** using the same email.

**Expected:** you reach the **same** account/household. (Email sign-in is always available by design, so provider removal can't lock you out.)

## QA-SET-06 — Settings requires auth • Edge (Web)

**Walkthrough:** signed out, navigate to /settings. **Expected:** redirect to /login.

## QA-SET-07 — Delete my account • Core (Web) Automated in CI

**Precondition:** use a **throwaway** account (this is destructive). Easiest: a member of another owner's household (so no dissolve). **Gherkin**

```
Given I am signed in on /settings
When I use the Danger zone "Delete my account" and confirm
Then my account and personal data are deleted and I'm signed out
```

### Walkthrough

- 1 **Settings -> Danger zone -> Delete my account** -> confirm the dialog.
- 2 **Expected (member):** account deleted; you're signed out and land on /login. Signing in again creates a brand-new account.
- 3 **Owner with other members:** an error tells you to **transfer ownership first** (nothing deleted).
- 4 **Sole owner:** a second confirm warns it also **dissolves the household**; on confirm, the account + household are deleted.

## QA-SET-08 — Theme: dark mode applies, persists, and follows the user • Core (Web) Automated in CI

### Gherkin

```
Given I am signed in
When I pick "Dark" in the header theme switcher
Then the app restyles dark immediately without a reload
And a reload first-paints dark (no light flash)
And signing in on a fresh browser profile renders dark as part of the sign-in
```

### Walkthrough

- 1 Signed in, pick **Dark** in the header switcher (login page and **Settings -> Preferences** have the same control). **Expected:** the page flips dark instantly — background, cards, buttons, and the brand lockup swaps to its dark variant; no reload.
- 2 Reload. **Expected:** the very first paint is dark — no white flash.
- 3 Sign in as the same user in a fresh browser profile (or private window). **Expected:** dark applies as part of signing in, no reload needed — the choice is stored per user server-side (PREFS-1, ADR-022).
- 4 Pick **Auto**. **Expected:** the app follows the OS scheme live (flip the OS setting to check). Auto is stored per user too: a second browser showing Dark returns to the OS scheme on its next sign-in/reload.

## QA-MFA-01 — Enable two-factor (authenticator TOTP) • Core (Web) Automated in CI

**Precondition:** signed in; an authenticator app (Google Authenticator, 1Password, Authy, ...) to hand. **Gherkin**

```
Given I am signed in on /settings with two-factor Off
When I enable it, scan the QR (or enter the key) and confirm with a 6-digit code
Then two-factor turns On and I'm shown one-time recovery codes
```

### Walkthrough

- 1 **Settings -> Two-factor authentication** shows an **Off** badge -> **Enable two-factor**.
- 2 A **QR code** renders next to a **manual key** (Base32). Scan it (or type the key) into the app.
- 3 Enter the app's current **6-digit code** -> **Verify & enable**.

- 4 **Expected:** a success banner, the badge flips to **On**, and a grid of 10 **recovery codes** appears (shown once) — short, typeable xxxxx-xxxxx codes (e.g. k7m2q-9xr4t; no ambiguous 0/0/1/I/L glyphs). **I've saved my codes** returns to the On state.
- 5 **Wrong code:** an inline error ("that code is incorrect or has expired"); nothing changes.

## QA-MFA-02 — Two-factor is required at sign-in • Core (Web) Automated in CI

**Precondition:** an account with two-factor **On** (QA-MFA-01). **Gherkin**

```
Given my account has two-factor enabled
When I sign in with an email OTP
Then I'm asked for an authenticator code before the session starts
And entering a valid code completes sign-in
```

### Walkthrough

- 1 Sign out. On /login, request an **email code**, enter it.
- 2 **Expected:** instead of landing signed-in, a **second prompt** asks for the authenticator code.
- 3 Enter the current 6-digit code -> you're signed in (lands on /).
- 4 **Wrong/expired code:** an inline error; you stay on the step-up prompt (no session).
- 5 **Note:** OAuth and magic-link sign-ins enforce the step-up too (QA-MFA-04); native (MAUI) too (QA-MFA-05).

## QA-MFA-03 — Use a recovery code, then disable two-factor • Core (Web)

**Gherkin**

```
Given my account has two-factor enabled
When I sign in and enter a recovery code at the step-up
Then sign-in completes (that code is now spent)
And I can disable two-factor from Settings with a valid code
```

### Walkthrough

- 1 Sign in as in QA-MFA-02; at the step-up, enter one **recovery code** instead of a TOTP -> signs in. Entry is forgiving: wrong case, a dropped hyphen, or stray spaces still match (K7M2Q9XR4T ≡ k7m2q-9xr4t).
- 2 **Settings** -> **Two-factor authentication** (On) -> **Disable two-factor** -> enter a current TOTP (or another recovery code) -> **Disable**.
- 3 **Expected:** the badge flips to **Off**; a subsequent sign-in no longer asks for a second step.

## QA-MFA-04 — Redirect logins (OAuth / magic link) enforce the step-up • Core (Web)

**Precondition:** an account with two-factor **On**, reachable via an OAuth provider and/or magic link. **Gherkin**

```
Given my account has two-factor enabled
When I sign in with Google/Microsoft or a magic link
Then I am redirected to the authenticator step-up before any session is issued
And entering a valid code completes sign-in
```

### Walkthrough

- 1 Sign out. Sign in via **Google/Microsoft** (or click a **magic link**).
- 2 **Expected:** instead of landing signed-in, you arrive on /login showing the **authenticator code prompt** (the URL carries a one-time ?mfa= challenge). No session exists yet.
- 3 Enter the current 6-digit code (or a recovery code) -> you're signed in (/auth-callback -> /).
- 4 **Security check:** confirm you are **not** signed in until the code is accepted — a wrong/expired code keeps you on the prompt with no session. (This closes the gap where redirect logins skipped MFA.)

## QA-MFA-05 — Native (MAUI) sign-in enforces the step-up • Core (Desktop/Android)

**Precondition:** an account with two-factor **On**; run the desktop/Android shell (see docs/MOBILE\_TESTING.md). Native has no magic link — use **email OTP** or **OAuth**. **Gherkin**

```
Given my account has two-factor enabled
When I sign in on the native app with an email code or OAuth
Then the app shows the authenticator step-up in-app before completing sign-in
And a valid code (or recovery code) finishes sign-in
```

### Walkthrough

- 1 In the native app, sign in with an **email code** (or a provider).
- 2 **Expected:** the app stays on the login screen and shows the **authenticator code prompt** (it does not sign in yet). No session/token is stored.
- 3 Enter the current 6-digit code (or a recovery code) -> you're signed in (lands on /).
- 4 **Wrong/expired code:** inline error; you remain on the prompt (no session). Tokens arrive in the response body (native transport), same as a normal native login.

### QA-NOTIF-01 — Notification bell + list • Core (Web) Automated in CI

**Note:** the platform has no built-in producer; to see items, a feature must call `INotificationService.NotifyAsync` (seed one in dev, or exercise a downstream feature that notifies). **Gherkin**

```
Given I am signed in
When I open the notification bell in the header
Then I see my notifications newest-first, with unread ones marked
And the bell shows an unread count when I have unread notifications
```

### Walkthrough

- 1 In the header, click the **bell**. **Expected:** a dropdown opens; with none, it reads "You're all caught up."
- 2 With unread notifications present: a red **count badge** shows on the bell; unread rows carry a dot + bold title; each shows a relative time ("just now", "5m", "3h", "2d").
- 3 Click the backdrop (outside the panel) -> it closes.

### QA-NOTIF-02 — Mark read / mark all read • Core (Web) Automated in CI

**Precondition:** at least one unread notification (see QA-NOTIF-01 note). **Gherkin**

```
Given I have unread notifications
When I click one (and, separately, "Mark all read")
Then that one clears its unread mark and the count drops
And "Mark all read" zeroes the count
```

### Walkthrough

- 1 Open the bell -> click an **unread** row. **Expected:** its dot/bold clears; the count decrements.
- 2 Click **Mark all read**. **Expected:** the count badge disappears; all rows show as read.
- 3 Reload the page -> the counts/read state persist (server-side).

### QA-NOTIF-04 — Delete a notification / clear read / clear all • Edge (Web)

**Precondition:** a mix of read and unread notifications (see QA-NOTIF-01 note). **Gherkin**

```
Given I have read and unread notifications
When I click a row's trash icon (and, separately, "Clear read" / "Clear all")
Then that row is removed (unread ones also drop the count)
And "Clear read" removes only the read rows; "Clear all" empties the list
```

### Walkthrough

- 1 Open the bell -> click the **trash icon** on the left of a row. **Expected:** the row disappears (without marking anything read — the trash doesn't trigger the row click); if it was unread the count decrements.
- 2 Footer -> **Clear read**. **Expected:** only the already-read rows vanish; unread ones (and the badge) survive. The button is disabled when nothing is read.
- 3 Footer -> **Clear all**. **Expected:** the list empties ("You're all caught up."), badge gone.
- 4 Reload -> deletions persist (server-side; `DELETE /api/notifications/{id}`; bulk requires an explicit scope — `?read=true` clears read, `?read=false` clears all, omitted -> 400 scope\_required).

### QA-NOTIF-03 — Delivery preferences • Core (Web) Automated in CI

**Gherkin**

```
Given I am signed in on /settings
When I toggle the In-app or Email notification switches
Then the choice is saved and survives a reload
```

#### Walkthrough

- 1 **Settings** -> **Notifications** card shows two switches (**In-app**, **Email**), both on by default.
- 2 Toggle one off. **Expected:** it saves immediately (optimistic; reverts with an error if it fails).
- 3 Reload -> the switch keeps its new state. (Email-off suppresses the email channel on future notifies; in-app-off suppresses the in-app row.)

## 10. Web — Localization (i18n) • Core

### QA-I18N-01 — Switch language on the login page • Core (Web) Automated in CI

#### Gherkin

```
Given I am on /login in English
When I choose Español in the language switcher
Then the page text renders in Spanish
```

**Walkthrough:** on /login, use the language switcher (bottom of the card) -> **Español**. **Expected:** titles, button labels, and prompts switch to Spanish; the choice persists on reload.

### QA-I18N-02 — Language persists per user across sessions • Core (Web) Automated in CI

#### Gherkin

```
Given I am signed in and set my language to Spanish
When I sign out and sign back in (even in a fresh browser)
Then the app loads in Spanish
```

#### Walkthrough

- 1 Signed in, switch to **Español** in **Settings** -> **Preferences**. (This saves the locale to your user record via PUT /api/auth/locale and into the JWT. A pre-auth pick on the login page also works: it's adopted into your user record when you sign in — PREFS-1, ADR-022.)
- 2 Sign out; sign back in (a fresh browser/private window is the stronger check).
- 3 **Expected:** app comes up in Spanish — the preference followed the \*user\*, not just the browser. On a mismatch the app persists the saved locale and reloads once.

### QA-I18N-03 — In-app UI is fully translated (no English leaks) • Edge (Web)

**Walkthrough:** in Spanish, walk Home -> Household -> Settings -> invite flow. **Expected:** all visible labels/buttons/validation/status messages are Spanish; flag any English string that leaks.

### QA-I18N-04 — Email language matches the requester's UI language • Core (Web)

#### Gherkin

```
Given my UI language is Spanish
When I trigger an OTP / magic link / invitation email
Then the email arrives in Spanish
```

#### Walkthrough

- 1 Set UI to **Español**. Trigger an OTP (and a magic link, and send an invite).
- 2 In Mailpit, open each. **Expected:** subject + body in Spanish. Repeat in English to confirm both.

## 10b. Web — Admin console (platform staff) • Core

**Precondition:** your account's email must be in the staff allowlist — set Admin\_\_StaffEmails\_\_0 in the repo-root .env (see .env.example) and restart the API. Non-staff accounts must **not** see any of this.

## QA-ADMIN-01 — Staff sees the console; non-staff don't • Core (Web) Automated in CI

### Gherkin

```
Given I am signed in as a platform-staff user
When I look at the header
Then I see an "Admin" link, and /admin lists every tenant with member counts
And a non-staff user sees no Admin link and is refused at /admin
```

### Walkthrough

- 1 Signed in as **staff**: an **Admin** button shows in the header -> open it (or go to /admin).
- 2 **Expected**: the **Tenants** list shows every tenant (name + member count). Click one -> detail panel shows members (name/email + role), subscription status, created date, audit-event count.
- 3 Sign in as a **non-staff** user: **no Admin link**; navigating directly to /admin shows "You don't have access to the admin console."

Automated: staff console + tenant list (announcement journey) and the non-staff /admin refusal.  
The header **Admin-link visibility** checks (steps 1 and 3's "no Admin link") remain manual.

## QA-ADMIN-02 — View a tenant is audited in that tenant • Core (Web)

### Gherkin

```
Given I am staff viewing a tenant's detail in /admin
When the detail loads
Then an audit event (admin.tenant.viewed) is recorded in that tenant
```

### Walkthrough

- 1 As staff, open a tenant's detail in /admin.
- 2 **Expected**: an `admin.tenant.viewed` event is written **in that tenant** (visible to that tenant's own audit trail) — the global tenant filter is never loosened; the read enters the target tenant.

## QA-ADMIN-03 — Impersonate a user, then stop • Core (Web)

### Gherkin

```
Given I am staff on a tenant's detail
When I "Sign in as" a member and confirm
Then I browse the app as that user with a persistent impersonation banner
And "Stop impersonating" returns me to my own staff identity
```

### Walkthrough

- 1 In a tenant detail, click **Sign in as** on a member -> confirm the dialog.
- 2 **Expected**: you land on / **as that user** (their name/household in the header); a yellow **impersonation banner** is pinned at the top; the **Admin** link is hidden while impersonating.
- 3 Click **Stop impersonating**. **Expected**: you're back as yourself (staff); the banner is gone.
- 4 The impersonation token is **short-lived (15 min) and non-refreshable** — a full page reload also returns you to your own identity. Impersonation is **audited** in the target's tenant.

## QA-ADMIN-04 — Staff announcement reaches a tenant's members • Edge (Web) Automated in CI

### Gherkin

```
Given I am staff on a tenant's detail in /admin
When I send an announcement (title + body) and confirm
Then every member of that tenant is notified through their preferred channels
And each member's bell shows the announcement; reading it clears the badge
And an admin.announcement.sent audit event is recorded in that tenant
```

### Walkthrough

- 1 As staff, open a tenant's detail in /admin -> fill **Send announcement** (title + message) -> **Send to all members** -> confirm. **Expected**: "Announcement sent to N member(s)."

- 2 Sign in as a member of that tenant. **Expected:** the bell badge shows the unread announcement; opening it shows title + message; clicking it marks it read and the badge clears. Members with email delivery on also get the email (Mailpit).
- 3 The send is audited **in that tenant** (`admin.announcement.sent`, with the member count).
- 4 **Targeted variant:** check one or more member rows (new checkbox column) — the button becomes **"Send to N selected"** and only those members are notified (the count in the confirmation and the "sent to N" ack match the selection). Unchecking all reverts to all-members. The selection clears after a send and when switching tenants.

## QA-ADMIN-05 — Platform-wide broadcast reaches every user • Edge (Web)

### Gherkin

```
Given I am staff on /admin
When I send an "Announce to everyone" broadcast and confirm
Then the request is acknowledged as queued
And every user of every tenant receives it once the outbox delivers
```

### Walkthrough

- 1 As staff on `/admin`, the **Announce to everyone** card sits above the tenant grid (it is not tenant-scoped). Fill title + message -> **Send to everyone** -> the confirm spells out the blast radius (EVERY user of EVERY tenant).
- 2 **Expected:** "Broadcast queued for delivery." — the fan-out is **asynchronous** (outbox): give the dispatcher a few seconds; delivery is not instant by design.
- 3 Sign in as users of **two different tenants**. **Expected:** both bells show the announcement.
- 4 There is **no in-tenant audit row** for a broadcast (the audit trail is per-tenant and this spans all tenants); the durable outbox message is the record.

## QA-ADMIN-06 — Comp a tenant to Pro and revert • Edge (Web)

### Gherkin

```
Given I am staff on a tenant's detail in /admin
When I use "Upgrade to Pro (comp)" (and later "Revert to Free")
Then the tenant's entitlements match the plan immediately, with no payment involved
And a provider-managed (Stripe-backed) subscription refuses the override
```

### Walkthrough

- 1 As staff, open a **Free** tenant's detail. The header shows a **plan badge** (free) next to the status badge; the **Subscription** section shows **Upgrade to Pro (comp)**.
- 2 Comp it -> confirm. **Expected:** "Subscription updated."; badge flips to `pro / active`; the button is replaced by **Revert to Free**. The comp **never lapses** (no period end) and is audited in-tenant (`admin.subscription.comp`ed).
- 3 As that tenant's owner, check `/billing`. **Expected:** plan **Pro**, seat limit 10 — same plan + entitlements as a completed checkout, but **no Manage subscription button** (a comp has no provider customer, so the portal is absent). This simulates payment completion for entitlement purposes; QA-BILL/QA-HH-14 behaviors follow the plan.
- 4 **Revert to Free** -> confirm. **Expected:** badge back to `free`; entitlements fall back (absence => Free, fail-closed); audited (`admin.subscription.reverted`). Reverting again is a no-op.
- 5 **Provider-managed guard:** for a tenant with a **real Stripe subscription** (QA-BILL-02), the section shows "Managed by the billing provider — change the plan there." and **no comp/revert buttons**; the API refuses with 409 (Stripe stays the source of truth — ADR-006).

## QA-ADMIN-07 — Reset a locked-out user's MFA • Edge (Web)

### Gherkin

```
Given a user has MFA enabled but lost both their authenticator and recovery codes
When staff clicks "Reset MFA" on that user's row in the tenant detail and confirms
Then the user's MFA secret and recovery codes are wiped and they can sign in with primary auth alone
And the reset is audited in the user's tenant and the user is notified in-app and by email
```

### Walkthrough

- 1 As a member user, enable MFA in Settings (QA-MFA-01), then pretend the authenticator and codes are lost — **not** disable it. Sign out. Confirm sign-in now demands the code you "lost" (QA-MFA-02).

- 2 As staff on `/admin`, open the tenant's detail. Each member row now shows a red **Reset MFA** button next to **Sign in as**. Click it for the locked-out user. **Expected:** the confirm spells out the blast radius (authenticator + recovery codes stop working immediately, the user is notified) and reminds you to verify identity **out-of-band** first. Confirm.
- 3 **Expected:** "Two-factor authentication was reset for ..." above the member table.
- 4 As the affected user, sign in again. **Expected:** primary auth alone signs you in — **no MFA step-up** (the second factor is gone; primary credentials are untouched). Settings shows MFA off; re-enrolling from scratch works (fresh QR + fresh recovery codes).
- 5 **Visibility:** the user's bell shows "Two-factor authentication was reset" and the email copy arrives in Mailpit; the tenant's audit trail (owner data export, QA-HH-13) contains an `admin.mfa.reset` event naming the staff actor.
- 6 **No silent no-op noise:** clicking **Reset MFA** for a member who never enrolled still reports success (idempotent) but writes **no** audit event and sends **no** notification.

## 10c. Web — Billing page • Core

With no Stripe keys configured (dev default) the **FakeBillingProvider** is active: checkout/portal return `https://billing.test/...` URLs (a dead domain — expected), and the webhook accepts the signature `valid`. With real Stripe test keys, use Stripe's hosted test checkout instead.

### QA-BILL-01 — Billing page shows plan + seats; owner-only • Edge (Web) Automated in CI Gherkin

```
Given I am the household owner on /billing
Then I see my current plan, its status, and seat usage vs the plan limit
And a member opening /billing sees only the "ask your owner" notice
```

#### Walkthrough

- 1 As **owner**, open **Billing** in the header. **Expected:** current plan shown as its localized label (e.g. **Free** — the raw free token stays wire-only), status badge, and seats (e.g. 1 of 3 used); an **Upgrade to Pro** button on the free plan; **Manage subscription** only when a provider customer exists (a comped tenant has a subscription row but no portal button).
- 2 As a **member**, open `/billing`. **Expected:** no plan/usage — just the owner-only notice.

### QA-BILL-02 — Upgrade via checkout + provider webhook lands on Pro • Core (Web) Automated in CI

#### Gherkin

```
Given the owner on the free plan clicks Upgrade to Pro
When the checkout redirect fires and the provider webhook lands (subscription active)
Then /billing shows plan pro, status active, the pro seat limit, and the portal button
```

#### Walkthrough

- 1 Click **Upgrade to Pro**. **Expected:** redirect to the provider checkout (fake: `billing.test/checkout/{tenantId}/pro` — the page won't load, which is fine).
- 2 Simulate payment completion by POSTing the webhook (fake provider): `POST {api}/api/billing/webhook` with header `Stripe-Signature: valid` and a PascalCase JSON body (`EventId`, `TenantId`, `PlanKey: "pro"`, `Status: "active"`, `StripeCustomerId`, `OccurredAt`). **Expected:** 200.
- 3 Reload `/billing`. **Expected:** plan **Pro** / status **Active** (localized labels; raw tokens on the wire), seats `x of 10`, **Manage subscription** now visible.

## 10d. Web — Budget settings (app slice BUDGET-1) • Core

The first **app** section (ADR-V001 port slice P1). Household-wide settings: any member may edit; changes apply to months created afterwards (ADR-V005).

## QA-BUD-01 — A new household sees the budget defaults • Core (Web)

### Gherkin

```
Given I am signed in to a household that has never saved budget settings
When I open /settings
Then the Budget card shows Thursday, "Last Thursday of the previous month", and 0 USD for both incomes
```

**Walkthrough:** sign in with a fresh account (QA-ONB-01), open **Settings**. **Expected:** a **Budget** card between Preferences and Notifications: \*Week starts on\* = Thursday, \*Month begins\* = "Last Thursday of the previous month", both income rows 0 / 0 / USD. Nothing has been saved (GET /api/budget-settings returns is\_default: true).

## QA-BUD-02 — Save the household's budget structure and see it persist • Core (Web)

### Gherkin

```
Given I am on /settings
When I set Monday, "1st of the month", primary 1500 / 1800 USD, secondary 400000 / 500000 CRC and click Save
Then the card confirms, and a reload (or another member's browser) shows the same values
```

### Walkthrough

- 1 Change \*Week starts on\* to **Monday** — **Expected:** the anchor options re-label to "...Monday...".
- 2 Pick **1st of the month**; enter the amounts; secondary currency **CRC**; **Save budget settings**.
- 3 **Expected:** "Budget settings saved." Reload the page: the values persist. Sign in as another member of the same household (QA-INV-02): they see the same values (household-wide, not per user).
- 4 Save again with a different weekday. **Expected:** still one row for the household (GET shows the new weekday; is\_default: false).

## QA-BUD-03 — Invalid values are refused and nothing changes • Core (Web / API)

### Gherkin

```
Given I am on /settings
When I try to save a negative amount, or PUT weekday 9 / anchor "x" / currency "EUR" via the API
Then the UI shows the "check the values" message and the API answers 400 invalid_request
And a GET still returns the previously saved values
```

**Walkthrough:** in the card, type **-5** in an amount and Save -> **Expected:** the red "Check the values..." message, no success banner. Via Postman (**11 • Budget settings -> Update — invalid (400)**) -> **Expected:** 400 { "error": "invalid\_request", "message": "week\_start\_weekday ..." }; a following **Get budget settings** is unchanged. Without a token -> 401.

## 10e. Web — Catalog: categories & banks (app slice CATALOG-1/2) • Core

Two soft-delete name catalogs (ADR-V008): unique per household case-insensitively, deactivate instead of delete, the inactive-clash **Reactivate** offer. Seeded once per household in the first reader's language (ADR-V009).

## QA-CAT-01 — A new household's first visit seeds the defaults in its language • Core (Web)

### Gherkin

```
Given a fresh household whose member's language is Spanish
When I open Settings -> Catalog -> Manage categories
Then I see the 7 example categories in Spanish (Alimentación ... Otro), all Active
And Manage banks shows 9 banks with "Efectivo" first
```

**Walkthrough:** sign up fresh (QA-ONB-01), switch the language to **Español** on the login page or Settings, then open **Settings -> Catálogo -> Administrar categorías**. **Expected:** 7 rows, Spanish names, Activo badges. Switch the language back to English and reload. **Expected:** the names **stay Spanish** — seeds are localized once (no retranslation). **Administrar bancos:** 9 rows, "Efectivo" present, the bank proper nouns unchanged.

## QA-CAT-02 — Create a category; a duplicate name is refused case-insensitively • Core (Web)

### Gherkin

```
Given I am on /categories
When I click New category, type "Viajes" and Create
Then "Viajes" appears Active
When I try to create "VIAJES"
Then I see "A category named 'Viajes' already exists" and nothing is created
```

**Walkthrough:** New category -> Viajes -> Create. **Expected:** "Created." and the row appears. Repeat with VIAJES. **Expected:** the red message in the form; no new row; no **Reactivate** button (the clash is with an *\*active\** entry).

## QA-CAT-03 — Deactivate, then the inactive clash offers Reactivate • Core (Web)

### Gherkin

```
Given "Viajes" exists and is active
When I Edit it, switch Active off and Save
Then it shows Inactive (still listed, greyed)
When I try to create "viajes"
Then I see the warning with a Reactivate button, and clicking it makes "Viajes" Active again
```

**Walkthrough:** Edit on Viajes -> toggle **Active** off -> **Save** -> **Expected:** Inactive badge. **New category** -> viajes -> **Create** -> **Expected:** yellow warning "...already exists but is inactive — reactivate it?" with **Reactivate**. Click it. **Expected:** "Updated.", Viajes is Active and still spelled "**Viajes**" (the stored name is restored, not the typed "viajes"). Via Postman (**12 · Catalog -> Create category — duplicate (409)**): error is category\_exists\_inactive with existing\_id and existing\_name.

## QA-CAT-04 — Banks behave the same and are household-wide • Core (Web / API)

### Gherkin

```
Given I am on /banks
When I rename "Lafise" to "Lafise CR" and create "Coopenae"
Then another member of the household sees both changes
And a PUT to a bank id from a different household returns 404
```

**Walkthrough:** on /banks, **Edit** Lafise -> Lafise CR -> **Save**; **New bank** -> Coopenae -> **Create**. Sign in as another member (QA-INV-02) -> /banks -> **Expected:** both changes visible (catalogs are household data). Via Postman, PUT /api/banks/{id} with an id copied from a *\*different\** household's list -> **Expected:** 404 (never 403 — no existence oracle).

## 10f. Web — Exchange rate (app slice FX-1) • Core

The live USD->CRC rate and its honest fallback chain (ADR-V006): live -> stale "as of ..." -> the household's last transaction -> unavailable. The app never invents a rate. Provider key: ExchangeRate\_\_ApiKey in .env (unset in a fresh checkout).

## QA-FX-01 — Home shows today's live rate • Core (Web / API)

### Gherkin

```
Given ExchangeRate__ApiKey is set in .env and the API was restarted
When I open Home
Then I see "Today's rate ■<rate> per $1" with a green "live" badge
And GET /api/exchange-rate returns 200 { rate, source: "live", as_of }
When I reload within the hour
Then the same as_of comes back (cached — no second provider call)
```

**Walkthrough:** set ExchangeRate\_\_ApiKey=<your free-tier key> in .env, restart the API, open **Home** -> **Expected:** the rate line under the welcome text with the green **live** badge; a plausible value (≈ 500–560 colones per dollar in 2026). Via Postman (**13 · Exchange rate -> Get exchange rate**) -> **Expected:** 200 with rate > 0, source =

live, as\_of ≈ now. Send it again -> **Expected:** identical as\_of (served from the one-hour cache). Without a token -> 401.

## QA-FX-02 — No provider -> the honest "unavailable" state, never a fabricated rate • Core (Web / API)

### Gherkin

```
Given ExchangeRate__ApiKey is unset (fresh checkout) and the household has no transactions
When I open Home
Then I see the red "Exchange rate unavailable – try again later" badge and no number
And GET /api/exchange-rate returns 503 { error: "exchange_rate_unavailable", message: "..." }
```

**Walkthrough:** comment out ExchangeRate\_\_ApiKey in .env, restart the API, open **Home** -> **Expected:** the red badge, no rate figure. Via Postman (**13 · Exchange rate -> Get exchange rate**) -> **Expected:** 503 with the shared error shape and error = exchange\_rate\_unavailable. Restore the key and restart -> QA-FX-01 passes again. (The stale-cache and last-transaction tiers are covered by Api. Tests; the last-transaction tier becomes manually testable once P5 ships.)

## 10g. Web — Envelopes (app slice ENV-1) • Core

Savings buckets with an annual target (■ and/or \$) and a reminder cadence (ADR-V007), managed like the other catalogs (ADR-V008): unique per household, deactivate instead of delete, the inactive-clash **Reactivate** offer. Never seeded — a fresh household starts empty.

## QA-ENV-01 — Create an envelope with targets and a reminder; duplicates are refused • Core (Web / API)

### Gherkin

```
Given I am on /envelopes (Settings -> Catalog -> Manage envelopes) in a fresh household
Then I see the empty-state message
When I click New envelope, type "Marchamo", ■718000, "Only on 5-week months" and Create
Then "Marchamo" appears with ■718,000.00, $0.00, "Only on 5-week months" and an Active badge
When I try to create "MARCHAMO"
Then I see "An envelope named 'Marchamo' already exists" and nothing is created
When I type a negative target
Then the form refuses it before calling the API
```

**Walkthrough:** **Settings -> Catalog -> Manage envelopes -> Expected:** "No envelopes yet...". **New envelope -> name Marchamo, Annual target (■) 718000, Reminder "Only on 5-week months" -> Create -> Expected:** "Created." and the row with both targets and the reminder. Repeat with MARCHAMO -> **Expected:** the red message in the form, no new row, no **Reactivate**. Type -5 in a target -> **Create -> Expected:** "Targets cannot be negative." and no request. Via Postman (**14 · Envelopes -> Create envelope**) -> 201; re-send -> 409 envelope\_exists; **Create envelope — invalid (400) -> invalid\_request** naming reminder\_cadence.

## QA-ENV-02 — Edit, deactivate, then the inactive clash restores it • Core (Web / API)

### Gherkin

```
Given "Marchamo" exists and is active
When I Edit it, change the target to ■750000, switch Active off and Save
Then it shows Inactive with the new target
When I try to create "marchamo" with ■800000
Then I see the warning with a Reactivate button, and clicking it makes "Marchamo" Active with ■800,000.00
And a PUT to an envelope id from another household returns 404
```

**Walkthrough:** **Edit** on Marchamo -> target 750000 -> **Active** off -> **Save -> Expected:** "Updated.", Inactive badge, ■750,000.00. **New envelope -> marchamo, 800000 -> Create -> Expected:** yellow "...already exists but is inactive — reactivate it?" with **Reactivate**. Click it -> **Expected:** "Updated.", **Marchamo** (stored spelling) Active with ■800,000.00. Via Postman (**14 · Envelopes -> Update envelope**) with an id copied from a \*different\* household's list -> **Expected:** 404 (never 403 — no existence oracle).

## 10h. Web — Months & transactions (app slice LEDGER-1/2) • Core

The core loop (ADR-V005/V006/V007): a transaction's date decides its pay-cycle month; months appear with their first transaction (weeks materialized, income snapshot) and leave with their last; the exchange rate is frozen at creation. Fixture with the default settings (Thursday / last Thursday of the previous month): **June 2026** = 4 weeks (28 May – 24 Jun), **July 2026** = 5 weeks (25 Jun – 29 Jul).

### QA-LED-01 — The first transaction creates its month with weeks and an income snapshot • Core (Web / API)

#### Gherkin

```
Given a fresh household with no months, Budget settings saved with 5-week incomes 3750 USD / 312500 CRC
When I open New transaction, type "AutoMercado", 50000 CRC, date 2026-07-10, bank Cash, class Budgeted
And I click "+ New" beside Category, type "Viajes" and Create
Then "Viajes" is selected without leaving the form (it also appears under Settings -> Categories);
typing "viajes" again just selects it
Then the date says "Goes to July 2026 — a new month will be created" and the rate is pre-filled
When I Save
Then I land on July 2026: 5 weeks (25 Jun – 29 Jul), income 3750 USD / 312500 CRC, one row ■50,000.00
/ $<50000 ÷ rate>
```

**Walkthrough:** Settings -> Budget -> save 5-week incomes 3750 USD and 312500 CRC. Home -> New transaction (or nav Months -> New transaction): fill the fields; beside **Category** click + New, type Viajes, **Create** -> **Expected:** the inline form closes and **Viajes** is selected (Enter also creates, Esc cancels; a blank name -> "A name is required."; a name matching an inactive category offers **Reactivate** "..."). Pick the date 2026-07-10 -> **Expected:** the "Goes to July 2026 — a new month will be created" hint under the date; the **Exchange rate** field pre-filled (or, without a key, the red hint asking for one — type 500). **Save** -> **Expected:** the **July 2026** page with 5 week badges, the income card showing 3750 USD / 312500 CRC, and the row. Via Postman (**15** • Months -> List months) -> 1 month with week\_count 5; **Resolve a date** with 2026-05-30 -> is\_new: true, month\_number 6 (June's window starts 28 May).

### QA-LED-02 — Edit keeps the frozen rate; a date fix moves the transaction • Core (Web / API)

#### Gherkin

```
Given the July 2026 transaction above (rate frozen at creation)
When I Edit it, change the amount to 100000 and Save
Then the $ amount doubles and the rate field was disabled (frozen) throughout
When I Edit again and change the date to 2026-06-05
Then I land on June 2026 (new, 4 weeks) and July 2026 no longer appears in Months
```

**Walkthrough:** on the month page -> **Edit** -> **Expected:** the rate input disabled with the "Frozen when the transaction was created" hint. Amount 100000 -> **Save** -> **Expected:** the row's \$ column doubles (same rate). **Edit** -> date 2026-06-05 -> **Expected:** "Goes to June 2026 — a new month will be created" -> **Save** -> **Expected:** the **June 2026** page (4 weeks); nav Months -> **Expected:** only June — July left with its last transaction. Via Postman (**16** • Transactions -> Update transaction) -> exchange\_rate\_used unchanged in the response.

### QA-LED-03 — Deleting the last transaction removes the month • Core (Web / API)

#### Gherkin

```
Given June 2026 holds exactly one transaction
When I click Delete, then Confirm delete
Then I am taken back to Months and June 2026 is gone
And GET /api/months/{id} returns 404
```

**Walkthrough:** on the month page -> **Delete** -> **Expected:** the button turns into **Confirm delete** (nothing is sent yet) -> click it -> **Expected:** "Transaction deleted." then the **Months** list without June and the empty-state text. Via Postman (**15** • Months -> Get month) with the old id -> **Expected:** 404 not\_found.

## QA-LED-04 — Month income is editable; invalid input and foreign ids are refused • Core (Web / API)

### Gherkin

```
Given a month exists
When I change its primary income to 1600000 CRC and Save
Then "Income updated." and the values persist on reload
When I PUT a negative amount or EUR via Postman
Then 400 invalid_request
When I PUT /api/months/{id}/income with an id from another household
Then 404
```

**Walkthrough:** on the month page's **Income this month** card -> primary 1600000, currency **CRC** -> **Save** -> **Expected:** "Income updated."; reload -> values kept. Via Postman (**15 · Months -> Update month income — invalid (400)**) -> **invalid\_request**. With an id copied from a *\*different\** household's list -> **Expected:** 404 (never 403 — no existence oracle). Also (**16 · Transactions -> Create transaction — invalid (400)**) -> **invalid\_request** naming the field.

## QA-LED-05 — An unplanned essential can expect a refund; the refund follows the transaction • Core (Web / API)

### Gherkin

```
Given I am on New transaction
When I pick class Unplanned
Then a "Refund expected" switch appears; switching it on shows a percentage field
When I enter "Hospital", 50000 CRC, 30 %, and Save
Then the month page lists an expected refund: Hospital · 30% · ■15,000.00 · $<30> · Pending
When I Edit the transaction to 80000 and Save
Then the refund reads ■24,000.00 (30 % of 80,000)
When I Edit it again, switch Refund expected off and Save
Then the refund is gone
```

**Walkthrough:** **New transaction** -> **Class** "Unplanned" -> **Expected:** the **Refund expected** switch appears (it is absent for every other class). Switch it on -> **Expected:** the percentage field; with 50000 and 30 the hint reads "Expected back: 15,000.00 CRC". Fill the rest and **Save** -> **Expected:** the month page's **Expected refunds** table shows Hospital · 30% · ■15,000.00 · Pending with a **Mark received** button. **Edit** -> amount 80000 -> **Save** -> **Expected:** the refund row reads ■24,000.00. **Edit** -> switch off -> **Save** -> **Expected:** "No refunds expected this month." Via Postman (**16 · Transactions -> Create transaction**) with **refund\_expected: true, refund\_percentage: 150** -> **Expected:** 400 **invalid\_request** naming **refund\_percentage**.

## QA-LED-06 — Marking a refund received books an inflow; reverting removes it • Core (Web / API)

### Gherkin

```
Given an expected refund of ■15,000.00 (Pending) on a purchase in this month
And the Received on date next to Mark received defaults to today and refuses a date before the purchase
When I keep a date inside this month and click Mark received
Then the badge reads "Received <date>" and the transactions table gains an Income (inflow) row of ■15,000.00 on that date, marked "Derived from a refund — read-only"
And that row has no Edit/Delete buttons
When I click Back to pending
Then the inflow row disappears and the badge is Pending again
When I pick a date in the NEXT month and click Mark received
Then the badge reads "Received <date>" with a "booked in another month — view" link, this month's table has NO inflow row, and the linked month (created if needed) holds it
When I click Back to pending -> the inflow is gone, and that month with it if it was otherwise empty
```

**Walkthrough:** on the month page, the pending row shows **Received on** (today) next to **Mark received**; the date input's minimum is the purchase date. **Mark received** -> **Expected:** "Refund updated.", the badge **Received <today>**, the button now **Back to pending**, and a new **Income (inflow)** row dated today with the refund's amounts whose actions column says "Derived from a refund — read-only". Via Postman (**16 · Transactions -> Delete transaction**) with that inflow's id -> **Expected:** 400 **derived\_transaction**. **Back to pending** -> **Expected:** the inflow row is gone, the

badge **Pending**. Via Postman (**17 · Refunds -> Update refund status**) send received twice -> **Expected**: 200 both times, one inflow in **List month transactions**. With an id copied from a *\*different\** household -> **Expected**: 404. (The concurrent-flip 409 is proven by `Api.Tests`.) **Cross-month (ADR-V017): Back to pending**, pick a **Received on** date in the *\*next\** month -> **Mark received** -> **Expected**: the badge "Received <date>" plus **booked in another month — view**; this month's transactions table has no inflow; the link opens the next month (auto-created if it did not exist) with the inflow row dated as picked. Postman **Update refund status** with `received_date` before the purchase -> **Expected**: 400 `invalid_request`. **Back to pending** -> **Expected**: the inflow is gone and the next month too if it held nothing else.

## 10i. Web — Budget lines: fixed & variable (app slice EXPENSES-1) • Core

The budget baseline (ADR-V007/V008): two ordered lists of single-currency lines, each tied to a category that backs at most one active line across both lists; optional bank; reorder with ▲▼. Never seeded — a fresh household starts empty.

### QA-EXP-01 — Create fixed and variable lines; the single-currency and category rules hold • Core (Web / API)

#### Gherkin

```
Given I am on Budget (nav) in a fresh household
Then both sections show "No lines yet"
When I add fixed "Mortgage", 300000 CRC, category Housing, bank BAC, Bank account, and Create
Then it appears with ■300,000.00 · Housing · BAC · Bank account · Active
When I add variable "Netflix", 13 USD, category Entertainment, no bank, Credit card
Then it appears with $13.00 · Entertainment · Unassigned
When I add fixed "Rent" with category Housing
Then the form shows "that category already backs another budget line" and nothing is created
```

**Walkthrough**: nav **Budget** -> **Expected**: "No lines yet — add the first one." under both headings. **New fixed line** -> name **Mortgage**, **Monthly budget** 300000 **CRC**, **Category** **Housing**, **Bank** **BAC**, **Payment method** **Bank account** -> **Create** -> **Expected**: "Created." and the row. **New variable line** -> **Netflix**, 13 **USD**, **Entertainment**, bank left **Unassigned**, **Credit card** -> **Create** -> **Expected**: the row shows \$13.00 and "Unassigned". **New fixed line** -> **Rent**, 50000 **CRC**, category **Housing** -> **Create** -> **Expected**: the red message about the category already backing another line. Via Postman (**18 · Expenses -> Create fixed expense — invalid (400)**) -> `invalid_request` ("exactly one of `budget_crc` or `budget_usd`...").

### QA-EXP-02 — Reorder with ▲▼; inactive lines stay out of the order • Core (Web / API)

#### Gherkin

```
Given fixed lines Mortgage (1st) and Water (2nd)
When I click ▼ on Mortgage
Then Water is first and Mortgage second, and a reload keeps that order
When I Edit Water, switch Active off, Save
Then Water shows Inactive without ▲▼, and Mortgage's ▲▼ are both disabled (only active line)
```

**Walkthrough**: add **Water** (15000 **CRC**, another category). ▼ on **Mortgage** -> **Expected**: the rows swap; **F5** -> order kept. **Edit Water** -> **Active** off -> **Save** -> **Expected**: Inactive badge, no arrows on that row, **Mortgage**'s arrows disabled. Via Postman (**18 · Expenses -> Reorder fixed expenses**) with only one of two active ids -> **Expected**: 400 `invalid_request` ("must exactly match the active fixed expense lines").

### QA-EXP-03 — Duplicate names per list; the inactive clash restores the line; foreign ids are 404 • Core (Web / API)

#### Gherkin

Given fixed "Mortgage" is active and fixed "Water" is inactive  
When I add fixed "MORTGAGE" -> "A fixed expense named 'Mortgage' already exists", nothing created  
When I add variable "Mortgage" -> created (names are unique per list)  
When I add fixed "water" with 20000 CRC -> the yellow warning with Reactivate; clicking it makes "Water" Active at ■20,000.00  
And a PUT to a line id from another household returns 404

**Walkthrough:** New fixed line MORTGAGE -> **Expected:** the red message, no row. **New variable line** Mortgage (any free category) -> **Expected:** created. **New fixed line** water, 20000 -> **Create** -> **Expected:** "...already exists but is inactive — reactivate it?" with **Reactivate** -> click -> **Expected:** "Updated.", **Water** (stored spelling) Active with ■20,000.00. Via Postman (**18 · Expenses** -> **Update fixed expense**) with an id copied from a \*different\* household -> **Expected:** 404 (never 403 — no existence oracle).

## 10j. Web — Dashboard (app slice DASH-1) • Core

The month at a glance (ADR-V004/V006/V007): every figure a ■/\$ pair. Actuals sum each transaction's frozen amounts; projections (income conversion, budget display, pending budgeted, remainder for debts) use the rate resolved through the chain. No rate -> projections are blocked, never guessed.

### QA-DASH-01 — The dashboard reflects income, lines vs actuals, other spending and the balance • Core (Web / API)

#### Gherkin

Given a household with fixed line Mortgage ■350,000 (Housing, BAC, Bank account) and no other lines  
And June transactions: Mortgage ■300,000 bank account on Jun 5, and a ■10,000 Unplanned lunch on Jun 12 in category Dining  
When I open Dashboard (nav)  
Then the newest month loads with "4 weeks · 28/5/2026 – 24/6/2026" and the rate line  
And Income shows the month's income converted at the rate; Expenses shows Bank account ■300,000.00, Credit card ■10,000.00, Total ■310,000.00  
And Fixed expenses shows Mortgage – Budgeted ■350,000.00 · \$700.00 – Actual ■300,000.00 in green  
And Other spending lists Dining ■10,000.00; Unplanned essentials shows ■10,000.00  
And Week by week shows the mortgage in week 2; By bank and payment method shows BAC / Bank account budget ■350,000 actual ■300,000  
When I Edit Mortgage's budget down to ■250,000 and reload the dashboard  
Then Mortgage's actual turns red (over budget) and Pending budgeted drops to ■0.00

**Walkthrough:** **Budget** -> add fixed Mortgage 350000 CRC, Housing, BAC, Bank account. **New transaction** -> Bank, 300000 CRC, Housing, BAC, Bank account, 2026-06-05, Budgeted -> **Save**. **New transaction** -> Soda, 10000 CRC, Dining, BAC, Credit card, 2026-06-12, Unplanned -> **Save**. Nav **Dashboard** -> **Expected:** June 2026 with the weeks line and "■... per \$1 ..."; the three cards; the Fixed table with Mortgage's actual in **green**; **Other spending** with Dining; **Unplanned essentials & refunds** ■10,000.00; **Week by week** 4 rows, week 2 = ■300,000.00 budgeted; **By bank and payment method** BAC · Bank account and Unassigned · Credit card (the lunch has no line). **Budget** -> **Edit Mortgage** -> 250000 -> **Save** -> **Dashboard** -> **Expected:** actual ■300,000.00 now **red**; **Pending budgeted** ■0.00. Via Postman (**19 · Dashboard** -> **Month summary**) -> 200 with exchange\_rate, rate\_source, summary.fixed\_expenses[0].actual.crc = 300000.

### QA-DASH-02 — Month selector, entry points, empty state, and the blocked projections when no rate resolves • Core (Web / API)

#### Gherkin

Given months June and July 2026 exist  
When I open /dashboard -> July (newest) loads; I pick June in the selector -> the URL becomes /dashboard/{june id} and June loads  
When I click Month details -> /months/{id}; on the month page, Dashboard -> back to /dashboard/{id}  
Given a brand-new household with no transactions  
When I open Dashboard -> "Nothing to show yet" with New transaction  
Given the provider key is unset and the household has no transaction yet (no rate resolves)  
When I GET /api/months/{id}/summary for a month created by another path -> rate\_unavailable true, summary null

**Walkthrough:** add a July transaction (2026-07-10). **Dashboard** -> **Expected:** July 2026 first; the selector lists both months; pick **June 2026** -> **Expected:** the URL ends in June's id and the June figures show. **Month details** -> **Expected:** /months/{id} (June). **Dashboard** button there -> **Expected:** back on June's dashboard. Sign in as a fresh household (or wipe) -> **Dashboard** -> **Expected:** "Nothing to show yet" + **New transaction**. Rate-unavailable: with ExchangeRate\_\_ApiKey empty, stop the API, restart it (empty cache), and in a household whose only transaction was just deleted there is nothing to resolve — via Postman (13 · **Exchange rate** -> **Current rate**) -> 503; the dashboard page for a remaining month shows the red "No exchange rate could be resolved..." block and no figures, while the month title and buttons stay. Postman (19 · **Dashboard** -> **Month summary**) with an unknown id -> 404.

## 10k. Web — Reports: category analysis & CSV export (app slice REPORTS-1/2) • Core

Read-only reporting over the frozen transaction amounts (ADR-V004/V006). One period rule for both: a month (its anchor window, ending on the last week's end date) or a from-to range. The CSV is delivered through the platform's signed-link download (ADR-010), so it works on web and native alike.

### QA-REP-01 — Category analysis by month shows budgets; a date range doesn't • Core (Web / API)

Gherkin

```
Given June 2026 has Groceries budgeted ■60,000 (a fixed line) and transactions: Groceries budgeted ■8,000 total, Dining Discretionary ■2,000, an Income (inflow) ■9,000
When I open Reports (nav)
Then the newest month loads with "one budget month – budgets shown next to actuals"
And Budgeted lists Groceries – Budgeted (month) ■60,000.00 – Actual ■8,000.00 in green, with a Total row
And Discretionary lists Dining ■2,000.00; Unplanned shows "Nothing in this class for the period."; the inflow appears nowhere
When I switch Period to "Date range", set 2026-01-01 – 2026-06-30 and Load
Then the note says "custom range – monthly budgets don't apply" and the Budgeted (month) column is gone
When I set From 2026-06-30 and To 2026-06-01 and Load
Then "From must not be after To" and nothing loads
```

**Walkthrough:** **Budget** -> fixed Supermarket 60000 CRC on Groceries. **New transaction** ×3 -> Groceries Budgeted 5000 (2026-06-05) and 3000 (2026-06-12), Dining Discretionary 2000 (2026-06-10), plus an **Income (inflow)** 9000. Nav **Reports** -> **Expected:** the month selector on the newest month; the Budgeted card with the budget column and the green actual; Dining under Discretionary; the inflow absent from every card. **Period** -> **Date range** -> From 2026-01-01, To 2026-06-30 -> **Load** -> **Expected:** the multi-month note, no budget column, same totals. Reverse the dates -> **Load** -> **Expected:** the red order message. Via Postman (20 · **Reports** -> **Category analysis (month)**) -> 200 with single\_month: true and budgeted[0].budgeted\_crc = 60000; (**Category analysis — no period (400)**) -> period\_required.

### QA-REP-02 — Export CSV downloads the shown period; the file has the fixed columns and 4-decimal rate • Core (Web / API)

Gherkin

```
Given Reports shows June 2026 (three spending rows + one inflow)
When I click Export CSV
Then "CSV ready – 4 rows. Your download has started." and transactions-<today>.csv lands in Downloads
And the file's first line is
date,payee,category,class,amount_crc,amount_usd,exchange_rate_used,payment_method,bank,source
And rows are newest first, amounts read like 5000.00 and 10.00, exchange_rate_used like 500.0000, no currency symbols
When I open a month page and click Export CSV
Then the same file downloads for that month
When I POST the export with month_id of another household
Then 404
```

**Walkthrough: Reports -> Export CSV -> Expected:** the green notice with the row count and the browser download (on Android/Windows: the OS share sheet). Open the file -> **Expected:** the header line exactly as above; one line per transaction incl. the inflow (the export is the whole period, not just spending); `exchange_rate_used` with four decimals; payees containing commas/quotes are quoted. **Months -> June -> Export CSV -> Expected:** the same download and the notice under the header. Via Postman (**20 · Reports -> Export transactions (CSV link)**) -> 200 with `download_url` (relative `/api/files/{token}` on local storage), `file_name`, `row_count`; open the URL **without** a token -> the CSV downloads (Content-Disposition: attachment); wait 15 minutes -> 404 (link expired). Postman with a foreign `month_id` -> 404.

## 10I. Web — Email inboxes: connect, filters & readers (app slice EMAIL-2/3) • Core

Your inbox, not the household's (ADR-V002): read-only consent on the account you're signed in with, tokens protected by the platform key ring (ADR-V016), one inbox per provider. Live consent needs the platform's Microsoft/Google OAuth apps configured (Authentication:\*) with the API callback `https://<api>/api/email/connections/callback` registered as a redirect URI.

### QA-EMAIL-01 — The Email settings page without credentials: honest errors, no dead ends • Core (Web / API)

#### Gherkin

```
Given Authentication:Google:ClientId is empty on the API
When I open Settings -> Manage inboxes
Then I see "No inbox connected yet." and the two Connect buttons
When I click Connect Gmail
Then "Gmail mail consent isn't configured on this server yet." and I stay on the page
When I POST /api/email/connections with tokens (Postman)
Then 400 use_consent_flow
```

**Walkthrough: Settings -> Manage inboxes (/email) -> Expected:** the empty message, **Connect Outlook / Connect Gmail**. Click **Connect Gmail** with no Google credentials -> **Expected:** the red "isn't configured" message. Via Postman (**21 · Email inboxes -> Create connection (refused, 400)**) -> `use_consent_flow`; (**Authorize (unknown provider, 400)**) -> `invalid_provider`; (**Suggested filters**) -> the BAC/BN senders and subjects with the two bank presets.

### QA-EMAIL-02 — Live consent round-trip (IdP boundary) and the pre-seeded connection • Core (Web)

#### Gherkin

```
Given the API has Authentication:Microsoft (or Google) credentials and the callback URL is a
registered redirect URI
When I click Connect Outlook and approve read-only access on my signed-in account
Then I land on /email?connected=microsoft with "Outlook connected..."
And the inbox shows Outlook - my address · Active · Last checked: <now> · every 15 min
And Edit shows sender notificacion@notificacionesbaccr.com, bncontacto@bncr.fi.cr and the three
subject prefixes pre-filled, Unread only on
And the Connect Outlook button is greyed out (one inbox per provider); re-running the consent URL by
hand -> /email?email_error=already_connected
```

**Walkthrough: Connect Outlook ->** the Microsoft consent page (scopes: read your mail, offline access, your email) -> **Accept -> Expected:** back on `/email` with the green notice and the row. **Edit -> Expected:** the pre-filled senders/subjects, **Unread only** on, interval 15, **Import mail from today**. **Expected:** the **Connect Outlook** button is now **disabled** (Connect Gmail stays live); the row's **Reconnect** is the only way back through consent. Paste the consent URL from before into the address bar and approve again -> **Expected:** "That provider is already connected." (the API guard behind the greyed button). Cancel the consent page instead -> **Expected:** `/email?email_error=consent_failed` and "Couldn't connect the inbox."

### QA-EMAIL-03 — Edit with real folders, backfill rule, disconnect, and nothing leaks across users • Core (Web / API)

## Gherkin

```
Given a connected Outlook inbox
And the row reads Folders: Inbox (default)
When I Edit -> Load folders
Then my real folders appear as checkboxes, subfolders as Inbox/Vouchers, and the Load folders link hides
When I tick Inbox/Vouchers and click Apply
Then the list closes and the chips read Inbox, Inbox/Vouchers (Cancel instead would drop the tick)
When I set interval 60, turn on "Fetch all unread (ignore date)", Save
Then "Saved.", the row reads every 60 min and Folders: Inbox, Inbox/Vouchers; a reload keeps both
When I set Import mail from to 7 days ago and Save -> GET the connection: last_polled_at moved back 7 days
When I set it to 3 days ago and Save -> last_polled_at is still 7 days ago
When I set interval 4 -> "Polling interval must be between 5 and 1440 minutes."; clear both filters -> "Provide at least one sender or subject filter."
When another user GETs/PUTs/DELETEs my connection id -> 404
When I Disconnect -> confirm -> the inbox is gone; the API list is empty
```

**Walkthrough:** the collapsed row reads **Folders: Inbox (default)**. **Edit -> Load folders -> Expected:** the checkbox list (Graph: nested names with /) with **Apply / Cancel** under it, the chips above it unchanged. Tick a subfolder -> **Cancel -> Expected:** list closed, chips unchanged. **Load folders -> tick it -> Apply -> Expected:** list closed, chips Inbox, Inbox/Vouchers. Interval 60, **Fetch all unread** on -> **Save -> Expected:** "Saved.", "every 60 min", the row's **Folders:** line names both; **F5** keeps them. Via Postman (**21 · Email inboxes -> Get connection**) after each import-from save -> **Expected:** last\_polled\_at follows a lower date and ignores a higher one. Interval 4 -> **Save -> Expected:** the interval message; blank both filter boxes -> **Save -> Expected:** the filters message. Second account (**Update connection** with the first user's id) -> 404. **Disconnect -> Yes, disconnect -> Expected:** "Inbox disconnected...", empty list.

## 10m. Web — Email ingestion: staging & dedup (app slice EMAIL-4) • Core

Voucher emails become inert review drafts in the owner's current household (ADR-V010) — nothing in the budget until confirmed (EMAIL-6). Needs a live-connected inbox (QA-EMAIL-02) with at least one real BAC/BN voucher email that matches the filters.

### QA-EMAIL-04 — Sync now stages drafts once, dedups re-fetches, and a dead inbox says so • Core (Web / API)

#### Gherkin

```
Given a connected inbox with two unread BAC voucher emails received after "Import mail from"
When I click Sync now
Then "Sync done – 2 staged for review, 0 already seen, K not a voucher." and Last checked updates to now
When I click Sync now again
Then "0 staged for review, 2 already seen" – the same emails never stage twice
When the inbox needs reconnecting (token revoked at the provider)
Then Sync now shows "Reconnect this inbox to sync it." and the row turns Needs reconnect
```

**Walkthrough:** **Settings -> Manage inboxes -> Sync now -> Expected:** the green summary with the counts; the emails stay **unread** in the mailbox. **Sync now** again -> **Expected:** the same count now under "already seen". Via Postman (**21 · Email inboxes -> Sync now**) -> 200 { staged, duplicates, unrecognized }; (**Get connection**) -> last\_polled\_at moved to the sync time. Revoke the app's access in the provider's account settings -> **Sync now -> Expected:** the reconnect message, badge **Needs reconnect**, Postman -> 409 needs\_reconsent. The drafts become visible in EMAIL-6's Review queue; until then confirm via SQL that PendingVouchers holds the rows with status = pending.

## 10n. Web — Email ingestion: suggestions & review queue (app slice EMAIL-5/6) • Core

The staged drafts (QA-EMAIL-04) become transactions only here. Merchant rules prefill the queue; the user always confirms. Can be run without a live inbox by staging a draft row directly (see the note in QA-EMAIL-06) — the confirm path is identical.

## QA-EMAIL-05 — Merchant rules suggest, never apply, and are unique per household • Core (Web / API)

### Gherkin

```
Given Settings -> Manage suggestions
When I add "AUTOMERCADO" -> Groceries and "Taco Bell" -> Dining / Extraordinary
Then both list with their category; adding "automercado" again says "A rule for this merchant already exists."
When a voucher from "TACO BELL PLAZA REAL C" is staged
Then the Review queue shows it with Dining / Extraordinary prefilled and a "Suggested" badge – but it is NOT a transaction until I confirm
```

**Walkthrough:** Settings -> Manage suggestions -> add the two rules -> **Expected:** the table shows pattern, category, class. Add automercado (lower-case) -> **Expected:** the red notice, no new row. Edit "Taco Bell" -> class Budgeted -> save -> the row follows; delete it (two-step) -> gone. Via Postman (22 · Review queue & merchant suggestions -> Create merchant rule twice) -> 201 then 409 mapping\_exists; List merchant rules -> category\_name filled. Stage a matching voucher (Sync now with a real email, or the SQL row from QA-EMAIL-06 with merchant = 'TACO BELL PLAZA REAL C') -> **Review** -> **Expected:** the category select already shows the mapped category, the "Suggested" badge is on, and Months shows no new transaction yet.

## QA-EMAIL-06 — Review queue: confirm books the transaction once, discard never reverts a confirm • Core (Web / API)

### Gherkin

```
Given a pending draft in the Review queue (header badge shows 1, dashboard banner says 1 waiting)
When I pick a category (or create one right there with "+ New" – every card on the queue then lists it) and class, tick "Remember this merchant" and Confirm
Then "Confirmed and remembered", the draft leaves the queue, the badge disappears, and the month lists a transaction with source email and the voucher's amount, bank and date
And Settings -> Manage suggestions now has a rule for that merchant
When I confirm the same draft again through the API
Then 409 not_pending, and no second transaction exists
When I discard another pending draft
Then it leaves the queue; discarding it again -> 409; the same email never re-stages on the next Sync now
```

**Walkthrough:** need a pending draft — either QA-EMAIL-04 with a real email, or stage one directly (dev only): INSERT INTO "PendingVouchers" (...) with your household's TenantId, a BankId from "Banks", Status = 'pending', Merchant, Amount, Currency = 'CRC', Date, Fingerprint, ProviderMessageId, ParsedBank = 'Bac', MissingFields = '{}'. Open **Dashboard** -> **Expected:** the amber banner "1 voucher(s) ... waiting for review -> Review now" (even with no months yet) and the header **Review** link with a 1 badge. **Review** -> **Expected:** the card shows merchant, ■ amount, date, type, bank; category prefilled only when a rule matches; parsed fields read-only (a draft with blanks shows "Could not read: ..." and opens exactly those fields). Pick a category — or + **New** beside the picker, type a name, **Create** -> **Expected:** selected on this card and offered on every other card — tick **Remember this merchant**, **Confirm** -> **Expected:** the green notice, the card gone, the badge gone; **Months** -> that month lists the transaction (source email); **Settings** -> **Manage suggestions** has the new rule. Postman (**Confirm pending voucher** with the same {{pendingVoucherId}}) -> **Expected:** 409 not\_pending; **Months** -> **transactions** still shows one row for it. Stage a second draft -> **Review** -> **Discard** -> **Expected:** "Draft discarded.", queue empty; Postman **Discard pending voucher** -> 409 not\_pending; **Sync now** (or re-staging the same fingerprint) -> not re-staged (the tombstone). Also: with the rate provider blocked (unset the API key and no prior transaction), **Confirm** -> **Expected:** "No exchange rate is available right now", the draft stays in the queue, nothing in Months.

## 11. Emails (Mailpit) — branding & content • Core

**Delivery is asynchronous** (the outbox dispatcher) — emails land in Mailpit a few seconds after the triggering action, and the send request succeeds regardless (see §1.1). Wait briefly before opening Mailpit; a missing email is a delayed/retrying/dead-lettered outbox message, not a request failure.

## QA-MAIL-01 — OTP email is branded & correct • Core

### Gherkin

```
Given I request an OTP code
When I open the email in Mailpit
Then it shows the brand logo, brand colours, the 6-digit code, and the tagline
```

**Walkthrough:** trigger an OTP; open it in Mailpit. **Expected:** the logo image renders (CID-embedded, not a broken image), brand-green styling, a clearly displayed code, footer wordmark + tagline.

## QA-MAIL-02 — Magic-link email • Core

**Walkthrough:** trigger a magic link; open in Mailpit. **Expected:** branded layout; a working sign-in button/link; sensible subject.

## QA-MAIL-03 — Invitation email • Core

**Walkthrough:** send an invite; open in Mailpit. **Expected:** branded layout; the recipient's address; a `/join?token=...` link that works (QA-INV-02).

## QA-MAIL-04 — Logo renders in a real client • Edge

**Walkthrough (optional, deliverability):** forward/inspect one email in a real Gmail/Outlook client. **Expected:** the CID logo still renders. \*(Note: from a non-verified domain, real delivery may land in spam — a domain/DKIM concern, not an app bug.)\*

## 12. Desktop — MAUI / Windows • Core

The desktop client reuses the same UI; only the **auth transport** (loopback browser flow, body token, OS secure storage) differs. Magic link is intentionally **absent** on native.

## QA-DSK-01 — OTP sign-in • Smoke (Desktop) — CI covers boot-to-login only

### Gherkin

```
Given the desktop app is on the login screen
When I request an OTP and enter the code from Mailpit
Then I am signed in within the app (no browser)
```

### Walkthrough

- 1 Launch the desktop app -> login screen. **Expected:** Google/Microsoft buttons + email field with **Email me a code**; **no magic-link button** (native hides it).
- 2 Enter an email -> request code -> get it from Mailpit -> enter it.
- 3 **Expected:** signed in, app shell shown, household + name in header.

## QA-DSK-02 — Google OAuth via loopback • Core (Desktop)

### Gherkin

```
Given the desktop login screen
When I click Continue with Google and complete consent in the system browser
Then the browser shows a "you can close this" page and the app completes sign-in
```

### Walkthrough

- 1 Click **Continue with Google**. **Expected:** your **system browser** opens to Google consent.
- 2 Approve. **Expected:** the browser tab shows a "you can close this tab" page; **focus returns to the app**, now signed in. (Repeat for **Microsoft**.)

## QA-DSK-03 — "Remember me" across app restart • Core (Desktop)

### Gherkin

```
Given I am signed in to the desktop app
When I fully close and reopen it
Then I am still signed in
```

**Walkthrough:** close the app completely; relaunch. **Expected:** lands signed in (refresh token held in Windows secure storage / DPAPI, silently exchanged on startup).

## QA-DSK-04 — Household & Settings load (authorized API calls) • Core (Desktop)

### Gherkin

```
Given I am signed in to the desktop app
When I open Household and Settings
Then both load their data without an auth error
```

**Walkthrough:** open **Household** (members load) and **Settings** (linked providers load). **Expected:** both populate — no spinner-forever, no "couldn't load" error. \*(This is the Bearer-token-handler path that previously failed on native; it must work.)\*

## QA-DSK-05 — Link a provider from Settings • Edge (Desktop)

**Walkthrough:** **Settings** -> **Link Microsoft** -> system browser loopback flow -> returns to app. **Expected:** Microsoft shows **Connected**; the app shell was never navigated away.

## QA-DSK-06 — Sign out • Edge (Desktop)

**Walkthrough:** **Sign out**. **Expected:** back to the login screen; reopening the app does **not** auto-sign-in (secure storage cleared).

## QA-DSK-07 — Core household flows work on desktop • Edge (Desktop)

**Walkthrough:** spot-check rename, invite (token revealed), and leave on desktop. **Expected:** same behavior as web (§7–8) — the UI is shared.

**\*\*NATIVE Wave 2 (ADR-018, docs/NATIVE\_PARITY.md):\*\*** the cases below verify the parity fixes per-feature on desktop — join-by-code (G5), culture persistence (G6), export share (G1), and the billing return-trip (G2) — plus the feature areas the old plan never exercised natively.

## QA-DSK-08 — Join a household by pasted invite code • Core (Desktop)

### Gherkin

```
Given a member account signed in on desktop and an invite code from the owner
When I open Household -> "Have an invite?" and paste the code
Then I join the owner's household exactly as the emailed link would
```

### Walkthrough

- 1 As the **owner** (web is fine): **Household** -> invite the member's email -> copy the revealed token.
- 2 On **desktop** as the member: **Household** -> **Have an invite?** -> paste the code -> **Join**. **Expected:** success state -> **Go to household** -> roster lists both members.
- 3 Negative: paste a garbage code. **Expected:** inline error, the form stays for a retry.

## QA-DSK-09 — Language choice survives an app restart • Core (Desktop)

### Gherkin

```
Given the desktop app on the login screen (signed out)
When I switch the language to Español and fully restart the app
Then it launches in Spanish
```

### Walkthrough

- 1 Signed out, on the login screen: switch the language selector to **Español**. **Expected:** the UI re-renders in Spanish (no restart needed).

- 2 Fully close the app; relaunch. **Expected:** still Spanish — the choice is read from OS Preferences before first render (NATIVE-5). Switch back to English; same persistence.
- 3 Note: after sign-in, a **server-saved** locale wins (the account preference follows you across devices) — that's by design.

## QA-DSK-10 — Data export downloads via the OS • Core (Desktop)

### Gherkin

```
Given I am the owner, signed in on desktop
When I request the data export and click Download
Then the file is offered through the platform share/save UI, not a dead WebView navigation
```

### Walkthrough

- 1 **Household** -> **Data** -> **Export my data** -> wait for the ready alert -> **Download**.
- 2 **Expected:** the **Windows share flyout** opens with the JSON bundle staged (server-named ...-<id>.json); the app page is not navigated away. Save it and open — valid JSON, no secrets (spot-check: no token hashes).

## QA-DSK-11 — Billing: checkout leaves, summary refreshes on return • Core (Desktop)

### Gherkin

```
Given I am the owner on the desktop Billing page (Stripe test mode configured)
When I click Upgrade, complete checkout in the system browser, and return to the app
Then the plan summary refreshes by itself – no re-navigation needed
```

### Walkthrough

- 1 **Billing** -> **Upgrade**. **Expected:** the **system browser** opens the hosted checkout; the app stays on Billing (it does not navigate away).
- 2 Complete checkout with a test card. **Expected:** the browser lands on the **web** app's billing page (by design — emailed/redirect links are web; docs/NATIVE\_PARITY.md G2).
- 3 Click back into the desktop app. **Expected:** the summary **refetches on focus** — the plan flips to **pro** without touching navigation. (Without Stripe keys the fake provider's checkout URL is a stub — then verify only: browser opened, app stayed, and refocusing refetches.)

## QA-DSK-12 — MFA: enroll and native step-up • Core (Desktop)

### Gherkin

```
Given I am signed in on desktop without MFA
When I enable the authenticator in Settings, sign out, and sign in again
Then the app itself prompts for the 6-digit code before completing sign-in
```

### Walkthrough

- 1 **Settings** -> **Two-factor** -> **Enable**. **Expected:** the QR renders inside the app (the vendored QR script ships in the native host too); manual key shown; confirm with a code; **recovery codes** displayed once.
- 2 Sign out -> OTP sign-in. **Expected:** after the OTP, the app shows the **in-app MFA prompt** (native step-up, MFA-4) — enter the authenticator code -> signed in. A recovery code also works (single-use).

## QA-DSK-13 — Notification bell & preferences • Edge (Desktop)

**Walkthrough:** header **bell** -> **Expected:** opens with the empty state (or your items), badge matches unread count.

**Settings** -> notification preferences -> toggle one off -> reload the page -> **Expected:** the switch state persisted. (For a real item end-to-end, a staff announcement — see QA-ADMIN-04 — lands in the native bell too; spot-check when staff is configured.)

## QA-DSK-14 — Admin console on desktop (staff only) • Edge (Desktop)

**Walkthrough:** with your email in Admin:StaffEmails, sign in on desktop. **Expected:** **Admin** appears in the nav; the console lists tenants; opening a detail works. Impersonate a user -> **Expected:** banner appears; **Stop** restores your staff session in-app (native refresh path).

## QA-DSK-15 — Theme: dark mode survives an app restart • Edge (Desktop)

**Walkthrough:** pick **Dark** in the header switcher -> **Expected:** the WebView restyles dark immediately. Quit the app fully and relaunch -> **Expected:** it boots dark with no light flash (the theme bootstrap reads the WebView's own localStorage pre-paint — verifies WebView storage persists across restarts on this platform). Pick **Auto** -> **Expected:** follows the OS light/dark setting live.

## 13. Android — MAUI • Core

Prereq every run: `**adb reverse tcp:5238 tcp:5238**` + API on the https profile. See docs/MOBILE\_TESTING.md.

### QA-AND-01 — OTP sign-in • Smoke (Android) Automated in CI

#### Gherkin

```
Given the Android app is on the login screen with adb reverse set
When I request an OTP and enter the code from Mailpit
Then I am signed in
```

#### Walkthrough

- 1 Confirm `adb reverse --list` shows `tcp:5238`. Launch the app.
- 2 Login screen: email field + **Email me a 6-digit code**; Google/Microsoft buttons; **no magic link**.
- 3 Enter an email -> request code -> read it in Mailpit (host) -> enter it.
- 4 **Expected:** signed in, app shell shown.

### QA-AND-02 — Google OAuth via custom scheme • Core (Android)

#### Gherkin

```
Given the Android login screen
When I tap Continue with Google and complete consent
Then the in-app browser returns to the app via the perezosoft:// scheme, signed in
```

#### Walkthrough

- 1 Tap **Continue with Google**. **Expected:** a browser tab opens to Google consent.
- 2 Approve. **Expected:** the tab returns control to the app (`perezosoft://auth intent`), now signed in. (Repeat **Microsoft** if its `:5238` redirect is registered.)

### QA-AND-03 — "Remember me" across app restart • Core (Android)

**Walkthrough:** swipe-close the app; reopen. **Expected:** still signed in (refresh token in the Android Keystore). \*(If `adb reverse` was lost on a device reboot, re-run it first — a startup failure after reboot is an environment issue, not an app bug.)\*

### QA-AND-04 — Household & Settings load • Core (Android)

**Walkthrough:** open **Household** and **Settings**. **Expected:** both load their data (the native Bearer path works), same as desktop QA-DSK-04.

### QA-AND-05 — Navigation drawer / header is reachable • Edge (Android)

#### Gherkin

```
Given I am signed in on Android
When I open the navigation (hamburger)
Then the menu is tappable and not hidden under the status bar
```

**Walkthrough:** tap the hamburger; use **Household/Settings/Sign out**. **Expected:** the header sits below the status bar (safe-area padding) and every item is tappable.

### QA-AND-06 — Core flows on Android • Edge (Android)

**Walkthrough:** spot-check language switch, invite (token revealed), and leave. **Expected:** parity with web.

**\*\*NATIVE Wave 2 (ADR-018, docs/NATIVE\_PARITY.md):\*\*** the cases below verify the parity fixes on Android — including the two that only exist on this platform (hardware back, share sheet).

## QA-AND-07 — Hardware back navigates in-app history • Smoke (Android)

### Gherkin

```
Given I am signed in on Android and have navigated Home -> Household -> Settings
When I press the hardware/gesture back button repeatedly
Then it walks back through the app's pages and only leaves the app at the root
```

### Walkthrough

- 1 Navigate **Home** -> **Household** -> **Settings** (three distinct pages).
- 2 Press **back**. **Expected:** Settings -> Household. Again: -> Home.
- 3 Press **back at Home (root)**. **Expected:** the app backgrounds/exits — the default, but only at the root. \*(Before NATIVE-4, any back press exited the app.)\*
- 4 Note: a full WebView reload (e.g. the language switch) restarts the in-page history — back exiting right after one is acceptable.

## QA-AND-08 — Join a household by pasted invite code • Core (Android)

**Walkthrough:** as QA-DSK-08, on Android: owner invites (web) -> member on Android: **Household** -> **Have an invite?** -> paste -> **Join** -> roster shows both. Garbage code -> inline error, retryable. \*(This was parity gap G5 — a native member previously had no way to join at all.)\*

## QA-AND-09 — Language choice survives an app restart • Core (Android)

**Walkthrough:** as QA-DSK-09: signed out, switch to **Español** (re-renders) -> **swipe-close** the app -> relaunch. **Expected:** still Spanish (OS Preferences bootstrap, NATIVE-5). Signed-in accounts reconcile to their server-saved locale — by design.

## QA-AND-10 — Data export via the share sheet • Core (Android)

**Walkthrough:** owner -> **Household** -> **Data** -> **Export my data** -> **Download**. **Expected:** the **Android share sheet** opens with the JSON bundle (server-named); share to Files/Drive and open — valid JSON. The app page is not navigated away. \*(Before NATIVE-3 this click did nothing — the WebView silently dropped it.)\*

## QA-AND-11 — Billing: checkout leaves, summary refreshes on return • Core (Android)

**Walkthrough:** as QA-DSK-11: **Billing** -> **Upgrade** -> **Expected:** the system browser/Custom Tab opens; complete checkout (test mode); switch back to the app (app switcher or back). **Expected:** the summary **refetches on resume** — plan shows **pro** without re-navigation (NATIVE-4; Android's return path is the Activity resume).

## QA-AND-12 — MFA: enroll and native step-up • Core (Android)

**Walkthrough:** as QA-DSK-12 on Android — QR renders in-app (scan it with a second device or use the manual key), recovery codes shown once; after sign-out, OTP sign-in prompts the **in-app** MFA step-up (MFA-4).

## QA-AND-13 — Edge-to-edge / status bar on Android 15 • Edge (Android)

### Gherkin

```
Given a device or emulator on Android 15 (API 35, edge-to-edge enforced)
When I use the app in portrait and landscape
Then no control is hidden under the status bar or gesture areas
```

**Walkthrough:** check the header/hamburger (extends QA-AND-05), the bell dropdown, and a page with bottom-of-screen buttons (Settings danger zone) in both orientations. **Expected:** nothing sits under the status bar or the gesture-nav pill; everything tappable. \*(Flagged [verify] by the parity audit — if this fails, it becomes a small safe-area fix slice.)\*

## QA-AND-14 — Theme: dark mode survives an app restart • Edge (Android)

**Walkthrough:** as QA-DSK-15 on Android — pick **Dark** (hamburger -> header controls), force-stop the app (or swipe it away) and relaunch. **Expected:** boots dark, no light flash (Android WebView localStorage persists). **Auto** follows the

system dark theme toggle live.

## QA-AND-15 — OAuth sign-in survives process death (NATIVE-12) • Core (Android)

### Gherkin

```
Given I tapped Continue with Google and the consent tab is open
When Android kills the app process before I finish consent
Then approving still signs me in – the redirect relaunches the app and completes on startup
```

### Walkthrough

- 1 Tap **Continue with Google**. **Expected:** the browser tab opens to Google consent.
- 2 With the tab in the foreground, kill the app process: `adb shell am kill com.perezosoftware.platform` (works because the app is backgrounded behind the browser; \*Don't keep activities\* + memory pressure reproduces it the organic way).
- 3 Approve consent in the still-open tab. **Expected:** the `perezosoftware://auth` redirect cold-starts the app, which **stays open** and lands signed in on Home (the stashed code is exchanged during startup — no "flash open and close").
- 4 (MFA account) same steps. **Expected:** the app opens on the Login MFA code prompt; entering the TOTP completes sign-in.
- 5 (Staleness) repeat 1–2, wait > 5 min before approving. **Expected:** the app opens on Login with "Your sign-in took too long to complete. Please try again." — no crash, retry works.

## 13b. iOS + macOS Catalyst — first-run smoke • Core

These platforms compile in CI but had never been RUN before this pass. Prereqs: a Mac with Xcode 26.5 (the CI pin), the repo, and the API + Postgres + Mailpit running on that Mac (the iOS simulator shares the host network, so `https://localhost:7160` works; a physical device needs the API bound to a LAN address + the dev cert trusted). Launch: `dotnet build src/Maui -t:Run -f net10.0-ios (simulator) / -f net10.0-maccatalyst`. The **G7 fix is required** (PR #109) — before it, both platforms crashed at first resolve (no `IOAuthInitiator` registered). OAuth is wired via `ASWebAuthenticationSession` + the `perezosoftware` scheme in `Info.plist`; first exercised **and passed** in the 2026-07-06 §13b run (PR #125 fixed the two gaps it found) — QA-IO-04 re-verifies it each pass.

## QA-IO-01 — App boots to the login screen • Smoke (iOS)

**Walkthrough:** launch on the simulator. **Expected:** the app opens (no startup crash — this \*was\* parity gap G7), the login screen renders: email + **Email me a 6-digit code**, provider buttons, **no magic-link button**, nothing under the notch/safe areas.

## QA-IO-02 — OTP sign-in • Smoke (iOS)

**Walkthrough:** request a code -> read it from Mailpit (on the Mac) -> enter it. **Expected:** signed in, app shell + household load (the native Bearer/body-token path works on iOS).

## QA-IO-03 — Core flows spot-check • Core (iOS)

**Walkthrough:** spot-check on the simulator: **Household** roster + invite (token revealed) + **join-by-code**, **Settings** (providers list, MFA card renders its QR), **language switch** -> re-render + relaunch persistence, **bell** empty state, **export** -> iOS share sheet. **Expected:** parity with Android (§13) — same shared RCL.

## QA-IO-04 — OAuth via ASWebAuthenticationSession • Core (iOS)

**Walkthrough:** **Continue with Google**. **Expected:** the system auth session sheet opens to Google consent; approving returns to the app via the `perezosoftware://auth` scheme, signed in. Also verify session-across-restart (Keychain-backed secure storage).

## QA-MAC-01 — App launches at a usable window • Smoke (macCatalyst)

**Walkthrough:** launch the macOS Catalyst build. **Expected:** no startup crash (G7); the window opens at a sensible default size and is resizable; login renders. \*(The audit's [verify] desktop-window-sizing cell for macOS.)\*

## QA-MAC-02 — OTP sign-in • Smoke (macCatalyst)

**Walkthrough:** as QA-IOS-02. **Expected:** signed in; Household + Settings load.

## QA-MAC-03 — Core flows + OAuth spot-check • Core (macCatalyst)

**Walkthrough:** as QA-IOS-03 (share = macOS share menu) + one OAuth round-trip (QA-IOS-04 flow) + restart persistence. **Expected:** parity.

## 13c. Native release checklist

Per release that ships a native client, run the platform's • Smoke cases plus one • Core feature spot-check, and record results in §16:

| Platform        | Always (• Smoke)       | Plus one of (• Core) |
|-----------------|------------------------|----------------------|
| Windows desktop | DSK-01, DSK-03, DSK-06 | DSK-08..12           |
| Android         | AND-01, AND-03, AND-07 | AND-08..15           |
| iOS             | IOS-01, IOS-02         | IOS-03, IOS-04       |
| macCatalyst     | MAC-01, MAC-02         | MAC-03               |

Full per-feature native regression (every case in §12–13b) is for releases that changed native glue (`src/Mauui/**`, the RCL seams: `ICulturePersistence` / `IFileDownloadLauncher` / `AppResumeNotifier`) or bumped the .NET/MAUI toolchain.

## 14. Cross-cutting security • Core

### QA-SEC-01 — Tenant isolation • Smoke

#### Gherkin

```
Given two households owned by two different users
When user A is signed in
Then A can only ever see A's household, members, and invitations – never B's
```

#### Walkthrough

- 1 Create household A (owner A) and a separate household B (owner B, different account/incognito).
- 2 As A, open **Household**. **Expected:** only A's members/invites. Confirm B's data never appears. \*(Deeper API-level probing — e.g. requesting another tenant's resource id — belongs in `automated Api . Tests`; this manual case verifies the UI never cross-contaminates.)\*

### QA-SEC-02 — Protected pages require auth • Core

**Walkthrough:** signed out, directly visit `/household`, `/settings`. **Expected:** each redirects to `/login`.

### QA-SEC-03 — Session is gone after sign-out • Core

#### Gherkin

```
Given I sign out
When I press the browser Back button or reload a protected page
Then I am not able to access it – I am sent to /login
```

**Walkthrough:** sign out, press **Back** to a protected page / reload it. **Expected:** bounced to `/login`; no stale authenticated view.

### QA-SEC-04 — Native open-redirect guard • Edge (Desktop/Android)

**Context/Expected:** the native OAuth flow only honors loopback `http` callbacks or the configured `perezosoftware://` scheme; arbitrary redirect targets are rejected. This is unit-tested (`NativeRedirectPolicyTests`); no manual action needed unless probing the API directly — record as **covered by automated tests**.

### QA-SEC-05 — Server-side hardening (automated) • Edge

**Context/Expected:** several invariants are enforced at the API/data layer and verified by tests/`Api.Tests`, not by manual UI steps — record as **covered by automated tests** unless probing the API directly:

- **Tenant write-stamping** — a new tenant-scoped row is stamped with the caller's tenant and a foreign-tenant write is rejected (`TenantStampingInterceptorTests`), so reads *\*and\** writes are tenant-isolated.
- **Refresh-token reuse detection** — replaying an already-rotated refresh token revokes all the user's sessions (`RefreshTokenServiceTests`). Manually observable only by capturing and replaying a refresh cookie/token; out of scope for routine QA.
- **Unverified-email takeover guard** fails closed (`ClaimsExtractorTests / UserServiceTests`).
- **Legacy refresh-cookie self-heal** — a stale `Path=/` refresh cookie left by an older build can shadow the live `Path=/api/auth` cookie and wedge sign-in into a `/refresh 401 -> "Authentication Failed"` loop (seen in Firefox, due to cookie send-order). Setting the refresh cookie now also emits an expiry for the orphan, so the next successful sign-in / refresh sweeps it automatically — no manual cookie-clearing, and upgraded deployments self-heal (`CookieServiceTests`). \*Manual repro needs a planted `Path=/` cookie; record as covered by automated tests. If a tester hits a stuck `/refresh 401` loop in Firefox after a deploy, a single re-sign-in clears it.\*

## 14a. Adversarial & tenant-isolation (QA-ADV-\*) • Core

This suite probes the failure classes a **v3 audit** surfaced: cross-tenant reads/writes at the **API** layer (not just the UI), impersonation attribution and confinement, billing idempotency, session/token lifecycle, preference bleed on shared devices, and deploy/native hardening. Most cases are **curl/Postman** driven with **two tenants A and B** — mint an **owner JWT for each** (sign in as each owner and copy its access token from `POST /api/auth/refresh` or the Swagger **Authorize** button, exactly as §14b describes) so you hold **\*\*two JWTs carrying different `tenant_id` claims\*\***. A few cases need the **two browser contexts** of §1.2 (a normal window + an incognito/second profile); those are flagged in the title. Base URL `https://localhost:7160` (use `-k` for the dev cert) locally, or the staging host for Environment B. Grab each tenant's ids up front: `GET /api/household` as A and as B gives you A's/B's household id + member user-ids; note one **B** member user-id, one **B** notification/webhook/api-key id (create them if needed) for the cross-tenant probes.

(!) **EXPECT-FAIL discipline**. Roughly half of these assert behaviour the v3 audit says is **broken at authoring time (2026-07)**; **ALL are fixed as of the v3 remediation (PRs #147–#191)**. Each formerly-broken case carries a ■ v3-landed note naming the finding. When it fails, record **Blocked (known defect)** against the id in §16 — **never Pass**. A QA plan that green-ticks a broken isolation path is worse than no case at all. The remaining cases should **Pass on current code**; a failure there is a real regression.

### QA-ADV-01 — Tenant A cannot read/export/erase Tenant B via the API • Smoke (curl)

#### Gherkin

```
Given I hold owner JWTs for two separate tenants A and B
When I use A's JWT to target B-scoped resource ids directly
Then every B id is refused (404/403), A's export contains only A, and no B row mutates
```

#### Walkthrough

- 1 With **A's JWT**, call `GET /api/household -> 200` showing **only A** (never B's name/members).
- 2 `POST /api/household/export` with A's JWT -> the JSON bundle enumerates **only A's** tenant, members and invitations — grep it for B's household name/emails: **absent**.
- 3 Target B directly with A's JWT: `DELETE /api/household/members/{B-userId}`, `POST /api/notifications/{B-notificationId}/read`, `DELETE /api/notifications/{B-notificationId}`.
- 4 **Expected:** each B-scoped call returns **404** (or 403) — the global tenant filter + RLS backstop hide B entirely; ids from another tenant simply don't exist for A.
- 5 Re-verify as **B** (`GET /api/household, bell`): B's member list and notifications are **unchanged**. This promotes QA-SEC-01 from a UI-only check to a direct API probe (audit **RLS-2/4**).

### QA-ADV-02 — Cross-tenant isolation on the newer tables (PUBAPI/HOOKS on) • Core (curl)

**Precondition:** set `PublicApi__Enabled=true + Webhooks__Enabled=true`, restart (§14b). In **each** tenant mint an API key (QA-API-02) and register a webhook + generate one delivery (QA-API-05/06). **Gherkin**

Given tenants A and B each own an API key, a webhook subscription and a delivery row  
When A's JWT targets B's api-key / webhook / delivery ids  
Then each is 404 and nothing cross-tenant is read, replayed or revoked

#### Walkthrough

- 1 With **A's JWT**: GET `/api/webhooks/{B-subscriptionId}/deliveries`, POST `/api/webhooks/deliveries/{B-deliveryId}/replay`, DELETE `/api/apikeys/{B-keyId}`.
- 2 **Expected: 404** for each — the delivery log/read side filters by `TenantId` and management routes are tenant-scoped, so B's rows are invisible and untouchable to A.
- 3 Confirm as B: B's key still authenticates, its subscription/deliveries are intact, nothing replayed (audit **LB-TEN-2 / RLS-8**).

### QA-ADV-03 — Export includes EVERY tenant-scoped table, secret-free • Core (curl)

■ **v3 REMEDIATION LANDED (2026-07, PRs #147–#191)** — this case now expects **PASS**; re-run and record normally. **Gherkin**

Given PUBAPI + HOOKS are enabled and my tenant has an API key, a webhook and metered usage  
When I export the household  
Then the bundle covers api-keys (metadata only), webhook subscriptions (no secret) and usage counters — or explicitly notes their exclusion

#### Walkthrough

- 1 Enable both flags; as owner mint an API key, register a webhook, and drive **one** metered `IQuotaService.TryConsumeAsync` consume (any endpoint an app has wired, or seed a `UsageCounter`).
- 2 POST `/api/household/export`; open the JSON.
- 3 **Expected (post-remediation)**: it contains an **api-keys** section (name/prefix/scopes, **no hash**), a **webhook-subscriptions** section (url/event-types, **no signing secret**), and the **usage counters** — or an explicit documented exclusion note for each.
- 4 **Was (pre-v3 audit LB-TEN-1)**: this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**. Also assert **no secret leaks** (hashes / `whsec_...`) regardless — the export stays secret-free.

### QA-ADV-04 — Dissolve / erasure actually deletes api keys, webhook secrets, usage counters, delivery logs • Core (curl + DB)

■ **v3 REMEDIATION LANDED (2026-07, PRs #147–#191)** — this case now expects **PASS**; re-run and record normally. **Gherkin**

Given a tenant with an API key, a webhook subscription (+ deliveries) and usage counters  
When the sole owner dissolves the household (or deletes the account)  
Then all those rows are physically gone — no orphaned keys, secrets, counters or delivery logs remain

#### Walkthrough

- 1 Set up a throwaway tenant with the same artefacts as QA-ADV-03.
- 2 As sole owner, dissolve (QA-HH-07) / delete account (QA-SET-07).
- 3 Query the DB (or the staff console) for that tenant's `ApiKey`, `WebhookSubscription`, `WebhookDelivery`, `UsageCounter` rows.
- 4 **Expected (post-remediation)**: **0 rows** for the dissolved tenant — every contributor cleaned up.
- 5 **Was (pre-v3 audit LB-TEN-1)**: this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**.

### QA-ADV-05 — Writes during impersonation are attributed to the acting staff • Core (curl)

■ **v3 REMEDIATION LANDED (2026-07, PRs #147–#191)** — this case now expects **PASS**; re-run and record normally. **Gherkin**

Given a staff user is impersonating the household owner (token carries impersonated\_by)  
When they perform audited tenant writes (export the household, change a member's role)  
Then each mutation's audit row records impersonated\_by=<staff>, not just the target

**Pick writes that are actually audited.** The audited-action catalog is small — tenant.exported, member.role\_changed, account.erased, and the staff-only admin.\* actions. Household rename (PUT /api/household) and mark-notification-read (POST /api/notifications/{id}/read) emit **no** AuditEvent, so they produce nothing to inspect; the two owner-gated writes below do. The stamp itself is ambient (AuditLog reads ICurrentImpersonation), so it lands on **every** audited event regardless of call site — the point is to exercise one that exists.

### Walkthrough

- 1 As staff, POST /api/admin/impersonate/{ownerUserId} -> short-lived token with impersonated\_by. Pick the household **owner** so the writes below are permitted; the tenant must also have **at least one other member** for the role change.
- 2 With that token, perform two **audited** tenant writes: POST /api/household/export (-> tenant.exported) and PUT /api/household/members/{memberUserId}/role (flip admin->member -> member.role\_changed).
- 3 Inspect the tenant's audit trail (staff-console audit view, or query the AuditEvent rows in the DB).
- 4 **Expected (post-remediation):** the tenant.exported **and** member.role\_changed rows each carry **\*\*impersonated\_by=<staff-id>\*\*** (with actor\_user\_id=<owner>), so an operator can tell staff-driven changes from the user's own — the stamp is applied to every event, not per call site.
- 5 **Was (pre-v3 audit LB-ADM-1):** this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**.

## QA-ADV-06 — An impersonation session cannot reach staff-only actions • Core (curl)

■ **v3 REMEDIATION LANDED (2026-07, PRs #147–#191) — this case now expects PASS; re-run and record normally. Gherkin**

Given I hold an impersonation token (impersonated\_by present, target is a normal member)  
When I call staff-only admin endpoints with it  
Then every one is refused at the staff gate – impersonation must not be a ladder back to staff power

### Walkthrough

- 1 Impersonate a **plain member** (POST /api/admin/impersonate/{memberUserId}, as in QA-ADV-05 step 1 but targeting a non-owner) -> token with impersonated\_by.
- 2 With it, attempt: POST /api/admin/impersonate/{x}, PUT /api/admin/tenants/{id}/subscription, DELETE /api/admin/users/{x}/mfa, POST /api/admin/announce-all.
- 3 **Expected (post-remediation): 403** on each — the staff gate treats a token bearing impersonated\_by as **non-staff**, closing privilege re-escalation.
- 4 **Was (pre-v3 audit ADM-2):** this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**.

## QA-ADV-07 — Impersonation cannot exceed the target's role • Core (curl)

### Gherkin

Given I am impersonating a plain member (not owner)  
When I attempt owner-only actions as that member  
Then I get exactly the 403 the member themselves would get

### Walkthrough

- 1 Impersonate a **plain member** of a tenant that has an owner + other members.
- 2 Attempt owner-only writes: POST /api/household/transfer-ownership, PUT /api/household/members/{id}/role, and (as staff-would-be) a comp — via the member token.
- 3 **Expected: 403** on each — impersonation inherits the **target's** role ceiling; a member seat confers no owner power (audit TB-ADM-3). Should **Pass** on current code.

## QA-ADV-08 — Impersonation never rewrites target prefs; shared-device pref poisoning •

### Core (curl + Web — two contexts)

■ v3 REMEDIATION LANDED (2026-07, PRs #147–#191) — this case now expects PASS; re-run and record normally. Gherkin

```
Given I impersonate a user and change theme/language in their session
Then the target's server-stored preference is unchanged after I Stop impersonating
And on a shared browser, a fresh sign-in never inherits the previous user's saved preference
```

#### Walkthrough

- 1 **Leg A (should Pass):** impersonate a user, change theme/language in-session, **Stop impersonating**. Re-read the target's server pref (GET /api/auth/me / their Settings -> Preferences). **Expected: unchanged** — preference sync is suppressed while impersonated\_by is set (PREFS-1/ADR-022).
- 2 **Leg B (EXPECT-FAIL):** in **context 1**, sign in as user A whose saved locale is **Español**; sign out. In the **same** browser, sign in as user B who has **never chosen** a language/theme.
- 3 **Expected (post-remediation):** B renders in B's own default (server never-set => B does not adopt A's leftover device value while a \*different\* account signs in).
- 4 **Was (pre-v3 audit LB-UI-4/5):** this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**.

## QA-ADV-09 — A staff MFA-reset notification cannot be silenced by target prefs • Core (curl)

■ v3 REMEDIATION LANDED (2026-07, PRs #147–#191) — this case now expects PASS; re-run and record normally. Gherkin

```
Given a user has turned BOTH notification channels (in-app + email) off
When staff reset that user's MFA
Then the security.mfa_reset in-app row AND the email are still delivered (security events ignore prefs)
```

#### Walkthrough

- 1 As the target, PUT /api/notifications/preferences with **in-app=false, email=false**.
- 2 As staff, DELETE /api/admin/users/{targetUserId}/mfa.
- 3 **Expected (post-remediation):** the target still gets the **\*\*security.mfa\_reset bell row** and **\*\* the email** — a security-critical notice is not suppressible by user prefs.
- 4 **Was (pre-v3 audit ADM-1):** this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**.

## QA-ADV-10 — MFA step-up locks out after repeated wrong codes • Core (curl)

■ v3 REMEDIATION LANDED (2026-07, PRs #147–#191) — this case now expects PASS; re-run and record normally. Gherkin

```
Given an MFA-enabled account at the sign-in step-up
When I submit wrong 6-digit codes past the attempt cap, including across freshly-requested challenges
Then a per-user cumulative MFA lockout engages – not merely the per-IP 429
```

#### Walkthrough

- 1 Trigger step-up (sign in as an MFA-on user); POST /api/auth/mfa/verify with wrong codes.
- 2 Keep going **past** the OTP-style attempt cap, and request **new** challenges to reset any per-IP window, pacing under the 429 verify throttle.
- 3 **Expected (post-remediation):** after N cumulative failures the **account's** step-up is locked (distinct from QA-AUTH-11's per-IP 429), mirroring the OTP cumulative lockout (QA-AUTH-04).
- 4 **Was (pre-v3 audit ADM-3):** this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**.

## QA-ADV-11 — A recovery code is single-use • Core (Web)

Gherkin

```
Given I used one MFA recovery code to complete step-up
When I sign out and submit the SAME recovery code again
Then it is rejected – recovery codes are consumed on first use
```

#### Walkthrough

- 1 On an MFA-on account, at step-up enter a **recovery code** (not the TOTP) -> signed in.
- 2 Sign out; start a fresh sign-in to the same account; at step-up submit the **same** recovery code.
- 3 **Expected:** rejected ("that code is incorrect or has expired"); the code was hashed + burned on first use (audit TB-AUTH-6). A different, unused code still works. Should **Pass**.

### QA-ADV-12 — Webhook replay + out-of-order + same-second idempotency • Core (curl)

**Precondition:** billing wired to the fake provider; HOOKS not required (this exercises the billing webhook inbox).

#### Gherkin

```
Given the billing webhook endpoint
When I POST the same EventId twice, then two distinct same-second events (created then active)
Then the duplicate is a no-op (inbox dedup) and the later state (active) still applies – not dropped as stale
```

#### Walkthrough

- 1 POST a provider webhook to /api/billing/webhook; \*\*repeat the exact same EventId\*\*.
- 2 **Expected:** the second POST is a **no-op** — the inbox dedups on event id; the subscription state is applied exactly once.
- 3 POST two **distinct** events with the **same whole-second** OccurredAt: first created, then active.
- 4 **Expected:** the flip to **active** is applied (**the strictly-older recency guard drops stale events; same-second ties apply in arrival order (exact redeliveries are inbox-deduped), not by a second-granular timestamp that would wrongly drop it as stale**) (audit LB-BILL-1). Should **Pass**\*\*.

### QA-ADV-13 — A first-ever webhook in a bad state does not false-notify • Core (curl)

■ v3 REMEDIATION LANDED (2026-07, PRs #147–#191) — this case now expects **PASS**; re-run and record normally. Gherkin

```
Given a tenant that has NEVER had a live subscription
When its first-ever billing webhook arrives as past_due (or canceled)
Then NO dunning notification is sent to the owner (there was nothing to lapse)
```

#### Walkthrough

- 1 Pick a tenant with no subscription history. POST a **first** webhook with Status=past\_due (or canceled) to /api/billing/webhook.
- 2 **Expected (post-remediation):** the owner receives **no** billing/dunning notification — a dunning notice requires a transition **out of** an active/paid state.
- 3 **Was (pre-v3 audit LB-BILL-4):** this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**.

### QA-ADV-14 — Comp / revert a churned (canceled) tenant • Core (curl)

■ v3 REMEDIATION LANDED (2026-07, PRs #147–#191) — this case now expects **PASS**; re-run and record normally. Gherkin

```
Given a tenant whose Stripe subscription is canceled (its subscription id still persisted)
When staff try to comp it to Pro (or revert)
Then the comp should succeed – a churned tenant is not permanently un-comp-able
```

#### Walkthrough

- 1 Take a tenant whose provider sub is **canceled** but whose Subscription row still holds the Stripe id. As staff, PUT /api/admin/tenants/{id}/subscription (comp to Pro).
- 2 **Expected (post-remediation):** comp **succeeds** — a canceled/churned sub is treated as not-provider-managed for comp purposes.

- 3 **Was (pre-v3 audit ADM-5):** this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**. (The guard now keys on *\*liveness\**: 409 only for a live provider sub — see QA-ADMIN-06, where 409 on a live Stripe sub is correct.)

## QA-ADV-15 — Concurrent acceptance of the last seat • **Core** (Web — two contexts)

### Gherkin

```
Given a tenant at seat cap minus one with two pending invitations
When both invitees accept near-simultaneously
Then exactly one joins, the other gets 402 seat_limit_reached, and seats never exceed the cap
```

### Walkthrough

- 1 Put a Free (cap 3) tenant at **2 seats used** with **two** distinct pending invites.
- 2 In **two browser contexts**, sign in as each invitee and open both `/join` links; click **accept** as close to simultaneously as you can (or double-submit).
- 3 **Expected: one** join succeeds (seat 3), the other returns **\*\*402 seat\_limit\_reached with the "household is full" state; the member count settles at exactly 3 — the atomic seat check has no race (audit TB-BILL-19 / BILLING-9). Should Pass\*\***.

## QA-ADV-16 — Magic-link / OTP double-redemption issues exactly one session • **Core** (Web — two contexts)

### Gherkin

```
Given a single magic link or a single OTP code
When I redeem it from two clients at once (open the link in two tabs / submit the OTP twice)
Then exactly one sign-in succeeds and the second attempt is rejected
```

### Walkthrough

- 1 Request a magic link; open the **same** link in two tabs nearly simultaneously (or double-click). Alternatively, request one OTP and POST `/api/auth/otp/verify` the same code from two clients at once.
- 2 **Expected: one** session is issued; the second redemption is rejected (token consumed single-use, no double-spend under concurrency) (audit **LB-AUTH-3**). Should **Pass**.

## QA-ADV-17 — Replaying a rotated refresh token revokes all sessions • **Core** (curl)

### Gherkin

```
Given I captured a refresh token, then refreshed once (rotating it)
When I replay the OLD (now-rotated) refresh token
Then it is rejected AND all of the user's sessions are revoked
```

### Walkthrough

- 1 Sign in; capture the refresh cookie/token. POST `/api/auth/refresh` once -> a **new** token (the old one is now rotated out).
- 2 Replay the **old** token to POST `/api/auth/refresh`.
- 3 **Expected: 401** — reuse detected — **and** the whole token family is revoked: a legitimate silent refresh from another live session now **fails** too (forces re-auth). Promotes QA-SEC-05's automated `RefreshTokenServiceTests` note to a manual probe. Should **Pass**.

## QA-ADV-18 — Spanish account on an English device accepts an invite • **Smoke** (Web — two contexts) Automated in CI

■ **v3 REMEDIATION LANDED (2026-07, PRs #147–#191)** — this case now expects **PASS**; re-run and record normally. Gherkin

```
Given a user whose saved locale is Español, on an English-default browser
When they open a valid /join?token=... (signed in, or signing in through it)
Then the locale-mismatch reload preserves the /join deep-link and the invite is accepted
```

### Walkthrough

- 1 User's server locale = **Español**; use a **fresh English-default** browser profile.

- 2 Open a valid `/join?token=...` while signed in (or sign in through the join flow).
- 3 **Expected (post-remediation):** the one-time locale-mismatch reload (WASM satellite assemblies, PREFS-1) **preserves** the `/join?token=...` URL and the invite is **accepted**.
- 4 **Was (pre-v3 audit UX-1, LB-UI-1/2):** this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**.

## QA-ADV-19 — Theme/locale doesn't revert after a soft (OTP/MFA) sign-in • Core (Web)

### Gherkin

```
Given on the login page I pick Dark + Español, for a user whose server prefs differ
When I complete an OTP soft-navigation sign-in
Then there is no flip-back-then-correct flicker; the switcher reflects the applied value all session
```

### Walkthrough

- 1 On `/login`, set **Dark + Español**. Complete an **OTP** sign-in (soft nav, no full reload) for a user whose stored prefs are e.g. Light/English.
- 2 **Expected:** the reconcile settles the applied theme/locale **once**, cleanly — no visible revert-then-reapply flash — and the header switcher shows the settled value for the rest of the session (PREFS-1 reconcile on **every** sign-in path, audit **UX-3/4**). Should **Pass**.

## QA-ADV-20 — "Clear read" never deletes unread notifications • Core (Web)

### Gherkin

```
Given my bell holds a mix of read and unread notifications
When I use "Clear read"
Then only the read ones are removed; every unread notification survives
```

### Walkthrough

- 1 Seed a mix (mark some read, leave some unread). In the bell, click **Clear read**.
- 2 **Expected:** the client sends `DELETE /api/notifications?read=true` — **read-only** clear; unread rows remain. Confirm the bulk clear **requires an explicit scope**: `?read=true` clears read only, `?read=false` is the distinct **Clear all**, and an omitted scope returns `**400 scope_required` — **so a dropped param can never silently wipe unread (audit LB-UI-10). Should Pass\*\***.

## QA-ADV-21 — Security headers on the single-origin host (staging / Environment B) • Core (curl)

■ **v3 REMEDIATION LANDED (2026-07, PRs #147–#191)** — this case now expects **PASS**; re-run and record normally. Gherkin

```
Given the deployed single-origin host serving API + WASM
When I inspect the response headers for the SPA shell and framework assets
Then HSTS, nosniff, a CSP/frame-ancestors and Referrer-Policy are present, with correct cache-control
```

### Walkthrough

- 1 `curl -I https://<app>-staging.onrender.com/` and `curl -I https://<app>-staging.onrender.com/_framework/blazor.webassembly.js`.
- 2 **Expected (post-remediation):** Strict-Transport-Security, X-Content-Type-Options: nosniff, a Content-Security-Policy (or frame-ancestors), and Referrer-Policy; **index.html** served no-cache, `_framework/*` fingerprinted assets immutable.
- 3 **Was (pre-v3 audit DEP-2/3):** this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**.

## QA-ADV-22 — Forged X-Forwarded-For cannot bypass the per-IP rate limit • Core (curl)

### Gherkin

```
Given the deploy is reachable other than via its trusted proxy (test the assumption)
When I send OTP requests with a rotating X-Forwarded-For header
Then the per-IP limit + OTP/MFA lockout is NOT bypassed
```

### Walkthrough

- 1 Hammer POST /api/auth/otp/send past the 5/min budget, rotating a spoofed X-Forwarded-For each request.
- 2 **Expected:** the throttle still trips **429** — the app only honours forwarded headers from the **configured trusted proxy** (DEPLOY-1's config-gated forwarded-headers), so a client-supplied XFF is ignored for rate-limit partitioning.
- 3 If the deploy is reachable **only** through its single trusted ingress, spoofing is moot — **document that sole-ingress assumption** in the run notes (audit **DEP-1 / ADM-10**). Should **Pass** (or be recorded N-A with the documented assumption).

### QA-ADV-23 — A Release native build points at a real HTTPS base URL, not cleartext localhost • **Core** (Desktop/Android)

■ **v3 REMEDIATION LANDED (2026-07, PRs #147–#191)** — this case now expects **PASS**; re-run and record normally. Gherkin

```
Given a Release (non-dev) native build with no dev overrides
When I inspect its configured API base URL and network security config
Then it targets the configured HTTPS API (build fails if none) – no http://localhost cleartext ships
```

### Walkthrough

- 1 Build a **Release** AAB/MSIX without dev overrides. Inspect the effective base URL + Android network security config.
- 2 **Expected (post-remediation):** base URL is the configured **HTTPS** API; a missing base URL **fails the build**; no http://localhost:5238 and no cleartext-permitting network config is shipped.
- 3 **Was (pre-v3 audit NAT-3):** this step used to FAIL and was recorded Blocked. The finding is fixed (v3 remediation, PRs #147–#191) — the assertions above now hold; expect **Pass**.

### QA-ADV-24 — Windows loopback OAuth binds state (login-CSRF guard) • **Edge** (Desktop) Gherkin

```
Given the desktop loopback OAuth callback listener with a pending state
When a callback arrives whose state does not match the pending listener
Then it is rejected – no session is minted from an unsolicited/forged callback
```

### Walkthrough

- 1 Start a desktop OAuth sign-in (loopback listener opens). Simulate a callback to the loopback URL with a **\*\*mismatched/blank state\*\***.
- 2 **Expected:** rejected — the client only completes the exchange when state matches the value it generated for the pending listener (login-CSRF / session-fixation guard), consistent with the native redirect policy (audit **NAT-10**). Should **Pass** (unit-backed; manual probe optional).

## 14b. API surfaces — PUBAPI + HOOKS (config-gated; curl / Postman) • **Core**

These two surfaces are **off by default** and have **no web UI** by design — they're for machines, so they're QA'd with an HTTP client. Any client works; the steps use `curl`. **Postman:** the repo ships a **complete, chained collection for the entire API** (all surfaces, not just these two) in docs/postman/, and CI mirrors it into the **Postman workspace** (postman-sync — open the workspace and pick an environment: local dev or staging/Render; importing the files by hand also works). It signs in via OTP (auto-fetching the code from Mailpit on local) and stores/rotates tokens per request. Alternatively, import GET /api/public/openapi.json (once PUBAPI is on) for just the public routes.

**Preconditions (do once):** in the repo-root .env set PublicApi\_\_Enabled=true and Webhooks\_\_Enabled=true, then restart the API. Management of keys/webhooks is **owner-only**, so sign in as an owner and grab a JWT access token from POST /api/auth/refresh (the Swagger "Authorize" button shows one) to call the /api/apikeys and /api/webhooks management routes below. Base URL in these steps is https://localhost:7160 (use -k for the dev cert).

## QA-API-01 — Config gate: surfaces are 404 when disabled • Edge (curl)

### Gherkin

```
Given PublicApi:Enabled and Webhooks:Enabled are false (the default)
When I call any /api/public, /api/apikeys or /api/webhooks route
Then it does not exist (404) – the routes aren't mapped and the API-key scheme isn't added
```

### Walkthrough

- 1 With both flags **unset/false**, restart the API and call `curl -k https://localhost:7160/api/public/openapi.json` and `.../api/apikeys` (with a JWT).
- 2 **Expected: 404** for both. Now set the two flags true, restart, and re-check — they become live (401/200). Leave them **on** for the rest of this section.

## QA-API-02 — Mint an API key (shown once) • Core (curl)

### Gherkin

```
Given I am the owner with PUBAPI enabled
When I create an API key
Then I receive the raw pk_... key exactly once, and listing later shows only its prefix/metadata
```

### Walkthrough

- 1 `curl -k -X POST https://localhost:7160/api/apikeys -H "Authorization: Bearer <JWT>" -H "Content-Type: application/json" -d '{"name":"qa","scopes":["read"]}'`
- 2 **Expected: 201** with a key field like `pk_...` — **copy it now** (never shown again). `GET /api/apikeys` lists it with `prefix/scopes` but **no** key.
- 3 **Non-owner:** repeat as a member/admin -> **403**.

## QA-API-03 — Call the public API with the key; scopes + tenant-scoping • Core (curl / Postman)

### Gherkin

```
Given a read-only API key for my tenant
When I call the public API with it
Then whoami returns my tenant, and a write-scoped route is refused (403 insufficient_scope)
```

### Walkthrough

- 1 `curl -k https://localhost:7160/api/public/whoami -H "X-API-Key: pk_..." -> 200`, body shows my `tenant_id`, the key name, and `["read"]`.
- 2 `curl -k -X POST https://localhost:7160/api/public/echo -H "X-API-Key: pk_..." -d '{"message":"hi"}'` with the **read-only** key -> **\*\*403 insufficient\_scope\*\***. (A key created with "write" succeeds.)
- 3 **No/blank/garbage key -> 401. Revoked key** (`DELETE /api/apikeys/{id}`) -> **401** afterwards.
- 4 **Postman:** import `/api/public/openapi.json`, set an X-API-Key header on the collection, run `whoami`.

## QA-API-04 — Per-key rate limit • Core (curl)

### Walkthrough

- 1 Fire `whoami` with one key ~65 times in a minute (`for i in $(seq 1 65); do curl -k -s -o /dev/null -w "%{http_code}\n" https://localhost:7160/api/public/whoami -H "X-API-Key: pk_..."; done`).
- 2 **Expected:** the first 60 are **200**, then **429**. A **second** key still returns **200** (budgets are per key, not shared).

## QA-API-05 — Register a webhook + send test + verify signature • Core (curl)

**Precondition:** a receiver URL that echoes requests — e.g. create one at <https://webhook.site> and copy it. **Gherkin**

```
Given HOOKS is enabled and I own the tenant
When I register my receiver and send a test event
Then my endpoint receives a signed POST I can verify with the secret
```

### Walkthrough

- 1 POST /api/webhooks (JWT) with {"url":"<webhook.site URL>","event\_types":["ping"]} -> **201** with a secret (whsec\_...) **shown once** — copy it.
- 2 POST /api/webhooks/{id}/test (JWT) -> **200** { "delivered": true, "status\_code": 200 }.
- 3 On webhook.site, confirm the request has headers **\*\*X-Webhook-Id, X-Webhook-Event: ping, and X-Webhook-Signature: sha256=...** **Verify: HMAC-SHA256 of the raw body\*\*** with your whsec\_... secret equals the signature (any HMAC tool, or the app's WebhookSignature.Compute).
- 4 **Non-owner** management -> **403. Bad URL / no event types** on create -> **400**.

## QA-API-06 — Delivery log + replay • Core (curl)

### Gherkin

```
Given I've sent test deliveries to my subscription
When I view its delivery log and replay one
Then I see per-attempt rows, and replay re-POSTs the same event to my endpoint
```

**Precondition:** send one or more **test** events first (QA-API-05 step 2) — the sync send-test records a delivery row per attempt (success and failure), so the log is populated in-template even though the sample app fires no published events. (Published events via IWebhookPublisher also log, through the outbox.) **Walkthrough**

- 1 GET /api/webhooks/{id}/deliveries (JWT) -> a list of attempts, newest first, each with success, status\_code, error, event\_id. Each send-test from QA-API-05 shows up here.
- 2 POST /api/webhooks/deliveries/{deliveryId}/replay (JWT) -> **202**; webhook.site receives the **same** event again (same X-Webhook-Id, so a real receiver can dedup). Replay goes through the outbox, so its own attempt is logged too.
- 3 **Failure path:** point the subscription at a URL that returns 500, send a test -> the response is { "delivered": false, "status\_code": 500 } and the log gains a success:false row. (The sync send-test does **not** retry; the outbox retry/backoff + dead-lettering applies to \*published\*/replayed deliveries — watch the API logs on a replay.) Replay of an unknown/other-tenant delivery id -> **404**.

## 15. Traceability matrix (feature -> cases -> API)

| Feature area                              | Test cases                                                                                                                                               | Key API endpoints                                                                                          |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| OAuth sign-in (Google/MS)                 | SMK-02, AUTH-02, DSK-02, AND-02                                                                                                                          | GET /api/auth/login/{provider}, GET /api/auth/callback/{provider}, native login/callback/exchange          |
| Magic link (web)                          | AUTH-01, 05, 06, MAIL-02                                                                                                                                 | POST /api/auth/magic-link/send, GET /api/auth/magic-link/verify                                            |
| Email OTP                                 | SMK-01/05/06, AUTH-03/04, DSK-01, AND-01, MAIL-01                                                                                                        | POST /api/auth/otp/send, POST /api/auth/otp/verify                                                         |
| Rate limiting / abuse guard               | AUTH-11                                                                                                                                                  | POST /api/auth/otp/send, .../magic-link/send, .../otp/verify (429)                                         |
| Session / refresh / sign-out              | SMK-03/04, DSK-03/06, AND-03, SEC-03, SEC-05 (legacy-cookie self-heal)                                                                                   | POST /api/auth/refresh, POST /api/auth/logout, GET /api/auth/me                                            |
| Enumeration / error handling              | AUTH-04/07/08/09                                                                                                                                         | (send + verify endpoints; /login query states)                                                             |
| Onboarding (auto tenant)                  | ONB-01/02, SMK-01                                                                                                                                        | (provisioned on first auth)                                                                                |
| Household view/rename                     | HH-01/02                                                                                                                                                 | GET /api/household, PUT /api/household                                                                     |
| Members (remove/leave /transfer/dissolve) | HH-03..08                                                                                                                                                | DELETE /api/household/members/{id}, POST /api/household/leave, POST /api/household/transfer-ownership      |
| Invitations                               | INV-01/06/07/08, MAIL-03                                                                                                                                 | POST /api/household/invitations, GET /api/household/invitations, POST .../{id}/regenerate, DELETE .../{id} |
| Join / accept                             | INV-02/03/04/05, <b>INV-10</b> (seat re-check after downgrade — BILLING-9, E2E), <b>DSK-08 / AND-08</b> (paste invite code — NATIVE-4b; web variant E2E) | POST /api/household/invitations/accept (402 seat_limit_reached when the tenant is over its downgraded cap) |

| Feature area                                              | Test cases                                                                                                          | Key API endpoints                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Linked accounts                                           | SET-01..06, DSK-05                                                                                                  | GET /api/auth/logins, POST /api/auth/link/{provider}, DELETE /api/auth/logins/{provider}                                                                                                                                                                                                                                                                          |
| Localization                                              | I18N-01..04, <b>DSK-09 / AND-09</b> (native restart persistence — NATIVE-5)                                         | PUT /api/auth/locale (+ resx)                                                                                                                                                                                                                                                                                                                                     |
| Theme / dark mode (THEME-1 + PREFS-1)                     | <b>SET-08</b> ( E2E ThemeJourneyTests) + <b>DSK-15 / AND-14</b> (native restart persistence)                        | PUT /api/auth/theme ("system" stored verbatim, null = never chose — ADR-022; theme JWT claim; pre-paint theme.js -> data-bs-theme; sign-in reconcile + device adoption)                                                                                                                                                                                           |
| Budget settings (app BUDGET-1)                            | BUD-01..03                                                                                                          | GET /api/budget-settings, PUT /api/budget-settings (400 invalid_request; household-wide, member-editable)                                                                                                                                                                                                                                                         |
| Catalog: categories + banks (app CATALOG-1/2)             | CAT-01..04                                                                                                          | GET/POST /api/categories, PUT /api/categories/{id}, same under /api/banks (409 *_exists / *_exists_inactive + existing_id + existing_name; uniform 404)                                                                                                                                                                                                           |
| Exchange rate (app FX-1)                                  | FX-01..02 + Api.Tests (ExchangeRateApiClientTests, ExchangeRateResolverTests)                                       | GET /api/exchange-rate (200 {rate, source: live\ cache\ transaction, as_of}; 503 exchange_rate_unavailable; 401 anonymous)                                                                                                                                                                                                                                        |
| Envelopes (app ENV-1)                                     | ENV-01..02                                                                                                          | GET/POST /api/envelopes, PUT /api/envelopes/{id} (400 invalid_request; 409 envelope_exists / envelope_exists_inactive + existing_id + existing_name; uniform 404)                                                                                                                                                                                                 |
| Months & transactions (app LEDGER-1/2)                    | LED-01..04 + Api.Tests (LedgerSliceTests)                                                                           | GET /api/months, GET /api/months/resolve?date=, GET /api/months/{id}, PUT /api/months/{id}/income, GET /api/months/{id}/transactions; POST /api/transactions, GET/PUT/DELETE /api/transactions/{id} (400 invalid_request / exchange_rate_unavailable / derived_transaction; uniform 404)                                                                          |
| Expected refunds & realization (app LEDGER-3)             | LED-05..06 + Api.Tests (RefundSliceTests, incl. the two-context concurrency proof)                                  | refund_expected / refund_percentage on POST/PUT /api/transactions; GET /api/months/{id}/refunds; PUT /api/refunds/{id} (200; 400 invalid_request; 404; 409 refund_status_conflict)                                                                                                                                                                                |
| Budget lines: fixed + variable (app EXPENSES-1)           | EXP-01..03                                                                                                          | GET/POST /api/expenses/{fixed\ variable}, PUT .../{id}, PUT .../order (400 invalid_request; 409 expense_exists / expense_exists_inactive + existing_id + existing_name; uniform 404)                                                                                                                                                                              |
| Dashboard (app DASH-1)                                    | DASH-01..02 + Core.Tests (DashboardSummaryServiceTests, 45 donor cases) + Api.Tests (DashboardSliceTests)           | GET /api/months/{id}/summary (200 {month, exchange_rate, rate_source, rate_as_of, rate_unavailable, summary}; 401 anonymous; uniform 404)                                                                                                                                                                                                                         |
| Reports: category analysis + CSV export (app REPORTS-1/2) | REP-01..02 + Core.Tests (CategoryAnalysisCalculatorTests, TransactionCsvWriterTests) + Api.Tests (ReportSliceTests) | GET /api/reports/category-analysis, POST /api/reports/transactions/export (month_id \ from+to; 400 period_required / period_ambiguous / period_incomplete / period_invalid; uniform 404; export -> signed download_url served by GET /api/files/{token})                                                                                                          |
| Email inboxes: connect + readers (app EMAIL-2/3)          | EMAIL-01..03 + Api.Tests (MailConsentServiceTests, EmailReaderTests, EmailConnectionSliceTests)                     | GET /api/email/connections (+ /{id}, /{id}/folders 409 needs_reconsent), GET .../authorize?provider= (400 invalid_provider / provider_not_configured), anonymous GET .../callback (-> /email?connected={email_error=), GET .../suggested-filters, POST ... (400 use_consent_flow), PUT /{id} (400 filters_required / invalid_interval), DELETE /{id}; uniform 404 |
| Email ingestion: staging + dedup (app EMAIL-4)            | EMAIL-04 + Core.Tests (VoucherFingerprintTests) + Api.Tests (VoucherStagingSliceTests incl. the poll job)           | POST /api/email/connections/{id}/sync (200 {staged, duplicates, unrecognized}; 409 needs_reconsent; uniform 404); the email-poll scheduled job                                                                                                                                                                                                                    |

| Feature area                                             | Test cases                                                                                                                                                                                                | Key API endpoints                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Email ingestion: merchant suggestions (app EMAIL-5)      | EMAIL-05 + Core.Tests (MerchantMatcherTests) + Api.Tests (MerchantMappingSliceTests incl. the race, VoucherStagingSliceTests suggestion case, ReviewEndpointTests) + Ui.Tests (MerchantMappingsPageTests) | GET/POST /api/merchant-mappings, PUT/DELETE .../{id} (400 invalid_request; 409 mapping_exists; uniform 404)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Email ingestion: review queue + confirm (app EMAIL-6)    | EMAIL-06 + Api.Tests (PendingVoucherSliceTests incl. the two-context concurrency proof, ReviewEndpointTests) + Ui.Tests (ReviewPageTests, ReviewBadgeTests)                                               | GET /api/pending-vouchers (+ /count), POST .../{id}/confirm (200 {transaction_id, month_id, amount_crc, amount_usd, remembered}; 400 invalid_request / exchange_rate_unavailable; 409 not_pending), POST .../{id}/discard (204; 409 not_pending); uniform 404                                                                                                                                                                                                                                                                                                                                                     |
| Emails / branding                                        | MAIL-01..04, I18N-04                                                                                                                                                                                      | (SMTP via Mailpit)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Tenant isolation / auth guards                           | SEC-01..05                                                                                                                                                                                                | (all [Authorize] endpoints; write-stamping + reuse detection are automated)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Platform health / readiness                              | SMK-07                                                                                                                                                                                                    | GET /health, GET /health/ready                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Transactional email delivery                             | (all email cases)                                                                                                                                                                                         | async via the outbox dispatcher (OutboxMessages)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Billing — checkout/portal/webhook + billing page         | <b>BILL-01/02</b> (\$10c, E2E BillingJourneyTests) + <b>DSK-11 / AND-11</b> (native refresh-on-return — NATIVE-4) + Api.Tests (Billing*/Entitlement* tests)                                               | POST /api/billing/checkout, .../portal, .../webhook                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Billing — quotas (BILLING-5)                             | <b>HH-14</b> (seat limit blocks invite -> 402 upgrade message) + Api.Tests (QuotaServiceTests)                                                                                                            | seats (members + pending invites vs Plan.SeatLimit) enforced on POST /api/household/invitations -> 402 seat_limit_reached; metered usage via IQuotaService.TryConsumeAsync (monthly UsageCounter). Limits in PlanCatalog (null = unlimited).                                                                                                                                                                                                                                                                                                                                                                      |
| Billing — trial/dunning (BILLING-6)                      | covered by Api.Tests (BillingWebhookHandlerTests, SubscriptionLapseSweepJobTests); manual via Stripe test triggers                                                                                        | webhook transition into past_due/canceled -> owner <b>notification</b> (in-app bell + outbox email, NOTIFY) once; SubscriptionLapseSweepJob (6h) nudges the owner once when a paid period lapses without a webhook (LapseNotifiedAt). Verify with stripe trigger invoice.payment_failed (test mode) -> owner sees a billing notification in the bell.                                                                                                                                                                                                                                                             |
| Billing — dissolve cleanup (BILLING-7)                   | covered by Api.Tests (BillingDissolveTests)                                                                                                                                                               | on tenant dissolve, BillingDataContributor wipes the Subscription projection <b>and</b> enqueues a "billing.cancel" outbox message -> IBillingProvider.CancelSubscriptionAsync (a deleted tenant stops being billed). HasDataAsync=false (billing never blocks leaving); export gains a billing section (plan/status/period, no Stripe ids). Manual (Stripe test mode): subscribe a throwaway tenant, delete the account, confirm the Stripe subscription is canceled.                                                                                                                                            |
| Public API + API keys (PUBAPI, <b>config-gated off</b> ) | <b>QA-API-01..04</b> (curl/Postman) + Api.Tests (ApiKeyServiceTests, RateLimitingTests); boot-verified on/off                                                                                             | PublicApi:Enabled toggles it. Owner-only /api/apikeys (create -> raw pk_... once, list, revoke; Permission.ManageApiKeys); API-key auth scheme mints a tenant_id-scoped principal; demo /api/public/whoami (read scope) + /api/public/echo (write scope) via .RequireApiScope. <b>PUBAPI-2</b> : per-key rate limit (60/min, isolated per key -> 429) + a leak-free public OpenAPI doc at /api/public/openapi.json (only the public routes). <b>Off (default) =&gt; routes 404</b> . Manual: PublicApi__Enabled=true, mint a key, curl -H "X-API-Key: pk_..." /api/public/whoami; fetch /api/public/openapi.json. |
| Feature area                                             | Test cases                                                                                                                                                                                                | Key API endpoints                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Outbound webhooks (HOOKS, <b>config-gated off</b> )      | <b>QA-API-01, 05, 06</b> (curl/webhook.site) + Api.Tests (WebhookSubscriptionServiceTests, WebhookDeliveryTests, WebhookDeliveryLogTests) + Core.Tests (WebhookSignatureTests); boot-verified on/off      | Webhooks:Enabled toggles it. Owner-only /api/webhooks (register -> signing secret whsec_... once, list, delete, <b>send test</b> ; Permission.ManageWebhooks). IWebhookPublisher.PublishAsync fans out to matching active subs -> one "webhook" <b>outbox</b> message each -> signed POST (X-Webhook-Signature), retry/dead-letter via the outbox. <b>HOOKS-2</b> : a delivery log (GET                                                                                                                                                                                                                           |

| Feature area            | Test cases                                                                                                                                                                                                                            | Key API endpoints                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                         |                                                                                                                                                                                                                                       | /api/webhooks/{id}/deliveries — one row per attempt, success/status/error) + <b>replay</b> (POST /api/webhooks/deliveries/{id}/replay — re-enqueue the exact payload). <b>Off (default) =&gt; routes 404.</b> Manual: Webhooks__Enabled=true, register a receiver (e.g. a webhook.site URL), hit <b>send test</b> , view deliveries, replay one.                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Audit log (API-only)    | covered by Api.Tests (AuditLogTests)                                                                                                                                                                                                  | append-only IAuditLog + interceptor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| RBAC roles (admin tier) | HH-09/10/11/12 (web roster promote/demote + admin capability/limits); Api.Tests (RolePermissionsTests, PermissionServiceTests, MemberRoleManagementTests)                                                                             | PUT /api/household/members/{id}/role (owner-only; admin<->member, owner via transfer only); permission seam gates tenant writes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| File storage (API-only) | covered by Api.Tests (LocalDiskFileStorageTests, FileDownloadTokenizerTests, FilesControllerTests, S3FileStorageMinioTests [real MinIO], FileStorageRegistrationTests)                                                                | IFileStorage (tenant-scoped keys; local disk / S3-compatible — AWS/MinIO/R2/B2, config-gated); local signed GET /api/files/{token} (expiring, single-key, tenant-checked -> 404 on any failure); S3 native presigned URLs                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| GDPR data export        | <b>HH-13</b> (owner Household -> Data -> download, E2E GdprExportJourneyTests) + <b>DSK-10 / AND-10</b> (native share — NATIVE-3) + Api.Tests (TenantExportTests)                                                                     | POST /api/household/export (owner-only ExportData -> 403 else; JSON bundle via IFileStorage, signed URL; secret-free, tenant-scoped, audited)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| GDPR account erasure    | <b>SET-07</b> (Settings -> Danger zone) + Api.Tests (AccountErasureTests)                                                                                                                                                             | DELETE /api/auth/me (wipes identity/PII in one tx; owner-with-members -> 400, solo owner -> 409 without confirm_dissolve; member removed not re-homed; audited; audit trail survives)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| MFA / TOTP              | <b>MFA-01..05, DSK-12 / AND-12</b> (native) (Settings enroll/QR/confirm/recovery + disable; step-up on OTP, OAuth/magic-link, <b>and</b> native logins) + Api.Tests (MfaServiceTests, MfaChallengeServiceTests, MfaLoginServiceTests) | GET POST /api/auth/mfa[/enroll /confirm /disable] (enroll/manage; secret encrypted, hashed single-use recovery codes) + <b>login step-up</b> POST /api/auth/mfa/verify (MFA-on logins get a signed challenge instead of a session; verify a TOTP/recovery code to complete). <b>Every sign-in path enforces it</b> (web + native): OTP returns the challenge as JSON; OAuth callback + magic-link redirect to /login?mfa=<challenge>; native OTP/OAuth-exchange return the challenge in the body and the MAUI client steps up in-app.                                                                                                                                                                                                                                                                  |
| In-app notifications    | <b>NOTIF-01..04, DSK-13</b> (header bell: list/unread-count/mark-read/delete/clear; Settings delivery-preference switches) + Api.Tests (NotificationServiceTests, NotificationFanOutTests)                                            | GET /api/notifications (+ ?before=&limit=), /unread-count, POST /{id}/read, /read-all, DELETE /{id}, DELETE /api/notifications?read=true false (scope REQUIRED — read-only vs all; omitted -> 400), and GET PUT /api/notifications/preferences — <b>per-user</b> (scoped to the caller). NotifyAsync fans out to in-app + email (outbox-backed) per prefs (default both on).                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Admin back-office       | <b>ADMIN-01..06, DSK-14</b> (native spot) (staff /admin console: tenant list/detail + impersonate w/ banner + stop; targeted/broadcast announce; plan comp/revert) + Api.Tests (PlatformStaffServiceTests, AdminControllerTests)      | GET /api/admin/me (staff probe, 200 {is_staff} for any caller — drives the nav/gate), GET /api/admin/tenants (+ /{id} — returns plan_key + provider_managed), POST /api/admin/impersonate/{userId}, POST /api/admin/tenants/{id}/announce (optional user_ids[] subset, intersected with membership), POST /api/admin/announce-all (202; outbox fan-out to <b>every</b> user), PUT DELETE /api/admin/tenants/{id}/subscription (comp/revert; 409 only for a LIVE provider sub — canceled Stripe-backed subs are comp-able) — <b>platform-staff only</b> (config Admin:StaffEmails; non-staff -> 403). Detail enters the target tenant (filter never loosened); impersonation returns a <b>short-lived, non-refreshable</b> token with an impersonated_by claim, <b>audited in the target's tenant</b> . |

**\*\*Adversarial & tenant-isolation (§14a, QA-ADV-\*) — v3-audit hardening probes. Rows tagged (!) v3 were authored against then-broken behaviour and sat Blocked until their finding landed; every tagged finding is fixed (v3 remediation, PRs #147–#191), so ALL rows now expect Pass\*\*.**

| Probe (finding)                                                                | Test case(s)                         | Key API endpoint(s) / surface                                                                                                                                            |
|--------------------------------------------------------------------------------|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cross-tenant read/export/erase (RLS-2/4)                                       | ADV-01                               | GET /api/household, POST /api/household/export, DELETE /api/household/members/{id}, POST\ DELETE /api/notifications/{id}/read] (foreign id -> 404/403)                   |
| Cross-tenant isolation, newer tables (LB-TEN-2/RLS-8)                          | ADV-02                               | GET /api/webhooks/{id}/deliveries, POST /api/webhooks/deliveries/{id}/replay, DELETE /api/apikeys/{id} (foreign id -> 404)                                               |
| Export completeness, secret-free ((!) v3 LB-TEN-1)                             | ADV-03                               | POST /api/household/export (must cover api-keys/webhooks/usage, no hashes/whsec....)                                                                                     |
| Dissolve/erasure cleanup ((!) v3 LB-TEN-1)                                     | ADV-04                               | dissolve/DELETE /api/auth/me -> 0 rows in ApiKey/WebhookSubscription/WebhookDelivery/UsageCounter                                                                        |
| Impersonation write attribution ((!) v3 LB-ADM-1)                              | ADV-05                               | POST /api/admin/impersonate/{id} then PUT /api/household, POST /api/notifications/{id}/read (audit impersonated_by)                                                      |
| Impersonation ≠ staff ladder ((!) v3 ADM-2)                                    | ADV-06                               | impersonation token vs POST /api/admin/impersonate/{x}, PUT /api/admin/tenants/{id}/subscription, DELETE /api/admin/users/{x}/mfa, POST /api/admin/announce-all (-> 403) |
| Impersonation role ceiling (TB-ADM-3)                                          | ADV-07                               | member impersonation vs POST /api/household/transfer-ownership, PUT /api/household/members/{id}/role (-> 403)                                                            |
| Pref bleed: impersonation + shared device ((!) v3 partial, ADM-8/9, LB-UI-4/5) | ADV-08                               | GET /api/auth/me prefs; localStorage theme/locale bootstrap across accounts                                                                                              |
| Security notice bypasses prefs ((!) v3 ADM-1)                                  | ADV-09                               | PUT /api/notifications/preferences (both off) + DELETE /api/admin/users/{id}/mfa -> security.mfa_reset in-app + email                                                    |
| Per-user MFA lockout ((!) v3 ADM-3)                                            | ADV-10                               | POST /api/auth/mfa/verify (cumulative cap, not just per-IP 429)                                                                                                          |
| Recovery code single-use (TB-AUTH-6)                                           | ADV-11                               | POST /api/auth/mfa/verify (recovery code burned on first use)                                                                                                            |
| Webhook replay/order/same-second idempotency (LB-BILL-1)                       | ADV-12                               | POST /api/billing/webhook (dup EventId no-op; same-second created->active applies)                                                                                       |
| No false dunning on first bad webhook ((!) v3 LB-BILL-4)                       | ADV-13                               | POST /api/billing/webhook first-ever past_due/canceled -> no owner notification                                                                                          |
| Comp/revert a churned sub ((!) v3 ADM-5)                                       | ADV-14                               | PUT\ DELETE /api/admin/tenants/{id}/subscription (canceled sub should be comp-able, not stuck 409)                                                                       |
| Concurrent last-seat accept (TB-BILL-19/BILLING-9)                             | ADV-15                               | POST /api/household/invitations/accept (one 200, one 402 seat_limit_reached)                                                                                             |
| Magic-link/OTP double-redemption (LB-AUTH-3)                                   | ADV-16                               | GET /api/auth/magic-link/verify, POST /api/auth/otp/verify (exactly one session)                                                                                         |
| Rotated refresh-token replay revokes family (SEC-05 promoted)                  | ADV-17                               | POST /api/auth/refresh (reuse -> 401 + all sessions revoked)                                                                                                             |
| Locale-reload preserves deep-link ((!) v3 UX-1/LB-UI-1/2)                      | ADV-18 (E2E LocaleMismatchJoinTests) | /join?token=... under a PREFS-1 locale-mismatch reload                                                                                                                   |
| No pref revert after soft sign-in (UX-3/4)                                     | ADV-19                               | OTP soft-nav sign-in reconcile (theme/locale claims)                                                                                                                     |
| "Clear read" spares unread (LB-UI-10)                                          | ADV-20                               | DELETE /api/notifications?read=true vs ?read=false; omitted scope -> 400 scope_required                                                                                  |
| Security/cache headers on single-origin ((!) v3 DEP-2/3)                       | ADV-21                               | curl -I /+/_framework/* (HSTS/nosniff/CSP/Referrer-Policy; cache-control)                                                                                                |
| Forged XFF ≠ rate-limit bypass (DEP-1/ADM-10)                                  | ADV-22                               | POST /api/auth/otp/send w/ rotating X-Forwarded-For (trusted-proxy only)                                                                                                 |
| Release native build HTTPS base URL ((!) v3 NAT-3)                             | ADV-23                               | Release AAB/MSIX base URL + Android network-security-config (no cleartext localhost)                                                                                     |
| Loopback OAuth state binding (NAT-10)                                          | ADV-24                               | desktop loopback callback rejects mismatched state                                                                                                                       |

**Per-client coverage:** Web = full (all suites). Desktop = DSK-01..15 (auth + per-feature parity). Android = AND-01..15 (auth + per-feature parity incl. hardware back, share sheet, OAuth kill drill). iOS = IOS-01..04 and macOS = MAC-01..03 (first-run smoke — first passed 2026-07-06; needs a Mac). Magic link is **web-only** by design; the \$13c

checklist is the per-release native subset.

**Automated (E2E CI):** the following manual cases have an equivalent Playwright/PHPUnit journey in `tests/E2E.Tests`, run on every push by the `e2e` job (`.github/workflows/ci.yml`) against a booted Postgres + Mailpit + API + Web stack — so they are continuously regression-guarded on **Web**:

| Manual case                                                                 | E2E test                                                                                                                                                                                                                                                                                   |
|-----------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| QA-SMK-01 (OTP sign-in happy path)                                          | <code>AuthFlowTests.Otp_SignIn_LandsInTheApp (+ Login_Page_Renders)</code>                                                                                                                                                                                                                 |
| QA-SMK-03 (sign out)                                                        | <code>AuthFlowTests.SignOut_ReturnsToLogin</code>                                                                                                                                                                                                                                          |
| QA-AUTH-09 (email-format validation)                                        | <code>AuthFlowTests.Invalid_Email_IsRejected_NoCodeStep</code>                                                                                                                                                                                                                             |
| QA-MFA-01 (enable TOTP)                                                     | <code>MfaJourneyTests.Enroll_ThenStepUp_OnNextSignIn (enroll leg)</code>                                                                                                                                                                                                                   |
| QA-MFA-02 (step-up enforced at sign-in)                                     | <code>MfaJourneyTests.Enroll_ThenStepUp_OnNextSignIn + StepUp_WithWrongCode_DoesNotSignIn</code>                                                                                                                                                                                           |
| QA-I18N-01 (switch language on login)                                       | <code>I18nTests.Switching_Language_ReRendersTheUi</code>                                                                                                                                                                                                                                   |
| QA-I18N-02 (language follows the user across browsers)                      | <code>I18nTests.LocaleChoice_FollowsTheUser_AcrossBrowsers</code>                                                                                                                                                                                                                          |
| QA-SET-08 (dark mode applies/persists/follows, incl. Auto propagation)      | <code>ThemeJourneyTests.ThemeChoice_AppliesLive_PersistsLocally_AndFollowsTheUser</code>                                                                                                                                                                                                   |
| QA-INV-10 (accept refused after a downgrade — seat re-check)                | <code>SeatQuotaJourneyTests.Accepting_An_Invite_After_A_Downgrade_Shows_The_HouseholdFull_State</code>                                                                                                                                                                                     |
| QA-AUTH-01/05 (magic link happy + single-use)                               | <code>MagicLinkJourneyTests</code>                                                                                                                                                                                                                                                         |
| QA-HH-02/03/05/07/08 (rename, invite/join, leave, dissolve, delete account) | <code>MembershipLifecycleTests</code>                                                                                                                                                                                                                                                      |
| QA-HH-09..12 (roster: promote/demote/remove/owner-protection)               | <code>RosterJourneyTests</code>                                                                                                                                                                                                                                                            |
| QA-HH-13 (data export download)                                             | <code>GdprExportJourneyTests</code>                                                                                                                                                                                                                                                        |
| QA-INV-01/02/08 (invite create/accept/regenerate)                           | <code>MembershipLifecycleTests (+ invalid-code inline error)</code>                                                                                                                                                                                                                        |
| QA-NOTIF-01..03 (bell list/unread/mark-read via announcements)              | <code>NotificationJourneyTests + AnnouncementJourneyTests</code>                                                                                                                                                                                                                           |
| QA-ADMIN-01/04 (staff console gate, announce)                               | <code>AnnouncementJourneyTests</code>                                                                                                                                                                                                                                                      |
| QA-BILL-01/02 (billing page + fake-provider upgrade loop)                   | <code>BillingJourneyTests</code>                                                                                                                                                                                                                                                           |
| QA-ADV-18 (locale-mismatch × invite acceptance)                             | <code>LocaleMismatchJoinTests</code>                                                                                                                                                                                                                                                       |
| QA-DSK-01 (desktop boot)                                                    | the <code>native-smoke-windows</code> job boots the REAL Windows exe as a process-alive + provider-probe canary (WebView2 150 strips CDP under elevation — PRs #170/#171); the OTP journey is CI-driven on Android only. <code>NativeSmokeTests</code> remains for local non-elevated runs |
| QA-AND-01 (Android OTP sign-in)                                             | <code>tests/native-smoke-android/smoke.js</code> — the <code>native-smoke-android</code> job boots a real emulator and drives the app via playwright-core's <code>_android</code> module                                                                                                   |

The two native smoke jobs run on develop pushes that touch native-relevant paths (see the `native-paths` gate in `ci.yml`) — they are boot-and-sign-in canaries, not the per-feature native regression, which stays manual (§12–13b). All other cases remain manual-only or API-test-backed as noted per row.

## 16. Sign-off sheet

Record one row per executed case. Build = API/web commit SHA (`git rev-parse --short HEAD`).

| Case ID   | Client | Result (P/F/Blocked/N-A) | Tester | Build (SHA) | Date | Notes / defect link |
|-----------|--------|--------------------------|--------|-------------|------|---------------------|
| QA-SMK-01 | Web    |                          |        |             |      |                     |
| QA-SMK-02 | Web    |                          |        |             |      |                     |
| QA-BUD-01 | Web    |                          |        |             |      |                     |
| QA-BUD-02 | Web    |                          |        |             |      |                     |
| QA-BUD-03 | Web    |                          |        |             |      |                     |

| Case ID     | Client | Result (P/F/Blocked/N-A) | Tester | Build (SHA) | Date | Notes / defect link |
|-------------|--------|--------------------------|--------|-------------|------|---------------------|
| QA-CAT-01   | Web    |                          |        |             |      |                     |
| QA-CAT-02   | Web    |                          |        |             |      |                     |
| QA-CAT-03   | Web    |                          |        |             |      |                     |
| QA-CAT-04   | Web    |                          |        |             |      |                     |
| QA-FX-01    | Web    |                          |        |             |      |                     |
| QA-FX-02    | Web    |                          |        |             |      |                     |
| QA-ENV-01   | Web    |                          |        |             |      |                     |
| QA-ENV-02   | Web    |                          |        |             |      |                     |
| QA-LED-01   | Web    |                          |        |             |      |                     |
| QA-LED-02   | Web    |                          |        |             |      |                     |
| QA-LED-03   | Web    |                          |        |             |      |                     |
| QA-LED-04   | Web    |                          |        |             |      |                     |
| QA-LED-05   | Web    |                          |        |             |      |                     |
| QA-LED-06   | Web    |                          |        |             |      |                     |
| QA-EXP-01   | Web    |                          |        |             |      |                     |
| QA-EXP-02   | Web    |                          |        |             |      |                     |
| QA-EXP-03   | Web    |                          |        |             |      |                     |
| QA-DASH-01  | Web    |                          |        |             |      |                     |
| QA-DASH-02  | Web    |                          |        |             |      |                     |
| QA-REP-01   | Web    |                          |        |             |      |                     |
| QA-REP-02   | Web    |                          |        |             |      |                     |
| QA-EMAIL-01 | Web    |                          |        |             |      |                     |
| QA-EMAIL-02 | Web    |                          |        |             |      |                     |
| QA-EMAIL-03 | Web    |                          |        |             |      |                     |
| QA-EMAIL-04 | Web    |                          |        |             |      |                     |
| QA-EMAIL-05 | Web    |                          |        |             |      |                     |
| QA-EMAIL-06 | Web    |                          |        |             |      |                     |
| ...         |        |                          |        |             |      |                     |

**\*\*§14a adversarial / tenant-isolation (QA-ADV-\*). All rows are Not-run (blank) until executed. The formerly pre-seeded Blocked (known defect) rows were reset when the v3 remediation completed (2026-07, PRs #147–#191) — their Notes record which defect each was blocked on, and every one of those cases now expects Pass\*\* on re-run.**

| Case ID   | Client | Result (P/F/Blocked/N-A) | Tester | Build (SHA) | Date | Notes / defect link                                                                       |
|-----------|--------|--------------------------|--------|-------------|------|-------------------------------------------------------------------------------------------|
| QA-ADV-01 | API    |                          |        |             |      |                                                                                           |
| QA-ADV-02 | API    |                          |        |             |      |                                                                                           |
| QA-ADV-03 | API    |                          |        |             |      | Was pre-seeded Blocked (LB-TEN-1 (export incomplete)) — fixed in v3; re-run               |
| QA-ADV-04 | API    |                          |        |             |      | Was pre-seeded Blocked (LB-TEN-1 (orphaned rows on dissolve)) — fixed in v3; re-run       |
| QA-ADV-05 | API    |                          |        |             |      | Was pre-seeded Blocked (LB-ADM-1 (impersonation write attribution)) — fixed in v3; re-run |
| QA-ADV-06 | API    |                          |        |             |      | Was pre-seeded Blocked (ADM-2 (staff gate re-escalation)) — fixed in v3; re-run           |

| Case ID   | Client          | Result (P/F/Blocked/N-A) | Tester | Build (SHA) | Date | Notes / defect link                                                                                                |
|-----------|-----------------|--------------------------|--------|-------------|------|--------------------------------------------------------------------------------------------------------------------|
| QA-ADV-07 | API             |                          |        |             |      |                                                                                                                    |
| QA-ADV-08 | API/Web         |                          |        |             |      | Was pre-seeded Blocked (LB-UI-4/5 shared-device pref bleed) — fixed in v3 (ADM-9 sign-out clear); re-run both legs |
| QA-ADV-09 | API             |                          |        |             |      | Was pre-seeded Blocked (ADM-1 (security notice suppressible by prefs)) — fixed in v3; re-run                       |
| QA-ADV-10 | API             |                          |        |             |      | Was pre-seeded Blocked (ADM-3 (no per-user MFA lockout)) — fixed in v3; re-run                                     |
| QA-ADV-11 | Web             |                          |        |             |      |                                                                                                                    |
| QA-ADV-12 | API             |                          |        |             |      |                                                                                                                    |
| QA-ADV-13 | API             |                          |        |             |      | Was pre-seeded Blocked (LB-BILL-4 (false dunning on first bad webhook)) — fixed in v3; re-run                      |
| QA-ADV-14 | API             |                          |        |             |      | Was pre-seeded Blocked (ADM-5 (comp stuck 409 on churned sub)) — fixed in v3; re-run                               |
| QA-ADV-15 | Web             |                          |        |             |      |                                                                                                                    |
| QA-ADV-16 | Web             |                          |        |             |      |                                                                                                                    |
| QA-ADV-17 | API             |                          |        |             |      |                                                                                                                    |
| QA-ADV-18 | Web             |                          |        |             |      | Was pre-seeded Blocked (UX-1/LB-UI-1/2 (locale reload drops /join deep-link)) — fixed in v3; re-run                |
| QA-ADV-19 | Web             |                          |        |             |      |                                                                                                                    |
| QA-ADV-20 | Web             |                          |        |             |      |                                                                                                                    |
| QA-ADV-21 | API             |                          |        |             |      | Was pre-seeded Blocked (DEP-2/3 (no security/cache headers)) — fixed in v3; re-run                                 |
| QA-ADV-22 | API             |                          |        |             |      |                                                                                                                    |
| QA-ADV-23 | Desktop/Android |                          |        |             |      | Was pre-seeded Blocked (NAT-3 (Release build cleartext localhost base URL)) — fixed in v3; re-run                  |
| QA-ADV-24 | Desktop         |                          |        |             |      |                                                                                                                    |

**Release gate (suggested):** all • **Smoke** Smoke + all • **Core** Core cases Pass on Web; the §13c native checklist Pass on every platform being shipped (iOS/macCatalyst once those ship); no open Critical/High defects. • **Edge** Edge cases triaged (Pass or accepted-known-issue).

## 17. Notes for maintainers

- This plan is the manual counterpart to the automated tests/E2E.Tests (Playwright/PHPUnit) suite. That suite now covers the **OTP auth happy-path + guards** (AuthFlowTests), the **MFA enroll -> step-up** journey incl. the wrong-code negative (MfaJourneyTests), and the **language switch** (I18nTests) — all over the page objects in Pages/, reading codes from Mailpit via the Mailpit REST client, and **run in CI** by the e2e job (.github/workflows/ci.yml, Web only). See tests/E2E.Tests/README.md for the run procedure (it documents the same Mailpit SMTP override noted in §1.1). The cases these journeys mirror are marked **Automated in CI** and listed in §15. The Gherkin blocks here are written to be lifted directly into new E2E scenarios — keep the two in sync as automation grows.

- When you add an app-specific domain feature on top of this platform, add a matching suite here and a row in the traceability matrix (§15) so "entire functionality" stays honest.
- docs/FEATURES.md describes the same JWT-based flows at the design level; this plan is their step-by-step verification. Keep the two in sync when behavior changes.
- **Updated 2026-06-22** for the security/quality remediation: OTP lockout is now **cumulative per email** and resend-proof (QA-AUTH-04); passwordless send/verify are **rate-limited** (QA-AUTH-11); the Settings **Unlink** now requires a fail-closed confirmation (QA-SET-04); and server-side hardening (write-stamping, refresh-reuse detection, fail-closed takeover guard) is captured as automated coverage (QA-SEC-05).
- **Updated 2026-06-23:** QA-AUTH-02 now documents the **tenant-gated same-email auto-link** rule (Microsoft trusted only on the consumers tenant; work/school + unknown providers fail closed — audit MITI-3); and QA-SEC-05 adds the **legacy refresh-cookie self-heal** as automated coverage (CookieServiceTests).
- **Updated 2026-06-26** for the platform-foundation work (JOBS/BILLING/OBS, ADR-006/007/008):
- **Transactional email is now delivered asynchronously** via the outbox dispatcher — a few-second delay, and the send request always succeeds (reliability moved to the background). Affects every email-based case; see the §1.1 and §11 notes. The E2E AuthFlowTests (which reads OTP codes from Mailpit) now traverses this async path — confirm it waits/polls for the email rather than assuming instant delivery.
- Added **API health/readiness** endpoints + smoke case **QA-SMK-07** (/health, /health/ready).
- The **billing API** (checkout/portal/webhook), the **append-only audit log**, and **OpenTelemetry** telemetry are API/operational-level with **no client UI** — covered by tests/Api.Tests, E2E pending; manual cases will follow when UI exists (see §2 + §15).
- **Updated 2026-06-30** for RBAC (ADR-009): the tenant role model gains an **\*\*admin tier behind a permission seam (owner > admin > member)**. **RBAC-1 added the seam (no behavior change)**; **RBAC-2 added the owner-only role-change endpoint\*\*** (PUT /api/household/members/{id}/role, admin<->member; owner is conferred only via transfer) and hardened member-removal so the **owner can't be removed**. This was API-only at first; **RBAC-3 added the web UI** — the Household roster now has owner-only **Make admin / Make member** controls, and the page is admin-aware (admin can rename + invite/remove members, but sees no role/transfer/dissolve controls). New web cases **QA-HH-09..12**; §7 intro updated for the three-tier model. API coverage stays automated (tests/Api.Tests).
- **Updated 2026-06-30** for file storage (ADR-010): an IFileStorage seam (tenant-scoped keys, local-disk dev default / S3-compatible prod) with a signed, time-limited download endpoint GET /api/files/{token}. **API-only** (no UI consumer yet) — covered by tests/Api.Tests (LocalDiskFileStorageTests, FileDownloadTokenizerTests, FilesControllerTests); see §2 + §15. Manual cases will follow when a feature (avatars/attachments) wires it to UI. FILES-3 added the **S3-compatible** backend (AWS/MinIO/R2/B2, config-gated by Storage:S3:Bucket), tested against a real **MinIO** container (S3FileStorageMinioTests); prod config is documented in .env.example. **This completes Wave 1** (RBAC + File storage).
- **Updated 2026-07-01** for GDPR data export (ADR-011, Wave 2): owner-only POST /api/household/export assembles the tenant's data (core + each feature's contributor section) into a JSON bundle stored via file storage and returns a **signed download URL**; **secret-free** (no token hashes), tenant-scoped, audited. **API-only** (no UI button yet) — covered by Api.Tests (TenantExportTests); see §2 + §15.
- **Updated 2026-07-01** for GDPR account erasure (ADR-011): DELETE /api/auth/me ("delete my account") wipes the caller's identity/PII (User/UserLogin/RefreshToken/LoginToken) in one transaction, single-owner-safe (owner-with-members -> transfer first; solo owner -> confirm to dissolve; member removed, not re-homed), audited (the audit trail survives — actor ids, never PII). **API-only** — covered by Api.Tests (AccountErasureTests). **GDPR epic complete (export + erasure)**.
- **Updated 2026-07-01** for MFA enrollment (ADR-012, Wave 2): authenticator-app **TOTP** (Otp.NET) — /api/auth/mfa/\* (enroll -> provisioning URI/QR; confirm with a code -> enable + one-time recovery codes; disable; status). Secret **encrypted at rest** (Data Protection); recovery codes **hashed + single-use**; MFA rows wiped by account erasure. **API-only** (MFA-1) — covered by Api.Tests (MfaServiceTests). **MFA-2 (login step-up)**: an MFA-on login returns a **signed challenge** instead of a session; POST /api/auth/mfa/verify completes it with a TOTP/recovery code. Wired into **OTP-verify + native-exchange**; the OAuth/magic-link **redirect** paths route to a client /mfa page (needs the MFA UI) and are a flagged **follow-up** — no platform-web user can enable MFA via those paths today (no enrollment UI). Covered by MfaChallengeServiceTests + MfaLoginServiceTests. **This completes Wave 2** (GDPR + MFA).
- **Updated 2026-07-01** for in-app notifications (ADR-013, Wave 3): a **per-user** notification center — GET /api/notifications (paginated), /unread-count, POST {id}/read, /read-all — scoped to the caller (never cross-user); features produce via NotifyAsync (staged in-app row). Notifications are user PII (wiped by

account erasure). **API-only** — covered by `Api.Tests (NotificationServiceTests)`. **NOTIFY-2**: per-user **delivery preferences** (`GET|PUT /api/notifications/preferences`, default both on) + `NotifyAsync` **fan-out** — in-app row + email via the outbox-backed `IEmailSender`, gated by prefs. Covered by `NotificationFanOutTests`. Bell-menu UI is an API-first follow-up. **NOTIFY epic + Wave 3's first item complete.**

- **Updated 2026-07-01** for the platform-staff admin surface (ADR-014, Wave 3): `GET /api/admin/tenants (+/{id})` — **staff-only** (config allowlist `Admin:StaffEmails`, out-of-band; non-staff -> 403). Read-only cross-tenant inspection; the per-tenant detail **enters the target tenant** (the global filter is never loosened) and is **audited in that tenant**. **API-only** — covered by `Api.Tests (PlatformStaffServiceTests, AdminControllerTests)`.
- **Updated 2026-07-01** for admin **impersonation** (ADR-014, ADMIN-2): `POST /api/admin/impersonate/{userId}` (staff-only) returns a **short-lived (15-min), non-refreshable** access token carrying the target's identity + an `impersonated_by` claim; **loudly audited in the target's tenant**. Unknown target -> 404. Covered by `AdminControllerTests`. **This completes the ADMIN epic — and the planned platform** (nine epics, ADRs 006–014).
- **Updated 2026-07-01** — UI pass (putting a face on the API-first surfaces). **UI-1 (GDPR)**: the owner **Data -> Download household data** button on Household (**QA-HH-13**) and **Settings -> Danger zone -> Delete my account (QA-SET-07)** — wired to `POST /api/household/export` and `DELETE /api/auth/me` (single-owner-safe, with the dissolve second-confirm). EN/ES localized.
- **Updated 2026-07-01** — **UI-2 (MFA)**: a **Two-factor authentication** card in Settings (`MfaCard` component) — enroll (`POST /api/auth/mfa/enroll`) renders a **client-side QR** of the `otpauth://` URI (vendored `qrcode-generator`, MIT, in `Shared.Ui/wwwroot/js/`; the secret never leaves the browser) alongside a manual key, confirm (`/confirm`) reveals one-time **recovery codes**, and **disable** (`/disable`) needs a live code. The **Login** page now handles the `OTP-verify mfa_required` response with a **step-up code prompt** -> `POST /api/auth/mfa/verify` (TOTP or recovery code) -> `/auth-callback`. **QA-MFA-01..03**; EN/ES localized. Native OTP + OAuth/magic-link step-up remain follow-ups (web-first).
- **Updated 2026-07-01** — **UI-3 (Notifications)**: a **header bell** (`NotificationBell` component) — unread-count badge (polled ~60s), a dropdown list (newest-first, unread dot + relative time), click-to-mark-read and **Mark all read** via `GET /api/notifications[/unread-count]`, `POST /{id}/read, /read-all`. A **Notifications** card in Settings (`NotificationPrefsCard`) with **In-app/Email** switches (optimistic save, reverts on error) via `GET|PUT /api/notifications/preferences`. **QA-NOTIF-01..03**; EN/ES localized. (No built-in producer — items appear once a feature calls `NotifyAsync`.)
- **Updated 2026-07-01** — **UI-4 (Admin console)**: a staff-only `/admin` page (`AdminConsole`) — tenant list + detail (members/subscription/audit count) and **Sign in as** (impersonation). Staff detection uses a new **non-gating** probe `GET /api/admin/me ({is_staff})` for any authenticated caller — the only API addition in the UI pass; the allowlist stays config-only, actions still 403 for non-staff, so the header shows an **Admin** link only to staff. Impersonation swaps the in-memory session to the short-lived token (`AuthService.BeginImpersonation`), pins an **impersonation banner** in `MainLayout` (reads the `impersonated_by` claim), and **Stop impersonating** restores the staff identity from the refresh cookie; a reload also reverts (the token is non-refreshable). **QA-ADMIN-01..03**; EN/ES localized. **This completes the UI pass (UI-1..4).**
- **Updated 2026-07-01** — **MFA-3 (redirect step-up, security fix)**: OAuth callback and magic-link verify now route through `IMfaLoginService.CompleteOrChallengeAsync` (like the OTP path) instead of issuing a session directly — closing the gap where an MFA-enabled user could sign in via Google/ magic link and **skip the second factor**. When MFA is on, the server redirects to `/login?mfa=<challenge>` (a signed, single-use, 5-min Data-Protection token — no secret), and `Login.razor` reuses the UI-2 step-up prompt -> `POST /api/auth/mfa/verify -> /auth-callback`. Property covered by `MfaLoginServiceTests` (MFA-on -> challenge, never a session); **QA-MFA-04**. The dead `IssueRefreshCookieAsync` helper was removed.
- **Updated 2026-07-01** — **MFA-4 (native step-up)**: the MAUI client now handles the `{mfa_required, challenge}` response on the native **OTP** and **OAuth-exchange** paths. `AuthService.VerifyOtpAsync/SignInWithOAuthAsync` now return a `SignInResult` (Success / Failed / MfaRequired+challenge) and a new `VerifyMfaAsync` completes the step-up (tokens in the body, native transport); `Login.razor`'s native branches reuse the same code prompt. Client-only — no API change; build-verified (native is E2E/manual per `MOBILE_TESTING.md`); **QA-MFA-05**. **MFA is now enforced on every sign-in path, web and native — the epic is fully closed, no open gaps.**
- **Updated 2026-07-01** — **BILLING-5 (quotas)**: `IQuotaService` adds plan **seat** limits (members + pending invites vs `Plan.SeatLimit`, enforced on the invite path -> `**402 seat_limit_reached`, **with an upgrade message in the Household invite UI**) and metered usage`**` (`TryConsumeAsync` against a monthly, self-resetting `UsageCounter`). Limits are `PlanCatalog` data — null/absent = unlimited, so it's inert until set (platform ships example caps: Free

- 3/3, Pro 10/100). New entity + migration AddUsageCounter. Covered by QuotaServiceTests (10 cases); **QA-HH-14**; EN/ES. Only **BILLING-6** (trial/dunning) and a billing-dissolve contributor remain from the BILLING epic.
- **Updated 2026-07-01 — BILLING-6 (trial/dunning):** the owner-facing reaction to the subscription lifecycle. IBillingNotifier notifies the tenant **owner** via the notification center (in-app bell + outbox email). The **webhook** notifies once on a transition into past\_due/canceled (no spam; inbox dedups). A **\*\*SubscriptionLapseSweepJob\*\*** (6h) nudges once when a paid period lapses without a webhook, recording Subscription.LapseNotifiedAt (migration AddSubscriptionLapseNotifiedAt) — Stripe stays source of truth, no fabricated status. Covered by BillingWebhookHandlerTests + SubscriptionLapseSweepJobTests; manual via stripe trigger. **The BILLING epic is now complete** (1–6); only optional follow-ups remain (advance trial nudge; billing-dissolve contributor).
  - **Updated 2026-07-01 — PUBAPI-1 (public API + API keys, config-gated OFF):** a programmatic surface for machines (the user reversed the earlier "no public API" stance). ApiKey (hash-only, pk\_... revealed once; migration AddApiKey); a second **API-key auth scheme** mints a tenant\_id-scoped principal (so tenant isolation applies for free); owner-only /api/apikeys management (Permission.ManageApiKeys); demo /api/public/whoami (read) + /echo (write) gated by .RequireApiScope. **\*\*PublicApi:Enabled** (default false) — strong gating: off => the scheme isn't added and the routes 404. **\*\*Covered by ApiKeyServiceTests** (9); boot-verified on (401 without a key) and off (404). **HOOKS** (outbound webhooks) is the companion outbound half — next.
  - **Updated 2026-07-01 — HOOKS-1 (outbound webhooks, config-gated OFF):** the outbound integration half. WebhookSubscription (url + event types + **encrypted** signing secret, revealed once; migration AddWebhookSubscription); IWebhookPublisher.PublishAsync fans out to matching active subs -> one "webhook" **outbox** message each (durable, retried, atomic with the change); WebhookOutboxHandler signs (HMAC-SHA256, X-Webhook-Signature) + POSTs, throwing on non-2xx so the outbox retries/dead-letters. Owner-only /api/webhooks (Permission.ManageWebhooks) with a synchronous **send test**. **\*\*Webhooks:Enabled** (default false) — off => routes 404. **\*\*Covered by WebhookSignatureTests** (3) + WebhookSubscriptionServiceTests + WebhookDeliveryTests (11 in Webhooks/); boot-verified on (401 and off (404). **This completes the integration story (PUBAPI inbound + HOOKS outbound), both default-off.**
  - **Updated 2026-07-01 — PUBAPI-2 (hardening): per-key rate limiting** (RateLimiting.PublicApiPolicy partitions on the key id — 60/min, one key can't exhaust another's budget -> 429; RateLimitingTests proves per-key isolation) and a **leak-free public OpenAPI doc** (GET /api/public/openapi.json, anonymous, emits only the /api/public routes so the internal v1 surface is never exposed; boot-verified it serves in Production when enabled and 404s when off).
  - **Updated 2026-07-01 — HOOKS-2 (delivery log + replay):** a tenant-facing debug trail. WebhookDelivery records **one row per delivery attempt** (event, success, status/error, and the sent body; not ITenantScoped — written from both the tenant-less outbox dispatcher and the request-scoped send-test, read side filters by TenantId; migration AddWebhookDelivery). Owner routes GET /api/webhooks/{id}/deliveries + POST /api/webhooks/deliveries/{id}/replay (re-enqueue the exact stored payload, same event id). Covered by WebhookDeliveryLogTests. **Candidate HOOKS-3 (not built):** a Blazor management UI for webhooks/API keys.
  - **Updated 2026-08-28 — HOOKS-2 fix (send-test now records a delivery):** the synchronous POST /api/webhooks/{id}/test delivered inline but wrote **no** WebhookDelivery row, and the sample app fires no published events — so GET /api/webhooks/{id}/deliveries was always empty and replay had nothing to replay (QA-API-06 unrunnable). The send-test now records one row per attempt (success **and** failure) via IWebhookSubscriptionService.SendTestAsync, so the log doubles as the in-template debug trail and replay is testable. Response shape unchanged ({ delivered, status\_code }, or { delivered:false, error:"delivery\_failed" }) on a transport error — internal detail stays in the row, GAP-3). New WebhookDeliveryLogTests (SendTest\_RecordsDelivery\_\*).
  - **Updated 2026-07-01 — BILLING-7 (dissolve cleanup):** closed the one real gap — deleting a billing-enabled tenant left the Stripe subscription active (still charging). BillingDataContributor now wipes the Subscription projection on dissolve and **cancels the provider subscription** via a "billing.cancel" outbox message (BillingCancelOutboxHandler -> new idempotent IBillingProvider.CancelSubscriptionAsync) — out-of-band, not an external call inside the teardown tx. HasDataAsync=false so billing never blocks leaving; export gains a secret-free billing section. Covered by BillingDissolveTests (6). **Closes the BILLING epic (1–7).**

- **Updated 2026-07-01** — added §14b — **manual QA for the API surfaces (PUBAPI + HOOKS)**: curl/Postman cases (QA-API-01..06) for the config gate, minting/using API keys (scopes, tenant-scoping, rate limit), and registering webhooks (send-test, signature verification, delivery log, replay). These surfaces have **no web UI by design** (they're for machines), so this is the human-testable complement to the automated tests — the Postman path is one import of /api/public/openapi.json away. Referenced from the §15 PUBAPI/HOOKS rows and the §2 "no client UI" note.
- **Updated 2026-07-02** — **E2E-in-CI (v2 audit B8-5/B8-6)**: the Playwright suite is now booted and run on every push (the e2e job in .github/workflows/ci.yml — Postgres + Mailpit + API + Web) and was expanded beyond the auth happy-path to the **MFA enroll -> step-up** journey (MfaJourneyTests, incl. a wrong-code negative) and the **login-page language switch** (I18nTests). Six manual cases now have a continuously-run Web equivalent and are marked **Automated in CI**: QA-SMK-01, QA-SMK-03, QA-AUTH-09, QA-MFA-01, QA-MFA-02, QA-I18N-01 (mapping table added under §15; how-to note in §2/§1 "How to use"). These stay in the manual plan for **Desktop/Android** (CI runs Web only) and area-change re-runs; human QA can spot-check them on Web rather than run them in full each cycle. data-testid hooks were added to MfaCard and LanguageSwitcher to keep the selectors stable.
- **Updated 2026-07-03** for NATIVE Wave 2 (ADR-018, docs/NATIVE\_PARITY.md): the parity audit's six gaps were fixed (join-by-code, culture persistence, export download/share, billing return-refresh, Android hardware back — plus **G7**, iOS/macCatalyst crashing at boot, found while writing this expansion) and this plan grew the per-feature native coverage that verifies them on hardware: **QA-DSK-08..14**, **QA-AND-07..13**, the first-ever **iOS/macCatalyst smoke** (§13b, QA-IOS-01..04 + QA-MAC-01..03), and the **per-release native checklist** (§13c). The web halves of the fixes are already -automated (Member\_Joins\_By\_Pasting\_The\_Invite\_Code, Owner\_Downloads\_The\_Data\_Export); the OS-chrome halves (share sheets, hardware back, real focus-return, safe areas) are exactly what these manual cases exist for.
- **Updated 2026-07-06** — **first Apple run of §13b** (maintainer's MacBook Air M1, iOS 26.5 simulator + Mac Catalyst): **QA-IOS-01 PASS** (boots to login — validates the G7 fix on a real Apple runtime), **QA-IOS-02 PASS**, **QA-IOS-04 PASS** (first-ever exercise of the ASWebAuthenticationSession -> perezosoft://auth path; also verified on iPhone 17 Pro Max + iPad Air 11" simulators), **QA-MAC-01 PASS**, **QA-MAC-02 PASS** and the OAuth leg of QA-MAC-03 PASS. Remaining: the core-flows spot-checks (QA-IOS-03, rest of QA-MAC-03 — share sheet, language + restart persistence). The pass surfaced two platform gaps, fixed in the same PR as this entry: (1) macOS trust evaluation fails Brevo's SMTP TLS handshake ("incomplete certificate revocation check") -> new Email:Smtp:CheckCertificateRevocation setting, default **on**, dev-box opt-out documented in .env.example (SmtpSettingsTests); (2) sign-in on ad-hoc-signed Mac Catalyst Debug builds died storing the refresh token — MAUI SecureStorage needs the restricted keychain-access-groups entitlement (MissingEntitlement without it, SIGKILL at launch with it) -> store entitlement added to Entitlements.plist for signed builds, Debug builds swap to Entitlements.Debug.plist (unsandboxed) + a DebugFileSessionStore fallback (MACCATALYST && DEBUG only); SecureStorage must be re-verified under real signing at the downstream first native release (ADR-024; NEW\_APP\_GUIDE.md Phase 9).
- **Updated 2026-07-09** — first findings + features from the manual QA pass (bugfix/qa-manual-pass): (1) **rate-limit split** — passwordless \*verify\* endpoints got their own per-IP budget (attempt cap + headroom, default 10/min) so the cumulative-lockout 401 (QA-AUTH-04) surfaces before the 429 can mask it, and the login UI now shows a dedicated "Too many requests..." message on 429 (QA-AUTH-11 names the exact copy; §1.1 pacing note updated). (2) **MFA recovery codes fixed** — they were 88-char opaque tokens that overflowed the maxlength-14 inputs (unusable); now short xxxxx-xxxxx codes, matched case/separator-insensitively (QA-MFA-01/03). (3) **Notification delete/clear** — per-row trash + "Clear read"/"Clear all" in the bell, backed by new per-user DELETE /api/notifications endpoints (new **QA-NOTIF-04**). (4) **Staff announce upgrades** — optional member targeting on the per-tenant announce (checkbox column -> user\_ids[]) and a platform-wide **Announce to everyone** card backed by an outbox fan-out (POST /api/admin/announce-all, 202 queued) (QA-ADMIN-04 extended, new **QA-ADMIN-05**). (5) **Staff plan comp** — PUT|DELETE /api/admin/tenants/{id}/subscription + console buttons simulate a completed checkout (Pro) and revert to Free; refused 409 for Stripe-backed subs (new **QA-ADMIN-06**). Suite 117 -> **120** cases.
- **Updated 2026-07-10** — **THEME-1 (dark mode)**: per-user Light/Dark/System theme on Bootstrap's data-bs-theme — header + login switcher, pre-paint theme.js bootstrap (no flash), device persistence (localStorage["app\_theme"]), server sync (PUT /api/auth/theme, theme JWT claim, cold-start reconcile like locale). New **QA-SET-08** (web, ThemeJourneyTests) + **QA-DSK-15 / QA-AND-14** (native restart persistence — also verifies WebView localStorage survives a restart per platform). Suite 120 -> **123** cases.
- **Updated 2026-07-10** — **\*\*staff MFA reset (ADR-021 addendum, feat/admin-mfa-reset)\*\***: a user who loses both the authenticator and the recovery codes was locked out permanently (self-serve disable demands a valid code;

every sign-in path steps up). New staff-gated DELETE /api/admin/users/{userId}/mfa wipes UserMfa + recovery codes (no code required — out-of-band identity verification first), audited in the target's tenant (admin.mfa.reset) with the user notified in-app + email (security.mfa\_reset); confirm-gated **Reset MFA** button on the admin member row (new **QA-ADMIN-07**). Suite 123 -> **124** cases.

- **Updated 2026-07-14 — PREFS-1 (ADR-022, per-user preference sync):** fixed the QA-I18N-02 failure (locale was never persisted server-side — the only switcher lived on the anonymous login page) and the "theme applies only after a manual reload" instability (the reconcile ran only on cold starts, missing OTP/MFA soft-navigation sign-ins). Language + theme now live in a **Settings -> Preferences** card; sign-in reconciles both ways (server value wins; a never-set server value adopts the device choice); a locale mismatch persists + reloads once (WASM satellite assemblies); **"system" is stored verbatim** so Auto propagates across devices. QA-I18N-02 is now automated (I18nTests.LocaleChoice\_FollowsTheUser\_AcrossBrowsers); QA-SET-08 updated (no workaround reload; Auto-propagation leg added). No new manual cases — suite stays **124**.
- **Updated 2026-07-14 — BILLING-9 (ADR-006 addendum, seat re-check at accept):** a downgrade (dunning lapse, cancel, or an ADR-021 comp revert) left pending invitations that could each still join — BILLING-5 checked seats only at invitation \*creation\*, so a Pro->Free tenant could grow past its cap by redeeming stale invites. AcceptAsync now refuses when the tenant is already over its limit (402 seat\_limit\_reached; accepts at exactly the cap stay allowed — the joiner consumes the seat their invite reserved) and /join shows a "This household is full" state (EN/ES); the token stays pending and self-heals on re-upgrade. New **QA-INV-10** (automated — SeatQuotaJourneyTests, fake-provider webhook downgrade). Suite 124 -> **125** cases.
- **Updated 2026-07-14** \*(recorded 2026-08-25 — the branch carrying this entry never merged and was recovered during branch housekeeping)\* — **FULL MANUAL PASS COMPLETE:** the maintainer finished the entire manual QA process as the plan stood that day — the web suite (the 2026-07-09/10 sessions' findings all fixed and merged), the §12–13 native columns (Android + Windows device pass), and the remaining §13b Apple spot-checks (QA-IOS-03 + rest of QA-MAC-03, on top of the 2026-07-06 first run) — **all 125 cases passing, no open findings**. With epic NATIVE closed the same day (ADR-024: distribution is downstream work), this pass is the platform's verification baseline; future passes follow §13c per release and the full plan on native-glue/toolchain changes. \*Rider:\* everything added below this entry postdates the baseline — the §14a adversarial cases (12 §16 re-run rows) and QA-AND-15 (NATIVE-12) are the open device items on the current plan.
- **Updated 2026-07-15 — \*\*§14a Adversarial & tenant-isolation (QA-ADV-\*): 24 new curl/Postman + two-browser-context cases from the v3 audit, probing cross-tenant read/write isolation at the API layer (RLS-2/4, LB-TEN-1/2), impersonation attribution/confinement (LB-ADM-1, ADM-2/3/5), billing-webhook idempotency + false-dunning (LB-BILL-1/4), session/token lifecycle (LB-AUTH-3, refresh-reuse), preference bleed on shared devices + the locale-reload deep-link break (UX-1, LB-UI-1/2/4/5/10), and deploy/native hardening (DEP-1/2/3, NAT-3/10). 12 cases are EXPECT-FAIL (assert not-yet-fixed behaviour): ADV-03, 04, 05, 06, 08 (partial), 09, 10, 13, 14, 18, 21, 23 — each formerly carried a PENDING v3 REMEDIATION banner (now ■ v3-landed notes) and their §16 rows are reset for a re-run (never Pass while the finding is open). The other 12 should Pass on current code. §15 gains a QA-ADV traceability block; §16 gains 24 sign-off rows. Suite 125 -> 149\*\* cases.**
- **Updated 2026-07-17 — NATIVE-12 (OAuth process-death resilience)** merged onto develop: an OS kill mid-consent no longer loses the sign-in — an IOAuthResumeStore marker (MAUI Preferences) brackets the browser round-trip, the cold-started callback activity stashes the redirect, and AuthService.TryCompletePendingOAuthAsync completes the exchange on startup (MFA handoff + 5-min TTL guard; interrupted links land on Settings' banner). New **QA-AND-15** (on-device kill test; renumbered from the branch's QA-AND-14 — that slot went to THEME-1's restart test in the interim). Suite 149 -> **150** cases.
- **Updated 2026-09-04 — Email settings: Connect greys out once a provider is connected.** The page always rendered both Connect buttons, so a second Outlook/Gmail attempt only surfaced as the already\_connected bounce. With the one-inbox-per-provider rule (EMAIL-2) now reflected in the UI, the button is disabled while a connection for that provider exists (the row's **Reconnect** is the way back through consent); the API guard is unchanged and stays reachable by re-running a consent URL. QA-EMAIL-02 Gherkin + walkthrough updated; EmailSettingsPageTests.Connect\_IsDisabled\_ForAProviderThatIsAlreadyConnected pins it. **Folder picker: Apply/Cancel + named chips.** "Load folders" used to leave the checklist open until Save, and the selection read only as a count because a connection stored provider ids alone (opaque Graph ids / Gmail Label\_n). Folders now travel as {id, name} pairs (EmailConnection.FolderNames, migration AddEmailConnectionFolderNames; readers still use the id): the edit form shows the selection as chips, the list opens under them with **Apply** (adopt the draft) / **Cancel** (drop it), and the collapsed row carries a **Folders:** line. Rows saved before names were stored are **back-filled once** from the provider's folder list on the next read

(BackfillFolderNamesAsync, best effort); a name the server cannot resolve (dead token) is null on the wire and shows an "Unnamed folder" placeholder — the opaque id is never presented. QA-EMAIL-03 updated; Folders\_RowShowsTheNames\_AndCancelDropsTheDraft + the reshaped Edit\_LoadsFolders\_AndPutsTheSettings + BackfillFolderNames\_ResolvesLegacyIdsOnce\_AndLeavesDeadTokensAlone pin it. Suite count unchanged (180).

- **Updated 2026-09-04 — ADR-V017: a realized refund lands in the month the money arrives.** The donor's placement rule booked the derived inflow into the purchase's month with the purchase's date, rewriting a past month's income. PUT /api/refunds/{id} now takes received\_date (default today; before the purchase -> 400); the inflow is dated with it and filed in that day's month through the ordinary anchor-window resolution (auto-created, retired on revert if emptied). The refund stays under its purchase's month with received\_date + inflow\_month\_id; the month page gains a **Received on** date next to **Mark received**, a "Received <date>" badge and a link to the inflow's month. QA-LED-06 extended (cross-month branch); MarkReceived\_WithADateInALaterMonth\_\*, MarkReceived\_DefaultsToToday\_\* and the two MonthDetail\_\*Refund\* UI cases pin it. Found by the walkthrough and fixed in the same change: the month page loaded only once per component instance, so a link from one month page to another (the new "view" link, or any month-to-month link) changed the URL but kept the old month on screen until a reload — it now reloads when its route id changes (MonthDetail\_ReloadsWhenTheRouteIdChanges). Suite count unchanged (180).
- **Updated 2026-09-04 — Inline category creation (owner request).** Categorising a voucher from the queue or entering a manual transaction no longer needs a trip to Settings: a shared CategoryPicker (select + + **New**) replaces the plain selects on the transaction form and every review card. Create posts to the existing categories endpoint and selects the result; an active clash selects the existing entry, an inactive clash offers **Reactivate** "**<stored name>**" (the Catalog page's rules, reused); Enter creates, Esc cancels. The page owns one category list per page, so a category created on one review card is offered on all of them. No API, schema or Postman change. QA-LED-01 and QA-EMAIL-06 gain the inline step; CategoryPickerTests (4), NewTransaction\_CanCreateACategoryInline\_AndSavesWithIt, Confirm\_CanCreateTheCategoryInline\_AndEveryCardSeesIt pin it. Suite count unchanged (180).