






IPV4


Complete Course on Computer Networks - Part II

Computer Network

Network Layer ✓







Functions of Network Layer

Host to Host Connectivity ✓



Logical Addressing ✓

Switching ✓

Routing ✓

Congestion Control ✓

Fragmentation ✓




Functions of Network Layer

Host to Host Connectivity

Logical Addressing

Switching

Routing




Functions of Network Layer

Host to Host Connectivity

Logical Addressing

Switching

Routing



← NL ← Logical → Any number → uni^o → entire world ✓
 Concepts
 ← DLL ← Physical → Any number → uni^o → within a n/w ✓

LA =
 PA =
 =

IP ✓
 MAC ✓

LA → IP?




IP ✓ 32 - glob
 MAC - 48 - glob

NIC → ROM
 ↓ HW
 MAC

→

✓ VID	✓ Date	48 S-NO ✓
-------	--------	-----------




Functions of Network Layer

Host to Host Connectivity


Logical Addressing

Switching ✓

Routing



21 → 11




Functions of Network Layer

Host to Host Connectivity

Logical Addressing

Switching

Routing



Computer Networks

GATE QUESTIONS

1.) An organization requires a range of IP addresses to assign one to each of its 1500 computers. The organization has approached an Internet Service Provider (ISP) for this task. The ISP uses CIDR and serves the requests from the available IP address space 202.61.0.0/17. The ISP wants to assign an address space to the organization which will minimize the number of routing entries in the ISP's router using route aggregation. Which of the following address spaces are potential candidates from which the ISP can allot any one to the organization? [GATE 2020]

I. 202.61.84.0/21

II. 202.61.104.0/21

III. 202.61.64.0/21

IV. 202.61.144.0/21

1.) An organization requires a range of IP addresses to assign one to each of its 1500 computers. The organization has approached an Internet Service Provider (ISP) for this task. The ISP uses CIDR and serves the requests from the available IP address space 202.61.0.0/17. The ISP wants to assign an address space to the organization which will minimize the number of routing entries in the ISP's router using route aggregation. Which of the following address spaces are potential candidates from which the ISP can allot any one to the organization? (GATE 2020)

- I. 202.61.84.0/21
- II. 202.61.104.0/21
- III. 202.61.64.0/21
- IV. 202.61.144.0/21

Solution: Option C

Given CIDR IP is 202.61.0.0/17 and for HID $32 - 17 = 15$ bits can be used.

And to Assign an IP address for 1500 computer, we require 11 bit from HID part.

So NID + SID = $17 + 4 = 21$ bits and HID = 11 bits

NID HID

202.61.0 0000 000.000000000

So, from the given option, possible IP Address is

- I. 84 - $\rightarrow 0\ 1010\ 100$ (Because in HID bit 1 is not possible)
- II. 104 $\rightarrow 0\ 1101\ 000$
- III. 64 $\rightarrow 0\ 1000\ 000$
- IV. 144 $\rightarrow 1\ 0010\ 000$ (Because in NID bit 1 is not possible)

2.) A computer network uses polynomials over GF(2) for error checking with 8 bits as information bits and uses $x^3 + x + 1$ as the generator polynomial to generate the check bits. In this network, the message 01011011 is transmitted as [GATE 2017]

- A 01011011010
- B 01011011011
- C 01011011101
- D 01011011100


Solution:

Given CRC generator polynomial = x^3+x+1

$$= 1 \cdot x^3 + 0 \cdot x^2 + 1 \cdot x + 1 \cdot x^0$$

$$= 1011$$

Message = 01011011



3.)The value of parameters for the Stop-and-Wait ARQ protocol are as given below:

Bit rate of the transmission channel = 1 Mbps.

Propagation delay from sender to receiver = 0.75 ms.

Time to process a frame = 0.25 ms.

Number of bytes in the information frame = 1980.

Number of bytes in the acknowledge frame = 20.

Number of overhead bytes in the information frame = 20.

Assume that there are no transmission errors. Then, the transmission efficiency (expressed in percentage) of the Stop-and-Wait ARQ protocol for the above parameters is _____ (correct to 2 decimal places). [GATE 2017]

3.)The value of parameters for the Stop-and-Wait ARQ protocol are as given below:

Bit rate of the transmission channel = 1 Mbps.

Propagation delay from sender to receiver = 0.75 ms.

Time to process a frame = 0.25 ms.

Number of bytes in the information frame = 1980.

Number of bytes in the acknowledge frame = 20.

Number of overhead bytes in the information frame = 20.

Assume that there are no transmission errors. Then, the transmission efficiency (expressed in percentage) of the Stop-and-Wait ARQ protocol for the above parameters is _____ (correct to 2 decimal places). [GATE 2017]

Solution:

Given Data:

$B = 1\text{Mbps}$, $L = 1980\text{Bytes}$, Overhead = 20Bytes

$T_{\text{Proc}} = 0.25\text{ms}$, $L_{\text{Ack}} = 20\text{Bytes}$

$T_p = 0.75\text{ms}$

Total Data size(L) = (L + overhead) = $1980 + 20 = 2000\text{Bytes}$

Efficiency of Stop & Wait ARQ?

$T_t = L/B = 2000\text{Bytes}/1\text{Mbps} = (2000 \times 8\text{bits})/(10^6 \text{ b/s}) = 16\text{msec}$

$T_{\text{Ack}} = L_{\text{Ack}}/B = (20 \times 8\text{bits})/(10^6 \text{ bits/sec}) = 0.16\text{msec}$

\therefore In Stop and Wait ARQ, efficiency

$\eta = T_t/(T_t + T_{\text{Ack}} + 2T_p + T_{\text{Proc}}) = 16\text{ms}/(16 + 0.16 + 2 \times 0.75 + 0.25\text{ms})$

$= 16\text{ms}/17.91\text{ms} = 0.8933 \approx \boxed{89.33\%}$

4.) A sender uses the Stop-and-Wait ARQ protocol for reliable transmission of frames. Frames are of size 1000 bytes and the transmission rate at the sender is 80 Kbps (1Kbps = 1000 bits/second). Size of an acknowledgement is 100 bytes and the transmission rate at the receiver is 8 Kbps. The one-way propagation delay is 100 milliseconds.

Assuming no frame is lost, the sender throughput is _____ bytes/second. [GATE 2016]

4.) A sender uses the Stop-and-Wait ARQ protocol for reliable transmission of frames. Frames are of size 1000 bytes and the transmission rate at the sender is 80 Kbps (1Kbps = 1000 bits/second). Size of an acknowledgement is 100 bytes and the transmission rate at the receiver is 8 Kbps. The one-way propagation delay is 100 milliseconds.

Assuming no frame is lost, the sender throughput is _____ bytes/second. [GATE 2016]

Solution:

Given,

Frame size (L) = 1000 bytes

Sender side bandwidth (BS) = 80 kbps = 10×10^3 bytes/sec

Acknowledgement size (LA) = 100 bytes

Receiver side bandwidth (BR) = 8 kbps = 1×10^3 bytes/sec

Propagation delay (T_p) = 100 ms

By formula:

Transmission delay (T_t) = $L/BS = 1000 \text{ bytes} / 10 \times 10^3 \text{ bytes/sec} = 100 \text{ ms}$

Acknowledge delay (T_{ack}) = $LA / BR = 100 \text{ bytes} / 1 \times 10^3 \text{ bytes/sec} = 100 \text{ ms}$

Total cycle time = $T_t + 2 \times T_p + T_{ack} = 100 \text{ ms} + 2 \times 100 \text{ ms} + 100 \text{ ms} = 400 \text{ ms}$

Efficiency (η) = $T_t / \text{Total cycle time} = 100 \text{ ms} / 400 \text{ ms} = 1 / 4 = 0.25$

Throughput = Efficiency (η) * Bandwidth (BS) = $0.25 \times 10 \times 10^3 \text{ bytes/s} = 2500 \text{ bytes/second}$

5.) A network has a data transmission bandwidth of 20×10^6 bits per second. It uses CSMA/CD in the MAC layer. The maximum signal propagation time from one node to another node is 40 microseconds. The minimum size of a frame in the network is _____ bytes. [GATE 2016]

5.) A network has a data transmission bandwidth of 20×10^6 bits per second. It uses CSMA/CD in the MAC layer. The maximum signal propagation time from one node to another node is 40 microseconds. The minimum size of a frame in the network is _____ bytes. [GATE 2016]

Solution:

For frame size to be minimum, its transmission time should be equal to twice of one way propagation delay. i.e, $T_t = 2 \times T_P$

Given,

Bandwidth (B) = 20×10^6 bps

$T_P = 40 \mu s \Rightarrow 40 \times 10^{-6}$ sec

Suppose minimum frame size is L.

$T_t = 2 \times T_P \Rightarrow L / B = 2 \times T_P$

$\Rightarrow L = 2 \times T_P \times B = 2 \times 40 \times 10^{-6} \times 20 \times 10^6 = 1600$ bits $\Rightarrow 200$ bytes

Therefore, L = 200 bytes

6.) Consider a 128×10^3 bits/ second satellite communication link with one way propagation delay of 150 milliseconds. Selective retransmission (repeat) protocol is used on this link to send data with a frame size of 1 kilobyte. Neglect the transmission time of acknowledgement. The minimum number of bits required for the sequence number field to achieve 100% utilization is _____ [GATE 2016]

6.) Consider a 128×10^3 bits/ second satellite communication link with one way propagation delay of 150 milliseconds. Selective retransmission (repeat) protocol is used on this link to send data with a frame size of 1 kilobyte. Neglect the transmission time of acknowledgement. The minimum number of bits required for the sequence number field to achieve 100% utilization is _____ [GATE 2016]

Solution:

To achieve 100% efficiency, the number of frames that we should send $N = 1 + 2 * a$
 $a = T_p / T_t$ where T_p is propagation delay, and T_t is transmission delay.

Given, $B = 128 \text{ kbps}$, $T_p = 150 \text{ msec}$,

$L = 1 \text{ KB} = 1 * 8 * 2^{10} \text{ bits}$

$T_t = L / B \Rightarrow 1 * 8 * 2^{10} \text{ bits} / 128 * 10^3 \text{ bps} \Rightarrow 0.064 \text{ sec} = 64 \text{ msec}$

So, $a = 150 \text{ msec} / 64 \text{ msec} = 2.343$

Efficiency (η) = 100 % $\Rightarrow 1 = N / 1 + 2 * a$

So, $N = 1 + 2 * a \Rightarrow 1 + 2 * 2.343 = 5.686$

No. of sequence numbers requires in SR is $2 * N = 2 * 5.686 = 11.375$

Minimum No. of bits required in the sequence number = $\lceil \log_2 (11.375) \rceil = 4$