



CFG and PDA - VII

Complete Course on Theory of Computation

$$(1) \quad S(a^*) = [S(a)]^*$$

Not

$$(2) \quad S(a+b+c) = S(a) + S(b) + S(c)$$

$$(3) \quad S(a \cdot b) = S(a) \cdot S(b)$$

$$(4) \quad S(\epsilon) = \epsilon$$

$$(5) \quad S(\phi) = \phi$$

~~4/4/4~~

$$\boxed{\underline{S} \rightarrow \frac{P(\Delta^*)}{R.L}}$$

ex $\Sigma = \{0, 1\}$ $\Delta = \{a, b\}$ substitution s is defined

as $s(0) = \underline{a}$, $s(1) = \underline{b^2}$

① $s(\underline{010}) = s(0) \cdot s(1) \cdot s(0) = a b^2 a$

② $s(0^2(0+1)1^2) = s(0^2) \cdot (s(0) + s(1)) \cdot s(1^2)$

Diagram illustrating the derivation of $s(0^2(0+1)1^2)$:

Left side (Tree Diagram):

- Root node: $0^2(0+1)1^2$
- Children: 0^2 , $(0+1)$, 1^2
- Further expansion shows 0^2 as $0 \cdot 0$ and 1^2 as $1 \cdot 1$.

Right side (Algebraic Derivation):

$$[s(0)]^2 \cdot (s(0) + s(1)) \cdot [s(1)]^2$$

$$(a + a^2 b^2) b^2$$

$$a^2 (a + b^2) \cdot (b^2)^2$$

$$a^2 (\underline{a + b^2}) \cdot \underline{b^2} \implies \underline{a^2 b^2}$$

Final result: $\underline{\underline{a^2 b^2}}$

ex $\Sigma = \{0\}$ $\Delta = \{a, b\}$ substitution f is defined

as $f(0) = (a+b)(a+b) = (a+b)^2$

find $f(00) = f(0) \cdot f(0) = (a+b)^2 \cdot (a+b)^2 = (a+b)^4$

$f(0^k) = [f(0)]^k = [(a+b)^2]^k =$ set of all
even length
strings.

Homomorphism


It is a special type of substitution where every symbol in Σ mapped to one of its string over Δ

(or)



Homomorphism

Subst



ex

$$\Sigma = \{0, 1\} \quad \Delta = \{a, b, c\}$$

and h is defined as

$$h(0) = \underline{ab} \implies h^{-1}(ab) = 0$$

$$h(1) = \underline{bbc} \implies h^{-1}(bbc) = 1$$

$$h(\underline{010}) = h(0) \cdot h(1) \cdot h(0)$$

$$= \underline{ab \cdot bbc \cdot ab} \implies abbbcab$$

$$h(\epsilon) = \epsilon$$

$$h(\emptyset) = \emptyset$$

$$h(a+b) = h(a) + h(b)$$

$$h(a \cdot b) = h(a) \cdot h(b)$$

$$\underline{h(a^b)} = [h(a)]^b$$

Inverse Homomorphism

$$h^{-1}(w) = \{x \mid \exists h(x) = w\}$$

\Downarrow
Homomorphism.

$$h(0) = w$$

$$h^{-1}(w) = 0$$

$$h^{-1}(\underline{aa}) = 0$$

ex $\Sigma = \{0, 1\}$ $\Delta = \{a, b\}$ and h is defined
as $h(0) = aa$, $h(1) = aba \Rightarrow h^{-1}(\underline{aba}) = 1$

let $L = \underline{(ab+ba)^* a}$ $\rightarrow aba,$

find $\underline{h^{-1}(L)} = h^{-1}(\underline{(ab+ba)^* a})$
 $= h^{-1}(aba) \Rightarrow 1$

ex

$$\Sigma = \{0, 1, 2\} \quad \Delta = \{a, b\}$$

$$h(0) = a, \quad h(1) = ab, \quad h(2) = ba$$

1. find $h^{-1}(\underline{ababa}) = h^{-1}(a) \cdot h^{-1}(ba) \cdot h^{-1}(ba)$
0 2 2 $\Rightarrow 022$

$$h^{-1}(\underline{ab} \underline{ab} \underline{a}) = 110$$

$$h^{-1}(\underline{ab} \underline{ab} \underline{a}) = 102$$

$$022, 110, 102$$

$$2. \quad h^{-1}(a(ba)^k) = h^{-1}(a) \cdot [h^{-1}(ba)]^k$$

$$\Downarrow$$

$$= 02^k$$

$$(ab)^k a$$

$$\Downarrow$$


$$[h^{-1}(ab)]^k \cdot h^{-1}(a)$$

$$\Downarrow$$

$$1^k \cdot 0$$

$$\underline{\underline{\quad}}$$

$$\underline{02^k} + \underline{1^k 0}$$



$$(ab)^* a = a (ba)^*$$

$$L = \{ \underline{ab}, \underline{d}, \underline{babc}, \text{, etc.}, \underline{bbb}, \underline{ccc} \}$$

half(L)
(or)
 $\frac{1}{2}L = \{ a, ba, bbb \}$

$$\text{2nd half}(L) = \{ b, bc, ccc \}$$

If L is reg $\frac{1}{2}L$ also reg

So R.L closed under $\frac{1}{2}L$.

$$L = \{ \underline{abc}, \underline{aabbcc}, \underline{aaabbbccc} \}$$

$$\frac{1}{3}L = \{ a, aa, aaa \}$$

$$2^{\text{nd}} \frac{1}{3}(L) = \{ b, bb, bbb \}$$

$$3^{\text{rd}} \frac{1}{3}(L) = \{ c, cc, ccc \}$$

$$9b \quad L - R \cdot L$$

$$\frac{1}{3}L - R \cdot L$$

$$\frac{1}{3}L \quad \checkmark$$

Regular Languages closed under



- | | | |
|-------------------------|----------------------|----------------------|
| (1) Union | (2) Intersection | (3) Kleenstar |
| (4) complement | (5) prefix | (6) suffix |
| (7) Substr | (8) Homomorph | (9) I. Homom |
| (10) complen | (11) Diffen | (12) Reversal |
| (13) Quotient operation | (14) $\frac{1}{2} L$ | (15) $\frac{1}{3} L$ |



Subset not closed over any Lang

$$L = \{ ab, bc \}$$


$$\underline{ab + bc}$$

Finite Automata

22

Regel Langue

25



Context Free Languages \neq Push Down Automata

Note

In the given R.L if every symbol substituted by
another R.L then result also R.L.

So R.L are closed under substitution
operation.

