FEAT-ZD-48600 · BE-02 Access to secrets · Secrets granted for the task's environments (names only)

Backend agent · item task.secrets_scope · source hobasa-backend-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by automated checks and independent judge

task.secrets_scope: FEAT-ZD-48600

Secrets scope for the Backend lane of FEAT-ZD-48600 (ZD-48600, "Show which overdue invoices belong to vendors that usually pay late"). This is step BE-02 Access to secrets (attempt 1). The file lists secret **names only**; it holds no values. org.permission_table is restricted, so this file refers to it by name and does not copy it.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	BE-02 Access to secrets (attempt 1)	record:brief
Inputs	feat.tasks (from hobasa-design-agent/outputs/FEAT-ZD-48600/feat.tasks.md at commit b0fd4d2); org.permission_table (restricted, by reference)	record:brief
Backend tasks in scope	TSK-05 (STORY-05), TSK-06 (STORY-06)	feat.tasks (sections 1, 3)
Repository	ap_aging	feat.tasks (section 1); record:brief

1. Secrets needed by the Backend tasks

Task	What it does	Environments it touches	Secrets needed	Source
TSK-05	New pure function `overdue_with_risk(invoices, as_of, risk_by_vendor)` in `src/ap_aging/aging.py`, with its unit tests	Local build and CI only; no runtime service	None	feat.tasks (TSK-05)
TSK-06	New function `overdue_rows_to_json(rows)` in `src/ap_aging/aging.py`; no transport layer	Local build and CI only; no runtime service	None	feat.tasks (TSK-06)

Why no secrets are needed:

- Both tasks are pure functions inside one module. TSK-06 explicitly adds no transport layer (a transport would re-trigger DES-01) (feat.tasks, TSK-06 "Must not change").
- The feature uses only the Python 3.9 standard library for this lane and adds no new technology (feat.tasks, intro and section 8, DD-1).
- The ap_aging source reads no environment variables, tokens or credentials and opens no network connection: `aging.py` imports only `datetime`, `decimal` and `typing` (file:ap_aging/src/ap_aging/aging.py). A search of the repository for environment-variable reads, secret, token, password, API-key and network-library patterns found no match (file:ap_aging/src/ap_aging/aging.py; file:ap_aging/ci.py).
- CI (`ci.py`) runs locally: compile, unit tests, coverage gate and static checks. It reads no secret (file:ap_aging/ci.py).

2. Secrets granted

Environment	Secret names granted	Source
Local development	None	tool:repo-access
CI (`/usr/bin/python3 ci.py`)	None	tool:repo-access; file:ap_aging/ci.py
dev / production	Not in this lane's scope: TSK-05 and TSK-06 add no deployed service	tool:repo-access; feat.tasks (TSK-06)

The tool registry states that no secrets are required or granted for ap_aging (permission table) (tool:repo-access).

3. Gap check

Check	Result	Source
Secrets needed but not granted	None	sections 1 and 2
Secrets granted but not needed (excess access)	None	tool:repo-access
Access request raised	Not needed	sections 1 and 2
Secret values in this file	None (names only, and there are no names to list)	this file

4. Outcome

Secrets are available with the right access permissions for TSK-05 and TSK-06 because the tasks need none and none are granted. BE-05 Coding can go ahead with an empty secrets scope. If a later change adds a transport, a database or an external call to ap_aging, that is a design change (feat.tasks, TSK-06), and BE-02 must run again.

5. Open questions

None blocking. None non-blocking.

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_aging] Tool registry: no secrets required or granted (permission table)