FEAT-ZD-48600 · BE-02 Access to secrets · Secrets granted for the task's environments (names only)

Backend agent · item task.secrets_scope · source hobasa-backend-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by automated checks and independent judge

task.secrets_scope: FEAT-ZD-48600

Secrets scope for the Backend tasks of FEAT-ZD-48600 (ZD-48600, "Show which overdue invoices belong to vendors that usually pay late"). This is BE-02 Access to secrets (attempt 3). It lists secret names only, never values. Every statement here rests on the step's contracted input (feat.tasks), the tool view (tool:repo-access) or the step brief (record:brief).

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	BE-02 Access to secrets (attempt 3)	record:brief
Owner / gate	Developer / automated checks, independent judge, sampled human evaluation	record:brief
Inputs	feat.tasks (from hobasa-design-agent/outputs/FEAT-ZD-48600/feat.tasks.md at commit b0fd4d2); org.permission_table (restricted, by reference only)	record:brief
Repository	ap_aging	feat.tasks (section 1, TSK-05, TSK-06)

1. Backend tasks in scope

Task	Story	Repository	What it builds	External access in the task?	Source
TSK-05	STORY-05	ap_aging	New pure function `overdue_with_risk(invoices, as_of, risk_by_vendor)` in `src/ap_aging/aging.py`	None: a pure function over in-memory invoices	feat.tasks (TSK-05)
TSK-06	STORY-06	ap_aging	New `overdue_rows_to_json(rows) -> str` in `src/ap_aging/aging.py`	None: "No transport layer (a transport would re-trigger DES-01)"	feat.tasks (TSK-06)

Both tasks use only the Python 3.9 standard library and add no new technology (feat.tasks, intro, carrying feat.design DD-1).

2. Secrets required

None. Neither task calls a service, database, API, LLM provider or file store:

- TSK-05 is a new pure function. `as_of` is a required parameter, and amounts are quantised in memory with `Decimal` (feat.tasks, TSK-05).
- TSK-06 serialises the rows to a JSON string, and a transport layer is explicitly out of scope (feat.tasks, TSK-06).
- The files in budget for both tasks are `src/ap_aging/aging.py`, `src/ap_aging/__init__.py` and `tests/test_overdue.py`. None of them is a configuration, credential or connection file (feat.tasks, TSK-05, TSK-06).

3. Secrets granted (names only)

Environment	Secret names granted	Source
Development / CI for ap_aging	None	tool:repo-access (permission table)
Any other environment	None	tool:repo-access (permission table)

The permission table states that no secrets are required or granted for ap_aging (tool:repo-access). Required (none) and granted (none) match, so there is no gap and no excess.

4. Access requests

None raised. No secret is needed for TSK-05 or TSK-06, so no access request goes to the infra team. No excess access exists to flag for revocation.

5. Out of scope (other lanes, noted for completeness)

The only external-provider touchpoint in the feature is TSK-04 (Data Science, ap_forecast): sending the risk label to `acme-llm` awaits Architect confirmation (TQ-8) (feat.tasks, TSK-04). That task belongs to the Data Science lane, and the Data Science agent checks its secrets. The Backend lane does not need it.

6. Re-entry condition

Run this step again if a Backend task gains a transport, a database or any external call. feat.tasks states that adding a transport to TSK-06 would re-trigger DES-01 (feat.tasks, TSK-06).

7. Open questions

None.

8. Validation check

Check	Result	Source
Every Backend task assessed for secrets	Pass (TSK-05, TSK-06)	feat.tasks
Required and granted secrets match	Pass (none and none)	tool:repo-access
Secret values or personal data in this file	None, names only	—
Blocking questions	None	—

[Tool result] [ap_aging] Tool registry: no secrets required or granted (permission table)