FEAT-ZD-48600 · BE-02 Access to secrets · Secrets granted for the task's environments (names only)

Backend agent · item task.secrets_scope · source hobasa-backend-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by automated checks and independent judge

task.secrets_scope: FEAT-ZD-48600

Secrets scope for the Backend lane of FEAT-ZD-48600 ("Show which overdue invoices belong to vendors that usually pay late"). This is BE-02 Access to secrets. It lists names only; no secret values appear here.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	BE-02 Access to secrets	record:brief
Inputs	feat.tasks (from hobasa-design-agent at commit b0fd4d2); org.permission_table (restricted, passed by reference only)	record:brief
Backend tasks	TSK-05 (STORY-05) and TSK-06 (STORY-06), both in ap_aging	feat.tasks (section 1)
Repository	ap_aging, GitHub remote `arghya05/ap-aging-sample`	file:ap-aging-sample/.git/config

1. Result

No secrets are required, and none are granted. No access request is needed.

Environment	Secrets required	Secrets granted	Access request raised	Source
Local development and CI (`/usr/bin/python3 ci.py`)	None	None	No	tool:repo-access; file:ap-aging-sample/CLAUDE.md; file:ap-aging-sample/ci.py
Any deployed environment	None (this feature adds no transport to ap_aging)	None	No	tool:repo-access; feat.tasks (TSK-06 "No transport layer")

2. Why no secret is needed

#	Finding	Source
S-1	The permission table grants no secrets for ap_aging and states none are required	tool:repo-access (org.permission_table, by reference)
S-2	TSK-05 adds a pure function, `overdue_with_risk(invoices, as_of, risk_by_vendor)`. It takes its inputs as arguments	feat.tasks (TSK-05)
S-3	TSK-06 adds `overdue_rows_to_json(rows)`, which serialises the rows to a string. The task forbids a transport layer, because adding one would re-trigger DES-01	feat.tasks (TSK-06)
S-4	The budgeted files are `src/ap_aging/aging.py`, `src/ap_aging/__init__.py` and the new `tests/test_overdue.py`. The only new import is `json`	feat.tasks (TSK-05, TSK-06)

#	Finding	Source
S-5	Today `aging.py` imports only `datetime`, `decimal` and `typing`. It reads no environment variable, file or network resource	file:ap-aging-sample/src/ap_aging/aging.py
S-6	Neither `aging.py` nor `ci.py` contains `os.environ`, `getenv`, `secret`, `token`, `password`, `api_key` or `credential`, and neither imports `os`, `urllib`, `http` or `socket`	file:ap-aging-sample/src/ap_aging/aging.py; file:ap-aging-sample/ci.py
S-7	CI runs locally with the standard library plus `coverage`. SonarQube is not available locally, so no SonarQube token is used	file:ap-aging-sample/ci.py
S-8	The language is Python 3.9 (standard library)	file:ap-aging-sample/CLAUDE.md

3. Out of scope for this lane

- **The LLM provider (`acme-llm`).** TSK-04 (Data Science, ap_forecast) is the only task that sends anything to `acme-llm`. The Backend lane does not call it: `overdue_with_risk` receives the vendor risk as its `risk_by_vendor` argument. Source: feat.tasks (TSK-04, TSK-05).

4. Re-entry

The findings in section 2 rest on the scope in feat.tasks: no transport and no external call in ap_aging. If a change brings either into ap_aging, this secrets scope should be checked again (agent judgement). feat.tasks states that a transport would also re-trigger DES-01. Source: feat.tasks (TSK-06).

5. Open questions

None. Nothing blocks this step.

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_aging] Tool registry: no secrets required or granted (permission table)