FEAT-ZD-48600 · BE-01 Checking the coding prerequisites ■ · Repository (and Databricks) availability and write access

Backend agent · item task.repo_access · source hobasa-backend-agent/outputs/FEAT-ZD-48600/task.repo_access.md · approved by automated checks and independent judge

task.repo_access: FEAT-ZD-48600

Repository availability and write access for the Backend lane of FEAT-ZD-48600 ("Show which overdue invoices belong to vendors that usually pay late"). Step BE-01, checking the coding prerequisites.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	BE-01, checking the coding prerequisites	record:brief
Backend tasks	TSK-05 (STORY-05) and TSK-06 (STORY-06), both in ap_aging	feat.tasks (section 1)
Inputs	feat.tasks, org.engineering_stack	record:brief

1. Result

The repository is available and the agent has write access. No repository needs to be created, and no Databricks or other workspace is needed.

Check	Result	Source
Repository needed by the Backend tasks	ap_aging (TSK-05, TSK-06 in "Backend / ap_aging")	feat.tasks (section 1)
Repository available	Yes, available locally	tool:repo-access
Repository creation needed	No. ap_aging already exists	tool:repo-access; org.engineering_stack
Write access for the agent identity	Yes (git status clean)	tool:repo-access
Working branch	`feature/story`, created from `dev` at `5d2cbb9`; HEAD points to `refs/heads/feature/story`	tool:repo-access; file:ap_aging/.git/HEAD
Branch model	`main` (released), `dev` (integration), `feature/<story>`	file:ap_aging/CLAUDE.md; org.engineering_stack; feat.tasks (section 2)
Databricks / database / other workspace	Not used by ap_aging; none needed	tool:repo-access; org.engineering_stack

2. Repository facts the coding steps rely on

Item	Value	Source
Language	Python 3.9 (standard library)	file:ap_aging/CLAUDE.md; tool:repo-access
Test framework	unittest	org.engineering_stack
CI command	`/usr/bin/python3 ci.py`	file:ap_aging/CLAUDE.md; org.engineering_stack
CI gate	Compile, unit tests, line coverage at least 90% (`COVERAGE_MIN = 90.0`), static checks standing in for SonarQube (no `print`, `eval`, `exec`, bare `except`; lines at most 140 characters)	file:ap_aging/ci.py; org.engineering_stack

Item	Value	Source
Package entry point	`src/ap_aging/__init__.py`: `__version__ = "1.4.0"`, `__all__ = ["aging_buckets"]`	file:ap_aging/src/ap_aging/__init__.py
Aging module	`src/ap_aging/aging.py` defines `BUCKETS`, `days_past_due`, `bucket_for` and `aging_buckets`	file:ap_aging/src/ap_aging/aging.py
Existing unit tests	`tests/test_aging.py` covers `days_past_due`, `bucket_for` and `aging_buckets`	file:ap_aging/tests/test_aging.py
Version step	TSK-05 owns the ap_aging version step from `1.4.0`	feat.tasks (section 2); file:ap_aging/src/ap_aging/__init__.py
Files in budget for TSK-05 and TSK-06	`src/ap_aging/aging.py`, `src/ap_aging/__init__.py`, and a new `tests/test_overdue.py`	feat.tasks (TSK-05, TSK-06)
Commit message rule	Starts with the story ID (`STORY-05` or `STORY-06`); the task ID may follow	org.engineering_stack; feat.tasks (section 2); record:memory

3. Assumptions and notes

ID	Note	Source
RA-1	Availability, branch and write access are taken from the step's tool view	tool:repo-access
RA-2	`ci.py` imports the `coverage` package (`import coverage`), while the repository is described as Python 3.9 standard library. The CI therefore needs `coverage` installed for `/usr/bin/python3`; this check does not confirm that it is installed	file:ap_aging/ci.py; file:ap_aging/CLAUDE.md
RA-3	The working branch is named `feature/story`, not a story-specific name such as `feature/STORY-05`. Both Backend tasks (TSK-05, TSK-06) are assumed to share this branch	tool:repo-access; feat.tasks (section 2)

4. Open questions (non-blocking)

ID	Question	Interim answer	Owner (proposed)
RAQ-1	Is the `coverage` package installed for `/usr/bin/python3` where the CI runs?	Assume yes; the first CI run in the coding steps will show it	Infra team
RAQ-2	Should TSK-05 and TSK-06 share the branch `feature/story`, or use one branch per story (`feature/STORY-05`, `feature/STORY-06`)?	Use the provided `feature/story` for both; commits carry the story ID	Developer

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_aging] Branch feature/story at 5d2cbb9; write access confirmed