FEAT-ZD-48600 · DE-02 Access to secrets · Secrets granted for the task's environments (names only)

Data Engineering agent · item task.secrets_scope · source hobasa-data-engineering-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by Data engineer sim.data_engineer

task.secrets_scope: FEAT-ZD-48600 (Data Engineering lane)

Secrets scope for the Data Engineering tasks of FEAT-ZD-48600, from DE-02 Access to secrets. The file lists secret names only. No secret values are read, stored or shown here.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	DE-02 Access to secrets	record:brief
Owner / gate	Data engineer / no gate (automated checks, independent judge, sampled human evaluation)	record:brief
Inputs	feat.tasks (from hobasa-design-agent at commit b0fd4d2); org.permission_table (restricted, read through the tool view only)	record:brief
Repository	ap_pipeline	feat.tasks (section 1)

1. Result

No secrets are needed, and none are granted. The Data Engineering tasks run without secret access, so there is nothing to request.

Check	Result	Source
Secrets required by the DE tasks	None	feat.tasks (TSK-01, TSK-02); file:ap_pipeline/src/ap_pipeline/ingest.py; file:ap_pipeline/src/ap_pipeline/pipeline.py
Secrets granted for ap_pipeline	None	tool:repo-access (org.permission_table)
Gap between required and granted	None. Nothing to request	tool:repo-access; feat.tasks
Access request raised	No, because nothing is missing	tool:repo-access; feat.tasks

2. Tasks in scope and their secret needs

Task	Story	What it changes	Outside systems it reaches	Secrets needed	Source
TSK-01	STORY-01	`src/ap_pipeline/transform.py`: optional `paid_date` parsing in `to_model`, with reason `'paid_date'` for invalid values; the version step in `__init__.py`	None. It parses the feed records it receives, and coding builds on synthetic v3 rows	None	feat.tasks (TSK-01)
TSK-02	STORY-02	New `src/ap_pipeline/delays.py`: `delays_by_vendor`, a pure function with "No I/O"	None	None	feat.tasks (TSK-02)

feat.tasks section 1 assigns TSK-03 to TSK-08 to the Data Science, Backend, Frontend and Testing Agent lanes, outside ap_pipeline. This file does not cover them.

3. Evidence from the code

- `ingest.parse_feed(csv_text: str)` parses CSV text with `csv.DictReader` over `io.StringIO`. It opens no connection and reads no credential (file:ap_pipeline/src/ap_pipeline/ingest.py).
- `pipeline.run(csv_text: str)` chains `parse_feed`, `to_model` and `quality_report` on the text it is passed. It calls no source system (file:ap_pipeline/src/ap_pipeline/pipeline.py).
- A case-insensitive search of the ap_pipeline checkout for `os.environ`, `getenv`, `secret`, `token`, `password`, `api_key`, `credential`, `http`, `urllib` and `socket` found no matches (file:ap_pipeline/src/ap_pipeline/ingest.py; file:ap_pipeline/src/ap_pipeline/pipeline.py; file:ap_pipeline/src/ap_pipeline/schedule.json).
- The repository uses the Python 3.9 standard library, and CI runs with `/usr/bin/python3 ci.py` (file:ap_pipeline/CLAUDE.md).
- The tasks choose no new technology: only the Python 3.9 standard library and Node.js 22 CommonJS (feat.tasks, introduction, citing feat.design DD-1).

4. Secrets scope by environment (names only)

Environment / branch	Secret names granted	Source
`feature/<story>` (development)	None	tool:repo-access; feat.tasks (section 2, branch and commit)
`dev` (integration)	None	tool:repo-access; file:ap_pipeline/CLAUDE.md
`main` (released)	None	tool:repo-access; file:ap_pipeline/CLAUDE.md

No input names deployment environments other than these branches. This file therefore scopes secrets per branch. See open question SQ-DE-2.

5. Data guardrail

Feed v3 in production (PQ-6) gates release, not coding. Coding builds on synthetic v3 rows (feat.tasks, TSK-01). No production source-system data is needed, so no source-system credential is needed either.

6. Open questions (non-blocking)

ID	Question	Interim answer	Owner (proposed)
SQ-DE-1	The pipeline has a schedule (`daily` at `02:00`, `Asia/Kolkata`, in `schedule.json`). Will scheduling the pipeline or sending its status notifications need a scheduler or notification credential?	Not in scope for TSK-01 or TSK-02, and the permission table grants none. Re-check this step on a re-entry trigger if a later step needs one	Data engineering lead
SQ-DE-2	Are there deployment environments beyond the `main`, `dev` and `feature/<story>` branches that need their own secret scope?	None are named in the inputs, so the scope is by branch	Data engineering lead

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_pipeline] Tool registry: no secrets required or granted (permission table)