FEAT-ZD-48600 · DE-02 Access to secrets · Secrets granted for the task's environments (names only)

Data Engineering agent · item task.secrets_scope · source hobasa-data-engineering-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by Data engineer sim.data_engineer

task.secrets_scope: FEAT-ZD-48600

Secrets scope for the Data Engineering lane of FEAT-ZD-48600 ("Show which overdue invoices belong to vendors that usually pay late"). The step is DE-02, Access to secrets. It has no human gate. Automated checks, the independent judge and sampled human evaluation review it. This file lists secret **names only**. It holds no secret values.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	DE-02 Access to secrets	record:brief
Trigger	Task creation (feat.tasks from DES-04)	record:brief; feat.tasks
Owner	Data engineer	record:brief
Inputs	feat.tasks (hobasa-design-agent, commit b0fd4d2); org.permission_table (restricted, passed by reference only, read through the tool view)	record:brief
Background read	feat.design (DES-02); feat.clarifications (DES-03)	journey:feat.design; journey:feat.clarifications
Lane tasks in scope	TSK-01 (STORY-01) and TSK-02 (STORY-02), both in ap_pipeline	feat.tasks (section 1)

1. Result

Repository	Task	Secrets required	Secrets granted	Access request needed	Source
ap_pipeline	TSK-01: optional `paid_date` in `transform.to_model`	None	None	No	feat.tasks (TSK-01); tool:repo-access; file:ap_pipeline/src/ap_pipeline/transform.py
ap_pipeline	TSK-02: new pure function `delays.delays_by_vendor` (no I/O)	None	None	No	feat.tasks (TSK-02); tool:repo-access

Granted secret names: none.

Outcome: this lane's tasks need no secret, and the permission table grants none for ap_pipeline. No access request is raised (tool:repo-access; feat.tasks).

2. Evidence

Check	Finding	Source
Permission table	"No secrets are required or granted for this repository"	tool:repo-access

Check	Finding	Source
Code that reads secrets	A case-insensitive search of the ap_pipeline checkout (excluding `.git`) for `environ`, `getenv`, `secret`, `token`, `password`, `api_key`, `credential`, `dbutils`, `databricks`, `http`, `urlopen` and `socket` found no match	file:ap_pipeline/src/ap_pipeline/ingest.py; file:ap_pipeline/src/ap_pipeline/transform.py; file:ap_pipeline/src/ap_pipeline/dq.py; file:ap_pipeline/src/ap_pipeline/pipeline.py; file:ap_pipeline/ci.py
Data source	The pipeline takes the feed as text: `run(csv_text)` calls `parse_feed`, then `to_model`, then `quality_report`. It opens no connection to a source system	file:ap_pipeline/src/ap_pipeline/pipeline.py; file:ap_pipeline/src/ap_pipeline/ingest.py
Task scope	TSK-01 changes only `transform.py`, `__init__.py` (version step) and `tests/test_pipeline.py`. TSK-02 adds `delays.py` and `tests/test_delays.py`, and its notes say "No I/O". Neither task touches `ingest.py`, `pipeline.py` or `schedule.json`	feat.tasks (TSK-01, TSK-02)
Design: purity	NF-10: "Every new function is pure and in-memory: no I/O, no network, no mutation of inputs"	journey:feat.design (A5)
Design: storage	DD-1: "No new repository, service, runtime, library or storage"; the Data boundary excludes "Storage, database, schema migration"	journey:feat.design (A1, A7)
Design: secrets	SE-4, "Secrets and personal data": "None added"; tests and examples use synthetic data	journey:feat.design (A6)
Clarifications: test data	CL-X9: "Synthetic only ... no secrets or personal data"	journey:feat.clarifications (section 2)
CI	`ci.py` runs compile, unit tests, a coverage gate and static checks locally. It reads no environment variable or credential	file:ap_pipeline/ci.py

3. Environments

The inputs name no deployment environments for ap_pipeline. feat.tasks names only the branches `main` (released), `dev` (integration) and `feature/<story>`. The permission table grants no secret for this repository, so the scope is "none" for every branch and environment of this lane (feat.tasks (section 2); tool:repo-access).

4. Open questions (non-blocking)

ID	Question	Interim answer	Owner (proposed)
SSQ-1	DE-13 schedules the pipeline (`schedule.json`: daily, `02:00`, `Asia/Kolkata`; unchanged by this feature per feat.design B1.1). No input names the scheduler platform, or says whether it needs a credential. Will DE-13 need a secret that this scope does not list?	No secret now. Re-run DE-02 (re-entry trigger) if DE-13 names a scheduler that needs a credential	Data engineering lead

No blocking questions.

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_pipeline] Tool registry: no secrets required or granted (permission table)