FEAT-ZD-48600 · DE-02 Access to secrets · Secrets granted for the task's environments (names only)

Data Engineering agent · item task.secrets_scope · source hobasa-data-engineering-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by Data engineer sim.data_engineer

task.secrets_scope: FEAT-ZD-48600

Secrets scope for the Data Engineering tasks of FEAT-ZD-48600 (ZD-48600, "Show which overdue invoices belong to vendors that usually pay late"). Step: DE-02 Access to secrets (attempt 1). This file lists secret **names only**. It contains no secret values. The restricted permission table is used by reference only, through the step's tool view.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	DE-02 Access to secrets (attempt 1)	record:brief
Owner / gate	Data engineer / no gate: automated checks, the independent judge and sampled human evaluation	record:brief
Inputs	feat.tasks (from hobasa-design-agent, commit b0fd4d2); org.permission_table (restricted, by reference)	record:brief
Repository in scope	ap_pipeline	feat.tasks (section 1, TSK-01 and TSK-02)

1. Data Engineering tasks in scope

Task	Story	Files in budget	External access needed	Source
TSK-01	STORY-01	`src/ap_pipeline/transform.py`, `src/ap_pipeline/__init__.py` (version step only), `tests/test_pipeline.py`	None. Coding uses synthetic feed v3 rows. Feed v3 in production (PQ-6) gates release, not coding	feat.tasks (TSK-01)
TSK-02	STORY-02	New `src/ap_pipeline/delays.py`, new `tests/test_delays.py`	None. This is a pure function with "No I/O"	feat.tasks (TSK-02)

TSK-03 to TSK-08 belong to the Data Science, Backend, Frontend and Testing lanes, so this agent does not assess them (feat.tasks, section 1).

2. Secrets required

None. TSK-01 and TSK-02 need no secret in any environment.

Evidence:

1. Both tasks change only Python source and its unit tests. TSK-02 is "No I/O", and TSK-01 builds on synthetic rows. `ingest.py`, `pipeline.py` and `schedule.json` are on TSK-01's "Must not change" list (feat.tasks, TSK-01 and TSK-02).
2. The pipeline entry point `run(csv_text)` receives the feed as text. It calls `parse_feed`, `to_model` and `quality_report` and opens no connection (file:ap_pipeline/src/ap_pipeline/pipeline.py).
3. Ingestion parses CSV text in memory with the standard-library `csv` and `io` modules. It reads no file, URL or credential (file:ap_pipeline/src/ap_pipeline/ingest.py).

4 The transform imports only `datetime`, `decimal` and `typing`. The data-quality report imports nothing. Both work on in-memory rows only and read no environment variable (file:ap_pipeline/src/ap_pipeline/transform.py; file:ap_pipeline/src/ap_pipeline/dq.py).

5 The package file contains only a docstring and `__version__ = "0.4.0"`. TSK-01 will step this version up (file:ap_pipeline/src/ap_pipeline/__init__.py; feat.tasks, section 2).

6 CI runs locally as `/usr/bin/python3 ci.py` (file:ap_pipeline/CLAUDE.md). `ci.py` compiles the code, runs the unit tests, checks coverage against `COVERAGE_MIN = 90.0` and runs static checks. It reads no environment variable or credential and makes no network call (file:ap_pipeline/ci.py).

7 The schedule file contains only `frequency`, `time` and `timezone` (daily, 02:00, Asia/Kolkata) and references no credential (file:ap_pipeline/src/ap_pipeline/schedule.json).

8 A search of the ap_pipeline checkout for `secret`, `token`, `password`, `api_key`, `environ`, `getenv` and `credential` found no matches (file:ap_pipeline, Grep over the repository).

9 The ap_pipeline tool registry states that no secrets are required or granted for this repository, based on the permission table (tool:repo-access).

3. Secrets granted (names only)

Environment	Secret name	Granted	Source
Development (`feature/<story>`, local CI)	none	Not needed	tool:repo-access; file:ap_pipeline/CLAUDE.md
Integration (`dev`)	none	Not needed	tool:repo-access; file:ap_pipeline/CLAUDE.md
Production (`main`)	none	Not needed	tool:repo-access; file:ap_pipeline/CLAUDE.md

Required compared with granted: nothing is required and nothing is granted. There is **no gap**, so **no access request is raised**. There is also no excess access to flag for revocation.

4. Data access boundary

- Coding and tests use synthetic data only (`SYN-INV-*`, "Synthetic Vendor <letter>"). No source-system production data is read (feat.tasks, TSK-01 dependencies and TSK-08 implementation notes).
- Feed v3 arriving in production (PQ-6) gates release only. This agent does not need a production feed credential for it (feat.tasks, TSK-01).

5. Re-entry

Run DE-02 again if a later step adds a connection. Examples are a file or network source in `ingest.py`, a scheduling workspace, or a transport layer. For this feature, feat.tasks keeps `ingest.py`, `pipeline.py` and `schedule.json` unchanged. It also says a transport layer would re-trigger DES-01 (feat.tasks, TSK-01 and TSK-06).

6. Open questions (non-blocking)

ID	Question	Interim answer	Owner (proposed)
SSQ-1	`schedule.json` defines a daily run. No input says which runtime executes the schedule, or whether that runtime needs its own credential to read the production feed. Does DE-13 scheduling need a secret?	TSK-01 and TSK-02 do not need one because they do not change the schedule. Check again at DE-13	Data engineering lead

7. Validation check

Check	Result	Source
Every DE task assessed for secrets	Pass (TSK-01, TSK-02)	feat.tasks
No secret values in this file	Pass (names only; none required)	record:brief
Required compared with granted	Pass: none required, none granted, no gap	tool:repo-access
No production data used	Pass (synthetic only)	feat.tasks
Blocking questions	None	—

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_pipeline] Tool registry: no secrets required or granted (permission table)