FEAT-ZD-48600 · DS-02 Access to secrets · Secrets granted for the task's environments (names only)

Data Science agent · item task.secrets_scope · source hobasa-data-science-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by automated checks and independent judge

task.secrets_scope: FEAT-ZD-48600

Secrets check for the Data Science lane of FEAT-ZD-48600 ("Show which overdue invoices belong to vendors that usually pay late"). This is DS-02 Access to secrets. The workbook action is to check access to the secrets the tasks need and to ask for access where needed. This file lists secret names only. It holds no secret values.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	DS-02 Access to secrets	record:brief
Owner / gate	Developer / no gate: automated checks, the independent judge and sampled human evaluation	record:brief
Inputs	feat.tasks (b0fd4d2); org.permission_table (restricted, passed by reference only; read through the tool view)	record:brief
Lane tasks	TSK-03 (STORY-03, `risk.vendor_risk`) and TSK-04 (STORY-04, `explain.build_explanation_request(..., risk=None)`), both in `ap_forecast`	feat.tasks (sections 1, 3)

1. Result

The Data Science tasks need no secrets, and none are granted. No access request is needed. The secrets scope is empty.

Check	Result	Source
Secrets granted for `ap_forecast`	None. The permission table grants no secrets for this repository	tool:repo-access
Secrets required by `ap_forecast`	None. The permission table requires no secrets for this repository	tool:repo-access
TSK-03 needs a secret	No. `vendor_risk` uses no LLM, makes no network call and does not read `models.json`. It calls only `predict_delay_days`, which computes from the history in memory	feat.tasks (TSK-03); journey:feat.clarifications (CL-DS4); file:ap_forecast/src/ap_forecast/predict.py
TSK-04 needs a secret	No. `build_explanation_request` builds and returns a request dict with `provider`, `model`, `max_tokens` and `messages`. It does not send the request, so it needs no provider credential. The provider and model come from `models.json` (`acme-llm`, `acme-text-2`) and stay unchanged	feat.tasks (TSK-04); journey:feat.clarifications (CL-DS8); file:ap_forecast/src/ap_forecast/explain.py; file:ap_forecast/src/ap_forecast/models.json
Secrets read by today's code	None. A search of the repository for secret, key, token, credential, password and environment-variable access matched only the `max_tokens` setting and the tests that check it	file:ap_forecast/src/ap_forecast/explain.py; file:ap_forecast/src/ap_forecast/models.json; file:ap_forecast/tests/test_forecast.py
CI command	`/usr/bin/python3 ci.py`, run in the repository	file:ap_forecast/README.md; file:ap_forecast/CLAUDE.md

Check	Result	Source
Secrets for CI	None. `ci.py` compiles the sources, runs the unit tests with a coverage gate and runs static checks. It reads no secret, credential or environment variable	file:ap_forecast/ci.py
Secrets for the existing tests	None. The tests build requests from `models.json` or from an explicit config dict, with no credential	file:ap_forecast/tests/test_forecast.py
Test data	Synthetic only, with no secrets or personal data	journey:feat.clarifications (CL-X9)
Secrets added by the design	None added. Tests and examples use synthetic data	journey:feat.design (SE-4)
External data flow	With `risk`, the explanation prompt also carries the vendor's risk label to the configured provider (`acme-llm`). The Architect must confirm this (TQ-8). That changes what the prompt says, not which secrets the lane needs	journey:feat.design (SE-3); journey:feat.clarifications (CL-DS8); feat.tasks (TSK-04)

2. Secrets scope (names only)

Secret name	Environment	Needed by	Granted	Access request
— (none)	—	—	—	Not needed

Source: tool:repo-access; feat.tasks (TSK-03, TSK-04).

3. Open questions (none blocking)

ID	Question	Interim answer	Owner (proposed)
SSQ-1	`explain.py` only builds the request for `acme-llm`. Whatever sends it would need the provider credential, and no input names that sender. Please confirm that credential is outside this lane's scope	Neither TSK-03 nor TSK-04 sends a request, and the design adds no secrets. Sending the risk label to `acme-llm` stays with the Architect (TQ-8) and gates release, not coding	Architect
SSQ-2	The permission table is restricted. This step read it only through the tool view, which answers per repository, not per environment. Please confirm that no environment grants or requires a secret for `ap_forecast`	Use the tool view's statement as given: no secrets are required or granted for this repository	Developer / shared services

4. Validation check

Check	Result	Source
Every lane task checked for secret needs	Pass (TSK-03, TSK-04)	feat.tasks (section 1)
Required secrets available with access	Pass. None are required	tool:repo-access
Access requests raised	None needed	tool:repo-access
Secret values or personal data in this file	None	—
Blocking questions	None	—

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_forecast] Tool registry: no secrets required or granted (permission table)