FEAT-ZD-48600 · DS-02 Access to secrets · Secrets granted for the task's environments (names only)

Data Science agent · item task.secrets_scope · source hobasa-data-science-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by automated checks and independent judge

task.secrets_scope: FEAT-ZD-48600 (Data Science lane, ap_forecast)

DS-02 Access to secrets (attempt 1). This step checks which secrets the Data Science tasks need in each environment, compares them with the permission table and asks for access where needed. Only secret **names** belong in this file. No values appear here.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	DS-02 Access to secrets (attempt 1)	record:brief
Owner / gate	Developer / automated checks, independent judge, sampled human evaluation	record:brief
Inputs	feat.tasks (commit b0fd4d2, produced by DES-04); org.permission_table (restricted, by reference through tool:repo-access)	record:brief; feat.tasks
Repository	ap_forecast, branch `feature/story`	feat.tasks (section 1, section 2); file:ap_forecast/CLAUDE.md

1. Data Science tasks in scope

Task	Story	What the code does	External call at run time?	Source
TSK-03	STORY-03	New `risk.vendor_risk(history)`: rule-based level from `predict_delay_days`. No LLM, no network, no `models.json` read	No	feat.tasks (TSK-03)
TSK-04	STORY-04	Adds `risk=None` to `explain.build_explanation_request`. The function only **builds** a request dict (provider, model, `max_tokens`, messages) from `config or load_config()`	No. The function sends nothing. Nothing new calls it with `risk`, and it is not part of the end-to-end wiring	feat.tasks (TSK-04); file: ap_forecast/src/ap_forecast/explain.py

Both tasks use only the Python 3.9 standard library, with no new technology (feat.tasks, preamble, DD-1). CI is the local command `/usr/bin/python3 ci.py`: compile, unit tests, `coverage` and AST static checks. It needs no credentials (file:ap_forecast/ci.py; file:ap_forecast/CLAUDE.md).

2. Code check: secret references in ap_forecast

I searched the whole checkout, excluding `.git`, case-insensitively for `environ`, `getenv`, `api_key`, `API_KEY`, `token`, `secret` and `password`.

Finding	Meaning	Source
`explain.py` line 15 and `models.json` line 4 match `max_tokens`	A model setting, not a credential	file:ap_forecast/src/ap_forecast/explain.py; file:ap_forecast/src/ap_forecast/models.json
`tests/test_forecast.py` lines 18–19 match `max_tokens`	The test passes an explicit config; no credential	file:ap_forecast/tests/test_forecast.py
No environment-variable reads, API keys, tokens or passwords	The code has no secret dependency today	file:ap_forecast/src/ap_forecast/explain.py; file:ap_forecast/ci.py

`models.json` names provider `acme-llm` and model `acme-text-2`. It holds no key, and the repository has no code that calls the provider (file:ap_forecast/src/ap_forecast/models.json; file:ap_forecast/src/ap_forecast/explain.py).

3. Secrets scope (names only)

Environment	Secrets required by TSK-03 / TSK-04	Granted (permission table)	Gap / access request
Local development and unit tests	None	None	None
CI (`ci.py`)	None	None	None
dev (integration branch)	None	None	None
main (released)	None	None	None

The permission table grants no secrets for ap_forecast and says none are required (tool:repo-access). This matches sections 1 and 2, so the required set and the granted set are both empty. **No access request is raised.** No excess access needs revoking.

4. Outcome

Secrets are available with the right permissions: the tasks need none, and none are granted. TSK-03 and TSK-04 can go on to DS-03 and DS-04 without any secrets prerequisite (tool:repo-access; feat.tasks).

5. Open questions (non-blocking)

ID	Question	Interim answer	Owner (proposed)
SSQ-1	If an `acme-llm` request is ever sent at run time, which runtime owns the provider credential and its permission-table entry? TSK-04 only builds the request. Sending the risk label to `acme-llm` waits on Architect confirmation (TQ-8), which gates release, not coding	Out of scope for this task: ap_forecast does not send the request, so it holds no credential	Architect / Shared services

6. Validation check

Check	Result	Source
Every DS task in feat.tasks considered (TSK-03, TSK-04)	Pass	feat.tasks (section 1)
Required secrets compared with the permission table	Pass: both sets are empty	tool:repo-access
No secret values or personal data in this file	Pass: no names to list	—
Blocking questions	None	—

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_forecast] Tool registry: no secrets required or granted (permission table)