FEAT-ZD-48600 · DS-01 Checking the coding prerequisites ■ · Repository (and Databricks) availability and write access

Data Science agent · item task.repo_access · source hobasa-data-science-agent/outputs/FEAT-ZD-48600/task.repo_access.md · approved by automated checks and independent judge

task.repo_access: FEAT-ZD-48600

Coding prerequisites for the Data Science lane of FEAT-ZD-48600. This is DS-01, "Checking the coding prerequisites". The workbook action is to check that the repository is available, create it if needed, and confirm write access.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	DS-01 Checking the coding prerequisites	record:brief
Owner / gate	Developer / automated checks, independent judge, sampled human evaluation	record:brief
Inputs	feat.tasks (b0fd4d2), org.engineering_stack (3b03f15)	record:brief
Lane tasks	TSK-03 (STORY-03, `vendor_risk`), TSK-04 (STORY-04, `build_explanation_request(..., risk=None)`)	feat.tasks (sections 1, 3)

1. Repositories this lane needs

Repository	Needed by	Language / test runner	CI command	Source
ap_forecast	TSK-03, TSK-04	Python 3.9, unittest	`/usr/bin/python3 ci.py`	feat.tasks (section 1); org.engineering_stack

Only ap_forecast is needed. The other tasks run in other lanes: ap_pipeline (TSK-01, TSK-02, Data Engineering), ap_aging (TSK-05, TSK-06, Backend) and ap_portal (TSK-07, Frontend) (feat.tasks section 1). Changes to those repositories are not in this lane's scope.

2. Availability and write access

Check	Result	Source
Repository available	Yes. ap_forecast is checked out locally	tool:repo-access
Repository creation needed	No. The repository already exists, so nothing new is created	tool:repo-access
Working branch	`feature/story`, created from `dev` at `d67e866`. The checkout's HEAD points to `refs/heads/feature/story`	tool:repo-access; file:ap_forecast/.git/HEAD
Branch tips	`main`, `dev` and `feature/story` all point to the same commit (`d67e866`…), so the feature branch has no commits yet	file:ap_forecast/.git/refs/heads/main; file:ap_forecast/.git/refs/heads/dev; file:ap_forecast/.git/refs/heads/feature/story
Branch roles	`main` (released), `dev` (integration), `feature/<story>`	file:ap_forecast/CLAUDE.md; org.engineering_stack
Write access	Yes. The agent identity can write; git status is clean	tool:repo-access

Check	Result	Source
Databricks / workspace / database	Not used. No Databricks or other workspace is used by ap_forecast, and no repository uses a database	tool:repo-access; org.engineering_stack

3. Repository readiness for TSK-03 and TSK-04

Item	Observed	Source
Code and test locations	Code in `src/ap_forecast/`, tests in `tests/`	file:ap_forecast/CLAUDE.md
Existing modules	`predict.py` provides `predict_delay_days(history)`, which TSK-03 calls. `explain.py` provides `build_explanation_request(vendor, predicted_days, config=None)`, which TSK-04 extends with `risk=None`. `risk.py` is new; TSK-03 creates it	file:ap_forecast/src/ap_forecast/predict.py; file:ap_forecast/src/ap_forecast/explain.py; feat.tasks (TSK-03, TSK-04)
Tests	`tests/test_forecast.py` holds `test_predict`, `test_request_uses_config` and `test_request_with_explicit_config`. TSK-03 adds a new `tests/test_risk.py`; TSK-04 extends `tests/test_forecast.py`	file:ap_forecast/tests/test_forecast.py; feat.tasks (section 2)
Current version	`__version__ = "0.9.0"`. TSK-03 owns the version step	file:ap_forecast/src/ap_forecast/__init__.py; feat.tasks (section 2)
Current exports	`__all__ = ["predict_delay_days", "build_explanation_request"]`	file:ap_forecast/src/ap_forecast/__init__.py
CI gate	`ci.py` checks compilation, runs the unit tests, requires coverage of at least 90 (`COVERAGE_MIN = 90.0`), and runs static checks. The static checks flag `print`, `eval` and `exec`, bare `except`, and lines longer than 140 characters	file:ap_forecast/ci.py; org.engineering_stack
CI dependency	`ci.py` imports the `coverage` package. CI was not run in this step, so whether `coverage` is installed on the runner is not confirmed here (see RAQ-1)	file:ap_forecast/ci.py
Commit convention	Commit messages start with the story ID (`STORY-03`, `STORY-04`); the task ID may follow	org.engineering_stack; feat.tasks (section 2); record:memory

4. Observations

1 **Branch name.** feat.tasks, org.engineering_stack and the repository's CLAUDE.md specify one feature branch per story (`feature/<story>`). The branch provided is the single branch `feature/story`, but this lane has two stories (STORY-03 and STORY-04). This step uses `feature/story` for both tasks, as the tool view provides. The story-ID commit prefixes still trace each commit to its story. This is listed as non-blocking question RAQ-2.

2 **How access was established.** DS-01 may not run shell commands under its tool policy. Availability, the branch's origin and write access come from the spine's repository-access tool view. Branch tips and repository layout come from reading files in the checkout. No product code was changed, and no git or CI commands were run in this step.

5. Outcome

The outcome is met: **ap_forecast is available, with write access, on `feature/story` (from `dev` at `d67e866`)**. No repository creation and no Databricks or database access are needed for TSK-03 or TSK-04 (tool:repo-access; org.engineering_stack).

6. Open questions (non-blocking)

ID	Question	Interim answer	Owner (proposed)
RAQ-1	Is the `coverage` package that `ci.py` imports installed for `/usr/bin/python3` on the runner?	Assume yes; the first CI run in DS-05/DS-06 will confirm	Developer / infra
RAQ-2	Should STORY-03 and STORY-04 use separate `feature/STORY-03` and `feature/STORY-04` branches instead of the single provided `feature/story`?	Use `feature/story` for both, with story-prefixed commits	Developer

[Tool result] [ap_forecast] Branch feature/story at d67e866; write access confirmed