FEAT-ZD-48600 · DS-07 Commit & Push · Commit traced to the story; CI result

Data Science agent · item task.commit · source hobasa-data-science-agent/outputs/FEAT-ZD-48600/task.commit.md · approved by automated checks and independent judge

task.commit: FEAT-ZD-48600 (Data Science lane, ap_forecast)

DS-07 Commit & Push (attempt 4). Workbook action: commit the code with a message that traces back to the user story, review and resolve any merge conflicts, push to the central repository, and confirm secrets access in all environments.

Result: the STORY-03 and STORY-04 code is committed on `feature/story` (commit `2e6fb82`), and CI passes on it. The commit message is `STORY # task.commit: FEAT-ZD-48600 (Data Science lane, ap_forecast)`. It does not start with a story ID, so it breaks the convention and does not trace to STORY-03 or STORY-04. Section 2 gives the corrected message, which the spine should apply before the push; this step may run no shell commands. The push to the central repository is the spine's job and follows this step's approval. No merge conflict needed manual resolution.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	DS-07 Commit & Push (attempt 4)	record:brief
Repository / branch	ap_forecast / `feature/story`	tool:repo; task.code (header)
Stories	STORY-03 (`vendor_risk`), STORY-04 (`build_explanation_request` with `risk`)	feat.stories (STORY-03, STORY-04); task.code (section 1)
Inputs	task.code (286af9a), task.unit_tests (79527ef), feat.stories (0590ea4)	record:brief
Shell in this step	Blocked by hook G9: DS-07 may run no shell commands, and git push, merge and reset are run only by the spine	tool:bash (hook response)

1. The commit

Item	Value	Source
Commit	`2e6fb82` on `feature/story`, made by the spine	tool:repo
Message (as committed)	`STORY # task.commit: FEAT-ZD-48600 (Data Science lane, ap_forecast)`	tool:repo
CI on the commit	Passed: tests 11, coverage 100.0%, static issues 0	tool:repo
Push to the central repository	Done by the spine after this step's checks and evaluation pass, not by this agent	record:brief; tool:bash (hook response)

1.1 Files in the change

File	Change	Produced by	Story	Source
`src/ap_forecast/risk.py`	New: `HIGH_ABOVE_DAYS = 30`, `MEDIUM_ABOVE_DAYS = 10`, `vendor_risk(history: Iterable[int]) -> str`, strict >	DS-05	STORY-03	task.code (sections 1, 2)
`src/ap_forecast/__init__.py`	Exports `vendor_risk` in `__all__`; `__version__` goes from `"0.9.0"` to `"0.10.0"`	DS-05	STORY-03	task.code (sections 1, 2)
`tests/test_risk.py`	New: `VendorRiskTest` with six tests (levels, boundaries, empty and early, any iterable, no LLM, exported)	DS-06	STORY-03	task.unit_tests (sections 1, 2.1)
`src/ap_forecast/explain.py`	`build_explanation_request(..., risk=None)`; appends `" Risk level: {risk}."` only when `risk is not None`	DS-05	STORY-04	task.code (sections 1, 2)
`tests/test_forecast.py`	Adds `test_request_with_risk` and `test_request_without_risk_unchanged`; `test_predict`, `test_request_uses_config` and `test_request_with_explicit_config` are unchanged	DS-06	STORY-04	task.unit_tests (sections 1, 2.2)
`README.md`	Public API table, example, CI command	DS-05	STORY-03, STORY-04	task.code (section 1)
`docs/ap_forecast.md`	New module documentation and changelog	DS-05	STORY-03, STORY-04	task.code (section 1)

`src/ap_forecast/predict.py` and `models.json` are unchanged (task.code section 1).

2. Commit message: fix before the push

The convention is "Commit messages start with the story ID" (record:memory). The committed message starts with `STORY #`, which is not a story ID. It names neither STORY-03 nor STORY-04, and the rest of it is this output file's heading, not a description of the change. In that form, `git log` cannot be traced back to the stories.

Requested action (spine, before the push): reword the message of the commit on `feature/story`. Only the message changes; the tree stays the same. Use this message:

```
STORY-03, STORY-04: add vendor_risk and risk-aware explanation request

FEAT-ZD-48600 / EP-1 / FT-2 / TK-03.1, TK-03.2, TK-04.1, TK-04.2

STORY-03 (AC-03.1 to AC-03.8)
- New src/ap_forecast/risk.py: vendor_risk(history) returns 'high' when the
  predicted delay is > 30 days, 'medium' when > 10, else 'low' (strict >, on
  the rounded prediction from predict_delay_days). No LLM call and no
  models.json read.
- Export vendor_risk in __all__; version 0.9.0 -> 0.10.0.
- New tests/test_risk.py: levels, boundaries 30/10 (L-007), empty and early
  histories, any iterable, no LLM, export.

STORY-04 (AC-04.1 to AC-04.5)
```

```
- build_explanation_request(vendor, predicted_days, config=None, risk=None):
  when risk is not None the prompt ends with " Risk level: <risk>."; without
  risk (or risk=None) the request is unchanged. Provider, model and max_tokens
  still come from config or models.json.
- tests/test_forecast.py: test_request_with_risk and
  test_request_without_risk_unchanged; existing tests unchanged.

Docs: README.md and new docs/ap_forecast.md.
```

The one commit holds both stories, so the subject names both. Splitting it into one commit per story would need a reset, and only the spine may run that (tool:bash hook response). A reworded single commit is enough for traceability.

3. CI result

Check	Result	Source
Compile	Pass	task.unit_tests (section 3)
Tests	11 run, 0 failures, 0 errors	task.unit_tests (section 3); tool:repo
Coverage (gate: at least 90%)	100.0, pass	task.unit_tests (section 3); tool:repo; record:brief
Static issues	None	task.unit_tests (section 3); tool:repo
Overall	Passed	task.unit_tests (section 3); tool:repo

The DS-06 run on the working tree and the tool view's CI on the commit report the same figures. Rewording the message changes no file, so the result still holds after the reword.

4. Merge conflicts

The spine's commit on `feature/story` succeeded, and CI passed on it (tool:repo). No conflict was reported and nothing needed manual review or resolution. The change touches only ap_forecast files that this lane owns (task.code section 1). This step cannot fetch the remote (tool:bash hook response). If the remote branch has moved by the time the spine pushes, the push will be rejected, and the conflict goes to the Developer for manual review (open question CP-2).

5. Push target

Item	Value	Source
Push	`feature/story` to the central ap_forecast repository, after the reword in section 2	tool:repo; record:brief
Not pushed	`main` and `dev`. This agent may not push to protected main or merge	record:brief (guardrails)
PR	Not raised in this step (open question CP-3)	record:brief

6. Secrets, database and environments

Item	Finding	Source
Secrets in the commit	None. A search of the checkout for `api_key`, `secret`, `token` and `password` found only the `max_tokens` config field	tool:grep; task.code (section 5)
Secrets needed by the code or the tests in any environment (local/CI, `feature/<story>`, `dev`, `main`)	None	task.code (section 5); task.unit_tests (section 4)
Secrets needed for the push	Write credentials for the central repository. The spine runs the push; this agent does not use them	tool:bash (hook response); record:brief

Item	Finding	Source
Database / Databricks	None	task.code (section 5)

7. Story traceability

Story	Acceptance criteria	Code	Tests	Commit
STORY-03	AC-03.1 to AC-03.8	`risk.py`, `__init__.py`	`tests/test_risk.py`	Spine commit on `feature/story` (message to be reworded)
STORY-04	AC-04.1 to AC-04.5	`explain.py`	`tests/test_forecast.py`	Spine commit on `feature/story` (message to be reworded)

Sources: feat.stories (STORY-03, STORY-04); task.code (section 3); task.unit_tests (section 2); tool:repo.

8. Open questions (non-blocking)

ID	Question	Interim answer	Owner (proposed)
CP-0	The spine's commit has the message `STORY # task.commit: …`, which does not start with a story ID. Will the spine reword it to the section 2 message before the push?	Reword the message only, then push; do not push the current message	Developer / spine owner
CP-1	The workbook says "push the code to central/main repository", but agents may not push to protected main. Is pushing `feature/story` the intended reading?	Push `feature/story` only; `dev` and `main` get the change through the PR and the deployment merge	Developer
CP-2	This step cannot fetch the remote to confirm that `feature/story` has not moved. Will the spine fetch before the push and send any conflict to the Developer?	Fetch before the push; on rejection, the Developer resolves manually	Developer / spine owner
CP-3	The workbook outcome says "PR is being raised". Is the PR expected from this step, or from the later PR step?	The later PR step raises it, after the push	Developer
Carried	CQ-C2 (version `0.10.0`), CQ-DS-1 (test file split), UT-1 (AC-03.5, AC-03.6, AC-04.5 rest on interim answers), CQ-DS-3, RAQ-1, TQ-8, PQ-5	Unchanged	As in task.code and task.unit_tests

9. Validation check

Check	Result	Source
Code committed on the story branch	Yes, on `feature/story`	tool:repo
Commit message traces to the story	**No, as committed.** The corrected message is in section 2 (CP-0)	record:memory; tool:repo
CI green on the commit (compile, tests, coverage of at least 90%, static)	Yes (section 3)	task.unit_tests (section 3); tool:repo; record:brief
Merge conflicts	None reported (section 4)	tool:repo
Pushed	Left to the spine, after approval	record:brief; tool:bash (hook response)

Check	Result	Source
No secrets or personal data in the commit	Yes (section 6)	tool:grep
No push to `main`, no merge, no self-approval by this agent	Yes	record:brief; tool:bash (hook response)
Blocking questions	None	—

[Tool result] [ap_forecast] Commit 2e6fb82 on feature/story: 'STORY # task.commit: FEAT-ZD-48600 (Data Science lane, ap_forecast)'. CI PASSED; tests 11; coverage 100.0%; static issues 0