FEAT-ZD-48600 · DS-02 Access to secrets · Secrets granted for the task's environments (names only)

Data Science agent · item task.secrets_scope · source hobasa-data-science-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by automated checks and independent judge

task.secrets_scope: FEAT-ZD-48600 (Data Science lane, ap_forecast)

This file is DS-02, Access to secrets. It records which secrets the Data Science tasks need in each environment and which secrets are granted for them. It gives names only and contains no secret values. org.permission_table is restricted, so this step uses it only through the tool view (tool:repo-access) and does not copy it here. The input feat.tasks comes from hobasa-design-agent at commit b0fd4d2 (record:brief).

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	DS-02 Access to secrets	record:brief
Owner / gate	Developer / automated checks, independent judge, sampled human evaluation	record:brief
Lane / repository	Data Science / ap_forecast	feat.tasks (section 1)
Tasks in scope	TSK-03 (STORY-03), TSK-04 (STORY-04)	feat.tasks (section 1)
Permission source	Tool registry for ap_forecast: the permission table requires and grants no secrets for this repository	tool:repo-access

1. Secrets needed, by task

Task	What it does	External call or credential needed?	Secrets needed	Source
TSK-03	Adds `vendor_risk(history)` in a new `risk.py`. It returns a rule-based level (`'high'`, `'medium'` or `'low'`) from the existing `predict_delay_days`	No. The task specifies no LLM, no network and no `models.json` read. `risk.py` imports only `predict_delay_days`	None	feat.tasks (TSK-03)
TSK-04	Adds a `risk=None` parameter to `build_explanation_request`. When `risk` is given, the prompt ends with `"Risk level: {risk}."`	No new access. The provider, model and `max_tokens` still come from `config or load_config()`, and `models.json` stays unchanged. The function builds and returns a request dict and does not send it. Sending the label to `acme-llm` waits on Architect confirmation (TQ-8), which gates release, not coding	None	feat.tasks (TSK-04); file: ap_forecast/src/ap_forecast/explain.py

2. Evidence from the repository

File	What it does	Credential, environment variable or network use	Source
`predict.py`	Imports `statistics.mean` and `typing.Iterable` and returns the rounded mean of past delays	None	file:ap_forecast/src/ap_forecast/predict.py
`explain.py`	Imports `json` and `pathlib`, reads `models.json` from the package directory, and returns a dict with `provider`, `model`, `max_tokens` and `messages`	None. It sends no request	file:ap_forecast/src/ap_forecast/explain.py
`models.json`	Names the provider `acme-llm` and the model `acme-text-2`	None. It contains no key and no endpoint	file:ap_forecast/src/ap_forecast/models.json
`__init__.py`	Re-exports `predict_delay_days` and `build_explanation_request`	None	file:ap_forecast/src/ap_forecast/__init__.py
`tests/test_forecast.py`	Tests `predict_delay_days` and checks the built request, using the packaged config or an explicit config dict	None. No live provider is called	file:ap_forecast/tests/test_forecast.py
`ci.py`	Compiles the code, runs the unit tests with coverage, and runs static checks	None. It reads no credential	file:ap_forecast/ci.py
`CLAUDE.md`	States the language (Python 3.9, standard library), the CI command `/usr/bin/python3 ci.py` and the branches `main` (released), `dev` (integration) and `feature/<story>`	None	file:ap_forecast/CLAUDE.md

3. Secrets scope by environment (names only)

Environment	Secrets required	Secrets granted	Access request raised	Source
CI (`/usr/bin/python3 ci.py`)	None	None	No	tool:repo-access; file:ap_forecast/CLAUDE.md
`feature/<story>`	None	None	No	tool:repo-access; feat.tasks (section 2); file:ap_forecast/CLAUDE.md
`dev` (integration)	None	None	No	tool:repo-access; feat.tasks (section 2); file:ap_forecast/CLAUDE.md
`main` (released)	None	None	No	tool:repo-access; feat.tasks (section 2); file:ap_forecast/CLAUDE.md

Result: the required secrets and the granted secrets match, and both lists are empty. No access request is needed. The outcome "Secrets are available with access permissions" holds because the Data Science tasks need no secrets (tool:repo-access; feat.tasks).

4. Boundaries and watch items

- Neither task adds an outbound call from ap_forecast. TSK-03 explicitly uses no network. Nothing new calls TSK-04's `build_explanation_request` with `risk`, and it is not part of the end-to-end wiring (feat.tasks, TSK-03 and TSK-04).

- Whatever component sends the explanation request to `acme-llm` will need a provider credential, and that component is outside TSK-03 and TSK-04. If a later change makes ap_forecast call the provider directly, this step must be re-entered and a credential requested through the permission table (non-blocking question SSQ-1).
- The planned tests need no live provider. `test_vendor_risk_no_llm` patches `ap_forecast.explain.load_config` to fail, and the TSK-04 tests check the text of the built prompt (feat.tasks, TSK-03 and TSK-04 "Tests to add").
- This file contains no secret value, credential name or personal data.

5. Open questions (non-blocking)

ID	Question	Interim answer	Owner (proposed)
SSQ-1	Which component sends the `build_explanation_request` payload to `acme-llm`, and who owns its credential?	Outside TSK-03 and TSK-04. The permission table grants ap_forecast no secrets, and this lane needs none	Architect / Shared services

[Tool result] [ap_forecast] Tool registry: no secrets required or granted (permission table)