FEAT-ZD-48600 · FE-02 Access to secrets · Secrets granted for the task's environments (names only)

Frontend agent · item task.secrets_scope · source hobasa-frontend-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by automated checks and independent judge

task.secrets_scope: FEAT-ZD-48600

Secrets scope for the Frontend task TSK-07 (STORY-07, "Render the overdue risk table") in repository `ap_portal`. This is FE-02 Access to secrets (attempt 1). It lists secret names only. No secret values appear here, and none were read.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	FE-02 Access to secrets (attempt 1)	record:brief
Task in scope	TSK-07 / STORY-07, Frontend lane, `ap_portal`	feat.tasks (sections 1, 3 TSK-07)
Inputs	feat.tasks (from hobasa-design-agent at commit b0fd4d2); org.permission_table (restricted, passed by reference only)	record:brief
Permission source	Tool registry for `ap_portal`	tool:repo-access

1. Secrets required by the task

None. TSK-07 adds a pure render function, `renderOverdueRisk(rows)`, plus private helpers and constants in `src/ap_portal/index.js`, a version step in `package.json`, and tests in `tests/portal.test.js` (feat.tasks TSK-07). It takes the CT-1 rows as an argument. It has no transport layer, network call, API key, database or LLM access. The task depends only on the CT-1 field list, not on Backend code (feat.tasks TSK-06, TSK-07).

What the repository shows:

Check	Finding	Source
Runtime dependencies	`package.json` declares no dependencies, only the `ci` script `node ci.mjs`	file:ap_portal/package.json
Environment use in CI	`ci.mjs` copies `process.env` and sets only `NODE_PATH: 'src'`; it reads no secret variable	file:ap_portal/ci.mjs
Secret references in the repository	A case-insensitive search for `process.env`, `secret`, `token`, `apikey`, `api_key` and `password` (excluding `.git`) found one match: the `NODE_PATH` line in `ci.mjs`	file:ap_portal/ci.mjs
Technology	Node.js 22 CommonJS and `node:test` only; no new technology	feat.tasks (header, DD-1); file:ap_portal/CLAUDE.md

2. Secrets granted for the task's environments (names only)

Environment	Secrets required	Secrets granted	Access request needed
Local / CI (`node ci.mjs`)	None	None	No
`feature/<story>` → `dev` (integration)	None	None	No
`main` (released)	None	None	No

The permission table grants no secrets to this repository, and none are required (tool:repo-access). Required and granted match, so the task does not need extra access and has no excess access to flag.

3. Access requests raised

None. No `capability_request` was needed.

4. Notes for later steps

- FE-04 Coding should not add environment variables, API keys or network calls. TSK-07 is a pure render function (feat.tasks TSK-07). If the scope changes and a secret becomes necessary, re-run this step; it is a re-entry trigger.
- The end-to-end harness TSK-08 belongs to the Testing Agent and runs on a synthetic feed only (feat.tasks TSK-08). It is outside this Frontend secrets scope.

5. Open questions

None blocking. None non-blocking.

6. Validation check

Check	Result	Source
Secret names only, no values	Pass	record:brief
Required secrets match granted secrets	Pass (none required, none granted)	tool:repo-access; feat.tasks (TSK-07)
Restricted permission table passed by reference only	Pass (not quoted)	record:brief
Blocking questions	None	—

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_portal] Tool registry: no secrets required or granted (permission table)