FEAT-ZD-48600 · FE-02 Access to secrets · Secrets granted for the task's environments (names only)

Frontend agent · item task.secrets_scope · source hobasa-frontend-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by automated checks and independent judge

task.secrets_scope: FEAT-ZD-48600 (Frontend lane)

FE-02 Access to secrets. This file records the secrets the Frontend lane needs for its task, and the secrets granted for them. It lists names only and holds no secret values.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	FE-02 Access to secrets	record:brief
Frontend task	TSK-07 (STORY-07): render the overdue risk table SC-1	feat.tasks (section 1, TSK-07)
Repository	ap_portal	feat.tasks (section 1, TSK-07)
Permission source	org.permission_table (restricted: passed by reference only, summarised by the tool view)	record:brief; tool:repo-access

1. Secrets the task needs

None. The evidence:

Check	Finding	Source
What the task builds	`renderOverdueRisk(rows)` is an exported function that returns an HTML string from the rows it is given. Its private helpers are `escapeHtml`, `toTwoDecimalString` and `riskClass`, and it uses the constants `RISK_CLASSES` and `OVERDUE_HEADINGS`. Invalid input raises `TypeError`.	feat.tasks (TSK-07 goal and implementation notes)
Files in the task's budget	`src/ap_portal/index.js`, `package.json` (version only) and `tests/portal.test.js`	feat.tasks (TSK-07 "Files in budget")
Calls to other services	None. The task depends only on the CT-1 field list. It can be built alongside TSK-06 and does not call TSK-06's code. There is no transport layer: TSK-06 rules one out, because adding one would re-trigger DES-01.	feat.tasks (TSK-06 "Must not change"; TSK-07 "Depends on")
Current source	`index.js` exports `VERSION`, `LABELS`, `formatAmount` and `renderAgingSummary`. It has no `require`, no network calls and does not read the environment.	file:ap_portal/src/ap_portal/index.js
Dependencies	`package.json` declares no dependencies and has one script, `ci` (`node ci.mjs`). No registry token is needed.	file:ap_portal/package.json
CI	`ci.mjs` copies `process.env` and adds `NODE_PATH: 'src'`. It reads no named secret. Its only steps are syntax checks, `node --test` with coverage, and static line checks.	file:ap_portal/ci.mjs

Check	Finding	Source
Tests	`tests/portal.test.js` loads only `node:test`, `node:assert` and `ap_portal`. Its tests call `formatAmount` and `renderAgingSummary` with literal values only, with no network access, file reads or environment reads.	file:ap_portal/tests/portal.test.js
Test data	The end-to-end proof (TSK-08) uses a synthetic feed only (`SYN-INV-*`). The Testing Agent owns it, not this lane.	feat.tasks (TSK-08 implementation notes)

2. Secrets granted

Environment	Secret names granted	Source
ap_portal, every environment the task uses (local build, CI)	None	tool:repo-access ("no secrets are required or granted for this repository (permission table)")

3. Gap between need and grant

Needed	Granted	Gap	Access request
None	None	None	No request raised. Asking for a secret the task does not need would grant more access than needed.

4. Outcome

The Frontend lane can start FE-03 and FE-04 for TSK-07 without any secret. This file grants no secret, and none should be added to the ap_portal branch, CI settings or test data for this task. If a later step adds a network call, a dependency that needs a registry token, or a deployed environment, FE-02 must run again, because that would be a re-entry trigger.

5. Open questions

None blocking. None non-blocking.

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_portal] Tool registry: no secrets required or granted (permission table)