FEAT-ZD-48600 · FE-03 Identify the components/layers to be changed · Components, layers, sources or pipelines to change

Frontend agent · item task.components · source hobasa-frontend-agent/outputs/FEAT-ZD-48600/task.components.md · approved by automated checks and independent judge

task.components: FEAT-ZD-48600

This file lists the components and layers that the Frontend lane creates or updates for FEAT-ZD-48600. Step: FE-03, "Identify the components/layers to be changed" (record:brief). The Frontend lane owns one task, TSK-07 (STORY-07, "Render the overdue risk table"), in repository ap_portal (feat.tasks, sections 1 and 3; task.repo_access, section 1).

This step only reads code. It changes no file in ap_portal. The current code is described from the ap_portal checkout on branch `feature/story` (tool:repo; task.repo_access, section 1; file:ap_portal/...). Statements marked **agent judgement** are this agent's proposal. No input states them as fact.

1. What the existing code does

Item	Current state	Source		
Repository layout	One source module, `src/ap_portal/index.js`, and one test file, `tests/portal.test.js`. The other files are `package.json`, `ci.mjs`, `README.md` and `CLAUDE.md`. There is no stylesheet, host page, router, service or transport layer	tool:repo; task.repo_access (section 2); file:ap_portal/package.json; file:ap_portal/ci.mjs; file:ap_portal/README.md; file:ap_portal/CLAUDE.md		
Layers	One layer: pure view helpers that take plain values and return an HTML string	file:ap_portal/src/ap_portal/index.js ("AP portal view helpers")		
`VERSION`	`'2.3.0'`. `package.json` has `"version": "2.3.0"`	file:ap_portal/src/ap_portal/index.js; file:ap_portal/package.json		
`LABELS`	Constant map from aging buckets to labels	file:ap_portal/src/ap_portal/index.js		
`formatAmount(value)`	`Number(value \`	\	0).toFixed(2)`. This formats through a binary float, against D-2026-044, so the new code must not use it. TQ-2 stays open	file:ap_portal/src/ap_portal/index.js; feat.trd (F-12); record:memory (D-2026-044)
`renderAgingSummary(buckets)`	Builds `<table class="aging-summary">` from template strings. It escapes nothing. The amount cell has `class="amount"`	file:ap_portal/src/ap_portal/index.js; feat.trd (F-13)		
Exports	`module.exports = { VERSION, LABELS, formatAmount, renderAgingSummary }`	file:ap_portal/src/ap_portal/index.js		

Item	Current state	Source		
Callers	`formatAmount` is called only by `renderAgingSummary` and by the tests. The repository has no other source module	file:ap_portal/src/ap_portal/index.js; file:ap_portal/tests/portal.test.js; tool:repo		
Existing tests	`formats amounts with two decimals` and `renders every bucket in order`. Both load the package with `require('ap_portal')`	file:ap_portal/tests/portal.test.js		
CI	Runs `node --check` on every `src/ap_portal/*.js` file. Tests run with `node --test` and `NODE_PATH=src`. Line coverage of `src/**` must be at least 90. CI fails on any line in `src/ap_portal/*.js` that matches `console\.log` or `\beval\(`, or is longer than 140 characters	file:ap_portal/ci.mjs		

2. Components and layers to create or update

The smallest change that meets STORY-07 is additive and stays in one existing module. It adds one exported function, its private helpers and two constants to `src/ap_portal/index.js`. It adds no new module, no new layer and no dependency (feat.design B4.1, DD-1; feat.tasks TSK-07 "Files in budget").

#	File / layer	Component	Kind	What changes	Why it is needed	Source
FC-1	`src/ap_portal/index.js` (view helper layer)	`RISK_CLASSES = ['high', 'medium', 'low', 'unknown']`	New module constant	Allow-list of the four risk values	The row class comes only from known values. An unexpected value renders `risk-unknown` (AC-07.3, AC-07.8)	feat.design (B4.2, B4.3); feat.trd (IF-7.4); feat.stories (STORY-07)
FC-2	`src/ap_portal/index.js`	`OVERDUE_HEADINGS = ['Invoice', 'Vendor', 'Days overdue', 'Amount']`	New module constant	The four headings, in order. The header row is built from this constant	AC-07.1, AC-07.2; NFR-10 ("Days overdue", never "Late")	feat.design (B4.2, B4.3); feat.trd (IF-7.2); feat.prd (AC-19, NFR-10)
FC-3	`src/ap_portal/index.js`	`escapeHtml(value)`	New private helper (not exported)	`String(value)` with &, <, >, " and ' escaped	`id` and `vendor` come from feed data, and the existing code escapes nothing (AC-07.7)	feat.design (B4.2, SE-2); feat.trd (IF-7.7, F-13, S-4)

#	File / layer	Component	Kind	What changes	Why it is needed	Source
FC-4	`src/ap_portal/index.js`	`toTwoDecimalString(value)`	New private helper (not exported)	String-only. The value must be a string that matches `^-?\d+(\.\d{1,2})?$`. It is padded to two decimals as a string (`"980.5"` → `980.50`). Anything else throws `TypeError`. `Number()`, `parseFloat` and `formatAmount` are never used	NFR-3; D-2026-044; AC-07.5, AC-07.6	feat.design (B4.2, B4.4, DD-5, DD-8); feat.tasks (TSK-07 implementation notes); record:memory (D-2026-044, L-011)
FC-5	`src/ap_portal/index.js`	`riskClass(risk)`	New private helper (not exported)	`'risk-' + risk` when `risk` is in `RISK_CLASSES`, else `'risk-unknown'`	AC-07.3, AC-07.8	feat.design (B4.2); feat.trd (IF-7.4)
FC-6	`src/ap_portal/index.js`	`renderOverdueRisk(rows)`	New exported function	Returns `''` when `rows` is `undefined`, `null` or `[]`. Throws `TypeError` when `rows` is any other non-array value. Otherwise returns `<table class="overdue-risk">`, a plain header row `<tr><th>…</th></tr>`, one `<tr class="risk-…">` per row in the given order with cells id, vendor, days and amount (`class="amount"`), then `</table>`. `days` must pass `Number.isInteger`, else `TypeError`. No re-sorting, no Risk column or risk text, no row actions	STORY-07 AC-07.1 to AC-07.9; screen SC-1	feat.design (HC-8, B4.2 algorithm, B4.4); feat.trd (IF-7.1 to IF-7.8); feat.tasks (TSK-07); feat.stories (STORY-07)
FC-7	`src/ap_portal/index.js`	`module.exports`	Updated (additive)	Adds `renderOverdueRisk`: `{ VERSION, LABELS, formatAmount, renderAgingSummary, renderOverdueRisk }`. The helpers stay private	AC-07.10; every existing export is kept	feat.design (B4.2); feat.stories (AC-07.10); file: ap_portal/CLAUDE.md ("Keep existing public signatures; add new functions for new behaviour.")

#	File / layer	Component	Kind	What changes	Why it is needed	Source
FC-8	`src/ap_portal/index.js`	`VERSION`	Updated	One minor step from `'2.3.0'`. The lane confirms the exact next number	DD-11; the version must move together with `package.json`	feat.tasks (section 2 "Version step", TSK-07 "Done when"); feat.design (DD-11)
FC-9	`package.json`	`"version"`	Updated (version only)	Same value as FC-8	Keeps `package.json` in step with `VERSION`	feat.tasks (TSK-07 "Files in budget", "Done when"); file:ap_portal/package.json
FC-10	`tests/portal.test.js` (test layer)	New `node:test` cases	Updated (additive)	The B4.5 tests: `renders overdue risk table`, `maps every risk value to its class`, `returns empty string for no rows`, `shows amount strings unchanged`, `pads short amounts as strings`, `rejects non-string amounts`, `escapes id and vendor`, `unexpected risk renders risk-unknown`. Also the coverage cases listed in feat.tasks: non-array `rows` → `TypeError`; non-integer `days` → `TypeError`; `null` → `''`; an amount with an exponent, a thousands separator or three decimals → `TypeError`. The two existing tests stay unchanged	Line coverage of at least 90 in CI; T-12 to T-16	feat.design (B4.5); feat.tasks (TSK-07 "Tests to add"); feat.trd (T-12 to T-16); file:ap_portal/ci.mjs

FC-10 is listed because `tests/portal.test.js` is a file in the TSK-07 budget and this task changes it (feat.tasks TSK-07 "Files in budget").

2.1 Why this is the minimum

- **One module, no new file.** Agent judgement: a new `src/ap_portal/*.js` file would fall outside the TSK-07 file budget (feat.tasks, section 2 "Size budget" and TSK-07). Every CI check in `ci.mjs` would also apply to it (file:ap_portal/ci.mjs).

- **No change to existing code.** LABELS, `formatAmount`, `renderAgingSummary` and their tests stay as they are (feat.tasks TSK-07 "Must not change"; feat.design HC-9). `formatAmount` is not reused because it goes through a float (feat.trd F-12).
- **Same style as the existing renderer.** Like `renderAgingSummary`, `renderOverdueRisk` builds the table from template strings and `join('')`, with no `<thead>`/`<tbody>` (feat.design B4.2 step 4; feat.trd IF-7.2).
- **Helpers stay private.** Only `renderOverdueRisk` is added to the public exports (feat.design B4.2 `module.exports`).
- **Header from a constant.** Agent judgement: the header row is built by mapping over `OVERDUE_HEADINGS`, so each heading appears only once in the code.

3. Components and layers not changed

Item	Reason	Source
LABELS, `formatAmount`, `renderAgingSummary`	Must not change. TQ-2 (the float inside `formatAmount`) is a separate decision	feat.tasks (TSK-07); feat.trd (C-9, F-12, TQ-2)
Existing tests in `tests/portal.test.js`	Must pass unchanged (T-16, AC-07.10)	feat.stories (AC-07.10); feat.trd (T-16)
`ci.mjs`, `CLAUDE.md`, `README.md`	Outside the TSK-07 file budget	feat.tasks (TSK-07 "Files in budget")
Host page, navigation, filters, row actions, transport for CT-1	Out of scope for this design. A transport would re-trigger DES-01	feat.design (A1, A3 "Transport for CT-1", A8, DD-3)
Stylesheet for the `risk-*` and `overdue-risk` classes	ap_portal has no stylesheet, and the design changes no host page. The component only sets the classes	tool:repo; feat.design (A1)
Other repositories (ap_aging serialiser, end-to-end harness)	Owned by the Backend lane (TSK-06) and the Testing Agent (TSK-08). The Frontend lane builds against the CT-1 field list only	feat.tasks (TSK-06, TSK-07 "Depends on", TSK-08); feat.design (A3 CT-1)
Database, Databricks	Not used	task.repo_access (section 1)
Secrets	None added	feat.design (SE-4)

4. Input contract the component consumes (CT-1)

Field	Type in CT-1	How `renderOverdueRisk` uses it	Source
`id`	string	Escaped text in the Invoice cell	feat.design (A3 CT-1, B4.2)
`vendor`	string	Escaped text in the Vendor cell	feat.design (A3 CT-1, B4.2)
`days`	integer	Integer text in the Days overdue cell; `TypeError` if it fails `Number.isInteger`	feat.design (A3 CT-1, B4.4); feat.trd (IF-7.6)
`amount`	two-decimal string	Passed through `toTwoDecimalString` into the Amount cell, which has `class="amount"`	feat.design (A3 CT-1, B4.2); feat.trd (IF-7.3, IF-7.5)
`risk`	one of `high`, `medium`, `low`, `unknown`	Becomes the row class through `riskClass`; never shown as text	feat.design (A3 CT-1); feat.trd (IF-7.4, IF-7.8)

Example (synthetic): `[{"id": "SYN-INV-004", "vendor": "Synthetic Vendor A", "days": 75, "amount": "1250.00", "risk": "high"}]` (feat.design A3).

5. CI constraints the change must respect

Constraint	Effect on the components	Source
Line coverage of `src/**` at least 90	Every branch of FC-3 to FC-6 needs a test, including each `TypeError` path	file:ap_portal/ci.mjs; feat.tasks (section 2 "CI bar")

Constraint	Effect on the components	Source
No line in `src/ap_portal/*.js` matching `console\.log` or `\beval\(`	The rule applies to comments too. The new code has no logging	file:ap_portal/ci.mjs; feat.tasks (section 2 "CI bar"); feat.trd (IF-7.9)
No line longer than 140 characters	The table template is split across lines where needed	file:ap_portal/ci.mjs
`node --check` on each source file	CommonJS syntax for Node.js 22; the existing `'use strict'` line stays	file:ap_portal/ci.mjs; file:ap_portal/CLAUDE.md; file:ap_portal/src/ap_portal/index.js

6. Traceability

Component	Story AC	TRD	Design
FC-1, FC-5	AC-07.3, AC-07.8	IF-7.4; T-12, T-15	B4.2; HC-8
FC-2	AC-07.1, AC-07.2	IF-7.2; T-12	B4.2
FC-3	AC-07.7	IF-7.7; T-15	B4.2; SE-2
FC-4	AC-07.5, AC-07.6	IF-7.5; T-14	B4.2; DD-5, DD-8
FC-6	AC-07.1 to AC-07.4, AC-07.9	IF-7.1 to IF-7.8; T-12, T-13	B4.2, B4.4; HC-8
FC-7	AC-07.10	C-9; T-16	B4.2
FC-8, FC-9	TK-07.5	T-A6	DD-11
FC-10	AC-07.1 to AC-07.10	T-12 to T-16	B4.5

Sources: feat.stories (STORY-07); feat.trd (IF-7, section 5); feat.design (B4); feat.tasks (TSK-07).

7. Open questions (none blocking)

ID	Question	Interim, as in the approved design	Owner (proposed)
CQ-FE-1	CT-1 types `id` and `vendor` as strings. No input says what to do when a row is missing either field or gives a non-string. The design's `escapeHtml` uses `String(value)`, so a missing value would render as the text `undefined`. Should `renderOverdueRisk` throw `TypeError` instead, as it does for `amount` and `days` (DD-8)?	Follow feat.design B4.2: `String(value)`, then escape	Architect
CQ-FE-2	Who styles the `overdue-risk` table and the `risk-*` row classes? ap_portal has no stylesheet, and the host page is out of scope for this design	The component sets the classes only	UX lead

Carried, unchanged: TQ-2, TQ-6, TQ-7, TQ-11 (feat.trd 7.2); OQ-B8, OQ-B9, OQ-B10 (feat.prd); RA-1 (branch name `feature/story` vs `feature/<story>`) and RA-2 (remote write access not yet tested) (task.repo_access, section 4). The pending markers on AC-07.2, AC-07.6, AC-07.7, AC-07.8 and AC-07.9 stay as in feat.tasks TSK-07.