FEAT-ZD-48600 · FE-02 Access to secrets · Secrets granted for the task's environments (names only)

Frontend agent · item task.secrets_scope · source hobasa-frontend-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by automated checks and independent judge

task.secrets_scope: FEAT-ZD-48600 (Frontend, ap_portal)

FE-02 Access to secrets. This file lists the secrets the Frontend task needs and the secrets granted for it. It gives names only and holds no secret values.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	FE-02 Access to secrets	record:brief
Task	TSK-07, STORY-07: render the overdue risk table SC-1 (`renderOverdueRisk`)	feat.tasks (sections 1, 3 TSK-07)
Repository	ap_portal	feat.tasks (TSK-07)
Inputs	feat.tasks; org.permission_table (restricted, passed by reference only)	record:brief

1. Secrets needed by the task

None. TSK-07 needs no secret in any environment.

Check	Finding	Source
Scope of the change	A pure render helper in `src/ap_portal/index.js`, plus `package.json` (version only) and `tests/portal.test.js`	feat.tasks (TSK-07 "Files in budget")
Data the function takes	The caller passes in rows that already have the CT-1 shape. TSK-07 depends only on the CT-1 field list, not on TSK-06 code	feat.tasks (TSK-07 "Depends on")
Transport, API or service call	None. The design adds no transport layer, because a transport would re-trigger DES-01	feat.tasks (TSK-06 "Must not change")
New technology or dependency	None; Node.js 22 CommonJS only	feat.tasks (intro, DD-1)
Package dependencies	`package.json` declares no dependencies, so no registry token is needed	file:ap_portal/package.json
Secret use in today's code	`src/ap_portal/index.js` reads no environment variable and calls no external service	file:ap_portal/src/ap_portal/index.js
Secret use in CI	`ci.mjs` copies the process environment and sets only `NODE_PATH: 'src'`. It reads no secret	file:ap_portal/ci.mjs
Secret use in tests	`tests/portal.test.js` loads only `node:test`, `node:assert` and `ap_portal`. Its tests call `formatAmount` and `renderAgingSummary` on literal values and read no environment variable	file:ap_portal/tests/portal.test.js

2. Secrets granted (names only)

Environment	Secrets granted	Source
Local / unit tests (`node ci.mjs`)	None	tool:repo-access
dev (integration)	None	tool:repo-access
main (released)	None	tool:repo-access

The tool registry says the permission table requires and grants no secrets for ap_portal. What the task needs matches what is granted, so no access request is raised.

3. Access requests

None. The task needs no secret that is not already granted.

4. Re-entry condition

This scope holds while TSK-07 stays within its file budget. FE-02 runs again if a later change adds a transport, an external API call or a package dependency that needs a token. Any request for access then goes to the owner of the permission table (agent judgement).

5. Open questions

None, blocking or non-blocking.

6. Validation check

Check	Result	Source
Names only; no secret values in this file	Pass	record:brief
Required secrets covered by grants	Pass (none required, none granted)	tool:repo-access; feat.tasks (TSK-07)
Conflict with an approved output	None	feat.tasks

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_portal] Tool registry: no secrets required or granted (permission table)