FEAT-ZD-48600 · FE-02 Access to secrets · Secrets granted for the task's environments (names only)

Frontend agent · item task.secrets_scope · source hobasa-frontend-agent/outputs/FEAT-ZD-48600/task.secrets_scope.md · approved by automated checks and independent judge

task.secrets_scope: FEAT-ZD-48600

Secrets scope for the Frontend task of FEAT-ZD-48600, from step FE-02 Access to secrets. It lists secret names only and records no values.

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	FE-02 Access to secrets	record:brief
Frontend task	TSK-07 Render the overdue risk table (STORY-07), ap_portal	feat.tasks (section 1, TSK-07)
Repository	ap_portal	feat.tasks (TSK-07); tool:repo-access
Permission table	org.permission_table is restricted and passed by reference only, so this step did not read it	record:brief

1. Secrets the task needs

None. TSK-07 adds a pure render function, `renderOverdueRisk(rows)`, together with constants and private helpers, in `src/ap_portal/index.js`. It also steps the version in `package.json` and adds tests in `tests/portal.test.js` (feat.tasks TSK-07). The feature has no transport layer (feat.tasks TSK-06, "No transport layer"), so the task makes no network call and uses no data store or external service.

Code check of the ap_portal checkout:

Check	Result	Source
`src/ap_portal/index.js`	Pure view helpers (`formatAmount`, `renderAgingSummary`) and constants. It has no `require`, no `process.env`, no network call and no URL	file:ap_portal/src/ap_portal/index.js
`package.json`	No dependencies are declared. The only script is `ci`	file:ap_portal/package.json
`ci.mjs` (CI)	Copies the process environment and sets only `NODE_PATH: 'src'`. It reads no secret	file:ap_portal/ci.mjs
`tests/portal.test.js`	Requires only `node:test`, `node:assert` and `ap_portal`. It reads no secret and calls no service	file:ap_portal/tests/portal.test.js

2. Secrets granted for the task's environments

Environment	Secret names granted	Source
Local build and unit tests (`node ci.mjs`)	None	tool:repo-access
CI pipeline	None	tool:repo-access
dev (integration) / main (released)	None	tool:repo-access

The tool registry for ap_portal states that the permission table requires and grants no secrets for this repository (tool:repo-access).

3. Gap and access requests

Required	Granted	Gap	Request raised
None	None	None	None needed

What the task needs matches what is granted. No access is excess, so nothing needs flagging, and no access is missing, so nothing needs requesting.

4. Re-entry rule

If a later change adds a transport layer, an API call or a package dependency to ap_portal, the secrets scope must be checked again. A transport layer would also re-trigger DES-01 (feat.tasks TSK-06). In that case FE-02 runs again before FE-04 Coding.

5. Open questions

None.

[Tool result] [ap_portal] Tool registry: no secrets required or granted (permission table)