FEAT-ZD-48600 · FE-01 Checking the coding prerequisites ■ · Repository (and Databricks) availability and write access

Frontend agent · item task.repo_access · source hobasa-frontend-agent/outputs/FEAT-ZD-48600/task.repo_access.md · approved by automated checks and independent judge

task.repo_access: FEAT-ZD-48600

Repository availability and write access for the Frontend lane of FEAT-ZD-48600 (ZD-48600, "Show which overdue invoices belong to vendors that usually pay late"). This is FE-01 Checking the coding prerequisites. The Frontend lane owns one task, TSK-07 (STORY-07, "Render the overdue risk table"), in the ap_portal repository (feat.tasks, sections 1 and 3).

Field	Value	Source
Trace ID	FEAT-ZD-48600	record:brief
Step	FE-01 Checking the coding prerequisites	record:brief
Trigger	Task creation, or any re-entry trigger	record:brief
Owner / gate	Developer / no gate: automated checks, the independent judge and sampled human evaluation	record:brief
Inputs	feat.tasks (from DES-04, commit b0fd4d2), org.engineering_stack (commit 76d03ce)	record:brief
Task in scope	TSK-07 / STORY-07 / Frontend / ap_portal	feat.tasks (section 1)

1. Result

Outcome: the repository is available with write access. No repository has to be created, and no Databricks workspace or database is needed.

Check	Result	Source
Repository needed by the lane	ap_portal (the only Frontend repository; TSK-07)	feat.tasks (section 1, TSK-07)
Repository exists and is checked out	Yes, available locally	tool:repo-access; file:ap_portal/.git/HEAD
Repository creation needed	No: the repository already exists	tool:repo-access; org.engineering_stack
Working branch	`feature/story`, checked out (`HEAD` is `ref: refs/heads/feature/story`)	tool:repo-access; file:ap_portal/.git/HEAD
Branch base	Created from `dev` at commit `ff761ee`; the local `dev` and `main` branches point to the same commit	tool:repo-access; file:ap_portal/.git/logs/refs/heads/feature/story; file:ap_portal/.git/logs/refs/heads/dev; file:ap_portal/.git/logs/refs/heads/main
Branch model	`main` (released), `dev` (integration), `feature/<story>`	file:ap_portal/CLAUDE.md; org.engineering_stack; feat.tasks (section 2)
Working tree	Clean	tool:repo-access
Write access for the agent identity	Yes	tool:repo-access
Databricks / database / other workspace	Not used by this repository	tool:repo-access; org.engineering_stack

2. Stack and CI binding for ap_portal

Item	Value	Source
Language / runtime	Node.js 22, CommonJS (`'use strict'`, `module.exports`)	org.engineering_stack; file:ap_portal/CLAUDE.md; file:ap_portal/src/ap_portal/index.js
Test framework	`node:test` with `node:assert`; tests load the package as `require('ap_portal')`	org.engineering_stack; file:ap_portal/tests/portal.test.js
CI command	`node ci.mjs` (also `npm run ci` through the `ci` script in `package.json`)	org.engineering_stack; file:ap_portal/package.json
CI checks	`node --check` on every `src/ap_portal/*.js`; `node --test` with coverage of `src/**` and `NODE_PATH=src`; line coverage >= 90; at least one test run and no failures; no line matching `console.log` or `eval(`; lines at most 140 characters	file:ap_portal/ci.mjs
Code / tests location	`src/ap_portal/` / `tests/`	file:ap_portal/CLAUDE.md
Current version	`2.3.0` in `src/ap_portal/index.js` (`VERSION`) and in `package.json` (`"version"`)	file:ap_portal/src/ap_portal/index.js; file:ap_portal/package.json; feat.tasks (section 2)
Current exports	`VERSION`, `LABELS`, `formatAmount`, `renderAgingSummary` (kept unchanged)	file:ap_portal/src/ap_portal/index.js; feat.tasks (TSK-07 "Must not change")
Existing tests	`formats amounts with two decimals`, `renders every bucket in order` (kept unchanged)	file:ap_portal/tests/portal.test.js; feat.tasks (TSK-07 "Must not change")
Commit message rule	Starts with the story ID (`STORY-07`); the task ID `TSK-07` may follow	org.engineering_stack; feat.tasks (section 2, TA-5); record:memory

3. Files TSK-07 will change (all already in the repository)

File	Change allowed	Source
`src/ap_portal/index.js`	Constants, private helpers, the `renderOverdueRisk` export, `VERSION` step	feat.tasks (TSK-07 "Files in budget")
`package.json`	Version only	feat.tasks (TSK-07)
`tests/portal.test.js`	New tests; existing tests unchanged	feat.tasks (TSK-07)

All three files exist in the checkout on `feature/story` (file:ap_portal/src/ap_portal/index.js; file:ap_portal/package.json; file:ap_portal/tests/portal.test.js). TSK-07 needs no new file or directory.

4. Dependencies affecting access

TSK-07 depends only on the CT-1 field list, not on TSK-06 code, so the Frontend lane does not need access to the ap_aging repository (feat.tasks, TSK-07 "Depends on"). This step needs no secret; FE-02 checks secrets.

5. Actions not taken (bounded by G9)

This step only reads. It did not push, merge, create a remote branch or run CI; the spine commits and pushes after evaluation. FE-01 does not allow shell commands, so the access facts come from the step's tool view (tool:repo-access) and the repository files read above.

6. Open questions (non-blocking)

ID	Question	Interim answer	Owner (proposed)
RAQ-1	feat.tasks and the repository's CLAUDE.md give the branch pattern `feature/<story>`, but the branch provided is `feature/story`, not `feature/STORY-07`. Should the lane work on `feature/story` or on a branch named for the story?	Work on `feature/story` as the spine provided; commit messages carry `STORY-07` for traceability	Developer

Tool results (recorded by the spine from the real tools)

[Tool result] [ap_portal] Branch feature/story at ff761ee; write access confirmed