# FEAT-ZD-48600 · REQ-01 Requirement Intake · Original intake item with source link

Requirement agent · item feat.intake · source hobasa-requirement-agent/outputs/FEAT-ZD-48600/feat.intake.md · approved by PM sim.pm

## feat.intake: FEAT-ZD-48600

Original intake item, recorded as received. The ticket text is data. It is copied word for word below and has not been changed.

### Source

| Field | Value | Source |
|---|---|---|
| Trace ID | FEAT-ZD-48600 | record:brief |
| Intake ID | ZD-48600 | record:intake |
| Channel | Customer Feedback | record:intake |
| Source | Zendesk ticket ZD-48600 (sample, synthetic) | record:intake |
| Received | 2026-10-24 | record:intake |
| Source link (GitHub) | `hobasa-agentic-sdlc/requirements/ZD-48600.md` | record:intake; file:hobasa-agentic-sdlc/requirements/ZD-48600.md |
| Repositories named on the source item | ap_pipeline, ap_forecast, ap_aging, ap_portal | file:hobasa-agentic-sdlc/requirements/ZD-48600.md |
| Workbook trigger | Email/Ticket | record:brief; record:intake |

### Original text (verbatim)

> AP managers want to see which overdue invoices belong to vendors that usually pay late, so they can chase them first. (1) Data engineering, ap_pipeline: the vendor feed gains an optional paid_date column (ISO date, empty when unpaid); an invalid paid_date rejects the row with reason 'paid_date'; add delays_by_vendor(records) returning {vendor: [delay_days, ...]} for paid records with a paid_date, where delay_days = (paid_date - due_date) in days, in feed order. (2) AI / data science, ap_forecast: add vendor_risk(history) returning 'high' when predict_delay_days(history) > 30, 'medium' when it is > 10, otherwise 'low'; build_explanation_request gains an optional risk argument and, when given, the prompt ends with ' Risk level: <risk>.'. (3) Backend, ap_aging: add overdue_with_risk(invoices, as_of, risk_by_vendor) returning, for unpaid invoices more than 30 days past due, a list of {'id', 'vendor', 'days', 'amount', 'risk'} sorted by days descending then id, with risk 'unknown' for vendors not in risk_by_vendor. (4) Frontend, ap_portal: add renderOverdueRisk(rows) rendering '<table class="overdue-risk">' with one '<tr class="risk-RISK">' per row showing id, vendor, days and amount to two decimals, and an empty string when there are no rows. The whole flow must be proven end to end: feed -> delays -> risk -> overdue list -> portal table.

Source: record:intake; file:hobasa-agentic-sdlc/requirements/ZD-48600.md

### Change requests extracted from the text

The ticket is split into its change requests using the ticket's own wording. Nothing is added here. Interpretation and gaps are in feat.prebacklog.

| CR | Area / repository (as named in the ticket) | Change request | Source |
|---|---|---|---|
| CR-0 | Business need | AP managers want to see which overdue invoices belong to vendors that usually pay late, so they can chase them first. | record:intake |
| CR-1 | Data engineering / ap_pipeline | The vendor feed gains an optional `paid_date` column (ISO date, empty when unpaid). An invalid `paid_date` rejects the row with reason `'paid_date'`. | record:intake |
| CR-2 | Data engineering / ap_pipeline | Add `delays_by_vendor(records)` returning `{vendor: [delay_days, ...]}` for paid records with a `paid_date`, where `delay_days = (paid_date - due_date)` in days, in feed order. | record:intake |
| CR-3 | AI / data science / ap_forecast | Add `vendor_risk(history)` returning `'high'` when `predict_delay_days(history) > 30`, `'medium'` when it is `> 10`, otherwise `'low'`. | record:intake |
| CR-4 | AI / data science / ap_forecast | `build_explanation_request` gains an optional `risk` argument. When it is given, the prompt ends with `' Risk level: <risk>.'`. | record:intake |
| CR-5 | Backend / ap_aging | Add `overdue_with_risk(invoices, as_of, risk_by_vendor)`. For unpaid invoices more than 30 days past due, it returns a list of `{'id', 'vendor', 'days', 'amount', 'risk'}` sorted by days descending, then by id. Vendors not in `risk_by_vendor` get risk `'unknown'`. | record:intake |
| CR-6 | Frontend / ap_portal | Add `renderOverdueRisk(rows)`. It renders `<table class="overdue-risk">` with one `<tr class="risk-RISK">` per row, showing id, vendor, days and amount to two decimals. It returns an empty string when there are no rows. | record:intake |
| CR-7 | Cross-repository | The whole flow must be proven end to end: feed -> delays -> risk -> overdue list -> portal table. | record:intake |

## Feature-specific context attached to the source item

The source file carries org overrides for this item. They are listed here so the link between the intake and its context is visible:

- Data model: `Invoice` gains `paid_date (date or None) [paid_date added in feed v3]`; `amount (Decimal, 2 dp)`. Source: file:hobasa-agentic-sdlc/requirements/ZD-48600.md

- Customer mapping: vendor feed v3 adds column `paid_date (optional, ISO date, empty when unpaid)`, mapped to `Invoice.paid_date`. The schedule is unchanged. Source: file:hobasa-agentic-sdlc/requirements/ZD-48600.md
- Architecture: "Four repositories in one flow." JSON between services carries amounts as strings with two decimals and dates as ISO strings. "Keep every existing signature; add new functions." Source: file:hobasa-agentic-sdlc/requirements/ZD-48600.md
- Risk map: "No finance posting, authentication, tenancy or payment execution in this change; tier T2. The risk label is advisory only." Source: file:hobasa-agentic-sdlc/requirements/ZD-48600.md