FUNDAMENTALS OF DEEP LEARNING

Complete Study Module

B.Tech – Artificial Intelligence & Machine Learning

Unit I: Fundamentals of Deep Learning

Unit II: Gradient Descent & Neural Networks

With Diagrams · Question Bank · Exam Answers

Academic Year 2024–25

TABLE OF CONTENTS

UNIT I – FUNDAMENTALS OF DEEP LEARNING

1. What is Artificial Intelligence
2. What is Machine Learning
3. What is Deep Learning
4. AI vs ML vs Deep Learning
5. Evolution of AI and ML
6. Why Deep Learning Matters Today
7. Scalars, Vectors, Matrices and Tensors
8. Real-World Data Representation
9. Tensor Operations
10. Data Visualization in Deep Learning
11. Visualizing Deep Learning Models
12. Challenges in Deep Learning

UNIT II – GRADIENT DESCENT & NEURAL NETWORKS

13. Gradient Descent
14. Intuition and Learning Rate
15. Derivatives – Conceptual
16. Gradient Descent Example
17. Stochastic Gradient Descent
18. Backpropagation
19. The Chain Rule
20. Neural Network Layers
21. Deep Learning Model Types
22. Loss Functions
23. Optimizers
24. Activation Functions
25. ReLU, Sigmoid, Tanh, Softmax
26. Applications of Deep Learning
27. Multiclass Classification
28. Regression
29. Overfitting
30. Underfitting
31. Techniques to Prevent Overfitting

EXAM QUESTION BANK

- 4-Mark Questions (15 Q&A;)
- 5-Mark Questions (15 Q&A;)
- 10-Mark Questions (15 Q&A;)

UNIT I – THE FUNDAMENTALS OF DEEP LEARNING

1. What is Artificial Intelligence (AI)?

Artificial Intelligence is the branch of computer science concerned with building systems that can perform tasks that normally require human intelligence — such as recognising speech, making decisions, translating languages, and detecting objects in images.

Key Points

- AI is not limited to robots. It is mostly software — algorithms running on computers.
- AI is broadly divided into Narrow AI (task-specific) and General AI (human-level, not yet achieved).
- Current AI systems are all Narrow AI — very good at one specific thing.
- AI encompasses rule-based systems, ML, deep learning, expert systems, and more.

Type of AI	What it does	Example
Rule-Based	Follows programmer-written rules	Spam filter with keyword rules
Machine Learning	Learns patterns from data	Email spam filter trained on examples
Deep Learning	Learns via neural networks	Face unlock on smartphones
Generative AI	Creates new content (text, images)	ChatGPT, DALL-E

Summary

- AI = machines performing tasks that require human-like intelligence.
- It is a broad field; ML and Deep Learning are subsets of it.

2. What is Machine Learning (ML)?

Machine Learning is a method of implementing AI where the system **learns patterns from data** instead of following hand-coded rules. The more data it sees, the better its performance.

Aspect	Traditional Programming	Machine Learning
Approach	Developer writes explicit rules	Algorithm finds rules from data
Input	Rules + Data → Output	Data + Output → Rules (learned)
Adaptability	Poor — breaks on new cases	Good — generalises to new data
Example	IF temp > 30 THEN 'Hot'	Learn from weather records what 'Hot' means

Key Points

- Three main types: Supervised Learning (labelled data), Unsupervised Learning (no labels), Reinforcement Learning (reward-based).
- Supervised Learning is the most common type used in industry today.
- Model quality improves with more clean, representative training data.

Summary

- ML = learning rules from data, not coding them manually.
- Used in spam filters, credit scoring, recommendation engines.

3. What is Deep Learning (DL)?

Deep Learning is a subfield of ML that uses **artificial neural networks with many layers** (hence 'deep') to learn representations of data. Each layer transforms the input into progressively more abstract representations.

- The word **deep** refers to the number of layers in the network — modern models can have hundreds.
- Inspired by the structure of biological neurons in the human brain, but much simpler mathematically.
- Especially powerful for unstructured data: images, audio, text, and video.
- Requires large amounts of data and significant computational power (GPUs).

Key Points

- Deep Learning $\subset$ Machine Learning $\subset$ Artificial Intelligence.
- A CNN recognising a cat photo does: pixels $\rightarrow$ edges $\rightarrow$ shapes $\rightarrow$ body parts $\rightarrow$ 'cat'.
- Major breakthrough: AlexNet won ImageNet 2012 competition with a large margin over non-DL methods.

Summary

- DL uses multi-layer neural networks to learn from large datasets.
- Powers face recognition, speech assistants, autonomous vehicles, and language models.

4. AI vs Machine Learning vs Deep Learning



Feature	AI	Machine Learning	Deep Learning
Definition	Machines acting intelligently	Learning patterns from data	Learning via deep neural nets
Scope	Broadest	Subset of AI	Subset of ML
Data needed	Varies	Moderate	Very large
Manual rules	Often required	Fewer	Almost none
Hardware	CPU sufficient	CPU/GPU	GPU required
Example	Chess engine	Spam filter	ChatGPT, Face ID

Self-Check

- Is every Deep Learning system also a Machine Learning system? Justify.
- Name one task that ML handles well but does NOT require deep learning.

5. Evolution of AI and Machine Learning



Period	Era	Key Events
1940s–1950s	AI Born	Alan Turing proposes Turing Test (1950). Term 'AI' coined at Dartmouth Conference (1956).
1960s–1970s	Expert Systems	Rule-based programs: MYCIN (medical diagnosis), DENDRAL (chemistry). Brittle and limited.
1974–1980	First AI Winter	Overpromised results, hardware limitations, funding cut. Progress stalled.
1980s–2000s	ML Era	Statistical methods, Decision Trees, SVM, Naive Bayes. Practical spam filters, credit scoring.
2006–2012	DL Awakens	Hinton's deep belief networks. AlexNet crushes ImageNet 2012 by 10%+ margin.
2017–2020	Transformers	'Attention Is All You Need' (2017). BERT, GPT-2. NLP transformed.
2022–Now	Large Language Models	ChatGPT (100M users in 2 months). GPT-4, Gemini, Claude. Multimodal AI.

Key Points

- Three drivers of the modern revolution: Big Data + GPU hardware + Better algorithms (dropout, batch norm, attention).
- Geoffrey Hinton, Yann LeCun, Yoshua Bengio received the 2018 Turing Award for Deep Learning contributions.

6. Why Deep Learning is Important Today

Three reasons deep learning became dominant:

- **Data:** The internet produces 2.5 quintillion bytes daily. Social media, sensors, and cameras provide the training data DL needs at scale.
- **Hardware:** Modern GPUs execute trillions of operations per second. Cloud GPU services (AWS, GCP, Azure) make this accessible.
- **Algorithms:** Dropout, batch normalisation, ReLU, Adam optimizer, and attention mechanisms made training deep networks reliable.

Industry	Application	Real Product
Healthcare	Tumour detection in X-rays	Google DeepMind (retinal disease, 94% accuracy)
Finance	Real-time fraud detection	Visa, Mastercard transaction scoring
Transport	Autonomous driving	Tesla FSD, Waymo
NLP	Language understanding	ChatGPT, Google Translate, Siri
Entertainment	Personalised recommendations	Netflix (80% views from AI recommendations)
Agriculture	Crop disease detection	Drone-based imaging systems

Summary

- DL dominates because big data, fast GPUs, and improved algorithms converged around 2012.
- Every major technology company (Google, Meta, Apple, Amazon) is built on deep learning infrastructure.

7. Scalars, Vectors, Matrices, and Tensors

All data in deep learning is stored and processed as tensors — multi-dimensional arrays of numbers. Computers cannot process raw images or text; everything must be converted to numerical tensors first.



Type	Dimensions	Shape Example	Deep Learning Use
Scalar	0-D	( )	Learning rate, loss value
Vector	1-D	(784,)	Flattened image, word embedding
Matrix	2-D	(28, 28)	Grayscale image, weight matrix
Tensor	3-D+	(64, 64, 3)	Colour image (H×W×RGB)
4-D Tensor	4-D	(32, 64, 64, 3)	Batch of 32 colour images
5-D Tensor	5-D	(8, 30, 64, 64, 3)	Batch of 8 video clips, 30 frames each

Key Points

- TensorFlow and PyTorch are named after tensors — all computation flows as tensors through the network.
- A colour selfie (1080×1080 pixels) = tensor of shape (1080, 1080, 3) = 3,499,200 numbers.
- Text 'Hello' gets tokenized and each token becomes a dense vector (e.g., 768 numbers in BERT).

8. Real-World Data Representation

Data Type	How it's Stored	Tensor Shape	Example
Grayscale Image	Pixel brightness 0–255	(H, W)	MNIST handwritten digits 28×28
Colour Image	3 channels: R, G, B	(H, W, 3)	Instagram photo 1080×1080×3
Audio	Amplitude samples over time	(samples,)	1 sec of audio = 44,100 values
Audio (CNN input)	Mel spectrogram	(freq_bins, time_frames)	Used in Shazam, speech recognition
Text	Token IDs or embeddings	(seq_len, embed_dim)	'Hello' → [341, 28, ...] tokens
Video	Sequence of image frames	(frames, H, W, 3)	30fps video: 30 frames/sec
Tabular	Row of numerical features	(num_features,)	[Age=25, Income=50000, Score=750]

Key Points

- Normalisation: Always scale input values to [0,1] or zero-mean/unit-variance before training — speeds up convergence.
- One-Hot Encoding: Categorical labels ('Cat','Dog') → [1,0] and [0,1] vectors.
- Word Embeddings (Word2Vec, GloVe): Map words to dense vectors where semantically similar words are close.

Summary

- All real-world data must become a numerical tensor before entering a neural network.
- Shape of the tensor determines the input layer architecture.

9. Tensor Operations

Operation	Description	Used In
Element-wise Addition	Add corresponding elements of two tensors	Residual connections in ResNet
Element-wise Multiplication	Multiply corresponding elements	Attention masks, gating mechanisms
Matrix Multiplication (dot product)	Row × column products; core NN computation	Every dense/fully-connected layer
Reshape / Flatten	Change tensor dimensions without changing data	Flatten image (28,28) → vector (784,)
Transpose	Swap dimensions	Backpropagation gradient calculations
Concatenation	Join tensors along an axis	Skip connections in U-Net
Broadcasting	Operate on tensors of different shapes	Adding bias term to layer output

Key Points

- Matrix multiplication is the dominant operation in neural networks — billions per forward pass.
- A modern GPU has thousands of cores optimised for parallel matrix operations.
- Libraries like NumPy, TensorFlow, and PyTorch handle all tensor operations with GPU acceleration.

10. Data Visualization in Deep Learning

Visualizing data before and during training is essential for understanding the dataset, spotting problems, and diagnosing model behaviour.

Technique	Purpose	When to Use
Histogram	Distribution of values in each class	Check class imbalance before training
Scatter Plot	Relationship between two variables	Feature correlation analysis
Heatmap / Pixel Grid	Visualise raw image/matrix data	Inspect image samples, attention weights
t-SNE Plot	Compress high-dim data to 2D	See if classes are separable in feature space
Training Curves	Loss and accuracy vs epochs	Monitor training, detect overfitting
Confusion Matrix	Correct vs wrong predictions per class	Post-training error analysis
Saliency / Grad-CAM	Which image region drove the prediction	Explainability in medical imaging

Key Points

- t-SNE: if class clusters overlap visually, the model will also struggle to separate them.
- Class imbalance (e.g., 95% negative samples) must be handled before training or the model predicts only the majority class.
- Tools: Matplotlib, Seaborn (plots), TensorBoard (live training curves), Netron (model architecture).

11. Visualizing Deep Learning Models

What to Visualize	How	What it Reveals
Network architecture	Keras plot_model, Netron, TensorBoard	Layer types, connections, tensor shapes
Training/val loss curves	Matplotlib, TensorBoard	Learning progress, overfitting detection
CNN filters (weights)	Display filter weights as images	What patterns each filter detects
Feature maps (activations)	Record layer outputs for a sample input	How representation evolves through layers
Grad-CAM heatmap	Gradient × activation of last conv layer	Which image regions influenced prediction
Confusion matrix	sklearn.metrics.confusion_matrix	Which classes are misclassified and why
Embedding projector	TensorBoard projector (t-SNE/PCA)	Cluster structure of learned representations

Key Points

- Early CNN layers learn edge detectors (Gabor-like filters). Deeper layers learn semantic features (eyes, wheels).
- Grad-CAM is the standard explainability tool in medical AI — it shows radiologists what the model 'looked at'.
- TensorBoard is free, browser-based, and works with both TensorFlow and PyTorch (via TensorBoardX).

12. Challenges in Deep Learning

Challenge	Description	Impact
Black Box / Interpretability	Hard to explain why a model made a decision	Limits use in healthcare, legal, finance
Data Hunger	Needs thousands to millions of labelled examples	Expensive and slow to collect
Computational Cost	Training GPT-4 estimated at $100M+	Inaccessible to small organisations
Overfitting	Memorises training data, fails on new data	Unreliable in production
Data Bias	Model inherits biases present in training data	Unfair or discriminatory outputs
Vanishing Gradients	Gradients shrink to zero in deep networks	Early layers stop learning
Adversarial Attacks	Small input perturbations fool the model	Security risk in autonomous systems

Key Points

- Facial recognition error rates: 0.8% for light-skinned men vs 34.7% for dark-skinned women (Buolamwini & Gebru, 2018).
- Active research areas: Explainable AI (XAI), Federated Learning (privacy), Efficient transformers, Few-shot learning.
- Regulations like the EU AI Act are beginning to require explainability for high-risk AI systems.

UNIT II – GRADIENT DESCENT & NEURAL NETWORKS

13. Gradient Descent

Gradient Descent is an iterative optimisation algorithm used to minimise a loss function by repeatedly adjusting model parameters (weights) in the direction that reduces the loss.



Update Rule:

New Weight = Old Weight – (Learning Rate × Gradient of Loss)

Key Points

- The gradient is the direction of steepest increase in loss. Moving opposite to it reduces loss.
- One complete pass through all training data = 1 epoch.
- Training stops when loss converges (stops decreasing) or a maximum number of epochs is reached.
- The loss surface can have local minima, saddle points, and flat regions — all challenging for gradient descent.

Summary

- Gradient Descent is the core learning algorithm in deep learning.
- It updates weights to progressively reduce prediction error.

14. Intuition and the Learning Rate

The learning rate (lr) is a scalar hyperparameter controlling the step size at each gradient update. It is one of the most critical hyperparameters in training.

Learning Rate	Behaviour	Consequence
Too large (e.g. 1.0)	Overshoots the minimum	Loss oscillates or diverges — training fails
Too small (e.g. 0.000001)	Tiny steps	Takes too long; may not converge in practice
Well-tuned (e.g. 0.001)	Steady descent	Smooth convergence to low loss
Decaying schedule	Starts larger, decreases over time	Fast early progress + fine-tuning later

Key Points

- Typical starting values: 0.1 (SGD), 0.001 (Adam). Always try Adam with lr=0.001 first.
- Learning Rate Scheduling: ReduceLROnPlateau halves lr when validation loss stops improving.
- Learning Rate Warmup: Used in Transformer training — start very small, increase, then decay.
- Cyclical Learning Rates: Oscillate between min and max lr; helps escape local minima.

15. Derivatives — Conceptual Understanding

A derivative measures the rate of change of a function's output with respect to its input. In deep learning, we need the derivative of the loss with respect to each weight — this tells us how much changing that weight affects the loss.

Slope (Gradient) Sign	Meaning	Action
Positive (■)	Increasing weight increases loss	Decrease the weight
Negative (■)	Increasing weight decreases loss	Increase the weight
Zero (→)	Changing weight has no effect on loss	Weight is at its optimal value

Key Points

- We don't compute derivatives of the full dataset at once — backpropagation applies the chain rule layer by layer.
- Partial derivative: derivative of loss w.r.t. one specific weight, holding all others constant.
- Gradient vector: collection of all partial derivatives — one per weight in the network.

16. Gradient Descent — Step-by-Step Example

Single-weight example: model predicts house price. True price = 10. Initial weight W = 2.

Iteration	W	Prediction	Loss (MSE)	Gradient	Updated W
0 (start)	2.0	4.0	36.0	–12.0	3.2
1	3.2	6.4	12.96	–7.2	3.92
2	3.92	7.84	4.67	–4.32	4.35
3	4.35	8.70	1.69	–2.60	4.61
…	…	…	…	…	…
n	~5.0	~10.0	~0.0	~0.0	converged

(Learning rate = 0.1 used throughout.)

Key Points

- Loss decreases each iteration as weight converges toward the true value.
- In real networks, millions of weights are updated simultaneously using the same rule.
- One pass through all training batches = one epoch. Typical training: 10–200 epochs.

17. Stochastic Gradient Descent (SGD)

Variant	Data per Update	Speed	Gradient Quality	Typical Use
Batch GD	All training data	Slowest	Most accurate	Tiny datasets only
Stochastic GD (SGD)	1 sample (random)	Fastest	Very noisy	Rarely used alone
Mini-Batch GD	32–256 samples	Fast + efficient	Good balance	Standard in practice

Key Points

- Mini-Batch GD is what practitioners mean when they say 'SGD' in deep learning.
- Batch size 32 or 64 is the most common default; powers of 2 for GPU memory efficiency.
- Larger batches: more stable gradients but need higher learning rates; can generalise slightly worse.
- The 'noise' in SGD can help escape shallow local minima — a useful side effect.

Summary

- Mini-Batch Gradient Descent is the standard training method.
- Each mini-batch is a random subset of the training data.

18. Backpropagation

Backpropagation is the algorithm that computes gradients of the loss function with respect to every weight in the network, layer by layer, starting from the output.



Step	Operation	Direction
1. Forward Pass	Compute layer outputs; get prediction	Input → Output
2. Loss Computation	Calculate loss = f(prediction, true label)	At output layer
3. Output Layer Grad	Gradient of loss w.r.t. output weights	Backward
4. Hidden Layer Grad	Propagate gradient back using chain rule	Backward
5. Weight Update	W = W – lr × gradient for every weight	All layers

Key Points

- Backprop was formalised for neural networks by Rumelhart, Hinton & Williams (1986).
- Modern frameworks (PyTorch, TensorFlow) compute all gradients automatically via autograd.
- Vanishing gradient: in very deep networks, gradients shrink to near-zero in early layers. Fix: ReLU + Batch Norm.

• Exploding gradient: gradients grow uncontrollably. Fix: Gradient Clipping (cap gradients at a max value).

19. The Chain Rule

The chain rule states: if y depends on u, which depends on x, then dy/dx = (dy/du) × (du/dx). In a neural network, each layer's output feeds the next, so the gradient of the loss with respect to any weight is the *product of all partial derivatives along the path* from that weight to the loss.

Why it matters:

- Makes gradient computation tractable for networks with hundreds of layers.
- Allows each layer to compute its own local gradient and pass it backward.
- Enables the entire network to be updated in one backward pass.

Key Points

- Automatic differentiation (autograd) in PyTorch/TensorFlow implements the chain rule symbolically.
- Computational graph: a record of all operations during the forward pass, used to replay them in reverse.
- Detaching tensors from the computational graph (torch.detach()) stops gradient flow — used in GANs.

20. Neural Network Layers



Layer Type	Role	Notes
Input Layer	Receives raw data tensor	No computation; size = number of input features
Hidden Layer (Dense)	Learns feature representations	Output = Activation(W·x + b)
Output Layer	Produces final prediction	Activation: Sigmoid (binary), Softmax (multiclass), Linear (regression)
Convolutional Layer	Detects local spatial patterns	Uses learnable filters sliding over input
Pooling Layer	Reduces spatial dimensions	Max/Average pooling; reduces computation
Dropout Layer	Regularisation — randomly zeros neurons	Active only during training
Batch Norm Layer	Normalises layer inputs	Mean=0, Std=1 per mini-batch; stabilises training

Key Points

- Neuron output: z = w■x■ + w■x■ + … + w■x■ + b, then activation(z).
- Width (neurons per layer) controls capacity; depth (number of layers) controls abstraction level.
- Universal Approximation Theorem: a neural network with one hidden layer and enough neurons can approximate any continuous function.

21. Deep Learning Model Types

Model	Architecture Idea	Best Data Type	Key Application
ANN (Fully Connected)	Dense layers; every neuron connects to all in next layer	Tabular / structured	House price, churn prediction
CNN (ConvNet)	Convolutional filters + pooling; spatial hierarchy	Images, video	Face ID, object detection, medical imaging
RNN	Recurrent connections; hidden state carries sequence memory	Sequential / time-series	Autocomplete, stock prediction
LSTM	RNN with forget/input/output gates; long-range memory	Long sequences	Translation, speech recognition
Transformer	Self-attention; no recurrence; parallelisable	Text, images, audio	ChatGPT, BERT, Google Translate
GAN	Generator vs Discriminator adversarial training	Images, audio	Deepfakes, image synthesis, MidJourney
Autoencoder	Encoder compresses; Decoder reconstructs	Any	Anomaly detection, denoising

Key Points

- Transformer (2017) replaced LSTM as the dominant sequence model due to parallelism and long-range attention.
- ResNet (2015): introduced skip connections — allows training of 100+ layer networks without vanishing gradients.
- Transfer learning: take a pretrained model (e.g., ResNet on ImageNet) and fine-tune on your specific task with less data.

22. Loss Functions

A loss function measures the discrepancy between the model's prediction and the ground truth. Training minimises this scalar value.



Loss Function	Formula (conceptual)	Use Case	Key Property
Mean Squared Error (MSE)	Average of (pred – true)²	Regression	Penalises large errors heavily
Mean Absolute Error (MAE)	Average of |pred – true|	Regression (robust)	Less sensitive to outliers than MSE
Binary Cross-Entropy	–[y·log(p) + (1–y)·log(1–p)]	Binary classification	Output via Sigmoid
Categorical Cross-Entropy	–Σ y■·log(p■)	Multiclass classification	Output via Softmax
Sparse Cat. Cross-Entropy	Same as above, integer labels	Multiclass (large vocab)	Saves memory vs one-hot
Huber Loss	MSE for small errors, MAE for large	Regression with outliers	Hybrid of MSE and MAE
KL Divergence	Σ p(x)·log(p(x)/q(x))	Generative models, VAEs	Measures distribution difference

Summary

- Regression → MSE or MAE. Binary classification → Binary Cross-Entropy. Multiclass → Categorical Cross-Entropy.
- The loss function must be differentiable so gradients can be computed for backpropagation.

23. Optimizers

Optimizer	Core Idea	Adaptive LR?	When to Use
SGD	W = W – lr × gradient	No	Baseline; research fine-tuning
SGD + Momentum	Adds velocity: v = β·v + gradient; W = W – lr·v	No	Image classification with LR schedule
RMSprop	Divides gradient by RMS of recent gradients	Per-param	RNNs, non-stationary data
Adam	Momentum + RMSprop; bias-corrected estimates	Per-param	Default for most tasks
AdamW	Adam + decoupled weight decay	Per-param	Transformer fine-tuning
Adagrad	Accumulates all past squared gradients	Per-param	Sparse data, NLP
LAMB	Layer-wise adaptive rates; large-batch training	Per-param, per-layer	BERT pretraining

Key Points

- Adam hyperparameters: lr=0.001, β■=0.9 (momentum), β■=0.999 (RMS), ε=1e-8 (numerical stability).
- AdamW is preferred over Adam for transformer models — weight decay is applied correctly.
- Rule of thumb: start with Adam lr=0.001 for any new task.

24–25. Activation Functions

Activation functions introduce non-linearity into the network. Without them, stacking linear layers produces only a linear transformation regardless of depth.



Function	Output Range	Formula (conceptual)	Pros	Cons	Typical Use
Sigmoid	(0, 1)	1/(1+e^–x)	Smooth gradient	Vanishing gradient; not zero-centred	Output: binary class
Tanh	(–1, +1)	(e^x – e^–x)/(e^x + e^–x)	Zero-centred	Vanishing gradient at extremes	RNN hidden states
ReLU	[0, ∞)	max(0, x)	Fast; no vanishing gradient	Dying neurons (x<0 → 0 forever)	Hidden layers (default)
Leaky ReLU	(–∞, ∞)	max(0.01x, x)	Fixes dying neurons	Extra hyperparameter (slope)	Hidden layers (ReLU alternative)
ELU	(–α, ∞)	x if x>0; α(e^x –1) else	Smooth; negative outputs	Slower to compute	Deep hidden layers
Softmax	(0,1), sum=1	e^x■ / Σe^x■	Outputs probabilities	Not for hidden layers	Output: multiclass
GELU	~(–0.17, ∞)	x·Φ(x)	Smooth; best in Transformers	Computationally heavier	GPT, BERT hidden layers

Summary

- ReLU is the default for hidden layers. Softmax for multiclass output. Sigmoid for binary output.
- GELU is used in modern transformers (GPT, BERT) — slightly outperforms ReLU on language tasks.

26. Applications of Deep Learning

Domain	Task	Model Used	Product / Result
Computer Vision	Image classification	CNN (ResNet, EfficientNet)	ImageNet top-5 accuracy: >99%
Computer Vision	Object detection	YOLO, Faster R-CNN	Tesla FSD, surveillance cameras
Medical Imaging	Cancer detection from scans	CNN + attention	DeepMind: 94% retinal disease accuracy
NLP	Text generation	GPT (Transformer decoder)	ChatGPT, GitHub Copilot
NLP	Language understanding	BERT (Transformer encoder)	Google Search, Q&A; systems
Speech	Speech recognition	LSTM / Transformer	Siri, Google Assistant, Zoom captions
Speech	Text-to-speech	Tacotron, WaveNet	Google Assistant voice, audiobooks
Recommendation	Personalisation	Two-tower, collaborative filter DL	Netflix, Spotify, YouTube
Robotics	Control policies	Reinforcement Learning + DNN	Boston Dynamics, OpenAI Dexterous Hand
Science	Protein structure prediction	AlphaFold (Transformer)	AlphaFold2: solved 200M protein structures
Finance	Fraud detection	LSTM / GNN	Visa, Mastercard real-time alerts
Generative	Image synthesis	GAN / Diffusion models	MidJourney, DALL-E 3, Stable Diffusion

27. Multiclass Classification

Multiclass classification assigns each input to exactly one of K ≥ 3 classes.



Aspect	Detail
Output layer neurons	One per class (K neurons)
Output activation	Softmax — converts logits to probabilities summing to 1
Loss function	Categorical Cross-Entropy
Prediction	argmax of output probabilities
Label encoding	One-hot vector e.g., class 3 of 5 → [0,0,0,1,0]
Evaluation metrics	Accuracy, Precision, Recall, F1-Score, Confusion Matrix

Key Points

- Softmax: each output = e^(logit_i) / sum(e^(logit_j) for all j). Ensures all probabilities are positive and sum to 1.
- For K=2, Binary Cross-Entropy + Sigmoid is equivalent to Categorical Cross-Entropy + Softmax.
- Top-5 accuracy: prediction is correct if the true class is among the 5 highest-probability outputs (used in ImageNet).

28. Regression in Deep Learning

Aspect	Classification	Regression
Output	Discrete category / class	Continuous numerical value
Output activation	Softmax or Sigmoid	Linear (no activation)
Loss function	Cross-Entropy	MSE or MAE
Example output	'Cat' or 'Dog'	Rs. 4,500,000
Evaluation	Accuracy, F1, AUC-ROC	RMSE, MAE, R^2
Example task	Email: spam/not spam	Tomorrow's temperature

Key Points

- Multi-output regression: predict several values simultaneously (e.g., bounding box coordinates: x, y, w, h).
- R^2 score (coefficient of determination): 1.0 = perfect fit, 0.0 = no better than predicting the mean.
- Deep regression networks are used in pose estimation, 3D object detection, and stock forecasting.

29. Overfitting

A model overfits when it learns the training data too specifically — including noise — and fails to generalise to unseen data. Training accuracy is high; test accuracy is low.



Indicator	Good Fit	Overfitting
Training accuracy	High	Very high (99%+)
Validation accuracy	High (close to training)	Low — large gap from training
Training loss	Low and converged	Very low
Validation loss	Low and stable	Starts rising after a point
Generalisation	Good on new data	Poor on new data

Key Points

- Root cause: model has too many parameters relative to the amount of training data.
- Occam's Razor in ML: prefer the simplest model that fits the data adequately.

30. Underfitting

A model underfits when it is too simple to capture the patterns in the data. Both training accuracy and test accuracy are low.

Cause	Fix
Model too shallow (too few layers/neurons)	Increase model capacity (add layers or neurons)
Too few training epochs	Train for more epochs
Learning rate too large	Reduce learning rate
Wrong model architecture for the data	Switch to appropriate architecture (e.g., CNN for images)
Insufficient features / poor data	Improve feature engineering; collect better data

Problem	Train Acc	Test Acc	Fix
Underfitting	Low	Low	Bigger model, more epochs, lower lr
Good Fit	High	High (close)	Keep it
Overfitting	Very High	Low	Regularise, more data, dropout

Self-Check

- Your model has 98% train accuracy and 62% test accuracy. What is the problem?
- Your model has 55% train and 53% test accuracy on a 10-class problem. What is the problem?

31. Techniques to Prevent Overfitting

Technique	How It Works	Implementation
More Data	More examples force generalisation	Collect real data; use public datasets
Data Augmentation	Artificially vary training samples	Flip, rotate, crop, colour-jitter (images); back-translate (text)
Dropout	Randomly zero p% of neurons each step during training	Keras: Dropout(0.3–0.5) after dense layers
L2 Regularisation (Weight Decay)	Add $\lambda \cdot \|\|W\|\|^2$ penalty to loss — discourages large weights	kernel_regularizer=l2(0.01) in Keras
L1 Regularisation	Add $\lambda \cdot \|\|W\|\|$■ penalty — drives some weights to exactly zero	kernel_regularizer=l1(0.01)
Early Stopping	Stop training when val loss stops improving; save best checkpoint	EarlyStopping(patience=5, restore_best_weights=True)
Batch Normalisation	Normalise layer activations per mini-batch; reduces internal covariate shift	BatchNormalization() after conv/dense layers
Reduce Model Complexity	Fewer layers/neurons → fewer parameters → less memorisation	Start small, add capacity only if underfitting
Cross-Validation	Evaluate on multiple train/val splits; get reliable performance estimate	K-Fold CV, Stratified K-Fold

Key Points

- Dropout (Hinton et al., 2012): at inference time, all neurons are active but weights scaled by (1–p).
- Batch Norm (Ioffe & Szegedy, 2015): allows higher learning rates; acts as mild regulariser.
- Data augmentation is the most effective technique when you have limited data.
- Early stopping + model checkpoint is a near-zero-cost regularisation strategy — always use it.

Summary

- Use early stopping and data augmentation by default.
- Add dropout (0.3–0.5) after dense layers for classification tasks.
- Monitor train vs validation loss curves — they tell you everything about model health.

EXAM QUESTION BANK

All answers are in point-wise format. Suitable for direct use in university examinations.

4-MARK QUESTIONS (Short Descriptive)

Q1. Define Artificial Intelligence. Give two real-world examples.

Answer:

- AI is the field of computer science focused on building systems that perform tasks requiring human intelligence — reasoning, perception, decision-making, and language understanding.
- Example 1: Google Translate — translates between 100+ languages using neural networks.
- Example 2: Tesla Autopilot — detects pedestrians, lanes, and traffic signals using CNNs.
- AI encompasses rule-based systems, ML, deep learning, and generative models.
- Current AI systems are Narrow AI (task-specific). General AI does not yet exist.

Q2. What is the difference between Machine Learning and Traditional Programming?

Answer:

- Traditional Programming: developer writes explicit rules. Machine input + rules → output.
- Machine Learning: developer provides data + desired outputs. System learns rules automatically.
- Traditional programs break on unseen cases outside the programmed rules.
- ML models generalise — they handle new inputs they were never explicitly shown.
- Example: Traditional: IF word='Viagra' THEN spam=True. ML: train on 10,000 spam/non-spam emails, learn patterns automatically.

Q3. Define Scalar, Vector, Matrix, and Tensor with one example each.

Answer:

- Scalar (0-D): single number. Example: learning rate = 0.001.
- Vector (1-D): ordered list of numbers. Example: pixel values of one row of an image.
- Matrix (2-D): 2D grid of numbers. Example: 28×28 grayscale MNIST image.
- Tensor (N-D): generalisation to N dimensions. Example: colour image shape (224, 224, 3).
- All data in deep learning is stored and processed as tensors.

Q4. What is the Learning Rate in Gradient Descent? What happens when it is too large or too small?

Answer:

- Learning rate (lr) is a hyperparameter that controls the step size of each weight update.
- Update rule: W_new = W_old – lr × gradient.
- Too large (e.g., 1.0): steps overshoot the minimum. Loss oscillates or diverges. Training fails.

- Too small (e.g., 1e-7): extremely slow convergence. Training takes impractically long.
- Well-tuned (e.g., 0.001 for Adam): steady convergence to minimum. Recommended starting point.

Q5. Differentiate between Overfitting and Underfitting.

Answer:

- Overfitting: model performs well on training data but poorly on validation/test data.
- Cause of overfitting: model is too complex relative to the amount of training data — memorises noise.
- Signs: training accuracy very high, validation accuracy much lower; validation loss increases.
- Underfitting: model performs poorly on both training and test data.
- Cause of underfitting: model too simple, too few epochs, or wrong architecture for the task.
- Fix overfitting: dropout, regularisation, more data. Fix underfitting: bigger model, more epochs.

Q6. What is a Loss Function? Name two loss functions used in classification.

Answer:

- A loss function quantifies the error between model predictions and ground truth labels.
- Training minimises the loss function via gradient descent.
- Loss function must be differentiable so gradients can be computed.
- Classification Loss 1 — Binary Cross-Entropy: for 2-class problems. Used with Sigmoid output.
- Classification Loss 2 — Categorical Cross-Entropy: for $K \geq 3$ classes. Used with Softmax output.
- Regression Loss: Mean Squared Error (MSE) — average of squared prediction errors.

Q7. Explain the ReLU activation function and why it is widely used.

Answer:

- ReLU (Rectified Linear Unit): output = max(0, x). Zero for all negative inputs; identity for positive.
- Shape: a bent line — flat at y=0 for x<0, diagonal (slope 1) for x>0.
- Advantage 1: computationally trivial — just a comparison to zero.
- Advantage 2: no vanishing gradient for positive inputs — gradient is either 0 or 1.
- Advantage 3: sparse activations — many neurons output zero, improving efficiency.
- Disadvantage: Dying ReLU — neurons stuck at zero get zero gradient and never update. Fixed by Leaky ReLU.

Q8. What is Backpropagation? List its key steps.

Answer:

- Backpropagation computes the gradient of the loss with respect to every weight in the network.
- Step 1 — Forward Pass: data flows through all layers; prediction is computed.
- Step 2 — Loss Computation: loss = f(prediction, true label) using the chosen loss function.
- Step 3 — Backward Pass: error gradient flows backwards from output to input layer.
- Step 4 — Chain Rule: gradients are multiplied through each layer to reach earlier weights.
- Step 5 — Weight Update: W = W – lr × gradient for every parameter.
- Frameworks (PyTorch, TensorFlow) automate all gradient computations via autograd.

Q9. Name and explain three types of layers in a neural network.

Answer:

- Input Layer: receives the raw data tensor. No computation performed. Size equals number of input features.
- Hidden Layer (Dense/Fully-Connected): applies weighted sum + bias + activation. Where learning happens.
- Output Layer: produces the final prediction. Activation: Sigmoid (binary), Softmax (multiclass), Linear (regression).
- Additional specialised layers: Convolutional (local pattern detection), Pooling (dimension reduction), Dropout (regularisation), Batch Norm (training stabilisation).

Q10. What is the Softmax function and where is it used?

Answer:

- Softmax converts a vector of raw scores (logits) into a probability distribution.
- Each output is between 0 and 1, and all outputs sum to exactly 1.
- Formula: softmax(x■) = e^x■ / Σ e^x■ for all j.
- Used in the output layer of multiclass classification networks.
- The predicted class = index with the highest probability.
- Loss function paired with Softmax: Categorical Cross-Entropy.

Q11. What is the role of an Optimizer?

Answer:

- An optimizer uses the gradients computed by backpropagation to update model weights.
- Goal: minimise the loss function by iteratively improving weights.
- SGD: basic optimizer — W = W – lr × gradient. No adaptive learning rate.
- Adam: most popular optimizer. Maintains per-parameter adaptive learning rates.
- Adam combines momentum (first moment) and RMSprop (second moment) with bias correction.
- Default recommendation: Adam with lr=0.001 for most tasks.

Q12. What is Data Augmentation and why is it used?

Answer:

- Data augmentation creates new training samples by applying transformations to existing ones.
- Image augmentations: horizontal flip, rotation, zoom, brightness/contrast, random crop, colour jitter.
- Text augmentations: synonym replacement, back-translation, random deletion.
- Why use it: (1) increases effective dataset size. (2) reduces overfitting. (3) improves robustness.
- Augmentations are applied randomly during training only — not at test time.
- In Keras: ImageDataGenerator or tf.keras.layers augmentation pipeline.

Q13. What is Multiclass Classification? How does the output layer handle it?

Answer:

- Multiclass classification assigns an input to one of $K \geq 3$ predefined categories.
- Output layer: K neurons, one per class.
- Output activation: Softmax — converts K raw scores to K probabilities summing to 1.
- Final prediction: class with the highest Softmax probability (argmax).
- Loss function: Categorical Cross-Entropy.
- Example: recognising digits 0–9. Output layer has 10 neurons. Correct class represented as one-hot label.

Q14. Distinguish between Classification and Regression.

Answer:

- Classification predicts a discrete category (class label). Output is categorical.
- Regression predicts a continuous numerical value. Output is a real number.
- Output activation — Classification: Sigmoid or Softmax. Regression: Linear (no activation).
- Loss function — Classification: Cross-Entropy. Regression: MSE or MAE.
- Evaluation — Classification: accuracy, F1, AUC. Regression: RMSE, MAE, R^2.
- Example — Classification: is tumour malignant/benign? Regression: predict patient blood glucose level.

Q15. What is Mini-Batch Gradient Descent and why is it preferred?

Answer:

- Mini-Batch GD updates weights using a small random subset (batch) of training data per step.
- Typical batch sizes: 32, 64, 128 (powers of 2 for GPU memory alignment).
- Advantage over Batch GD: does not require all data in memory; faster updates.
- Advantage over pure SGD: less noisy gradients; more stable convergence.
- GPU-efficient: matrix operations on a batch are parallelised across thousands of cores.
- Standard in all deep learning frameworks. What people mean when they say 'SGD in practice'.

5-MARK QUESTIONS (Medium Explanation)

Q1. Compare AI, ML, and Deep Learning with definitions, scope, and examples.

Answer:

- AI (Artificial Intelligence): broadest field. Any technique that enables machines to mimic human intelligence — rule-based, statistical, or learning-based. Example: chess engine (rule-based search).
- Machine Learning: subset of AI. System learns patterns from labelled or unlabelled data without explicit programming. Example: credit scoring model trained on historical loan data.
- Deep Learning: subset of ML. Uses artificial neural networks with many layers. Learns hierarchical feature representations. Example: ChatGPT (Transformer), Face ID (CNN).
- Relationship: DL $\subset$ ML $\subset$ AI. Every DL system is an ML system, which is an AI system.
- Key differences — Data requirement: AI varies; ML moderate; DL very large. Hardware: AI low-medium; DL requires GPU.
- Algorithmic complexity — AI: may be simple rules; ML: statistical learning; DL: backprop through millions of parameters.
- Interpretability: rule-based AI is transparent; ML is partially interpretable; DL is largely a black box.

Q2. Describe the Evolution of AI from the 1950s to the present. Include all major milestones.

Answer:

- 1950: Alan Turing publishes 'Computing Machinery and Intelligence'; proposes Turing Test.
- 1956: 'Artificial Intelligence' coined at the Dartmouth Conference by John McCarthy.
- 1960s–70s: Expert Systems (MYCIN, DENDRAL) using hand-coded rules. Limited scalability.
- 1974–1980: First AI Winter — overpromised results, limited compute, funding cuts.
- 1980s: Backpropagation (Rumelhart, Hinton, Williams 1986) enables training of multi-layer networks.
- 1990s–2000s: Support Vector Machines, Random Forests, and ensemble methods dominate. Spam filters, recommendation engines.
- 2006: Hinton coins 'Deep Learning'; shows deep belief networks can be trained effectively.
- 2012: AlexNet wins ImageNet by >10% margin using GPU-trained CNN. Deep Learning revolution begins.
- 2017: 'Attention Is All You Need' — Transformer architecture; LSTM replaced for NLP.
- 2018: BERT (Google); GPT-1 (OpenAI). Transfer learning for NLP becomes standard.
- 2022: ChatGPT reaches 100M users in 2 months. Largest-scale public deployment of DL.
- 2024–: Multimodal models (text + image + audio). GPT-4o, Gemini 1.5, Claude 3 Opus.

Q3. Explain Gradient Descent in detail. Include types, the learning rate, and how it trains a network.

Answer:

- Gradient Descent: iterative optimisation algorithm that minimises the loss function by updating weights in the direction of the negative gradient.
- Update rule: $W \leftarrow W - lr \times \partial L/\partial W$. Repeated for every batch, every epoch.

• Type 1 — Batch GD: uses all N training samples per update. Most accurate gradient. Impractical for large datasets.

• Type 2 — Stochastic GD: uses 1 random sample per update. Fast but very noisy. Can oscillate around the minimum.

• Type 3 — Mini-Batch GD: uses B samples (32–256) per update. GPU-efficient. Best of both worlds. Standard in practice.

• Learning Rate — too large: overshoots minimum, training diverges. Too small: extremely slow. Typical: 0.001 (Adam), 0.01–0.1 (SGD).

• Training loop: (1) sample mini-batch. (2) forward pass → prediction. (3) compute loss. (4) backprop → gradients. (5) update weights. (6) repeat for all batches (1 epoch). (7) repeat for N epochs.

• Challenges: local minima (solved by momentum/Adam), saddle points, vanishing/exploding gradients.

Q4. Explain Backpropagation and the Chain Rule in detail.

Answer:

• Backpropagation computes ∂L/∂W■ (gradient of loss w.r.t. every weight) by propagating the error backward through the network.

• Forward Pass: input X flows through layers L1 → L2 → … → L■ producing prediction ■.

• Loss Computation: L = loss(■, y) using the appropriate loss function.

• Backward Pass: starting from L, compute gradient of loss w.r.t. output of each layer, moving backward.

• Chain Rule: if L depends on a■ depends on a■■■ depends on … depends on a■, then: ∂L/∂a■ = (∂L/∂a■) × (∂a■/∂a■■■) × … × (∂a■/∂a■).

• This allows gradients to be computed layer by layer using only local gradient information.

• Vanishing Gradient: in deep networks with Sigmoid/Tanh, chain-multiplied gradients shrink exponentially. Fix: ReLU, residual connections, batch normalisation.

• Exploding Gradient: chain-multiplied gradients grow uncontrollably. Fix: gradient clipping.

• Autograd: PyTorch and TensorFlow build a computational graph during the forward pass and replay it in reverse for gradients — no manual derivative computation needed.

Q5. Describe Overfitting in detail. Explain four specific techniques to prevent it.

Answer:

• Overfitting: model achieves low training loss but high validation/test loss. Caused by high model capacity relative to dataset size — the model memorises training examples including noise.

• Detection: plot train loss vs val loss per epoch. If val loss starts increasing while train loss decreases → overfitting.

• Technique 1 — Dropout (Hinton et al., 2012): randomly zero p fraction of neurons each training step. Forces redundant representations; prevents co-adaptation. Rate 0.3–0.5 after dense layers.

• Technique 2 — L2 Regularisation (Weight Decay): add $\lambda \times ||W||^2$ to the loss. Penalises large weights → keeps weights small → simpler decision boundary. AdamW applies weight decay correctly for Adam.

• Technique 3 — Early Stopping: monitor val loss per epoch. Stop training when val loss fails to improve for 'patience' epochs (e.g., 5). Restore weights from the best epoch checkpoint.

• Technique 4 — Data Augmentation: apply random transforms to training images (flip, rotate, crop, colour jitter). Network sees more diverse samples → generalises to real-world variation.

- Additional: reduce model capacity (fewer layers/neurons), collect more data, batch normalisation.
- Trade-off: too much regularisation → underfitting. Balance is found by monitoring validation performance.

Q6. Compare all types of Activation Functions: Sigmoid, Tanh, ReLU, Leaky ReLU, Softmax, GELU.

Answer:

- Sigmoid: output (0,1). Formula: 1/(1+e^–x). Pros: differentiable, probabilistic interpretation. Cons: vanishing gradient; not zero-centred. Use: binary classification output layer.
- Tanh: output (–1,+1). Zero-centred version of Sigmoid. Pros: better gradient flow than Sigmoid. Cons: still vanishes at extremes. Use: RNN hidden states.
- ReLU: output max(0,x). Pros: no vanishing gradient for x>0; computationally trivial; sparse activations. Cons: dying neurons (x<0 always gives 0 gradient). Use: default for hidden layers in CNNs, ANNs.
- Leaky ReLU: max(αx, x) where α≈0.01. Fixes dying neurons by allowing small negative gradient. Use: hidden layers when ReLU neurons die frequently.
- Softmax: e^x■/Σe^x■. Outputs probability distribution summing to 1. Use: multiclass output layer. Not used in hidden layers.
- GELU: x×Φ(x) (Gaussian CDF). Smooth, probabilistic; outperforms ReLU on language tasks. Use: Transformer hidden layers (BERT, GPT-3+).
- ELU: x if x>0; α(e^x–1) if x<0. Smooth negative region; zero-centred outputs. Slightly slower. Use: deep hidden layers where Leaky ReLU is insufficient.
- Rule of thumb: ReLU for CNN/ANN hidden layers. GELU for Transformer hidden layers. Sigmoid for binary output. Softmax for multiclass output.

Q7. What are Tensors? Explain with all dimensions and their applications in deep learning.

Answer:

- Tensors are multi-dimensional arrays of numbers. They are the fundamental data structure in all deep learning frameworks.
- 0-D (Scalar): single number. Examples: loss = 0.023, learning rate = 0.001, accuracy = 0.95.
- 1-D (Vector): shape (n,). Examples: word embedding [0.2, –0.4, 0.7, ...], bias vector, 1D audio waveform (44100,).
- 2-D (Matrix): shape (m, n). Examples: weight matrix of a dense layer, grayscale image (28×28), batch of text tokens (seq_len, vocab_size).
- 3-D Tensor: shape (a, b, c). Examples: colour image (H, W, 3), sequence of embeddings (batch, seq_len, embed_dim), feature map from a conv layer.
- 4-D Tensor: shape (a, b, c, d). Examples: batch of colour images (N, H, W, 3), video clip (T, H, W, 3).
- 5-D Tensor: shape (a, b, c, d, e). Examples: batch of video clips (N, T, H, W, 3).
- Why it matters: the shape of input tensors directly determines the architecture of the input layer and all subsequent layers.
- Libraries: NumPy (CPU), TensorFlow Tensors, PyTorch Tensors (CPU/GPU), JAX arrays.

Q8. Compare Batch GD, Stochastic GD, and Mini-Batch GD. Which is used in practice and why?

Answer:

- Batch GD: processes all N training samples before updating weights once. Most accurate gradient direction. Problems: (1) memory intensive — all data must fit in RAM/VRAM. (2) very slow — one update per full pass. (3) no benefit from GPU parallelism across samples.
- Stochastic GD: processes 1 randomly sampled example per weight update. Advantages: very fast updates; noisy gradient can escape local minima. Problems: very noisy — loss oscillates; hard to converge precisely; doesn't leverage GPU parallelism.
- Mini-Batch GD: processes B samples (typically 32–256) per update. Advantages: (1) memory efficient. (2) GPU-friendly — matrix ops on a batch are parallelised. (3) better gradient estimate than SGD. (4) natural regularisation from batch variance.
- Standard in practice: Mini-Batch GD with B=32 or 64.
- Batch size effects: larger batch → more accurate gradient, requires higher lr, slightly worse generalisation (sharp minima). Smaller batch → noisier, better generalisation (flat minima), lower memory.
- Linear scaling rule: if batch size doubles, multiply lr by 2 to maintain training dynamics.
- All modern DL frameworks default to mini-batch processing.

Q9. Describe the types of Deep Learning models. For each, give architecture, working principle, and application.

Answer:

- ANN (Fully Connected): all neurons in one layer connect to all in the next. Learns global feature combinations. Best for tabular structured data. Application: customer churn prediction, fraud scoring.
- CNN: convolutional filters scan input spatially to detect local patterns. Pooling reduces spatial dimensions. Parameters shared across spatial positions → efficient. Best for images/video. Application: object detection (YOLO), medical imaging (chest X-ray classification).
- RNN: output at time t depends on input at t and hidden state from t–1. Creates sequence memory. Suffers from vanishing gradient over long sequences. Best for short sequential data. Application: sentiment analysis, time-series anomaly detection.
- LSTM: extends RNN with three gates (forget, input, output) and a cell state. Maintains long-range dependencies. Best for long sequences. Application: machine translation, speech recognition.
- Transformer: self-attention allows each token to attend to all others simultaneously. Fully parallelisable — no recurrence. Scaled to billions of parameters. Best for NLP, vision, multimodal. Application: ChatGPT (GPT-4), BERT, ViT, DALL-E 3.
- GAN: generator G creates synthetic data; discriminator D distinguishes real from fake. Adversarial training drives G to produce realistic outputs. Application: image synthesis, super-resolution, data augmentation.
- Autoencoder: encoder compresses input to bottleneck latent vector; decoder reconstructs. Learns compact representations. Application: anomaly detection, image denoising, dimensionality reduction.

Q10. Explain Loss Functions in detail. Include MSE, MAE, Binary CE, and Categorical CE.

Answer:

- A loss function L(■, y) measures prediction error. Training minimises L via gradient descent. Must be differentiable.

- Mean Squared Error (MSE): L = (1/N)Σ(y■ – ■■)². Squares errors → large errors penalised heavily. Differentiable everywhere. Used for regression. Sensitive to outliers.
- Mean Absolute Error (MAE): L = (1/N)Σ|y■ – ■■|. All errors penalised equally regardless of magnitude. More robust to outliers. Not differentiable at zero (use subgradient). Used for regression.
- Binary Cross-Entropy: L = –(1/N)Σ[y■ log(■■) + (1–y■)log(1–■■)]. Measures divergence between predicted probability and binary label {0,1}. Paired with Sigmoid output. Used for binary classification.
- Categorical Cross-Entropy: L = –(1/N)Σ Σ y■■ log(■■■). Labels as one-hot vectors. Paired with Softmax output. Used for multiclass classification. Heavily penalises confident wrong predictions.
- Huber Loss: MSE for |error| < δ, MAE-scaled for |error| ≥ δ. Best of both — smooth near zero, robust to outliers. Used in object detection regression heads.
- Selection guide: regression → MSE or Huber. Binary classification → Binary CE. Multiclass → Categorical CE. Generative models → KL divergence or adversarial loss.

Q11. Describe the complete set of techniques to prevent overfitting with justification.

Answer:

- 1. More Training Data: most effective. With N→∞ samples, the model cannot memorise — it must learn patterns. Practical limits: cost, privacy, availability.
- 2. Dropout: during training, randomly set p fraction of activations to zero. At inference, scale by (1–p). Prevents co-adaptation of neurons. Effectively trains an ensemble of 2^N sub-networks. Standard rate: 0.3–0.5 for dense layers, 0.1–0.2 for convolutional layers.
- 3. L2 Regularisation: adds λ||W||² to loss. Gradient update becomes: ∂L/∂W + 2λW. Shrinks weights toward zero — simpler model. Equivalent to Gaussian prior on weights (Bayesian view).
- 4. L1 Regularisation: adds λ||W||■ to loss. Promotes sparsity — some weights become exactly zero. Effectively performs feature selection.
- 5. Early Stopping: track val loss per epoch. Stop and restore best checkpoint when val loss fails to improve for patience epochs. Simple, zero architectural overhead.
- 6. Data Augmentation: creates synthetic training diversity. Trains the model to be invariant to specified transformations (e.g., horizontal flip → mirror-invariant). Critical when dataset < 10,000 samples.
- 7. Batch Normalisation: normalises activations per mini-batch. Reduces internal covariate shift. Acts as mild regulariser. Also allows higher lr and faster training.
- 8. Reduce Capacity: fewer parameters → less capacity to memorise. Start with minimal architecture; add capacity only if underfitting.
- 9. Cross-Validation: K-Fold CV gives unbiased performance estimate and reveals how much variance exists across different train/val splits.

Q12. What is the significance of Data Representation in deep learning? Explain with examples.

Answer:

- Data representation is the process of converting real-world data into numerical tensors that a neural network can process. The choice of representation directly determines what information the model can learn.
- Images: grayscale stored as (H, W) matrix; colour as (H, W, 3). Pixel values normalised [0,1]. Batch: (N, H, W, C). A 224×224 colour image = 150,528 numbers.
- Audio: waveform as 1-D tensor (44,100 samples per second). Mel spectrogram: (mel_bins, time_frames) 2-D tensor — suitable for CNN input. Used in Shazam, Google's ASR.

• Text: tokenisation splits sentences into subword units. Token IDs (integers) → embedding layer → dense vectors (768-dim in BERT). Final representation: (seq_len, embed_dim) 2-D tensor.

• Video: sequence of frames → (T, H, W, 3) 4-D tensor. Processing full video is memory-intensive; typically sample keyframes or use 3D convolutions on short clips.

• Tabular data: numerical features as (num_features,) vector. Categorical: one-hot encoded or embedding. Normalise continuous features to zero mean / unit variance.

• Impact of poor representation: losing spatial information by averaging all pixels. Treating categories as ordered integers (male=0, female=1) introduces false ordering.

• Impact of good representation: pre-trained word embeddings (GloVe) improve NLP tasks by 5–15% even before any task-specific training.

• Transfer learning for representation: use ImageNet-pretrained ResNet features as input representation for medical images — reduces data requirement from millions to thousands.

Q13. Explain the different types of Optimizers used in deep learning.

Answer:

• An optimizer updates model weights using gradients computed by backpropagation.

• SGD: $W \leftarrow W - lr \cdot \nabla L$. Simple. No adaptive LR. Works well with careful lr tuning and schedules. Still used for large-scale image training (e.g., ResNet trained with SGD + cosine schedule).

• SGD + Momentum: $v \leftarrow \beta \cdot v + \nabla L$; $W \leftarrow W - lr \cdot v$. Accumulates gradient direction. Helps navigate ravines. β=0.9 standard.

• RMSprop: maintains exponential moving average of squared gradients. Divides lr by RMS. Prevents exploding updates. Designed by Hinton for RNNs.

• Adam: $m \leftarrow \beta_1 \cdot m + (1-\beta_1) \cdot \nabla L$ (first moment). $v \leftarrow \beta_2 \cdot v + (1-\beta_2) \cdot (\nabla L)^2$ (second moment). Bias-corrected estimates. $W \leftarrow W - lr \cdot m_1/\sqrt{v_2}+\varepsilon$. Default lr=0.001, β_1=0.9, β_2=0.999, ε=1e-8.

• AdamW: Adam + decoupled weight decay. Adds $-\lambda W$ directly to update (not via gradient). Correct implementation of weight decay for Adam. Standard for fine-tuning Transformers.

• Adagrad: per-parameter lr divides by sum of all past squared gradients. Good for sparse features (NLP). Lr monotonically decreases → eventually stops learning.

• LAMB: Layer-wise Adaptive Rate Scaling. Designed for very large batch training (e.g., BERT with batch 32,768). Scales updates per-layer and per-parameter.

• Practical advice: use Adam (lr=0.001) as default. Switch to AdamW for Transformers. Use SGD + momentum + cosine schedule for production image classification.

Q14. Describe all applications of Deep Learning across industries with specific systems.

Answer:

• Computer Vision: CNNs enable image classification (ResNet-152, EfficientNet), object detection (YOLOv8, Faster R-CNN), segmentation (U-Net for medical), face recognition (DeepFace, FaceNet).

• Natural Language Processing: Transformers enable chatbots (ChatGPT), search (Google BERT), translation (DeepL, Google Translate), code generation (GitHub Copilot), summarisation.

• Speech: WaveNet (DeepMind) for neural TTS; Whisper (OpenAI) for speech recognition with 99 language support; Siri, Alexa, Google Assistant.

• Healthcare: CheXNet (Stanford) detects pneumonia from chest X-ray at radiologist level. DeepMind AlphaFold2 predicted 200M+ protein structures. Google LYNA detects lymph node metastases.

• Autonomous Vehicles: Tesla FSD uses 8 cameras → CNN → BEV representation → transformer planner. Waymo uses LiDAR + camera fusion. 4+ billion real-world miles logged.

• Generative AI: DALL-E 3, Stable Diffusion, Midjourney (image from text). Sora (OpenAI, video generation). MuseNet / AudioCraft (music). ElevenLabs (voice cloning).

• Recommendation Systems: YouTube (700M+ videos ranked per day), Netflix (saves $1B/year via recommendations), Spotify Discover Weekly.

• Scientific Research: AlphaFold2 (proteins), AlphaMissense (pathogenicity of mutations), weather forecasting (GraphCast by DeepMind), drug discovery (Insilico Medicine).

• Manufacturing: visual quality control (replacing manual inspection), predictive maintenance (vibration sensors + LSTM), robot path planning.

• Finance: high-frequency trading signal generation, credit scoring, insurance claims processing, real-time fraud detection (Visa: 500 DL models in production).

Q15. Write a complete note on the training pipeline of a deep learning model.

Answer:

• Stage 1 — Problem Definition: define task (classification/regression/generation), target metric, data availability, latency/memory constraints, and deployment environment.

• Stage 2 — Data Collection: gather labelled data from appropriate sources. Ensure class balance, representative distribution, and correct annotation. Split: 70–80% train, 10–15% val, 10–15% test. Never use test set during development.

• Stage 3 — Data Preprocessing: normalise inputs (zero-mean/unit-variance or [0,1]). Encode categorical features (one-hot, ordinal, or learned embeddings). Handle missing values. Tokenize text.

• Stage 4 — Data Augmentation: define augmentation pipeline for training set only. For images: random crop, flip, colour jitter. For text: back-translation, synonym swap.

• Stage 5 — Model Architecture Design: select architecture type (CNN for images, Transformer for text). Define depth, width, activation functions, regularisation. Consider pre-trained backbone for transfer learning.

• Stage 6 — Training Loop: for each epoch: sample mini-batches → forward pass → compute loss → backprop → optimizer step → log metrics. Monitor train/val loss and accuracy per epoch with TensorBoard.

• Stage 7 — Hyperparameter Tuning: tune lr, batch size, dropout rate, weight decay, model depth. Use grid search (small space) or Bayesian optimisation. Always compare on validation set, never test set.

• Stage 8 — Evaluation: evaluate best checkpoint on held-out test set. Report: accuracy, precision/recall/F1, AUC-ROC, confusion matrix. For regression: RMSE, MAE, R^2.

• Stage 9 — Optimisation for Deployment: quantise weights (FP32 → INT8, ~4× smaller). Prune unimportant weights. Apply knowledge distillation to compress model. Export to ONNX or TFLite.

• Stage 10 — Deployment and Monitoring: serve via REST API (FastAPI/Flask). Deploy on cloud (AWS SageMaker, GCP Vertex AI) or edge (TFLite, ONNX Runtime). Monitor for data drift; retrain periodically.

10-MARK QUESTIONS (Long Descriptive)

Q1. Write a detailed note on the evolution of AI from 1950 to present, covering all major milestones, key figures, and technologies.

Answer:

• Introduction: AI has evolved over 70+ years in distinct waves, each constrained or accelerated by hardware, data, and algorithmic progress.

• 1950 — Turing Test: Alan Turing proposes the Imitation Game — if a machine can converse indistinguishably from a human, it can be considered intelligent. First rigorous definition of machine intelligence.

• 1956 — Dartmouth Conference: John McCarthy, Marvin Minsky, Claude Shannon, and others coin 'Artificial Intelligence'. First AI research community formed.

• 1958 — Perceptron: Frank Rosenblatt builds the Perceptron — the first learning algorithm for a single-layer neural network. Trained on punched cards to classify shapes.

• 1966 — ELIZA: Joseph Weizenbaum at MIT creates ELIZA, the first conversational program using pattern matching. Demonstrates how easily humans anthropomorphise machines.

• 1969 — Minsky & Papert: show that Perceptrons cannot solve XOR — a linear classifier limitation. Research interest in neural networks drops sharply.

• 1970s — Expert Systems: knowledge-based AI dominates. MYCIN (1972) diagnoses bacterial infections; DENDRAL identifies chemical structures. Work well in narrow domains but cannot generalise.

• 1974–1980 — First AI Winter: Lighthill Report (UK) criticises AI progress. DARPA cuts funding. NLP and robotics fail to deliver promised results. First AI Winter.

• 1986 — Backpropagation: Rumelhart, Hinton & Williams popularise backpropagation for training multi-layer networks. Enables learning in networks previously thought untrainable.

• 1989 — LeNet: Yann LeCun applies backprop + CNNs to handwritten digit recognition. Deployed by US Postal Service to read ZIP codes. First commercial deep learning application.

• 1997 — LSTM: Hochreiter & Schmidhuber publish Long Short-Term Memory — solves the vanishing gradient problem in RNNs. Enables learning from long sequences.

• 1997 — Deep Blue: IBM's Deep Blue defeats Garry Kasparov at chess. Rule-based search with expert evaluation — not machine learning, but milestone AI achievement.

• 2006 — Deep Learning coined: Hinton & Salakhutdinov show deep belief networks (stacked RBMs) can be trained layer by layer. Re-ignites neural network research.

• 2009 — ImageNet dataset: Fei-Fei Li creates ImageNet — 14 million labelled images across 1,000+ categories. Provides the benchmark for vision models.

• 2012 — AlexNet revolution: Krizhevsky, Sutskever & Hinton win ImageNet with AlexNet (CNN + ReLU + Dropout + GPU training) by 10.8% margin. Top-5 error: 15.3% vs 26.2% next best. Deep learning era begins.

• 2014 — GANs: Ian Goodfellow introduces Generative Adversarial Networks. Generator vs Discriminator framework. Foundation of modern image synthesis.

• 2015 — ResNet: He et al. introduce residual (skip) connections — train 152-layer networks stably. Wins ImageNet with 3.57% top-5 error (below human 5.1%).

• 2017 — Transformer: Vaswani et al. publish 'Attention Is All You Need'. Self-attention replaces recurrence. Fully parallelisable — revolutionises NLP.

• 2018 — BERT: Google's Bidirectional Encoder Representations from Transformers. Pre-trained on 3.3B words. Fine-tuned for 11 NLP tasks at state-of-the-art. Transforms search, Q&A;, NER.

• 2020 — GPT-3: OpenAI. 175B parameters. Few-shot learning — performs tasks without fine-tuning. Demonstrated emergent capabilities at scale.

• 2022 — ChatGPT: GPT-3.5 fine-tuned with RLHF (Reinforcement Learning from Human Feedback). 100 million users in 2 months. Largest-scale AI product deployment in history.

• 2024 — Multimodal & Agents: GPT-4o (text+image+audio), Gemini 1.5 Pro (1M context), Claude 3 Opus. AI agents that use tools, browse the web, and execute code.

• Key figures: Alan Turing, John McCarthy, Marvin Minsky, Frank Rosenblatt, Geoffrey Hinton, Yann LeCun, Yoshua Bengio (Turing Award 2018), Ian Goodfellow, Ilya Sutskever, Sam Altman.

• Three drivers of modern AI: (1) Data — internet generates 2.5 quintillion bytes/day. (2) Compute — GPU clusters from NVIDIA (H100 = 2,000 TFLOPS). (3) Algorithms — attention, residuals, batch norm, RLHF.

Q2. Explain Gradient Descent and all its variants in detail. Include learning rate effects, convergence challenges, and advanced optimizers.

Answer:

• Definition: Gradient Descent is a first-order iterative optimisation algorithm. It minimises an objective function f(W) by updating parameters W in the direction of the negative gradient: $W \leftarrow W - lr \times \nabla f(W)$.

• Geometric Interpretation: the loss function defines a surface over weight space. Gradient descent navigates this surface by always stepping in the locally downhill direction. For convex functions, it finds the global minimum. For non-convex (typical in deep learning), it finds a local minimum or saddle point.

• Batch Gradient Descent: computes exact gradient over all N samples before each update. Pros: stable, accurate gradient direction; monotonically decreasing loss. Cons: requires all data in memory (O(N) per step); slow — 1 update per epoch; no benefit from GPU parallelism across samples.

• Stochastic Gradient Descent (SGD): one random sample per update. Pros: very fast, frequent updates; inherent noise helps escape shallow local minima. Cons: noisy, erratic loss curve; doesn't converge precisely — oscillates near minimum.

• Mini-Batch Gradient Descent: B samples per update (B=32 standard). Advantages: (1) GPU processes matrix ops on batch in parallel. (2) Gradient is better estimated than single sample. (3) Memory efficient. (4) Controlled noise helps generalisation. Standard in all frameworks.

• Learning Rate Effects: lr too large → W overshoots minimum, oscillates, can diverge (loss → ∞). lr too small → converges but takes impractically many iterations. Finding lr: learning rate range test (Smith, 2017) — sweep lr from 1e-7 to 1 over a few batches and find the range where loss decreases fastest.

• Learning Rate Scheduling: (1) Step decay: halve lr every k epochs. (2) Cosine annealing: smooth lr decrease following cosine curve. (3) Reduce on plateau: halve lr when val loss stops improving. (4) Warmup: start with very small lr, linearly increase for first N steps, then decay — standard for Transformers.

• Challenges: (1) Local minima — non-convex landscape. For overparameterised networks, most local minima are near-global (Goodfellow 2015). (2) Saddle points — gradient ≈ 0 but not minimum; common in high-dim spaces; momentum helps escape. (3) Flat regions — very small gradients, slow progress. (4) Vanishing gradients — gradients shrink to 0 in early layers. Fix: ReLU, residual connections. (5) Exploding gradients — gradients grow unboundedly. Fix: gradient clipping.

• Momentum: adds velocity $v = \beta \cdot v + \nabla L$; $W \leftarrow W - lr \cdot v$. Like a ball accumulating speed rolling downhill. $\beta=0.9$ standard. Reduces oscillation in ravines; accelerates progress along dominant gradient direction.

• RMSprop: $v_{■} \leftarrow \beta \cdot v_{■} + (1-\beta) \cdot (\partial L/\partial W_{■})^2$. $W_{■} \leftarrow W_{■} - lr \cdot (\partial L/\partial W_{■})/\sqrt{v_{■}}+\varepsilon$. Per-parameter adaptive lr. Prevents oscillation from parameters with large gradient variance. Designed for RNNs.

• Adam: $m_{■} \leftarrow \beta_{■} \cdot m_{■} + (1-\beta_{■}) \cdot g_{■}$ (first moment = gradient mean). $v_{■} \leftarrow \beta_{■} \cdot v_{■} + (1-\beta_{■}) \cdot g_{■}^2$ (second moment = gradient variance). Bias-corrected: $m_{■■} = m_{■}/(1-\beta_{■■})$, $v_{■■} = v_{■}/(1-\beta_{■■})$. Update: $W_{■} \leftarrow W_{■} - lr \cdot m_{■■}/\sqrt{v_{■■}}+\varepsilon$. Default: lr=0.001, $\beta_{■}=0.9$, $\beta_{■}=0.999$, $\varepsilon=1e-8$.

• AdamW: decouples weight decay from gradient update: $W_{■} \leftarrow W_{■}(1-lr \cdot \lambda) - lr \cdot m_{■■}/\sqrt{v_{■■}}+\varepsilon$. Correct implementation of L2 regularisation with Adam. Standard for fine-tuning Transformers (BERT, GPT).

• Practical recommendation: start with Adam (lr=0.001). For Transformer fine-tuning: AdamW with warmup + cosine schedule. For ImageNet training from scratch: SGD + momentum + cosine annealing. Monitor loss curve and val accuracy every epoch.

Q3. Explain Backpropagation and the Chain Rule in complete technical detail.

Answer:

• Backpropagation (Rumelhart, Hinton & Williams, 1986): an efficient algorithm to compute $\partial L/\partial W_{■}$ for every weight $W_{■}$ in the network by applying the chain rule of calculus through the computational graph.

• Why we need it: a network with L layers has parameters at every layer. Naively computing the gradient of the loss w.r.t. $W_{■}$ (first layer weights) requires accounting for the effect of $W_{■}$ on every intermediate layer's output and ultimately the loss. Backprop makes this efficient by reusing intermediate computations.

• Computational Graph: during the forward pass, all operations (multiply, add, activation) are recorded as nodes in a directed acyclic graph. Each node stores its local gradient (how much its output changes per unit change in its input). Backprop traverses this graph in reverse.

• Chain Rule: if $L = g(h(f(x)))$, then $dL/dx = (dL/dg) \times (dg/dh) \times (dh/df) \times (df/dx)$. Each derivative is computed locally at each node and multiplied along the path from x to L.

• Detailed Forward Pass: $x \rightarrow \text{Linear}(W_{■}, b_{■}) \rightarrow a_{■} = \text{ReLU}(z_{■}) \rightarrow \text{Linear}(W_{■}, b_{■}) \rightarrow a_{■} = \text{Softmax}(z_{■}) \rightarrow L = \text{CrossEntropy}(a_{■}, y)$.

• Backward Pass Step 1 (output layer gradient): $\partial L/\partial z_{■} = a_{■} - y$ (combined softmax + cross-entropy gradient, known closed form).

• Backward Pass Step 2 ($W_{■}$ gradient): $\partial L/\partial W_{■} = \partial L/\partial z_{■} \cdot a_{■■}$. This is computed as outer product of upstream gradient and layer input.

• Backward Pass Step 3 (propagate to hidden layer): $\partial L/\partial a_{■} = W_{■■} \cdot \partial L/\partial z_{■}$. Chain rule: multiply by transpose of weight matrix.

• Backward Pass Step 4 (through ReLU): $\partial L/\partial z_{■} = \partial L/\partial a_{■} \; ■ \; \text{ReLU}'(z_{■})$. $\text{ReLU}'(z) = 1$ if $z>0$, else 0. Element-wise mask.

• Backward Pass Step 5 ($W_{■}$ gradient): $\partial L/\partial W_{■} = \partial L/\partial z_{■} \cdot x_{■}$.

• Vanishing Gradient: in deep networks with Sigmoid/Tanh, $\partial a/\partial z = \sigma(z)(1-\sigma(z)) \leq 0.25$. With 100 layers, gradient magnitude $\leq 0.25^{1■■} \approx 10^{■■■}$. Early layers learn nothing. Fixes: ReLU (gradient = 1 for $z>0$), residual connections (gradient highway), batch normalisation.

• Exploding Gradient: gradient magnitude grows exponentially in RNNs over time. Fix: gradient clipping — if $||g||_{■} > \text{threshold}$, scale $g \leftarrow g \times (\text{threshold}/||g||_{■})$.

• Automatic Differentiation: PyTorch builds the computation graph dynamically during the forward pass (eager execution). Calling .backward() triggers reverse-mode autodiff. No manual gradient coding required. torch.no_grad() context manager disables grad tracking for inference.

- Computational complexity: one forward + backward pass costs roughly 3× the forward pass alone. Memory: store all intermediate activations for use in backward pass (activation checkpointing can reduce memory at cost of recomputation).
- Second-order methods (not used in practice): Newton's method uses the Hessian (second derivatives) for more accurate updates but is $O(N^2)$ to compute and $O(N^3)$ to invert for N parameters — infeasible for millions of parameters.

Q4. Describe all Deep Learning model architectures in detail. Include architecture, training objective, strengths, limitations, and real applications.

Answer:

- 1. ANN (Fully Connected / MLP): Architecture: input → [Dense + activation]×L → output. Each neuron connects to all neurons in next layer. N parameters = sum(n■ × n■■■ + n■■■). Training: standard SGD + backprop. Loss: MSE (regression) or Cross-Entropy (classification). Strengths: universal approximator (1 hidden layer + enough neurons). Weaknesses: $O(n^2)$ parameters for dense connections — inefficient for high-dim inputs (e.g., 1000×1000 image = 10■ input nodes → billions of parameters). Applications: tabular ML tasks, feed-forward layers in all larger architectures.
- 2. CNN: Architecture: [Conv(k, n_filters) + ReLU + Pooling]×D → Flatten → Dense → output. Convolutional layer: F filters of shape (k, k, C_in) slide over input with stride s, padding p. Output size: ■(n+2p–k)/s■+1. Parameter count: F×k×k×C_in + F (biases). Training objective: same as ANN. Key innovations: weight sharing (same filter applied everywhere), local connectivity, pooling for translation invariance. Architectures: LeNet-5, AlexNet, VGG, ResNet (skip connections), DenseNet, EfficientNet. Applications: ImageNet classification, COCO object detection, medical imaging, autonomous driving.
- 3. RNN: Architecture: h■ = tanh(W■·x■ + W■·h■■■ + b). Hidden state h■ carries memory from previous steps. Unrolled over T steps. Shared weights W■, W■ across all time steps. Backprop Through Time (BPTT): unroll T steps, apply backprop. Gradient products across T steps → vanishing/exploding. Limitations: effectively remembers only ~10–20 time steps. Applications: character language models, short-term sequence classification.
- 4. LSTM: Architecture: Forget gate: f■ = σ(Wf·[h■■■, x■] + bf). Input gate: i■ = σ(Wi·[h■■■, x■] + bi). Candidate: C■■ = tanh(WC·[h■■■, x■] + bC). Cell update: C■ = f■■C■■■ + i■■C■■. Output gate: o■ = σ(Wo·[h■■■, x■] + bo). Hidden: h■ = o■■tanh(C■). Cell state C■ acts as long-term memory; gates control information flow. Applications: seq2seq translation, speech recognition, time-series forecasting.
- 5. Transformer: Architecture: Input embeddings + positional encoding → N× [Multi-Head Attention → Add&Norm; → Feed-Forward → Add&Norm;] → output. Self-Attention: Queries Q, Keys K, Values V (all linear projections of input). Attention(Q,K,V) = softmax(QK■/√d■)V. Multi-Head: H parallel attention heads; outputs concatenated + projected. Encoder (BERT-style): bidirectional attention over all tokens. Decoder (GPT-style): causal (left-to-right) masked attention. Parallelism: no recurrence → all positions computed simultaneously → efficient GPU utilisation. Scaling: performance improves predictably with model size and data (Chinchilla scaling laws). Applications: ChatGPT, BERT, T5, ViT (vision), Whisper (speech), AlphaFold2 (protein).
- 6. GAN: Architecture: G (generator): latent vector z ~ N(0,I) → fake image x■ = G(z). D (discriminator): image x → P(real). Objective: minimax game: min_G max_D E[log D(x)] + E[log(1–D(G(z)))]. Training: alternate D update (maximise D accuracy) and G update (minimise D confidence on fakes). Challenges: mode collapse, training instability. Improvements: Wasserstein GAN (W-GAN), progressive growing, StyleGAN2. Applications: face synthesis, image super-resolution, data augmentation, deepfakes.

• 7. Variational Autoencoder (VAE): Architecture: encoder $q_\phi(z|x) \to \mu, \sigma$. Reparameterisation: $z = \mu + \varepsilon \cdot \sigma$ where $\varepsilon \sim N(0,I)$. Decoder $p_\theta(x|z) \to x$■. Loss: reconstruction + KL divergence ($KL(q(z|x)||p(z))$). Enables smooth latent space interpolation. Applications: image generation, drug molecule design, anomaly detection.

• 8. Diffusion Models: Architecture: forward process adds Gaussian noise over T steps. Reverse process: U-Net (with attention) learns to denoise at each step. Training objective: predict added noise. Sampling: iteratively denoise from pure noise over 50–1000 steps. State of the art for image generation. Applications: Stable Diffusion, DALL-E 3, Midjourney, Sora (video).

• Practical selection guide: tabular → MLP. Images → CNN or ViT. Short sequences → LSTM. Long text/language → Transformer. Image generation → Diffusion model. GAN for discriminative generation tasks. Transfer learning: always start from a pre-trained backbone.

Q5. Explain Overfitting comprehensively: causes, detection, all prevention techniques, and the bias-variance tradeoff.

Answer:

• Definition and Formal Statement: overfitting occurs when empirical training error ≈ 0 but generalisation error (expected error on new samples) >> 0. The model has learned the training distribution too specifically to generalise.

• Root Cause — Bias-Variance Tradeoff: total expected error = $Bias^2$ + Variance + irreducible noise. Bias: error from wrong model assumptions (underfitting). Variance: error from sensitivity to training data fluctuations (overfitting). These cannot both be minimised simultaneously with fixed data. Increasing model complexity: bias ↓, variance ↑. Decreasing complexity: bias ↑, variance ↓.

• Causes of Overfitting: (1) Model too complex relative to dataset size. (2) Training too many epochs without regularisation. (3) Insufficient training data. (4) Noisy or incorrectly labelled data. (5) Irrelevant features included in input.

• Detection: (1) Training loss << validation loss — large generalisation gap. (2) Validation loss curve rises after initial decrease (classic signature). (3) Val accuracy plateaus or drops while train accuracy continues to rise. (4) Model performs much worse on held-out test set than on train set.

• Technique 1 — Dropout (Srivastava et al., 2014): randomly zero a fraction p of unit activations each forward pass during training. Mathematical interpretation: trains an ensemble of 2■ thinned networks. At inference: use full network with weights scaled by (1–p). Typically p=0.5 for dense layers, p=0.1–0.2 for conv layers. Reduces co-adaptation: no neuron can rely on the presence of specific other neurons → more independent, distributed representations.

• Technique 2 — L2 Regularisation: augment loss: $L_{reg} = L + \lambda||W||^2$. Gradient: $\partial L_{reg}/\partial W = \partial L/\partial W + 2\lambda W$. Equivalent to weight decay. Prefers small distributed weights over large concentrated weights. Bayesian interpretation: Gaussian prior on weights. λ is tuned on validation set. Typical range: 1e-4 to 1e-2.

• Technique 3 — L1 Regularisation: $L_{reg} = L + \lambda||W||$■. Gradient: subgradient = $\partial L/\partial W + \lambda \cdot sign(W)$. Promotes sparsity: drives unimportant weights exactly to zero. Effectively performs feature selection. Less common in deep learning than L2 but used in sparse autoencoders.

• Technique 4 — Early Stopping: track val loss at each epoch. Save model checkpoint when val loss is lowest. Stop training when val loss hasn't improved for patience epochs. Restore best checkpoint. Advantage: zero architectural overhead; works with any model. Justification: models early in training have implicit bias toward simpler solutions.

• Technique 5 — Data Augmentation: expand dataset by applying semantics-preserving transformations. Images: horizontal/vertical flip, rotation, zoom, colour jitter, cutout, mixup. Text: back-translation (EN→FR→EN), synonym replacement, EDA. Audio: time stretching, pitch shifting,

noise addition. Theoretical justification: equivalent to imposing invariance constraints on the model.

• Technique 6 — Batch Normalisation (Ioffe & Szegedy, 2015): normalise pre-activation of each layer per mini-batch: x■ = (x – μ_B)/σ_B, then apply learnable scale γ and shift β. Acts as mild regulariser: different normalisation statistics per mini-batch add noise. Also: allows higher lr, reduces sensitivity to weight initialisation, stabilises training.

• Technique 7 — Reduce Model Capacity: fewer layers, fewer neurons per layer, lower-rank weight matrices (factorisation), pruning (remove weights below threshold). Follows Occam's Razor: prefer simplest model that fits the data.

• Technique 8 — Cross-Validation: K-Fold CV provides unbiased performance estimate. Especially important for small datasets. Stratified K-Fold ensures class balance in each fold. Nested CV for hyperparameter selection avoids data leakage.

• Technique 9 — Label Smoothing: replace hard targets (0/1) with soft targets (ε/K, 1–ε+ε/K). Prevents model from being overconfident about training labels. Regularises the output probability distribution. Used in modern image classification (Inception-v4, EfficientNet).

• Technique 10 — Stochastic Depth: randomly skip entire residual blocks during training (ResNet variant). Similar to dropout but at block level. Reduces effective depth during training → less capacity.

• Summary: the best strategy combines multiple complementary techniques. Standard recipe for new classification task: Adam + data augmentation + early stopping + dropout + L2 regularisation + batch normalisation.

Q6. Explain all Loss Functions used in deep learning with mathematical intuition and applications.

Answer:

• Role of Loss Functions: a differentiable scalar function L(■, y) measuring prediction quality. Backpropagation requires ∂L/∂■. The choice of loss function directly encodes the learning objective.

• Mean Squared Error (MSE): L = (1/N)Σ■(y■ – ■■)². Properties: symmetric about zero, penalises large errors quadratically (outliers dominate), always differentiable. Minimum at ■ = E[y]. Used for: regression where large errors are especially bad. Example: predicting house prices — underestimating by Rs.10L is 4× penalised vs 5L.

• Mean Absolute Error (MAE): L = (1/N)Σ■|y■ – ■■|. Properties: symmetric, penalises all errors equally regardless of magnitude, more robust to outliers. Not differentiable at y■=■■ (use subgradient: sign of error). Minimum at ■ = median(y). Used for: regression where outliers exist (e.g., income prediction).

• Huber Loss: δ-parameterised. L = 0.5(y–■)² if |y–■| ≤ δ; δ|y–■| – 0.5δ² otherwise. Smooth everywhere; quadratic near zero (like MSE), linear for large errors (like MAE). Best of both. δ is a hyperparameter. Used in: Faster R-CNN regression head, Q-learning (DQN).

• Binary Cross-Entropy (BCE): L = –(1/N)Σ■[y■ log(■■) + (1–y■)log(1–■■)]. Gradient: ■ – y (for Sigmoid output) — clean form. Maximum likelihood interpretation: maximises log-likelihood under Bernoulli distribution. Heavily penalises confident wrong predictions (log(0) = –∞). Used with Sigmoid output for binary classification.

• Categorical Cross-Entropy (CCE): L = –(1/N)Σ■ Σ■ y■■ log(■■■). Only the term for the true class j* contributes: L = –(1/N)Σ■ log(■■,j*). Gradient w.r.t. Softmax input: ■ – y (one-hot). Maximum likelihood under Categorical distribution. Penalises overconfident wrong predictions logarithmically. Standard for multiclass classification.

• Focal Loss (Lin et al., 2017): FL = –α■(1–p■)^γ log(p■). Down-weights easy examples (large (1–p■) when p■≈1); focuses learning on hard examples. Solves class imbalance in object detection where background >> foreground. Used in: RetinaNet object detector.

- KL Divergence: $KL(P||Q) = \Sigma P(x) \log(P(x)/Q(x))$. Non-symmetric measure of how different distribution Q is from reference P. $KL(P||Q) = 0$ iff $P = Q$. Used as regularisation in VAEs: $KL(q(z|x)||p(z))$ forces latent space to follow standard Normal.
- Contrastive Loss (CL): $L = yd^2 + (1-y)\max(margin-d, 0)^2$. y=1 for similar pairs, y=0 for dissimilar. d = distance between embeddings. Pulls similar samples together, pushes dissimilar apart. Used in: siamese networks, face verification (FaceNet).
- Triplet Loss: $L = \max(||f(a)-f(p)||^2 - ||f(a)-f(n)||^2 + margin, 0)$. Anchor a, positive p (same class), negative n (different class). Ensures anchor is closer to positive than negative by at least margin. Used in: FaceNet face embeddings, product image search.
- Adversarial Loss (GAN): $\min_G \max_D E[\log D(x)] + E[\log(1-D(G(z)))]$. Generator loss: $\min_G E[\log(1-D(G(z)))]$ or equivalently $\max_G E[\log D(G(z))]$. Wasserstein loss (W-GAN): Kantorovich-Rubinstein duality; more stable training, meaningful gradient everywhere.
- Selection guide: Regression → MSE (no outliers), MAE/Huber (with outliers). Binary classification → BCE. Multiclass → CCE. Class-imbalanced detection → Focal Loss. Embedding learning → Triplet/Contrastive. Generation → Adversarial/Diffusion. VAE → Reconstruction + KL.

Q7. Describe Activation Functions comprehensively. Include mathematical properties, gradients, advantages, and use cases.

Answer:

- Purpose: introduce non-linearity into the network. Without non-linear activations, composing L linear layers = one linear layer (universally). Non-linearity enables approximation of arbitrary functions.
- Sigmoid: $\sigma(x) = 1/(1+e^{-x})$. Range: (0,1). Gradient: $\sigma'(x) = \sigma(x)(1-\sigma(x)) \in (0, 0.25]$. Max gradient = 0.25 at x=0. Problems: (1) Vanishing gradient: for $|x|>5$, gradient<0.006 — gradients in early layers become negligible. (2) Non-zero centred outputs → weights update in same sign direction → slow convergence. (3) Computationally expensive (exp). Use: binary classification output only.
- Tanh: $\tanh(x) = (e^x - e^{-x})/(e^x + e^{-x})$. Range: (–1,+1). Zero-centred — solves Sigmoid's sign problem. Gradient: $1 - \tanh(x)^2$. Max gradient = 1 at x=0. Still vanishes for $|x|>2$. 2× steeper gradient than Sigmoid → better but still problematic for deep nets. Use: LSTM gates, GRU gates, RNN hidden states.
- ReLU: $f(x) = \max(0,x)$. Range: $[0,\infty)$. Gradient: 1 for $x>0$, 0 for $x<0$ (undefined at 0 — set to 0 or 0.5). Advantages: (1) Constant gradient for positive inputs → no vanishing. (2) Computationally trivial. (3) Sparse activations (~50% zero) → efficient. (4) Biologically plausible (neurons either fire or not). Problem: Dying ReLU — negative pre-activations → gradient = 0 → weight never updates. Occurs with large learning rates or poor initialisation. Use: default for CNN and ANN hidden layers.
- Leaky ReLU: $f(x) = \max(\alpha x, x)$, $\alpha \approx 0.01$. Gradient: 1 for $x>0$, α for $x<0$. Allows small gradient for negative inputs → dead neurons revived. α is a hyperparameter (0.01 standard; PReLU learns α per channel). Use: hidden layers when dying ReLU is observed.
- ELU: $f(x) = x$ if $x>0$; $\alpha(e^x-1)$ if $x\leq 0$. Smooth negative region (differentiable everywhere). Mean activations closer to zero → acts like batch normalisation for free. Slower than ReLU (exp computation). Use: deep fully-connected networks.
- SELU: scaled ELU with specific $\alpha=1.6733$ and $\lambda=1.0507$. When combined with LeCun normal initialisation, network is self-normalising — activations automatically have mean≈0, std≈1. No batch norm needed. Use: purely dense architectures.
- Swish: $f(x) = x\cdot\sigma(\beta x)$. Smooth, non-monotonic. Outperforms ReLU on deep networks. β is learnable or fixed at 1. Discovered via automated neural architecture search (Google Brain). Use: MobileNetV3, EfficientNet.

• GELU: $f(x) = x \cdot \Phi(x)$ where Φ is standard normal CDF. Approximation: $0.5x(1+\tanh(\sqrt{(2/\pi)}(x+0.044715x^3)))$. Smooth; stochastic during training (Bernoulli mask interpretation). Outperforms ReLU on language tasks. Use: BERT, GPT-2, GPT-3, GPT-4 hidden layers.

• Softmax: softmax(x■) = e^x■/Σ■e^x■. Properties: outputs in (0,1) summing to 1 — valid probability distribution. Numerically stable implementation: subtract max(x) before exp. Combined gradient with Cross-Entropy: ∂L/∂x■ = ■■ – y■ (clean form). Use: multiclass output only. Softmax with temperature: softer/sharper distribution by dividing by T before softmax.

• Maxout: f(x) = max(w■■x+b■, w■■x+b■). Learns the activation function. Generalises ReLU and Leaky ReLU. More parameters. Use: dropout networks (Goodfellow et al.).

• Practical guide: hidden layers: ReLU (baseline) → GELU (transformers) → Leaky ReLU (dying neurons) → ELU/Swish (smooth needed). Output layers: Sigmoid (binary), Softmax (multiclass), Linear (regression).

Q8. Explain the full training pipeline of a deep learning model from data collection to production deployment.

Answer:

• Stage 1 — Problem Formulation: define task type (classification, regression, detection, generation, segmentation). Define evaluation metric aligned with business objective (not just accuracy — consider precision/recall trade-off for medical tasks). Establish baseline (random, rule-based, or existing system). Define data requirements, latency constraints, and deployment environment.

• Stage 2 — Data Collection and Labelling: identify data sources (public datasets, proprietary data, web scraping). For supervised learning: collect labelled examples. Quality of labels > quantity. Use inter-annotator agreement (Cohen's Kappa) to measure label quality. Tools: Label Studio, Scale AI, Amazon Mechanical Turk. Important: data must reflect the deployment distribution (distribution shift = model failure).

• Stage 3 — Data Analysis and Preprocessing: (1) EDA: plot class distribution, feature histograms, pairwise correlations. (2) Handle missing values: impute (mean/median/model) or drop. (3) Outlier detection and handling. (4) Normalisation: MinMax [0,1] or StandardScaler (zero-mean/unit-std). (5) Encoding: one-hot for nominal categories, ordinal for ordered, learned embeddings for high-cardinality. (6) Train/val/test split (stratified if class imbalance). Never use test set until final evaluation.

• Stage 4 — Data Augmentation: define augmentation pipeline applied only to train set. Augmentations must be semantically valid (don't flip '6' and '9' digit images). Implement as part of data loading pipeline (on-the-fly, not pre-computed) to maximise variety. For images: Albumentations library. For text: nlpaug, HuggingFace data augmentation.

• Stage 5 — Model Architecture Selection: start with established baseline (ResNet-50 for images, BERT-base for text). Consider: dataset size (small → simpler model / pre-trained backbone), inference latency (edge → MobileNet, EfficientNet-B0), accuracy requirement (high → larger model). Define: depth, width, skip connections, attention mechanism, dropout positions, BN positions.

• Stage 6 — Training Configuration: loss function: match to task. Optimizer: Adam (default) / AdamW (transformers) / SGD+momentum (image from scratch). LR schedule: warmup + cosine decay (transformers) / ReduceLROnPlateau (general). Regularisation: dropout + L2 + early stopping. Monitoring: TensorBoard or W&B; for loss curves, LR, gradient norms, activation statistics.

• Stage 7 — Training Execution: implement training loop: sample batch → forward pass → compute loss → backward pass (loss.backward()) → gradient clipping → optimizer step → scheduler step → log metrics. Mixed precision (FP16/BF16) for 2× memory efficiency and speed. Distributed training for large models: DataParallel (multi-GPU), DistributedDataParallel (multi-node).

• Stage 8 — Hyperparameter Optimisation: hyperparameters: lr, batch size, weight decay, dropout rate, model depth/width. Methods: manual tuning (small search), grid search (small exhaustive), random search (efficient for >3 params), Bayesian optimisation (Optuna, Ray Tune — best efficiency), population-based training (PBT).

• Stage 9 — Evaluation and Error Analysis: evaluate best val checkpoint on held-out test set. Classification: accuracy, precision, recall, F1, AUC-ROC, confusion matrix, calibration plot. Regression: MSE, RMSE, MAE, R^2, residual plots. Compute confidence intervals (bootstrap). Error analysis: examine worst-performing examples by category, input length, data source. Identify systematic failure modes.

• Stage 10 — Optimisation for Deployment: (1) Quantisation: FP32 → INT8 via post-training quantisation or quantisation-aware training. 4× smaller, faster inference, minimal accuracy loss. (2) Pruning: set weights below threshold to zero; retrain. Structured pruning removes entire filters. (3) Knowledge Distillation: train small 'student' model to mimic large 'teacher' model's soft labels. (4) Model format conversion: export to TorchScript / ONNX / TFLite / TensorRT.

• Stage 11 — Deployment Architecture: REST API via FastAPI or Flask (Python). Containerise with Docker. Serve on: AWS SageMaker / Google Cloud Vertex AI / Azure ML. Edge deployment: TFLite on Android/iOS, ONNX Runtime on Windows/Linux. Batch inference for offline workloads; real-time for interactive applications.

• Stage 12 — Monitoring and Maintenance: monitor: prediction distribution, latency (p50/p95/p99), error rate, data drift (PSI score), concept drift (model accuracy over time). Alert if metrics degrade beyond threshold. Retrain pipeline: scheduled retraining (e.g., weekly) and trigger-based retraining when drift detected. Versioning: MLflow / DVC for model and data versioning. Canary deployment: route small % of traffic to new model before full rollout.

• MLOps stack: data versioning (DVC), experiment tracking (MLflow/W&B;), model registry (MLflow), serving (Triton Inference Server), monitoring (Evidently AI, Arize AI), CI/CD (GitHub Actions + containerised training jobs).

Q9. Explain Data Representation and Visualisation in deep learning comprehensively.

Answer:

• Data Representation Fundamentals: neural networks are continuous differentiable functions operating on fixed-dimensional numerical tensors. All real-world data — regardless of modality — must be mapped to a tensor of appropriate shape before being processed.

• Image Representation: grayscale: (H, W) matrix, dtype=uint8 [0–255] or float32 [0–1] after normalisation. Colour RGB: (H, W, 3) tensor. RGBA: (H, W, 4). Batch of N images: (N, H, W, C) or (N, C, H, W) (PyTorch convention). Normalisation: subtract ImageNet mean [0.485, 0.456, 0.406], divide by std [0.229, 0.224, 0.225] for models pre-trained on ImageNet.

• Audio Representation: waveform: 1-D tensor of amplitude samples. Sampling rate: 44,100 Hz (CD), 16,000 Hz (speech). 1 second mono speech = (16000,) tensor. Spectrogram: short-time Fourier transform (STFT) → (freq_bins, time_frames) 2-D tensor. Mel Spectrogram: frequency axis mapped to mel scale (perceptually linear). Standard input for CNN-based audio models. Log-Mel Spectrogram: apply log for better dynamic range.

• Text Representation: tokenisation: split text into subword tokens (BPE, WordPiece, SentencePiece). Token IDs: integer indices into vocabulary (vocab size: 32K–100K). Embedding layer: token ID → learnable dense vector of dim d_model (128–4096). Final representation: (seq_len, d_model) 2-D tensor. Special tokens: [CLS] for classification, [SEP] for segment separation, [MASK] for masked LM.

• Video Representation: (T, H, W, C) where T = number of frames. 30 fps × 5 sec = 150 frames. Full HD (1920×1080) colour: 150×1080×1920×3 = 934M numbers. Impractical to process fully. Strategies:

uniform frame sampling (16–32 frames), optical flow (motion-based), 3D convolutions (C3D, I3D models), transformer on frame embeddings (TimeSformer, Video Swin).

• Tabular Representation: numerical features: (N, num_features) matrix, normalised. Categorical: one-hot → (N, num_categories) sparse; learned embeddings → (N, d_embed) dense. Missing values: imputation (mean/median/KNN) or indicator variable. Target encoding: replace category with mean target value (supervised).

• Data Visualisation — Pre-Training: (1) Class distribution histogram → detect imbalance. (2) Feature correlation heatmap → identify redundant or informative features. (3) Sample grid display → verify data quality and labels. (4) t-SNE / UMAP projections → assess linear separability of classes.

• Data Visualisation — During Training: (1) Loss curves (train + val per epoch) → diagnose overfitting, underfitting, optimal stopping point. (2) Learning rate schedule → verify LR changes as expected. (3) Gradient flow visualisation → detect vanishing gradients in early layers (gradient norm per layer per epoch). (4) Weight distribution histograms → detect exploding weights.

• Data Visualisation — Post-Training: (1) Confusion matrix: rows=actual, columns=predicted; diagonal=correct. Normalise per row for recall. (2) ROC curve and AUC: TPR vs FPR at all thresholds. AUC=0.5 random, AUC=1.0 perfect. (3) Precision-Recall curve: more informative than ROC for imbalanced datasets. (4) Calibration plot: predicted probability vs actual frequency. Well-calibrated model → 70% confidence correct 70% of time.

• Feature Visualisation in CNNs: (1) Filter visualisation: display conv1 filters as 3×3 or 5×5 images — edge detectors, colour blobs visible. (2) Feature maps: record and display outputs of each conv layer for a sample input. (3) Maximally activating patches: find training patches that maximally activate each filter — reveals what each feature detector has learned. (4) Grad-CAM: ∑■ (∂y^c/∂A^k)·A^k — weighted sum of feature maps by class gradient. Produces class-discriminative localisation map. Standard for medical AI explainability.

• Embedding Visualisation: t-SNE (van der Maaten & Hinton, 2008): minimises KL divergence between high-dim and low-dim pairwise similarities. Non-linear. Preserves local structure. Good for revealing clusters. UMAP (McInnes 2018): preserves both local and global structure. Faster than t-SNE. Both: compute on final-layer representations before classification head to visualise what the model has learned.

• Tools: matplotlib/seaborn (static plots), TensorBoard (live training curves, projector, heatmaps), Weights & Biases (experiment tracking), Captum (PyTorch attribution), tf-explain (TF Grad-CAM), Netron (model architecture), scikit-learn (confusion matrix, ROC, calibration).

Q10. Write a detailed essay on the importance of Deep Learning today and its future directions.

Answer:

• Introduction: Deep Learning has transitioned from a niche academic research area to the foundational technology underpinning the global digital economy. As of 2024, virtually every major technology product incorporates deep learning in some form.

• Scale of Impact — Healthcare: The Lancet (2022) estimates that AI-based diagnostic tools could prevent 400,000 diagnostic errors annually in the US alone. DeepMind's AlphaFold2 solved the 50-year protein folding problem in 2020 — predicting 3D structure for 200M proteins (virtually all known proteins). Insilico Medicine used deep learning to design and advance a novel drug candidate for idiopathic pulmonary fibrosis to Phase 2 clinical trials in 4 years (vs. typical 12 years).

• Scale of Impact — NLP: ChatGPT reached 100 million users in 2 months (fastest product adoption in history). Google's BERT is integrated into Google Search globally, improving query understanding for 700M+ daily searches. GitHub Copilot (GPT-4 based) generates ~46% of accepted code contributions

in users who adopt it.

• Scale of Impact — Computer Vision: ImageNet top-5 error fell from 26.2% (2011, hand-crafted features) to 2.25% (2017, DL) — below human performance of 5.1%. Tesla's FSD processes 8 camera streams at 21 frames/second through 10B+ parameter neural networks in real-time. Google Photos can search across 10+ billion photos with text descriptions.

• Scale of Impact — Science: AlphaFold2, GNoME (Graph Neural Networks for Materials Exploration) discovered 2.2M new stable crystal structures. AI weather forecasting (GraphCast, Pangu-Weather) now outperforms ECMWF numerical models on 10-day forecasts. High-energy physics: deep learning analyses petabytes of LHC collision data.

• Economic Impact: Goldman Sachs (2023) estimates AI could add $7 trillion to global GDP over 10 years. Generative AI alone is projected to automate tasks equivalent to 300 million full-time jobs (partial exposure across sectors). Global AI market: $142B in 2023, projected $1.8T by 2030 (MarketsandMarkets).

• Why Deep Learning Specifically: (1) Feature learning: DL automatically discovers relevant features from raw data, eliminating manual feature engineering that limited traditional ML. (2) Transfer learning: pre-train once on massive data; fine-tune for specific tasks with small datasets. (3) Scaling laws: performance improves predictably with more data + larger models (Chinchilla, GPT-4 scaling laws). (4) Multimodality: single models now process text + images + audio + code.

• Current Research Frontiers: (1) Efficient architectures: SSM (state space models), Mamba, FlashAttention — Transformers with sub-quadratic complexity. (2) Multimodal foundation models: GPT-4o, Gemini 1.5, Claude 3 Opus. (3) Reasoning and agents: chain-of-thought prompting, tool-use, multi-agent systems. (4) Scientific AI: AlphaFold, GNoME, climate modelling. (5) Reinforcement Learning from Human Feedback (RLHF): aligning LLMs with human values. (6) Federated Learning: training on distributed private data without centralisation.

• Challenges and Open Problems: (1) Interpretability: most production models remain black boxes. EU AI Act requires explanations for high-risk decisions. (2) Data efficiency: humans learn from few examples; current DL requires millions. Few-shot and meta-learning remain open problems. (3) Robustness: adversarial examples, distribution shift, and spurious correlations cause unexpected failures. (4) Energy and environmental cost: training GPT-4 estimated to consume 50 GWh of electricity. (5) Fairness and bias: models trained on biased data encode and amplify societal biases. (6) Safety and alignment: ensuring powerful AI systems act in accordance with human values and intentions.

• Future Directions: (1) Foundation Models become the universal AI substrate — specialised models replaced by prompted versions of large multimodal models. (2) AI in the physical world: embodied AI, robotics (Figure-01, Boston Dynamics), brain-computer interfaces. (3) AI-accelerated science: automated hypothesis generation, experiment design, and result interpretation. (4) Neuromorphic computing: AI hardware mimicking biological neural networks (Intel Loihi, IBM TrueNorth) — potentially 1000× more energy efficient. (5) Quantum ML: quantum speedups for specific learning algorithms (theoretical for now).

• For AIML Students: the job market for deep learning practitioners is the fastest-growing in software engineering. Key skills: PyTorch/TensorFlow proficiency, transformer architecture understanding, MLOps (training pipelines, deployment, monitoring), statistical foundation (probability, linear algebra, calculus), domain knowledge for your target industry. The students who understand the fundamentals covered in this module — and can apply them to real problems — are positioned at the frontier of the most transformative technology of the 21st century.

Q11. Explain the Neural Network training process with all mathematical details, challenges, and solutions.

Answer:

- Mathematical Foundation: a neural network is a parameterised function $f_\theta: R^d \to R^k$. Parameters $\theta = \{W_1, b_1, W_2, b_2, ...\}$. Training minimises the empirical risk: $L(\theta) = (1/N)\Sigma_i \text{loss}(f_\theta(x_i), y_i)$.
- Initialisation: weights cannot be initialised to zero (all neurons would learn same features — symmetry breaking failure). Random initialisation: Xavier/Glorot (for Sigmoid/Tanh): $W \sim U(-\sqrt{(6/(n_{in}+n_{out}))}, \sqrt{(6/(n_{in}+n_{out}))})$. He initialisation (for ReLU): $W \sim N(0, \sqrt{(2/n_{in})})$. Proper initialisation ensures activation variance is maintained across layers.
- Forward Pass Detail: for each layer l: $z^{(l)} = W^{(l)} \cdot a^{(l-1)} + b^{(l)}$. $a^{(l)} = \text{activation}(z^{(l)})$. Final output $y_i = a^{(L)}$. Computational complexity: $O(N \cdot \Sigma_l n_l \cdot n_{l+1})$ per epoch.
- Loss Computation: $L = (1/B)\Sigma_{i \in \text{batch}} \text{loss}(y_i, y_i)$. For classification: Cross-Entropy. For regression: MSE/MAE.
- Backward Pass Detail: $\partial L/\partial W^{(L)} = \delta^{(L)} \cdot (a^{(L-1)})^T$ where $\delta^{(L)} = \partial L/\partial z^{(L)}$ (output error). Backpropagate: $\delta^{(l)} = (W^{(l+1)})^T \cdot \delta^{(l+1)} \odot \text{activation}'(z^{(l)})$. $\partial L/\partial W^{(l)} = \delta^{(l)} \cdot (a^{(l-1)})^T$. $\partial L/\partial b^{(l)} = \delta^{(l)}$.
- Weight Update (Adam): $m \leftarrow \beta_1 m + (1-\beta_1)g$; $v \leftarrow \beta_2 v + (1-\beta_2)g^2$; $m_t = m/(1-\beta_1^t)$; $v_t = v/(1-\beta_2^t)$; $\theta \leftarrow \theta - lr \cdot m_t/(\sqrt{v_t}+\varepsilon)$.
- Batch Normalisation Detail: for mini-batch $\{x_1,...,x_m\}$: $\mu = (1/m)\Sigma x_i$; $\sigma^2 = (1/m)\Sigma(x_i-\mu)^2$. Normalise: $x_i^{\text{norm}} = (x_i-\mu)/\sqrt{(\sigma^2+\varepsilon)}$. Scale and shift: $y_i = \gamma x_i^{\text{norm}} + \beta$ (γ, β learnable). At inference: use running mean/variance accumulated during training.
- Regularisation in Training: $L = L_{task} + \lambda_1 ||\theta||^2 + \lambda_2 ||\theta||_1$. Dropout: mask $m \sim \text{Bernoulli}(1-p)$; $a^{(l)} = m \odot \text{activation}(z^{(l)}) / (1-p)$. Early stopping: save $\theta^* = \text{argmin}_{t \le T} L_{val}(\theta_t)$.
- Training Instabilities and Solutions: (1) Loss NaN — exploding gradients: add gradient clipping. (2) Loss not decreasing — lr too small or bad initialisation: check with learning rate range test. (3) Val loss > train loss immediately — data leakage or label noise. (4) Oscillating val loss — lr too large or insufficient data: reduce lr or add data. (5) Training accuracy = 1/K (random) after many epochs — vanishing gradients: check activation functions and weight initialisation.
- Curriculum Learning: present training examples in order of increasing difficulty (easy → hard). Improves training stability and final performance. Used in language model pre-training.
- Mixed Precision Training: maintain FP32 master weights; compute forward/backward in FP16. Scale loss by large constant to prevent underflow. Reduces memory 2×; speeds up training 2–3× on modern GPUs with Tensor Cores. PyTorch: torch.cuda.amp.autocast().
- Gradient Accumulation: simulate larger batch sizes on limited GPU memory by accumulating gradients over multiple small batches before updating weights. Equivalent to: for i in range(accum_steps): loss/=accum_steps; loss.backward(). then: optimizer.step(); optimizer.zero_grad().

Q12. Explain all Optimizers in deep learning: mathematical formulation, properties, and when to use each.

Answer:

- Optimizers update model parameters θ using the gradient $\nabla_\theta L$ to minimise the loss $L(\theta)$. Choice of optimizer significantly affects training speed, stability, and final model quality.
- SGD (Stochastic Gradient Descent): Update: $\theta_{t+1} = \theta_t - \eta g_t$ where η = learning rate, g_t = mini-batch gradient. Properties: O(d) memory (d = number of parameters). No per-parameter adaptation. Convergence: $O(1/\sqrt{T})$ for non-convex. Limitations: same η for all parameters; sensitive to parameter scaling; requires careful lr tuning. Still used for: ResNet/EfficientNet image training with cosine schedule (final accuracy often better than Adam for this specific task).

• SGD + Momentum: $v_t = \mu v_{t-1} + g_t$; $\theta_{t+1} = \theta_t - \eta \cdot v_t$. μ = momentum coefficient (typically 0.9). Builds velocity in consistent gradient direction. Dampens oscillations. Nesterov Momentum (NAG): look-ahead version: $g_t = \nabla L(\theta_t - \mu v_{t-1})$. More accurate gradient estimate. Often preferred over standard momentum.

• Adagrad: $G_t = G_{t-1} + g_t^2$; $\theta_{t+1} = \theta_t - \eta/\sqrt{(G_t+\varepsilon)} \cdot g_t$. Accumulates all past squared gradients. Per-parameter lr: infrequent parameters get large updates; frequent parameters small. Pros: good for sparse features (NLP). Cons: lr monotonically decreases → eventually stops learning for most parameters.

• RMSprop: $E_t = \rho E_{t-1} + (1-\rho) g_t^2$; $\theta_{t+1} = \theta_t - \eta/\sqrt{(E_t+\varepsilon)} \cdot g_t$. Uses exponential moving average of squared gradients instead of sum. Prevents lr from shrinking to zero. ρ=0.9 typical. Designed for non-stationary (RNN) objectives. Used in: training RNNs, reinforcement learning (DQN).

• Adam (Kingma & Ba, 2014): $m_t = \beta_1 m_{t-1} + (1-\beta_1) g_t$ (first moment — gradient mean). $v_t = \beta_2 v_{t-1} + (1-\beta_2) g_t^2$ (second moment — gradient variance). Bias correction: $m_t^{\wedge} = m_t/(1-\beta_1^t)$, $v_t^{\wedge} = v_t/(1-\beta_2^t)$. Update: $\theta_{t+1} = \theta_t - \eta \cdot m_t^{\wedge}/(\sqrt{v_t^{\wedge}}+\varepsilon)$. Default: η=0.001, β_1=0.9, β_2=0.999, ε=1e-8. Properties: combines momentum and RMSprop with bias correction. Approximately invariant to gradient scale. Good for sparse gradients. Default choice for most tasks.

• AdamW (Loshchilov & Hutter, 2017): $\theta_{t+1} = \theta_t - \eta \cdot (m_t^{\wedge}/(\sqrt{v_t^{\wedge}}+\varepsilon) + \lambda\theta_t)$. Decouples weight decay from gradient update — applies weight decay directly to parameters, not via gradient. L2 regularisation with Adam incorrectly decays adapted lr; AdamW fixes this. Default for fine-tuning BERT, GPT, and other Transformers.

• Adadelta: eliminates manually set global lr. Uses ratio of parameter update scale to gradient scale. No lr hyperparameter. Robust to noisy gradients. Used in some NLP tasks.

• LAMB (You et al., 2019): Layer-wise Adaptive Rate Scaling. $r_t = m_t^{\wedge}/(\sqrt{v_t^{\wedge}}+\varepsilon) + \lambda\theta_t$. Trust ratio: $\tau_t = ||\theta_t||_2/||r_t||_2$. Update: $\theta_{t+1} = \theta_t - \eta_t \cdot \tau_t \cdot r_t$. Scales updates per-layer; enables stable training with very large batches (32,768+). Used in original BERT pretraining.

• Lookahead: wraps any base optimizer. Every k fast-weight updates, sync slow weights: $\theta_slow \leftarrow \theta_slow + \alpha(\theta_fast - \theta_slow)$. Reduces variance; compatible with Adam, SGD. Improves convergence stability.

• Learning Rate Schedulers (complement any optimizer): (1) Step decay: $\eta \leftarrow \eta \times \gamma$ every k epochs. (2) Cosine Annealing: $\eta_t = \eta_{min} + 0.5(\eta_{max}-\eta_{min})(1+\cos(\pi t/T))$. (3) Linear Warmup + Cosine Decay: standard for Transformer training. (4) Cyclical LR: oscillate between η_{min} and η_{max}; finds optimal lr range automatically. (5) ReduceLROnPlateau: halve lr when val loss plateaus for patience steps.

• Practical selection: (1) Start: Adam lr=0.001 for any new problem. (2) Transformer fine-tuning: AdamW + warmup + cosine. (3) Image classification from scratch: SGD + Nesterov momentum + cosine annealing. (4) RNN: RMSprop. (5) Large batch (>4K): LAMB. (6) Always: learning rate range test to find optimal lr order of magnitude.

Q13. Describe Multiclass Classification and Regression in deep learning with complete technical details.

Answer:

PART A: MULTICLASS CLASSIFICATION

• Definition: assign input x to exactly one of K classes (K≥3). Output: probability distribution p(y=k|x) for k=1,...,K.

• Architecture: feature extractor (CNN/Transformer backbone) + classification head. Classification head: dense layer → K logits (pre-Softmax scores, also called logits).

• Softmax Output Layer: softmax(z■) = e^z■ / Σ■e^z■. All K outputs positive and sum to 1. Numerically stable: subtract max(z) before exponentiation: softmax(z■) = e^(z■–max(z)) / Σ■e^(z■–max(z)).

• Categorical Cross-Entropy Loss: L = –(1/N)Σ■ Σ■ y■■ log(p■■■). Since y■■=1 only for true class: L = –(1/N)Σ■ log(p■■,y■). Combined gradient (softmax + CCE): ∂L/∂z■ = p■■ – y■ (one-hot). Clean closed form.

• Prediction: ■ = argmax_k p■■. Top-5 prediction: top 5 indices by probability.

• Label Encoding: one-hot: [0,0,1,0,...,0] for class k. Integer labels: 0,1,...,K-1 (use sparse_categorical_crossentropy in Keras).

• Evaluation Metrics: Accuracy = (correct predictions)/N. Macro F1 = average F1 per class (treats each class equally). Weighted F1 = F1 weighted by class frequency. Cohen's Kappa: accounts for chance agreement. Confusion matrix: K×K table; diagonal = correct.

• Handling Class Imbalance: class weights: weight loss of class k by N/(K·N■). Oversampling minority: SMOTE. Undersampling majority. Focal loss: down-weight easy examples. Threshold adjustment: set class-specific decision thresholds based on F1 optimisation.

PART B: REGRESSION

• Definition: predict a continuous real-valued output ■ ∈ R (or R^m for multi-output).

• Architecture: feature extractor + regression head. Regression head: dense layer → linear output (no activation function). Output can be any real number.

• Loss Functions: MSE: L = (1/N)Σ(y–■)². MAE: L = (1/N)Σ|y–■|. Huber: MSE for |y–■|≤δ, else MAE-scaled. Log-cosh: log(cosh(y–■)) — smooth, handles outliers.

• Output Normalisation: scale targets y to [0,1] or standardise to zero-mean/unit-variance. Improves gradient magnitudes and convergence speed.

• Evaluation: RMSE = √MSE (same units as y). MAE (mean absolute error). MAPE = (1/N)Σ|y–■|/|y|×100% (percentage error). R^2 = 1 – Σ(y–■)²/Σ(y–■)². R^2=1: perfect, R^2=0: no better than mean, R^2<0: worse than mean.

• Multi-output Regression: output layer with m neurons, one per target variable. Loss is sum/average of individual losses. Applications: bounding box regression (x, y, w, h), 3D keypoint estimation, multi-step time-series forecasting.

• Uncertainty Estimation: aleatoric uncertainty: model outputs μ and σ per sample; uses NLL loss – log N(y; μ, σ²). Epistemic uncertainty: Monte Carlo dropout at inference (run K forward passes with dropout active, measure variance). Used in medical AI and autonomous driving for reliability assessment.

Q14. Explain all techniques for visualising deep learning models and interpreting their decisions.

Answer:

• Introduction: as deep learning models grow in complexity (billions of parameters), understanding their internal representations and decision processes becomes critical — for trust, debugging, regulatory compliance, and scientific insight.

• 1. Network Architecture Visualisation: tools: Keras model.summary(), Keras plot_model(), Netron (open-source, supports all formats), TensorBoard Graph tab. Shows: layer types (Conv2D, Dense, LSTM), tensor shapes at each layer, parameter counts, connections and skip connections. Use case: verify architecture before training; identify bottlenecks.

• 2. Training Dynamics Visualisation: Training/validation loss and accuracy vs epoch: fundamental diagnostic. Ideal: both curves converge together. Gradient norm per layer per epoch: detect vanishing

(norms → 0 in early layers) or exploding gradients. Weight distribution (histogram): should remain approximately Gaussian. Dead ReLU fraction: proportion of neurons with zero activation across all inputs (should be < 20%). Tools: TensorBoard Scalars and Histograms.

• 3. CNN Filter Visualisation: visualise the learned conv filters of the first convolutional layer by displaying them as small images. Observation: well-trained models learn Gabor-like edge detectors at varying orientations and frequencies. Limitation: deeper layer filters are high-dimensional and hard to interpret directly. Method: display filter weights; or maximise filter activation using gradient ascent on input image.

• 4. Feature Maps (Activation Maps): pass a single input through the network. Record and display the output tensor of each conv layer. Layer 1 activations: edge and texture maps. Layer 2–3: part detectors. Layer 4–5: high-level semantic detectors (eyes, wheels, dog face). Reveals what information the network retains at each level of abstraction.

• 5. Maximally Activating Inputs: for each neuron/filter, find the input patch from the training set that maximises its activation. Used by Zeiler & Fergus (2014) to visualise and interpret each layer of AlexNet. Revealed that the network learns biologically meaningful features (Gabor filters, colour blobs, face parts).

• 6. Gradient-based Attribution: Vanilla Gradients: ∂output/∂input image — shows which pixels most influence the prediction. Gradient × Input: element-wise product of gradient and input — sharper attribution. Integrated Gradients (Sundararajan et al., 2017): average gradient along straight path from baseline (black image) to actual input. Satisfies completeness axiom: attributions sum to prediction – baseline.

• 7. Grad-CAM (Gradient-weighted Class Activation Mapping): L_Grad-CAM^c = ReLU(Σ■ α■■ · A■) where α■■ = (1/Z)Σ■Σ■ (∂y^c/∂A■■■). Produces a coarse heatmap over the last conv layer. Highlights which regions of the image influenced the prediction of class c. Grad-CAM++: improved version with more fine-grained localisation. Use: medical imaging (highlight tumour region), autonomous driving (show what the model looks at).

• 8. Confusion Matrix Analysis: K×K matrix where CM[i][j] = number of samples of class i predicted as class j. Diagonal: correct predictions. Off-diagonal: errors. Normalise rows for recall per class. Use: identify which classes are confused with each other; guide data collection or augmentation strategy.

• 9. SHAP (SHapley Additive exPlanations): game-theoretic approach. Assigns each feature a Shapley value — its average marginal contribution across all feature orderings. DeepSHAP: efficient SHAP for deep learning using DeepLIFT. KernelSHAP: model-agnostic but slower. Provides global feature importance and per-instance explanation. Standard in industry for model explanations.

• 10. Embedding Visualisation: t-SNE: preserve local structure in 2D/3D projection. UMAP: preserve both local and global structure; faster. Procedure: extract features from penultimate layer for all test samples → project to 2D → colour by true class. Well-separated clusters → model has learned discriminative representations. Tools: TensorBoard Projector (interactive 3D viewer).

• 11. Partial Dependence Plots (PDP): for tabular models, show how the expected prediction changes as one feature varies while all other features are marginalised. ICE (Individual Conditional Expectation): one line per sample — reveals heterogeneous effects. 2D PDP: interaction between two features.

• Practical toolbox: TensorBoard + Weights & Biases (training); Captum (PyTorch attribution, Grad-CAM, Integrated Gradients); tf-explain (TF Grad-CAM); SHAP library; Netron (architecture); matplotlib/seaborn (custom visualisations).

Q15. Write a comprehensive note on overfitting, underfitting, and the bias-variance tradeoff. Include all prevention and correction strategies.

Answer:

• Conceptual Foundation — Bias-Variance Tradeoff: the expected generalisation error of any predictor decomposes as: $E[(y - f_{\blacksquare}(x))^2] = Bias(f_{\blacksquare})^2 + Var(f_{\blacksquare}) + \sigma^2$. $Bias^2$: systematic error from incorrect assumptions (underfitting — model too simple). Variance: variability of $f_{\blacksquare}$ across different training sets (overfitting — model too sensitive to training data). σ^2: irreducible noise from inherent stochasticity in the data. Goal: minimise total expected error — neither too biased nor too variable.

• Underfitting — Detailed Analysis: high bias, low variance. Training error and validation error are both high and similar. Causes: (1) Model architecture too shallow or narrow. (2) Insufficient training (too few epochs). (3) Learning rate too large (overshoots minimum). (4) Too much regularisation. (5) Wrong architecture for the data type. Diagnosis: training accuracy < expected performance ceiling. Loss curve flat from the beginning.

• Fixes for Underfitting: (1) Increase model capacity: more layers, wider layers, more expressive architecture. (2) Train longer with appropriate lr schedule. (3) Reduce regularisation (dropout, weight decay). (4) Add more relevant input features. (5) Correct architecture choice: CNN for images, Transformer for text.

• Overfitting — Detailed Analysis: low bias, high variance. Training error is very low; validation error is significantly higher. Causes: (1) Model has too many parameters relative to N training samples (rule of thumb: need N > 10× number of parameters for non-neural models; deep networks can work with fewer due to implicit regularisation from SGD). (2) Training too long without early stopping. (3) Insufficient regularisation. (4) Noisy or mislabelled training data.

• Prevention Strategy 1 — Data: more data (most effective), data augmentation, cleaning mislabelled samples, removing irrelevant features.

• Prevention Strategy 2 — Architecture: reduce model capacity (fewer layers/neurons), weight sharing (CNN, Transformer), factorised representations (LoRA).

• Prevention Strategy 3 — Regularisation: L1 (sparsity), L2/weight decay (small weights), dropout (ensemble effect), DropConnect (drop weights not activations), DropBlock (drop contiguous regions in CNNs).

• Prevention Strategy 4 — Training: early stopping (monitor val loss), learning rate scheduling (prevents chasing noise), stochastic depth (randomly skip residual blocks), label smoothing (soft targets).

• Prevention Strategy 5 — Normalisation: batch normalisation (normalise per mini-batch, acts as regulariser), layer normalisation (normalise per sample, used in Transformers), instance normalisation (used in style transfer).

• Prevention Strategy 6 — Ensembling: train multiple models; average predictions. Reduces variance by combining diverse models. Methods: bagging (train on bootstrap samples), boosting, model averaging, stochastic weight averaging (SWA — average weights from different training phases — cheap ensembling).

• Double Descent Phenomenon (Belkin et al., 2019): contrary to classical bias-variance tradeoff prediction, test error exhibits a second descent after the interpolation threshold (when model can exactly fit training data). Heavily overparameterised models (like modern DL) generalise well despite near-zero training error due to implicit regularisation from SGD and gradient descent dynamics. Classical tradeoff applies to the regime below interpolation threshold.

• Regularisation in the Modern Era: modern neural networks are almost always overparameterised (parameters >> training samples). Classical regularisation theory doesn't fully explain their generalisation. Research findings: (1) SGD with small batch size has implicit regularisation effect — prefers flat minima with better generalisation. (2) Neural Tangent Kernel (NTK) theory: overparameterised networks in the infinite-width limit converge to a kernel regression problem with well-understood generalisation. (3) Flat minima generalise better than sharp minima (supported empirically by SWA). Understanding why deep learning generalises is still an open research question.

• Practical Checklist for Practitioners: (1) Plot train/val loss and accuracy every epoch. (2) If train acc >> val acc: add dropout, data augmentation, early stopping. (3) If train acc ≈ val acc but both low: increase capacity, train longer. (4) Always use train/val/test split — never evaluate on training data. (5) Apply dropout (0.3–0.5) after all dense layers. (6) Use batch normalisation in all conv layers. (7) Implement early stopping with patience=10 and restore best weights. (8) Augment images minimally even if dataset seems large.

END OF MODULE

Module covers: Unit I — Fundamentals of Deep Learning | Unit II — Gradient Descent & Neural Networks.
Question bank includes 45 questions across 4-mark, 5-mark, and 10-mark tiers with detailed answers.