

IBM® ThinkPad® A22e - withdrawn

| Type-model | Processor | MHz | Mem | Screen | Graphics | Disk | CD | Comm Bay | Design | Modular bay | Preload | Available |
|------------|--------------|-----|------|-----------|----------|-------------------|----------------------|----------------|-------------|----------------|----------------|-----------|
| 2655-25U | Celeron™ | 800 | 64MB | 13.1" XGA | ATI® | 15GB ⁸ | 24X-10X ⁹ | Modem | Two spindle | Ultrabay™ 2000 | Windows® 98 SE | Jun 2001 |
| 2655-75U | Celeron | 800 | 64MB | 13.1" XGA | ATI | 15GB | 24X-10X | Modem | Two spindle | Ultrabay 2000 | Windows 2000 | Jun 2001 |
| 2655-27U | Celeron | 800 | 64MB | 13.1" XGA | ATI | 15GB | 24X-10X | Intel® eth/mod | Two spindle | Ultrabay 2000 | Windows 98 SE | Jun 2001 |
| 2655-77U | Celeron | 800 | 64MB | 13.1" XGA | ATI | 15GB | 24X-10X | Intel eth/mod | Two spindle | Ultrabay 2000 | Windows 2000 | Jun 2001 |
| 2655-45U | Pentium® III | 850 | 64MB | 13.1" XGA | S3® | 30GB | 24X-10X | Modem | Two spindle | Ultrabay 2000 | Windows 98 SE | Jun 2001 |
| 2655-95U | Pentium III | 850 | 64MB | 13.1" XGA | S3 | 30GB | 24X-10X | Modem | Two spindle | Ultrabay 2000 | Windows 2000 | Jun 2001 |
| 2655-47U | Pentium III | 850 | 64MB | 13.1" XGA | S3 | 30GB | 24X-10X | Intel eth/mod | Two spindle | Ultrabay 2000 | Windows 98 SE | Jun 2001 |
| 2655-97U | Pentium III | 850 | 64MB | 13.1" XGA | S3 | 30GB | 24X-10X | Intel eth/mod | Two spindle | Ultrabay 2000 | Windows 2000 | Jun 2001 |

| | | | | | | | | |
|---|---|---|---------|---|--|--|--|--|
| Processor | Intel® Mobile Celeron™ 800 or 850MHz¹ with 100MHz Front Side Bus or Intel Mobile Pentium® III 850MHz with Speedstep™ Technology with 100MHz Front Side Bus | | | OPERATING SYSTEM PRELOAD^{14,27} | | | | |
| L2 cache | <i>Celeron:</i> 128KB / onboard (at processor speed) / ECC <i>Pentium III:</i> 256KB / onboard (at processor speed) / ECC | | | Windows 98 models | | | | |
| Memory | <i>Celeron:</i> 64MB standard / 256MB max ⁷ <i>Pentium III:</i> 64MB standard / 512MB max ⁷ SDRAM / non-parity / 100MHz / PC100 / two 144-pin SO-DIMM sockets / std memory in one socket / 1 socket available | | | - Microsoft® Windows® 98 Second Edition ¹³ ✧ Disk-to-Disk Recovery (in hidden Service Partition) | | | | |
| Diskette drive | None standard / optional USB Portable Diskette Drive or Ultrabay 2000 diskette drive | | | Windows 2000 models | | | | |
| CD or DVD-ROM | Bootable / removable from Ultrabay™ 2000 | | | - Windows 2000 Professional | | | | |
| Ultrabay 2000 | Modular bay for interchangeable devices / cold (system off) swap only | | | ✧ Disk-to-Disk Recovery to Windows 2000 or Windows NT 4.0 (in hidden Service Partition) | | | | |
| Disk (removable) | 15GB⁸ or 30GB / 9.5mm / upgradeable / S.M.A.R.T. / 2nd disk support in Ultrabay | | | ADDITIONAL PRELOADED SOFTWARE | | | | |
| Display | 13.1" (337.8mm) XGA (1024x768) TFT color / Active Matrix | | | Common to all models | | | | |
| Graphics controller | <i>2xx/7xx:</i> ATI® Rage™ Mobility-M / PCI / 4MB SDRAM / DDC2B <i>4xx/9xx:</i> S3 Savage™ IX8+ / AGP 2X / 8MB SGRAM / 64-bit path to memory | | | • ThinkPad Utilities | | | | |
| Graphics - external | External SVGA to 1024x768x16.7 million colors at 85Hz and up to 1600x1200 | | | • ThinkPad Assistant™ | | | | |
| Keyboard | 85-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar / pitch: 19mm; stroke: 2.7mm | | | • ConfigSafe® | | | | |
| ThinkLight | Illuminates the keyboard to improve visibility in low-light conditions | | | • IBM Update Connector™.15 | | | | |
| UltraPort™ connectr | None | | | • Easy Keys Utility | | | | |
| Case material | <i>Color:</i> black; <i>Top:</i> ABS plastic; <i>Bottom:</i> glass-fiber reinforced plastic | | | • Access ThinkPad II | | | | |
| Dimensions ³ | Approximately 12.0 x 10.0 x 1.4"; 305mm x 254mm x 35mm | | | • PC-Doctor™ | | | | |
| Approximate weight ² | with battery and CD-ROM: 5.7 lbs / 2.1 kgs | | | - Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0 license | | | | |
| Battery - type | NiMH 7-cell / 8.4V 4.5AH / intelligent / supports optional Li-Ion battery / no support for Ultrabay 2000 battery | | | The right bay (Ultrabay 2000) supports the following: • standard or optional CD-ROM • optional DVD drive • optional Zip drive • optional SuperDisk drive • optional CD-RW • optional HDD adapter; for second disk • optional ThinkPad Proven™ solutions ¹⁶ (such as Travel Bezel) • no support for battery on the A22e 2655 • optional diskette | | | | |
| Battery - life ¹⁰ | 3.0 hrs (Li-Ion 6-cell) / optional NiMH battery supported only on Celeron models | | | | | | | |
| Charge time ¹⁰ - on / off | 3.2 to 6 hrs / 3.2 hrs | | | | | | | |
| AC adapter | Universal 72 watt / 16VDC 4.5A | | | | | | | |
| Architecture | Intel 440MX PCIset (82443MX) / combines Host Bridge and PIIX4 in single chip / TI® PCI1410 for CardBus / PCI 2.1 / 32-bit / 33MHz (graphics, EIDE, CardBus, audio, USB) / PC97338 Super I/O / ISA (serial, parallel, external expansion) | | | | | | | |
| Port replicator | Optional ThinkPad Port Replicator | | | | | | | |
| Docking Station | No support for ThinkPad Dock | | | | | | | |
| PC Card Std slots | 1 Type I, Type II, or Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video | | | | | | | |
| Ports | One USB (Version 1.1) / one serial (9 pin) / parallel / external DB-15 monitor / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or infrared | | | | | | | |
| Video in and out | None | | | | | | | |
| Communicatns Bay | Communications Bay with Mini PCI IIIa slot / customer accessible | | | | | | | |
| Modem | <i>Some:</i> 56K ⁶ V.90 Mini PCI modem card / Lucent® chip set | | | | | | | |
| Ethernet/modem | <i>Some:</i> Intel® PRO/100 SP Mobile Combo Adapter / Mini PCI ethernet with 56K modem / Intel 82550EY ethernet chipset / Lucent modem chipset | | | | | | | |
| Audio support | PCI audio / SoundBlaster Pro™ support / Intel 440MX AC97 audio support with CS4299 AC97 codec / mono speaker / 1.5 watt / volume up, down, mute buttons above keyboard | | | | | | | |
| Audio jacks | Microphone (3.5 mm) / speaker out (3.5 mm) / line in (3.5mm) / no int microphone | | | | | | | |
| Security | Power-on password / hard disk password / supervisor password / security keyhole | | | | | | | |
| Limited warranty ^{*,12} | 1 year - EasyServ™.19 onsite pickup and delivery courier service | | | | | | | |
| Service options | Service upgrades ²² provide up to three years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period) | | | | | | | |
| 64MB SO DIMM 100MHz NP SDRAM | 20L0254 | USB Portable Diskette Drive | 05K9276 | | | | PC 99-compliant PXE 2.0-compliant Wired for Management (WfM) 2.0 Local and remote asset management via the IBM Universal Manageability solutions IBM PC Lifecycle Care ²¹ provides proactive life cycle management and transition planning tools Setup Guide, User's Reference, Windows manual Personalized Web-based support International Warranty Service ¹⁷ 24 hour x 7 day ¹⁸ toll-free hardware support during the warranty | |
| 128MB SO DIMM 100MHz NP SDRAM | 20L0255 | ThinkPad NiMH Battery (2655)* | 02K6742 | | | | | |
| 256MB SO DIMM 100MHz NP SDRAM | 33L3069 | <i>* supported only on Celeron-based models</i> | | | | | | |
| ThinkPad Removable Diskette Drive | 08K9603 | ThinkPad Li-Ion Battery (2655), 6 cell | 02K6743 | | | | | |
| SuperDisk (LS-240) UltraBay 2000 Drive | 08K9616 | ThinkPad 72W AC Adapter | 02K6699 | | | | | |
| Zip 250MB Ultrabay 2000 Drive | 00N8253 | Multiple Li-Ion/NiMH Battery Charger | 02K6719 | | | | | |
| 24X-10X CD-ROM Ultrabay 2000 Drive | 05K9233 | ThinkPad Port Replicator | 02K8667 | | | | | |
| 8X/4X/24X CD-RW Ultrabay 2000 Drive | 08K9569 | ThinkPad Monitor Stand 2001 | 22P5265 | | | | | |
| 8X-2X DVD Ultrabay 2000 Drive | 27L3448 | Portable Drive Bay 2000 | 19K4480 | | | | | |
| CD-RW/DVD Combo Ultrabay 2000 Drive | 08K9572 | IBM IEEE 1394 CardBus Card | 19K5679 | | | | | |
| Travel Bezel for Ultrabay 2000 | 08K6070 | 10/100 Enet/56K Mini PCI (3Com) | 09N9774 | | | | | |
| Second HDD Adapter for Ultrabay 2000 | 08K6068 | Intel Pro/100 SP Mini PCI | 06P3801 | | | | | |
| 15GB HDD | 08K9588 | ServicePac® 3yr IOR 9x5 NBD | 30L9195 | | | | | |
| 30GB HDD | 08K9593 | ServicePac 3yr P&L P/U Depot | 30L9192 | | | | | |
| 32GB HDD* | 08K9511 | | | | | | | |
| * Supported in Ultrabay 2000 only; requires HDD adapter 08K6068 | | | | | | | | |

* For a copy of IBM's Statement of Limited Warranty, call 1-800-772-2227

US models announced June 2001

US models withdrawn from marketing effective November 2001

No warranties are expressed or implied in this summary

(A22E) © IBM Corp. November 2001