IBM ThinkPad 760C - withdrawn

IBM® ThinkPad®:	✂ **760C**
	12.1" or 10.4" TFT color
Processor type	**Pentium®** (P54LM) / 64 bit to L2 cache / 32 bit to memory
Processor speed	**90/60 or 120/60 MHz** (see below)
Processor upgrade	to Pentium 120/60 MHz
L2 cache	256 KB / write-through / direct mapped / 10 ns / synchronous / soldered
Removable diskette	Internal 3.5" 1.44 MB ○ (in UltraBay)
Removable CD-ROM	None (diskette bay is called UltraBay™) - cannot install an int CD-ROM

ThinkPad 760C strengths:

- ⇨ **Tilt up keyboard and palm rest space**
- ⇨ **Largest notebook display models -- 12.1 inch**
- ⇨ **UltraBay: 2nd disk, 2nd battery, diskette**
- ⇨ **Integrated 28.8 Kbps modem, audio, telephony**
- ⇨ **Two high speed infrared ports**

Price	U21	U2A	U22	U2B	U27	U2H	U28	U2J
Type - model **all 9546**								
Preload (see side)	SelectaSys	Win 95	SelectaSys	Win 95	SelectaSys	Win 95	SeIctaSys	Win 95
Pentium speed	**90/60 MHz**		**90/60 MHz**		**120/60 MHz**		**120/60 MHz**	
Remv disk - size / ms	**720 MB** / 13 ms / EIDE○		**720 MB** / 13 ms / EIDE○		**720 MB** / 13 ms / EIDE○		**1.08 GB** / 13 ms / EIDE○	
Avail / withdrawn date	Oct 1995 / Oct 1996		Oct 1995 / Oct 1996		Nov 1995 / Oct 1996		Jan 1996 / Oct 1996	

Display - diagonal size	**12.1 inch**	**10.4 inch**	**12.1 inch**	**12.1 inch**
Display - type	**SVGA color / 640 x 480 or 800 x 600 / 65,536 simultaneous colors**			
Display - techology	**Black Matrix TFT - active matrix** / 100 to 1 contrast ratio			

Graphics - controller	Trident™ CYBER9320 with 1 MB DRAM
Graphics - external	External SVGA to 1024 x 768 w/ 256 colors up to 75 Hz
Graph - arch/data path	VL-Bus 2.0 local bus / 32 bit / Simultaneous LCD and CRT / 180 degree tilt

Memory - std / max	**8 MB** / 64 MB 70 ns / non-parity / 3.3 volt / fast page
Mem - upgrade	2 sockets for two JEDEC 88 pin EDO SO DIMMs of 8 or 16 MB (acts like fast page)

SELECTASYSTEM PRELOAD

- IBM DOS 7.0
- Windows 3.11
- OS/2 Warp 3.0 (dual boot) with selected BonusPak
- IBM PC Card Director™ 3.0
- Online Users Guide
- ThinkPad Features Program
- Diskette Factory
1. Lotus® cc:Mail™, e-mail for IBM Global® network; 2. Lotus Organizer™
3. Lotus ScreenCam™
4. Triton CoSession™ Host; 5. PRODIGY®
6. SofNet FaxWorks™ Voice™
7. Video For Windows™ 1.1 Runtime
8. Puma TranXit™ 9. COMPEL™ PE
10. Mind Path Presentation F/X Pro
11. Internet for Windows
12. Compuserv for Win; 13. WIN32s Runtime
14. NetFinity for Windows and OS/2
- Complimentary Applications CD-ROM
- Lotus SmartSuite 4.0 CD-ROM

Keyboard / # of keys	Full size alp/num / 85 (8 Fn key functions)	***Liftable (pop-up) keyboard** to access and remove diskette drive, 1st/2nd disk, and 1st/2nd battery*
Keyboard slope	**Automated tilt up keyboard** (5.5 degrees)	
Pointing / palm rest	**TrackPoint III™ / integrated palm rest**	
Ext keyboard support	Yes (with option cable)	

Dimensions (cubic in)	*10.4" models:* 11.7 x 8.3 x 1.74" (169)	*12.1" models:* 11.7 x 8.3 x 1.92" (186)
Weight (with battery)	*10.4" models:* 6.1 pounds	*12.1" models:* 6.8 pounds
Battery - type	*10.4" models:* Lithium Ion / intelligent	*12.1" models:* Lithium Ion / intelligent
Battery - life (1 batt)	*10.4" models:* 3.8 hours *Opt*	*12.1" models:* 3.5 hours *Opt*
Battery - life (2 batt)	*10.4" models:* 7.6 hours *NiMH*	*12.1" models:* 7 hours *NiMH*
Charge time - on / off	*10.4" models:* 2 to 3 hrs / 1.5 to 2.5 hrs	*12.1" models:* 2 to 3 hrs / 1.5 to 2.5 hrs

Architecture	ISA (EIDE, audio, PCMCIA, diskette, serial, parallel, 240 pin ext expansion)
	VL-Bus 2.0 / 32 bit / 33 MHz (graphics)
Docking Station	Dock I and II
Port replicator	Port Replicator I and II
PCMCIA™ 2.1 slots	2 Type I or 2 Type II or 1 Type III
Serial / parallel ports	One 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)
Other features	APM-aware BIOS / Universal AC adapter 3 prong (35 watts) / Selectable boot

WINDOWS 95 PRELOAD

- Microsoft Windows 95
- Online User's Guide
- ThinkPad Features Program
- Diskette Factory
1. Lotus® cc:Mail™, e-mail for IBM Global® network; 2. Lotus Organizer™
3. Lotus ScreenCam™
4. Triton CoSession™ Host; 5. PRODIGY®
6. SofNet FaxWorks™ Voice™
7. Puma TranXit™
8. Compuserv for Windows
9. Mind Path Presentation F/X Pro
10. COMPEL Personal Edition
- Lotus SmartSuite 96 CD-ROM

Motion video accel	None
MPEG decoder	None
DSP function	**Mwave MDSP2780 DSP with modem, fax, audio, telephony function**
Data/fax modem	**Data/fax modem function via DSP** (v.34 to 28.8 Kbps) / Mwave 2.0
Audio support	**16 bit audio chip on planar with Mwave DSP**
	Int stereo speakers / .5 watt / slide volume control / internal microphone
Audio in/out jacks	Input jack (3.5 mm) / output jack (3.5 mm)
Infrared ports	**Infrared ports (front and back) / IrDA 1.0 compatible / up to 115 kbs**
Telephone	Telephone / answering machine / full duplex speakerphone

Security	Power-on password / Hard disk password / Supervisor password / Locking device keyhole (Kensington MicroSaver™ cable lock) / Security latch for keyboard and DIMMS (requires Kensington) / PC Card lock

Preinstalled software	Choice of two preloaded configurations (listed to right)
Warranty	**3 year -** ThinkPad EasyServ only (optional Overnight Repair Option) or carry-in

FEATURES OF 760 MODELS

Product Map; **LCD indicator panel**
LCD of remaining battery life
LCD icons for two batteries
Plug and Play 1.0a
Discharge battery via mouse click
Non-disruptive battery exchange
Standby, suspend, and hibernation modes
US EPA Energy Star compliant
Personalized nameplate in indention
Personalization screen at startup
International Warranty Service
24 hour / 7 day telephone, bulletin board, fax, electronic, and Internet (http://www.pc.ibm.com) support
IBM and dealer warranty/service
Online Housecall (remote diagnostics)

The left bay (UltraBay™) supports:
① 2nd disk (requires Second HDD Adapter)
② 2nd battery
③ std diskette drive
④ 2.88 MB diskette drive (option)
⑤ PCMCIA Cartridge (option)
⑥ IBM Wireless Modem for ARDIS (option)
⑦ IBM Wireless Modem for Cellular/CDPD (option)

Maximum internal disk capacity on 760C is 2.16 GB with two 1.08 GB disks.

Easy-Setup is entered by holding F1 when turning on.

Integrated Mwave™ DSP provides:
① **Data modem function** (to 28.8 Kbps)
② **Fax modem function** (to 14.4 Kbps)
③ **Audio function** (wave table synthesis)
④ **Telephone function**
  - Full duplex speakerphone
⑤ **Digital Simultaneous Voice and Data**

Compatible in ThinkPad 760 family:
- Disks: (360/750/755 IDE disks not supported)
  720 MB HDD II EIDE   12.5 mm 29H9383
  1.08 GB HDD II EIDE   12.5 mm 29H9319
  1.2 GB HDD II (CD only) 17 mm 29H9325
- Second HDD Adapter   29H9333
- Dock I (1 slot / 1 bay)   3545001
- Dock II (2 slot / 2 bay)   3546001
- Port Replicator I (w/ PCMCIA) 66G3510
- Port Replicator II   66G3520
- 1.44 MB diskette   std in newer
- 2.88 MB diskette   66G0108
- PCMCIA Cartridge   84G1301
- **760 NiMH Battery (black)   41H9720**
- **Li-Ion Battery Pack II (gray) 29H9329**
- Travel Quick Charger   85G1522
- FDD External Attachment Kit 66G3618
- **Pentium 120/60 MHz upgrade 29H9340**
- Car Battery Adapter   49G2167
- ThinkPad AC Adapter (50 watts) 66G3541
- 8 MB SO DIMM 3.3v non-parity EDO 92G7315
- 16 MB SO DIMM 3.3v non-parity EDO 92G7316
- ThinkPad headset   85G1301