

IBM ThinkPad 365 (CD-ROM models) - withdrawn

IBM® ThinkPad®:		365CSD		365CD		ThinkPad 365 (CD-ROM models) strengths
		10.4" dual scan - CD-ROM		10.4" TFT - CD-ROM		
Processor	Cyrix Cx 486DX4™ 75/25 MHz / integrated math coprocessor					✧ Entry-priced CD-ROM notebook ✧ Integrated audio, microphone, speaker ✧ Simultaneous external diskette ✧ Joystick/MIDI port ✧ Infrared port
Processor upgrade	None					
Memory cache	8 KB in DX4 (write-back) / no L2 cache					
Diskette (not internal)	External 3.5" 1.44 MB (connects to back of system) / use simultaneously w/ CD-ROM					
CD-ROM (not remove)	5.25" CD-ROM / double speed / multi-session / XA / front loaded / ATAPI					
Price						SELECTASYSTEM PRELOAD - IBM DOS 7.0 - Windows 3.11 - OS/2® Warp 3.0 (dual boot) with selected BonusPak applications - IBM PC Card Director™ 1.4 - IBM ThinkPad Demo - Online Users Guide - ThinkPad features ; Diskette Factory 1. Lotus® cc:Mail™, e-mail for IBM Global® Network 2. Lotus Organizer™ 3. Lotus ScreenCam™ 4. Triton CoSession™ Host 5. PRODIGY® 6. SofNet FaxWorks™ 7. Video For Windows™ Runtime 8. Puma TranXit™ 9. Compuserp for Windows 10. NetFinity for Windows and OS/2
Type - model all 2625	2625-A05	2625-W14	2625-B05	2625-W15		
Part number	38H5724	41H8663	38H5726	41H8664		
Preload (see side)	SelectaSystem	Windows 95	SelectaSystem	Windows 95		
Disk - capacity	540 MB	540 MB	540 MB	540 MB		
Disk - ms / interface	13 ms / EIDE	13 ms / EIDE	13 ms / EIDE	13 ms / EIDE		
Avail / withdrawn date	Nov 1995 / Jun 96	Nov 95 / Jun 96	Nov 95 / Jun 96	Nov 95 / Jun 96		
Display - diagonal size	10.4" Dual scan		10.4" Black Matrix TFT - active matrix			
Display - type	VGA color / 640 x 480		VGA color / 640 x 480			
Display - color	256 simultaneous colors		262,144 simultaneous colors			
Display - contrast	30 to 1		100 to 1			
Graphics - controller	Chips and Technologies™ 65545 with 1 MB DRAM					WINDOWS 95 PRELOAD - Microsoft Windows 95 - IBM ThinkPad Demo - Online Users Guide - ThinkPad features; Diskette Factory 1. Lotus® cc:Mail™, e-mail for IBM Global® Network 2. Lotus Organizer™ 3. Lotus ScreenCam™ 4. Triton CoSession™ Host 5. PRODIGY® 6. SofNet FaxWorks™ 7. Puma TranXit™ 8. Compuserve for Windows
Graphics - external	External SVGA to 1024 x 768 w/ 256 colors up to 70 Hz					
Graph - arch/data path	VL-Bus 2.0 local bus / 32 bit / Simultaneous LCD and CRT / 180 degree tilt					
Memory - std / max	8 MB / 24 MB 70 ns / non-parity / 3.3 volt / fast page					
Mem - upgrade	1 socket for one JEDEC 72 pin SO DIMM of 4 or 16 MB					
Keyboard / # of keys	Full size alp/num / 85 (8 Fn key functions)		Liftable (pop-up) keyboard to access and remove battery (and upgrade memory and disk); CD-ROM is not removable			
Keyboard slope	Yes (legs pop out)					
Pointing	TrackPoint III™					
Ext keyboard support	Yes (with option cable or Port Replicator)					
Dimensions (cubic in)	11.7 x 8.3 x 2.0" (194 cubic inches)					
Weight (with battery)	6.4 pounds 6.3 pounds					
Battery - type	NiMH / non-intelligent					
Battery - life	2.5 to 9 hours					
Charge time - on / off	6 hrs / 2 hrs					
Architecture	ISA (audio, PCMCIA, diskette, serial, parallel, 240 pin external expansion) VL-Bus 2.0 / 32 bit / 25 MHz (graphics, disk)					
Docking Station	None					
Port replicator	Port Replicator and Charger (with built-in battery charger and palm rest)					
PCMCIA™ 2.1 slots	2 Type I or 2 Type II or 1 Type III					
Serial / parallel ports	One 9 pin; 16550A / one (IEEE P1284, EPP, ECP, bidirectional)					
Other features	APM-aware BIOS / Universal AC adapter (35 watts) / Phoenix™ BIOS					
MPEG decoder	None					
Data/fax modem	None					
Audio support	16 bit audio chip / 18 voice MIDI FM Synthesis / ESS1688 with OPL3 Internal speaker / .5 watt / dial volume control / internal microphone					
Audio in/out jacks	Input jack (stereo) / microphone jack / output jack (stereo) Joystick/MIDI port (includes Joystick/MIDI cable)					
Infrared ports	Infrared port in back / IrDA 1.0 compatible / up to 115 Kbps					
Security	Power-on password / Supervisor password / Locking device keyhole (Kensington™ MicroSaver™ cable lock) / keyboard lock (requires Kensington)					
Preinstalled software	Choice of two preloaded configurations (listed to right)					
Warranty	1 year - ThinkPad EasyServ (optional Overnight Repair Option) or carry-in					
The Port Replicator and Charger provide cable management, a battery charger for an optional second battery, a palm rest when installed on the system, and has complete port replication.			Options for ThinkPad 365: - 4 MB SO DIMM 3.3v non-parity 72 pin 92G7287 - 16 MB SO DIMM 3.3v non-parity 72 pin 92G7293 - 720 MB EIDE HDD 13 ms PIO Mode 3 38H6306 - 810 MB EIDE HDD 13 ms PIO Mode 4 42H4012 - 1.08 GB EIDE HDD 13 ms Mode 4 69H7956 - Port Replicator and Charger 38H6303 - NiMH Battery Pack 38H6304			
The Port Replicator can charge a battery whether or not a ThinkPad is connected to it. When the ThinkPad is attached to the Port Replicator, it will attempt to recharge the battery in ThinkPad first (if there is one) before charging the battery in the Port Replicator.			Setup is entered by Ctrl + Alt + F11 from any full-screen DOS prompt Fn + F2 = Battery guage Fn + F3 = Standby Fn + F4 = Suspend Fn + F7 = LCD/CRT/Simultaneous Fn + F8 = Reverse video Fn + F11 = Power mgmt Fn + F12 = Hibernation PgUp = Speaker enable PgDn = Speaker disable System enters hibernation mode when keyboard is lifted up.			
Port Replicator and Charger connectors: - Serial (RS-232, 9 pin) - Parallel (EPP, ECP, 25 pin) - External display (15 pin) - Keyboard - Mouse - Diskette drive (26 pin) - Game with MIDI support (15 pin) - Audio in (3.5 mm) - Audio out (3.5 mm) - DC input connector - Spare battery connector (to charge 2nd battery)						
✕ = Withdrawn from marketing						