

IBM® ThinkPad® X20 - withdrawn

Type-model	Processor	MHz	Memory	Screen	Disk	DVD drive	Communications Bay	Preload	Available
2662-11U	Celeron™	500	64MB	12.1" SVGA	10GB ⁸	opt via UltraBase™ X2 or Dock	modem	Windows 98 SE	Sept 00
2662-12U	Celeron	500	64MB	12.1" SVGA	10GB	option via UltraBase X2 or Dock	modem	Windows 2000	Sept 00
2662-31U	Pentium® III	600	128MB	12.1" XGA	20GB	option via UltraBase X2 or Dock	modem	Windows 98 SE	Sept 00
2662-32U	Pentium III	600	128MB	12.1" XGA	20GB	option via UltraBase X2 or Dock	modem	Windows 2000	Sept 00
2662-34U	Pentium III	600	128MB	12.1" XGA	20GB	option via UltraBase X2 or Dock	Intel® ethernet/modem	Windows 98 SE	Sept 00
2662-35U	Pentium III	600	128MB	12.1" XGA	20GB	option via UltraBase X2 or Dock	Intel ethernet/modem	Windows 2000	Sept 00
2662-36U	Pentium III	600	128MB	12.1" XGA	20GB	option via UltraBase X2 or Dock	3Com® ethernet/modm	Windows 98 SE	Sept 00
2662-37U	Pentium III	600	128MB	12.1" XGA	20GB	option via UltraBase X2 or Dock	3Com ethernet/modem	Windows 2000	Sept 00
Processor							Intel® Mobile Celeron™ 500MHz ¹ with 100MHz system bus or Intel Mobile Pentium® III 600MHz with Intel SpeedStep™ technology and 100MHz system bus		
L2 cache							Celeron: 128KB / onboard (at processor speed) / ECC Pentium III: 256KB / onboard (at processor speed) / ECC		
Memory							64MB or 128MB standard / 320MB maximum ⁷ / SDRAM / non-parity / 100MHz / PC 100 / 3.3v / one 144-pin SO-DIMM socket / 64MB on systemboard / 1 socket available on 64MB models; socket occupied by 64MB SO-DIMM in 128MB models		
Diskette drive CD or DVD-ROM UltraBay™ 2000							None standard / 3.5" 1.44MB integrated in optional UltraBase X2 media slice None standard / optional CD or DVD-ROM removable from optional UltraBase X2 Modular bay for interchangeable devices / support for UltraBay™ 2000 devices in optional UltraBase X2 media slice or ThinkPad Dock		
Disk							10GB ⁸ or 20GB / user upgradeable / S.M.A.R.T. / ATA-66		
Display							12.1" (308mm) SVGA (800x600) TFT color / Active Matrix / 125 nits or 12.1" (308mm) XGA (1024x768) TFT color / Active Matrix / 150 nits		
Graphics controller							ATI™ Rage™ Mobility M / AGP 2X / 4MB SGRAM / DDC2B		
Graphics - external							External SVGA to 1024x768x16.7 million colors at 75Hz and up to 1600x1200		
Keyboard ThinkLight™ UltraPort™							ThinkPad Button / palm rest / TrackPoint®, Press-to-Select, Internet Scroll Bar Illuminates the keyboard to improve visibility in low-light conditions UltraPort connector on top of display for options such as digital UltraPort Camera		
Dimensions ³							11U/12U: 11" x 8.9" x .94"-1.1"; 279mm x 227mm x 23.8-27.9mm Others: 11" x 8.9" x .98"-1.2"; 279mm x 227mm x 24.9-30.5mm		
Travel weight ²							11U/12U: 3.1 lbs Others: 3.5 lbs		
Case material							Titanium Composite in the top cover for enhanced strength ⁴		
Battery - type							11U/12U: Lithium Ion 4-cell / intelligent Others: Lithium Ion 6-cell / intelligent		
Battery - life ¹⁰							11U/12U: 2.1 hrs Others: 3.8 hrs		
Architecture							Intel 440ZX™ AGPset / Intel PIIX4M (EIDE with Ultra DMA/33 or PIO Mode 4 support, ISA Bridge, USB) / Ricoh® R5C476II CardBus controller for PC Card and Compact Flash / AGP 2X for graphics / PCI 2.1 / 32-bit / 33MHz (EIDE, CardBus, audio, USB, ext expansion) / PC97338 Super I/O / ISA (diskette, serial, parallel, infrared, ext exp)		
Port replicator							Optional ThinkPad Port Replicator		
Docking Station							Optional ThinkPad Dock (includes Ultrabay 2000 and half-size PCI slot)		
Compact Flash slot							Compact Flash slot / 1 CF+ Type II / supports optional IBM Microdrive		
PC Card Std slot							One Type II / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video		
Ports							Two USB (Version 1.1) / external DB-15 monitor / RJ-11 (modem) / RJ-45 (ethernet) / no serial, parallel, keyboard, mouse or infrared ports		
Video out							None		
Communicatns Bay							Communications Bay with Mini PCI IIlb slot / customer accessible		
Modem							Some models: 56K ⁶ V.90 Mini PCI modem card / Lucent® chip set		
Ethernet/modem							Some models: IBM 10/100 Ethernet Mini PCI Adapter with 56K Modem (3Com ethernet chipset / 3Com modem chip set) Some models: IBM 10/100 EtherJet™ Mini PCI Adapter with 56K Modem / Intel ethernet chipset / Lucent modem chip set		
Audio support							PCI audio / SoundBlaster Pro™ support / CS4281 with CS4297A AC97 codec / mono speaker / 0.5 watt / volume up, down, mute buttons / internal microphone / input jack (3.5 mm) / output jack (3.5 mm) / line in jack		
Security							Power-on password / dual hard disk password / supervisor pwrd / security keyhole		
Limited warranty ¹²							3 year - EasyServ™.19 onsite pickup and delivery courier service		
Service options ²²							Optional service upgrades provide up to three years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)		
Communication Bay					- 64MB SO DIMM 100MHz NP SDRAM		20L0254		72 watt AC Adapter PC 99-compliant CIM and DMI 2.0 compliant Wired for Management 2.0 Local and remote asset management via the IBM Universal Manageability solutions IBM PC Lifecycle Care ²¹ provides proactive life cycle management and transition planning tools ENERGY STAR compliant Setup Guide, User's Reference, Windows OS manual Personalized Web-based support International Warranty Service ¹⁷ IBM SystemXtra®.20 24 hour x 7 day ¹⁸ toll-free hardware support during the warranty
- IBM 10/100 EtherJet Mini PCI Adapter with 56K Modem by 3Com 09N9774					- 128MB SO DIMM 100MHz NP SDRAM		20L0255		
- IBM 10/100 EtherJet Mini PCI Adapter with 56K Modem 19K5887					- 256MB SO DIMM 100MHz NP SDRAM		33L3069		
					- 10GB HDD		08K9510		
					- 20GB HDD		27L3439		
					- 32GB HDD ²³		08K9511		
Ultrabay 2000 interchangeable accessories					- Second HDD Adapter for Ultrabay 2000		08K6068		
- 8X ⁹ -3X DVD Ultrabay 2000 Drive 27L3448					- 1GB Microdrive		07N5574		
- 2X SuperDisk (LS-120) UltraBay 2000 27L3451					- UltraBase X2 media slice		08N1180		
- 24X-10X CD-ROM Ultrabay 2000 Drive 05K9233					- ThinkPad Port Replicator		02K8667		
- 4X/4X/20X CD-Read/Write Ultrabay 2000 00N8252					- ThinkPad Dock		263110U		
- Zip 250MB Ultrabay 2000 Drive 00N8253					- ThinkPad X Series Battery (6-cell)		02K6651		
- Portable Drive Bay 2000 19K4480					- Li-Ion Multiple Battery Charger		02K6643		
Wireless connectivity					- ThinkPad 72W AC Adapter		02K6699		
- IBM High Rate Wireless LAN PC Card 09N9863					- ThinkPad Monitor Stand		00N8222		
- IBM High Rate Wireless LAN Access Point 9085NA2					- IBM UltraPort Camera II		04P6135		
					- Multi-Port USB Hub		00N8215		
- Bluetooth™ PC Card (avail 4Q 2000) 09N9812					- USB Portable Diskette Drive		05K9276		

All trademarks are the property of their respective owners
Models withdrawn effective April 2001 or July 2001

No warranties are expressed or implied in this summary
(X20) © IBM Corp. July 2001