

IBM ThinkPad 380D - withdrawn

IBM® ThinkPad®:		⚡ 380D	
		12.1" SVGA DSTN or TFT / 8 x CD-ROM	
Processor type	Pentium® 150/60 MHz or 150/60 MHz with MMX™ technology/ 64 bit transfer to L2 cache / 64 bit transfer to memory		
Processor upgrade	None		
L2 cache	256 KB / write-through / direct mapped / 8 ns / synchronous pipelined burst		
Diskette drive	Internal 3.5" 1.44 MB / use simultaneously with CD-ROM / on right side		
External FDD port	None since diskette internal		
CD-ROM	5.25" CD-ROM / 8 x speed / multi-session / XA / ATAPI / not bootable / not removable / on right side		
Type - model (code)	2635-2AU	2635-3AU	All-in-one integration means the disk, diskette drive, and CD-ROM are all within the covers of the notebook; keyboard does not lift up
Preload (see side)	Windows 95 OSR2	Windows 95 OSR2	
Avail / withdrawn date	May 1997 / January 1998	May 1997 / January 1998	
Pentium speed	150/60 MHz	150/60 MHz with MMX technology	
Disk - size / ms	1.35 GB / 13 ms / PIO Mode 4	2.1 GB / 13 ms / PIO Mode 4	
Disk controller	EIDE / PCI 2.1 / supports one internal disk / no DMA or busmaster support / not removeable / upgrade only by IBM or dealer		
Display - size and type	12.1 inch DSTN color		12.1 inch TFT color
Display - technology	SVGA / 640 x 480 or 800 x 600 Dual scan 65,536 sim colors / 30 to 1 contrast		
Graphics - controller	NeoMagic™ MagicGraph128ZV™ (NM2093) / 128 bit SVGA accelerator / Zoomed Video support / DDC1 and DDC2B 1.125 MB / iDRAM™ (embedded) / color space conversion and interpolation in X and Y axis / support for DCI, DirectDraw PCI 2.1 / 32 bit / external SVGA to 1024 x 768 with 256 colors		
Graph - arch/data path	Simultaneous LCD and CRT / 150 degree tilt		
Graphics - features	Simultaneous LCD and CRT / 150 degree tilt		
Memory - std / max	16 MB / 80 MB / non-parity / 3.3 volt / EDO		
Memory - features	1 socket for one JEDEC 144 pin EDO SO DIMM of 8, 16, 32, or 64 MB / socket accessed from bottom via screw		
Keyboard / # of keys	Full size alp/num / 85 (6 Fn key functions) / keyboard slope with Port Replicator		
External keyboard	External keyboard support with option cable 06G8619 or Port Replicator		
Pointing / palm rest	TrackPoint III™ / no drag lock keys		
Dimensions	11.8 x 9.2 x 2.4" (260 cubic inches)		
Weight	7.1 pounds (3.2 kg)	6.9 pounds (3.1 kg)	
Battery - type / life	NiMH / non-intelligent / 2.0 hrs		Li-Ion / non-intelligent / 2.6 hrs
Charge time - on / off	3.5 to 9 hrs / 2.5 to 3.5 hrs		
Architecture	PCI 2.1 / 32 bit / 33 Mhz (EIDE, graphics, PCMCIA, Port Replicator) ISA (audio, diskette, serial, parallel, infrared) Intel® Mobile Triton 82430 PCIsset / Intel 82371MX PIIX / NS PC87338		
Docking Station	None		
Port replicator	① ThinkPad Enhanced Port Replicator, ② ThinkPad 560 Port Replicator, ③ ThinkPad 380/385 Port Replicator		
PCMCIA™ slots	2 Type I or 2 Type II or 1 Type III / Zoomed Video support in lower slot / PCMCIA 2.1 compatible / PC Card Standard 95 / Cirrus Logic CL-PD6729 (PCI) One 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)		
Serial / parallel ports	APM-aware BIOS / Univers AC adapter, barrel (35 watts) / Selectable boot		
Other features			
Video in/out	None		
Data/fax modem	None		
Audio support	16 bit audio chip / 20 voice MIDI FM Synthesis / Crystal Semiconductor™ CS4236 One internal speaker / .5 watt / dial volume control / internal mic / full duplex Input/microphone jack (stereo) / output jack (stereo) / no joystick port		
Audio in/out jacks	Infrared port on left side / IrDA 1.1 compatible / up to 4 Mbps		
Infrared ports			
Security	Power-on password / Hard disk password / security keyhole		
Preinstalled software	Microsoft Windows 95 OSR2 wth applications (listed on right)		
Warranty	1 year - ThinkPad EasyServ (optional Overnight Repair Option) or carry-in		
Service options	On-site, M-F, 8-5, next bus day (71 cities) / warranty extension to 3 or 5 years		
The ThinkPad Enhanced Port Replicator provide cable management, additional I/O ports, and CardBus PC Card slots. Features include: - Dual IBM lock slots to secure the ThinkPad 380, PC Cards, and Port Replicator Port Replicator connectors: - USB - Serial (9 pin); parallel (EPP, ECP, 25 pin) - External display (15 pin) - Keyboard - Mouse - Audio in (3.5 mm) - Audio out (3.5 mm) - Joystick/MIDI port (15 pin) - not on system - External diskette drive conntr - not on system - Power connector (requires AC power; can not run on battery) Features of the PC Card slots: - Two Type III slots (side by side) - PC Card Standard 95 compliant - CardBus compliant (PCI 2.1 / 32 bit) - 8/16 bit PC Card support (no Zoomed Video) - Texas Instruments PCI1131 controller - Requires no PCI-to-PCI bridge		Options for ThinkPad 380: - 8 MB SO DIMM 3.3v NP EDO 64 bit 92G7340 - 16 MB SO DIMM 3.3v NP EDO 64 bit 92G7341 - 32 MB SO DIMM 3.3v NP EDO 64 bit 92G7342 - 64 MB SO DIMM 3.3v NP EDO 64 bit 76H0268 - ThinkPad 560 Port Replicator 46H4209 - ThinkPad 380/385 Port Replicator 84G1316 - ThinkPad Enhanced Port Replicator 11J8997 - Li-Ion Battery Pack 73H9793 - 35 watt AC Adapter (barrel, slim) 76H0139 - 8 x CD-ROM 73H9795 - 2.1 GB HDD 13 ms 73H9797 - 3.2 GB Disk 13 ms 02K0487 - 5.1 GB Disk 12 ms 02K0506 - 33.6 Kbps Modem with XJACK 55H6759 - 56K PC Card Modem Kit 04K0052	
		WINDOWS 95 PRELOAD - Microsoft Windows 95 OSR2 (FAT16) - Online User's Guide - ThinkPad Features Program - SystemSoft CardWorks™ - Diskette Factory and Utilities 1. Triton CoSession™ Host 2. NetFinity for Windows 95 3. Puma TranXit™ 4. IntelliLink Connect 5. IBM Anti-Virus 6. IGN/Netscape Navigator browser 7. Media Player 8. IntelliQuest Registration Mailer 9. CompuServe WinCIM 10. Lotus Organizer 11. Ergonomics 12. Marketing Demo - Lotus SmartSuite CD-ROM - Recovery CD-ROM with boot diskette - Windows 95 CD-ROM (no installation) Fn + F2 = Battery guage Fn + F3 = Standby Fn + F4 = Suspend Fn + F7 = LCD/CRT/Simultaneous Fn + F11 = Power mgmt Fn + F12 = Hibernation	
		Easy-Setup is entered by holding F1 when turning on. 1.08 GB = DMA Mode 2 or PIO Mode 4 1.35 GB = DMA Mode 2 or PIO Mode 4 2.1 GB = DMA Mode 2 or PIO Mode 4 3.2 GB = Ultra DMA/33 or PIO Mode 4 5.1 GB = Ultra DMA/33 or PIO Mode 4	
		FEATURES OF 380 MODELS Quick Setup Guide System Status Indicators Plug and Play 1.0a Standby, suspend, safe suspend (RediSafe), and hibernation modes US EPA Energy Star compliant Personalization screen at startup International Warranty Service IBM SystemXtra Program 24 hour / 7 day telephone, bulletin board, fax, electronic, and Internet (http://www.pc.ibm.com) support IBM and dealer warranty/service Online Housecall (remote diagnostics)	

ThinkPad EasyServ™: customer calls 1-800-772-2227, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). Overnight repair option in US available for \$99.

All trademarks are the property of their respective owners
 No warranties are expressed or implied in this summary
 (380D) Compiled by Roger Dodson, IBM. December 1997